

Cu/Al 60/75° C WIRE

| | |
|---------------|-------|
| AVG. IN. LBS. | 14-10 |
| | 25 |

1 Pole
Type QP
Interrupting Rating
MAX. RMS, 57kV, 40°C
10,000 120/240 VAC
MAG Type, 50k, 40°C
Siemens
@Lund Ckt. Bk.
WI-5116

CU ONLY

20

2 Pole Type QP
Interrupting Rating
MAX. RMS, 57kV, 40°C
10,000 120/240 VAC
MAGN Type, 40°C
@Lund Ckt. Bk.
NB-6123
Siemens

40

Cu/Al 60/75° C WIRE

| | |
|---------------|-------|
| AVG. IN. LBS. | 14-25 |
| | 14-20 |
| | 14-15 |
| | 14-10 |
| | 14-5 |
| | 14-0 |

CU ONLY

40

Cu/Al 60/75° C WIRE

| | |
|---------------|-------|
| AVG. IN. LBS. | 14-10 |
| | 25 |

1 Pole
Type QP
Interrupting Rating
MAX. RMS, 57kV, 40°C
10,000 120/240 VAC
MAGN Type, 50k, 40°C
Siemens
@Lund Ckt. Bk.
WI-5116

CU ONLY

20

Cu/Al 60/75° C WIRE

| | |
|---------------|----|
| AVG. IN. LBS. | 25 |
| | 10 |

1 Pole
Type QP
Interrupting Rating
MAX. RMS, 57kV, 40°C
10,000 120/240 VAC
MAGN Type, 40°C
@Lund Ckt. Bk.
NB-6123
Siemens

25

Cu/Al 60/75° C WIRE

| | |
|---------------|----|
| AVG. IN. LBS. | 25 |
| | 10 |

1 Pole
Type QP
Interrupting Rating
MAX. RMS, 57kV, 40°C
10,000 120/240 VAC
MAGN Type, 40°C
@Lund Ckt. Bk.
NB-6123
Siemens

25

Cu/Al 60/75° C WIRE

| | |
|---------------|----|
| AVG. IN. LBS. | 25 |
| | 10 |

1 Pole
Type QP
Interrupting Rating
MAX. RMS, 57kV, 40°C
10,000 120/240 VAC
MAGN Type, 40°C
@Lund Ckt. Bk.
NB-6123
Siemens

20

Cu/Al 60/75° C WIRE

| | |
|---------------|----|
| AVG. IN. LBS. | 25 |
| | 10 |

1 Pole
Type QP
Interrupting Rating
MAX. RMS, 57kV, 40°C
10,000 120/240 VAC
MAGN Type, 40°C
@Lund Ckt. Bk.
NB-6123
Siemens

20

2
4
6
8
10
12