

# CITY OF GRAND JUNCTION


## 2022 WATERLINE REPLACEMENT - PHASE 2

### GRAND JUNCTION, COLORADO

#### BID DOCUMENTS

**CONTACTS**

<b>OWNER:</b>	CITY OF GRAND JUNCTION 333 WEST AVENUE, BUILDING C GRAND JUNCTION, CO 81501	JOHN EKLUND, P.E. 970-224-1558 JOHNE@GJCITY.ORG
<b>ENGINEER:</b>	JVA, INC 817 COLORADO AVENUE, SUITE 301 GLENWOOD SPRINGS, CO 81601	COOPER BEST, P.E. 970-404-3003 CBEST@JVAJVA.COM
<b>SURVEYOR:</b>	CITY OF GRAND JUNCTION 333 WEST AVENUE, BUILDING C GRAND JUNCTION, CO 81505	RENEE PARENT, P.E. PLS, CFedS 970-256-4003 RENEEP@GJCITY.ORG



**JVA, Inc.** 817 Colorado Ave., Suite 301  
Glenwood Springs, CO Zip 81601  
970.404.3100  
[www.jvajva.com](http://www.jvajva.com)  
Boulder • Fort Collins • Winter Park  
Glenwood Springs • Denver


MARCH 2023

PREPARED UNDER THE SUPERVISION OF


\_\_\_\_\_  
JVA, Inc.

**DRAWING INDEX**

SHEET NO.	TITLE
G0.0	COVER
G0.1	LEGENDS, NOTES, AND ABBREVIATIONS
CE1.0	EROSION CONTROL NOTES
CE1.1	EROSION CONTROL NOTES
CE1.2	EROSION CONTROL NOTES
C0.0	OVERALL UTILITY PLAN
C1.0	HALL AVE WATER PLAN & PROFILE
C2.0	N 18TH ST WATER PLAN & PROFILE
C2.1	N 18TH ST WATER PLAN & PROFILE
C2.2	N 18TH ST WATER PLAN & PROFILE
C2.3	N 18TH ST WATER PLAN & PROFILE
C3.0	N 19TH ST WATER PLAN & PROFILE
C3.1	N 19TH ST WATER PLAN & PROFILE
C3.2	N 19TH ST WATER PLAN & PROFILE
C3.3	N 19TH ST WATER PLAN & PROFILE
C4.0	N 20TH ST WATER PLAN & PROFILE
C4.1	MESA AVE WATER PLAN & PROFILE
C4.2	N 21ST ST WATER PLAN & PROFILE
C5.0	N 20TH ST WATER PLAN & PROFILE
C5.1	N 20TH ST WATER PLAN & PROFILE
C6.0	N 21ST ST WATER PLAN & PROFILE
C6.1	N 21ST ST WATER PLAN & PROFILE
C7.0	HALL AVE WATER PLAN & PROFILE
C7.1	HALL AVE WATER PLAN & PROFILE
C8.0	MESA AVE WATER PLAN & PROFILE
C8.1	MESA AVE WATER PLAN & PROFILE
C8.2	MESA AVE WATER PLAN & PROFILE
C8.3	MESA AVE WATER PLAN & PROFILE
C8.4	MESA AVE WATER PLAN & PROFILE
C9.0	N 26TH ST WATER PLAN & PROFILE



VICINITY MAP  
NTS




PROJECT LOCATION MAP  
NTS

ABBREVIATIONS

Table of abbreviations for various engineering terms, including AASHTO, ABAN, AC, ADDL, ADDM, ADJ, AL, ALT, AMT, APPROX, ARCH, ARV, ASTM, ASPH, ASSY, ASYM, AUTO, AVG, AWWA, BC, BFCV, BLDG, BLK, BM, BMP, BS, BOS, BOT, BSM, BVCE, BVCS, BW, CB, CCW, CDDT, CIP, CJ, CL, CLR, CMP, CMU, CONC, CONST, CONT, COR, CR, CTR, CY, DEMO, DIA, DIAG, DIP, DOM, DN, DR, DWG, DWL, E, EA, ECC, EJ, EL, ELB, ELEC, ENGR, EOP, EQ, EQUIP, ESMT, EST, EVCE, EVCS, EW, EXP, EXIST, FND, FES, FF, FG, FH, FL, FN, FOC, FPM, FPS, FT, FTG, G, GA, GAL, GCV, GCO, GIP, GJWRP, GND, GPD, GPM, GR, GRG, GSP, GV, H, HB, HE, HDWL, HNDRL, HORIZ.

DESIGN LEGEND




GENERAL NOTES


- 1. ALL MATERIALS AND WORKMANSHIP SHALL BE IN CONFORMANCE WITH THE LATEST STANDARDS AND SPECIFICATIONS OF THE CITY OF GRAND JUNCTION, COLORADO DEPARTMENT OF TRANSPORTATION, GRAND JUNCTION FIRE PROTECTION REQUIREMENTS, AND APPLICABLE STATE AND LOCAL STANDARDS AND SPECIFICATIONS. THE CONTRACTOR SHALL HAVE IN POSSESSION AT ALL TIMES ONE (1) SIGNED COPY OF APPROVED PLANS, STANDARDS AND SPECIFICATIONS. CONTRACTOR SHALL CONSTRUCT AND MAINTAIN EMERGENCY ACCESS ROUTES TO THE SITE AND STRUCTURE AT ALL TIMES PER THE APPLICABLE GRAND JUNCTION FIRE PROTECTION DISTRICT REQUIREMENTS. THE CONTRACTOR SHALL OBTAIN WRITTEN APPROVAL FOR ANY VARIANCE TO THE ABOVE DOCUMENTS. NOTIFY ENGINEER OF ANY CONFLICTING STANDARDS OR SPECIFICATIONS. IN THE EVENT OF ANY CONFLICTING STANDARD OR SPECIFICATION, THE MORE STRINGENT OR HIGHER QUALITY STANDARD, DETAIL OR SPECIFICATION SHALL APPLY.
2. THE CONTRACTOR SHALL OBTAIN, AT HIS OWN EXPENSE, ALL APPLICABLE CODES, LICENSES, STANDARD SPECIFICATIONS, PERMITS, BONDS, ETC., WHICH ARE NECESSARY TO PERFORM THE PROPOSED WORK, INCLUDING, BUT NOT LIMITED TO A LOCAL AND STATE GROUNDWATER DISCHARGE AND COLORADO DEPARTMENT OF HEALTH AND ENVIRONMENT (CDPHE) STORMWATER DISCHARGE PERMIT ASSOCIATED WITH CONSTRUCTION ACTIVITY.
3. THE CONTRACTOR SHALL BE RESPONSIBLE FOR NOTIFYING THE REQUIRED PARTY OWNER AT LEAST 48 HOURS PRIOR TO START OF ANY CONSTRUCTION, PRIOR TO BACKFILLING, AND AS REQUIRED BY JURISDICTIONAL AUTHORITY AND/OR PROJECT SPECIFICATIONS. THE CONTRACTOR SHALL CONTINUE WITH NOTIFICATIONS THROUGHOUT THE PROJECT AS REQUIRED BY THE STANDARDS AND SPECIFICATIONS.
4. THE LOCATIONS OF EXISTING UTILITIES ARE SHOWN IN THE APPROXIMATE LOCATION BASED ON INFORMATION BY OTHERS. NOT ALL UTILITIES MAY BE SHOWN. THE CONTRACTOR SHALL DETERMINE THE EXACT SIZE, LOCATION AND TYPE OF ALL EXISTING UTILITIES WHETHER SHOWN OR NOT BEFORE COMMENCING WORK. THE ENGINEER AND/OR OWNER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS SHOWN ON PLANS. THE CONTRACTOR SHALL BE FULLY AND SOLELY RESPONSIBLE FOR ANY AND ALL DAMAGES AND COSTS WHICH MIGHT OCCUR BY THE CONTRACTOR'S FAILURE TO EXACTLY LOCATE AND PRESERVE ANY AND ALL UTILITIES. THE CONTRACTOR SHALL NOTIFY ALL PUBLIC AND PRIVATE UTILITY COMPANIES AND DETERMINE THE LOCATION OF ALL EXISTING UTILITIES PRIOR TO PROCEEDING WITH GRADING AND CONSTRUCTION. ALL WORK PERFORMED IN THE AREA OF UTILITIES SHALL BE PERFORMED AND INSPECTED ACCORDING TO THE REQUIREMENTS OF THE UTILITY OWNER. LIKEWISE, THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING AND MAPPING ANY EXISTING UTILITY (INCLUDING DEPTH) WHICH MAY CONFLICT WITH THE PROPOSED CONSTRUCTION, AND FOR RELOCATING ENCOUNTERED UTILITIES AS DIRECTED BY THE ENGINEER. CONTRACTOR SHALL CONTACT AND RECEIVE APPROVAL FROM UTILITY OWNER AND ENGINEER BEFORE RELOCATING ANY ENCOUNTERED UTILITIES. CONTRACTOR RESPONSIBLE FOR SERVICE CONNECTIONS, AND RELOCATING AND RECONNECTING AFFECTED UTILITIES AS COORDINATED WITH UTILITY OWNER AND/OR ENGINEER, INCLUDING NON-MUNICIPAL UTILITIES (TELEPHONE, GAS, CABLE, ETC.), WHICH SHALL BE COORDINATED WITH THE UTILITY OWNER. THE CONTRACTOR SHALL IMMEDIATELY CONTACT ENGINEER UPON DISCOVERY OF A UTILITY DISCREPANCY OR CONFLICT. AT LEAST 48 HOURS PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL NOTIFY THE UTILITY NOTIFICATION CENTER OF COLORADO (1-800-922-1987, WWW.UNCC.ORG). SEE SURVEY UTILITY LOCATION INFORMATION BELOW.
5. THE CONTRACTOR SHALL BE SOLELY AND COMPLETELY RESPONSIBLE FOR CONDITIONS AT AND ADJACENT TO THE JOB SITE, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY DURING THE PERFORMANCE OF THE WORK. THE CONTRACTOR SHALL PREPARE A TRAFFIC CONTROL PLAN FOR OWNER AND/OR CITY APPROVAL AND PROVIDE ALL LIGHTS, SIGNS, BARRICADES, FENCING, FLAGMEN OR OTHER DEVICES NECESSARY TO PROVIDE FOR PUBLIC SAFETY. THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS. THE CONTRACTOR AGREES TO COMPLY WITH THE PROVISIONS OF THE TRAFFIC CONTROL PLAN AND THE LATEST EDITION OF THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES," PART VI, FOR CONSTRUCTION SIGNAGE AND TRAFFIC CONTROL. ALL TEMPORARY AND PERMANENT TRAFFIC SIGNS SHALL COMPLY TO THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) WITH REGARD TO SIGN SHAPE, COLOR, SIZE, LETTERING, ETC. UNLESS OTHERWISE SPECIFIED. IF APPLICABLE, PART NUMBERS ON SIGNAGE DETAILS REFER TO MUTCD SIGN NUMBERS.
6. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVING ANY GROUNDWATER ENCOUNTERED DURING THE CONSTRUCTION OF ANY PORTION OF THIS PROJECT. GROUNDWATER SHALL BE PUMPED, PIPED, REMOVED AND DISPOSED OF IN A MANNER WHICH DOES NOT CAUSE FLOODING OF EXISTING STREETS NOR EROSION ON ADJUTING PERMITES IN ORDER TO CONSTRUCT THE IMPROVEMENTS SHOWN ON THESE PLANS. GROUNDWATER TO BE PUMPED SHALL BE TESTED, PERMITTED, AND PUMPED PER THE STATE OF COLORADO AND LOCAL GROUNDWATER DISCHARGING REQUIREMENTS.
7. RIM AND GRATE ELEVATIONS SHOWN ON PLANS ARE APPROXIMATE ONLY AND ARE NOT TO BE TAKEN AS FINAL ELEVATIONS. THE CONTRACTOR SHALL ADJUST RIMS AND OTHER IMPROVEMENTS TO MATCH FINAL PAVEMENT AND FINISHED GRADE ELEVATIONS.
8. THE EXISTING AND PROPOSED ELEVATIONS OF FLATWORK, SIDEWALKS, CURBS, THRESHOLDS, PAVING, ETC. AS SHOWN HEREON ARE BASED ON EXTRAPOLATION OF FIELD SURVEY DATA, EXISTING CONDITIONS, AND DATA PROVIDED BY OTHERS. AT CRITICAL AREAS HYDRANT LATERALS AND SITE FEATURES, CONTRACTOR SHALL HAVE FORWORK INSPECTED AND APPROVED BY OWNER, OWNER'S REPRESENTATIVE, OR ENGINEER PRIOR TO PLACING CONCRETE. MINOR ADJUSTMENTS, AS APPROVED, TO PROPOSED GRADES, INVERTS, ETC. MAY BE REQUIRED TO PREVENT PONDING OR SLOPE NOT IN CONFORMANCE WITH MUNICIPAL STANDARDS. ALL FLATWORK MUST PREVENT PONDING AND PROVIDE POSITIVE DRAINAGE AWAY FROM EXISTING AND PROPOSED BUILDINGS, WALLS, ROOF DRAIN OUTFALLS, ACROSS DRIVES AND WALKS, ETC., TOWARDS THE PROPOSED INTENDED DRAINAGE FEATURES AND CONVEYANCES.
9. FINAL LIMITS OF REQUIRED ASPHALT SAWCUTTING AND PATCHING MAY VARY FROM LIMITS SHOWN ON PLANS. CONTRACTOR TO PROVIDE SAWCUT AND PATCH WORK TO ACHIEVE POSITIVE DRAINAGE AND A SMOOTH TRANSITION TO EXISTING ASPHALT WITHIN SLOPES ACCEPTABLE TO THE ENGINEER AND WITHIN MUNICIPAL STANDARDS. CONTRACTOR SHALL PROVIDE ADDITIONAL SAWCUTTING AND PATCHING AT UTILITY WORK, CONNECTION POINTS TO EXISTING PAVEMENT AND FEATURES, ETC. THAT MAY NOT BE DELINEATED ON PLANS.
10. ANY EXISTING MONITORING WELLS, CLEANOUTS, VALVE BOXES, ETC. TO BE PROTECTED AND TO REMAIN IN SERVICE. IF FEATURES EXIST, EXTEND OR LOWER TO FINAL SURFACE WITH LIKE KIND CAP WITH STANDARD CAST ACCESS LID WITH SAME MARKINGS. IN LANDSCAPED AREAS PROVIDE A CONCRETE COLLAR (18"x18"x6" THICK) AT ALL EXISTING AND PROPOSED MONITORING WELLS, CLEANOUTS, VALVE BOXES, ETC.
11. OWNER TO APPROVE ALL PRIVATE CONCRETE FINISHING, JOINT PATTERNS AND COLORING REQUIREMENTS PRIOR TO CONSTRUCTION. SUBMIT JOINT LAYOUT PLAN TO OWNER FOR APPROVAL PRIOR TO CONSTRUCTION.
12. PIPE LENGTHS AND HORIZONTAL CONTROL POINTS SHOWN ARE FROM CENTER OF STRUCTURES, END OF FLARED END SECTIONS, ETC. SEE STRUCTURE DETAILS FOR EXACT HORIZONTAL CONTROL LOCATION. CONTRACTOR IS RESPONSIBLE FOR ADJUSTING ACTUAL PIPE LENGTHS TO ACCOUNT FOR STRUCTURES AND LENGTH OF FLARED END SECTIONS.
13. ALL SURPLUS MATERIALS, TOOLS, AND TEMPORARY STRUCTURES, FURNISHED BY THE CONTRACTOR, SHALL BE REMOVED FROM THE PROJECT SITE BY THE CONTRACTOR. ALL DEBRIS AND RUBBISH CAUSED BY THE OPERATIONS OF THE CONTRACTOR SHALL BE REMOVED, AND THE AREA OCCUPIED DURING CONSTRUCTION ACTIVITIES SHALL BE RESTORED TO ITS ORIGINAL CONDITION, WITHIN 48 HOURS OF PROJECT COMPLETION, UNLESS OTHERWISE DIRECTED BY THE MUNICIPALITY OR OWNER'S REPRESENTATIVE.
14. THE CONTRACTOR IS REQUIRED TO PROVIDE AND MAINTAIN EROSION AND SEDIMENT CONTROL MEASURES IN ACCORDANCE WITH THE LOCAL JURISDICTION, THE STATE OF COLORADO, MILE HIGH FLOOD DISTRICT "URBAN STORM DRAINAGE CRITERIA MANUAL VOLUME 3", THE M-STANDARD PLANS OF THE COLORADO DEPARTMENT OF TRANSPORTATION, AND THE APPROVED EROSION CONTROL PLAN. JURISDICTIONAL AUTHORITY MAY REQUIRE THE CONTRACTOR TO PROVIDE ADDITIONAL EROSION CONTROL MEASURES DUE TO UNFORESEEN EROSION PROBLEMS OR IF THE PLANS DO NOT FUNCTION AS INTENDED. THE CONTRACTOR IS RESPONSIBLE FOR PROHIBITING SILT AND DEBRIS LADEN RUNOFF FROM LEAVING THE SITE, AND FOR KEEPING ALL PUBLIC AREAS FREE OF MUD AND DEBRIS. THE CONTRACTOR IS RESPONSIBLE FOR RE-ESTABLISHING FINAL GRADES AND FOR REMOVING ACCUMULATED SEDIMENTATION FROM ALL AREAS INCLUDING SWALES AND DETENTION/WATER QUALITY AREAS. CONTRACTOR SHALL REMOVE TEMPORARY EROSION CONTROL MEASURES AND REPAIR AREAS AS REQUIRED AFTER VEGETATION IS ESTABLISHED AND ACCEPTED BY OWNER AND MUNICIPALITY.
15. ADA COMPLIANCE: THE CROSS-SLOPE OF ALL WALKS MUST BE LESS THAN 1:48 (2.0%) PERPENDICULAR TO DIRECTION OF TRAVEL. RUNNING SLOPE OF ACCESSIBLE WALKS MUST BE NOT STEEPER THAN 1:20 (5.0%) IN DIRECTION OF TRAVEL. MAXIMUM GRADE OF ACCESSIBLE CURB RAMPS AND RAMPS IS 1:12 (8.3%). CURB RAMPS SHALL PROVIDE A LANDING AT THE TOP AND RAMP RUNS PROVIDE LANDINGS AT THE BOTTOM AND TOP OF EACH RAMP RUN AT A SLOPE NOT TO EXCEED 1:48. RAMP RUNS EXCEEDING SIX INCHES SHALL INCLUDE HANDRAILS. ACCESSIBLE PARKING SPACES AND ACCESS AISLES SHALL NOT EXCEED 1:48 IN ALL DIRECTIONS. CONTRACTOR SHALL NOTIFY ENGINEER PRIOR TO PLACEMENT OF FLATWORK OF SITE CONDITIONS OR DISCREPANCIES WHICH PREVENT TYPICAL REQUIRED GRADES FROM BEING ACHIEVED. ALL RAMPS, STAIRS, DECK PROTECTION, AND RAILINGS SHALL BE CONSTRUCTED IN ACCORDANCE WITH CURRENT ADA STANDARDS. ACCESSIBLE CURB RAMPS SHALL CONFORM TO THE CDOT M-STANDARDS (SEE DETAIL M-608-1, ETC). ACCESSIBLE FEATURE WITHIN THE PUBLIC RIGHTS-OF-WAY SHALL BE CONSTRUCTED TO CONFORM TO THE LOCAL AUTHORITY HAVING JURISDICTION REQUIREMENTS.
16. PROTECT ALL TREES AND VEGETATION. PLACE CONSTRUCTION FENCING AT DRIP LINE OF TREES AND PLANTS NEAR THE WORK ZONE. DEEP WATER TREES WEEKLY. HAND EXCAVATION REQUIRED AT ROOT ZONES WHERE PROPOSED PAVING OR UTILITY WORK IS WITHIN DRIPLINE OF TREES.
17. LOCATIONS OF CLEANOUTS, LIGHTS, SIGNAGE, JUNCTION BOXES, AND OTHER SIGNIFICANT SITE FEATURES TO BE STAKED FOR ENGINEER AND OR OWNER APPROVAL PRIOR TO WORK. CLEANOUTS, JUNCTION BOXES, AND ADJACENT GRADES TO BE RAISED ONE-HALF INCH AT ASPHALT/CONCRETE (OR 1" AT LANDSCAPING) TO PROVIDE POSITIVE DRAINAGE AWAY FROM FEATURES.
18. SURVEY INFORMATION: BENCHMARK INFORMATION: TOPOGRAPHIC INFORMATION WAS PROVIDED BY THE CITY OF GRAND JUNCTION. SEE EXISTING CONDITIONS SURVEY 2021 WATER LINE REPLACEMENTS - PHASE 2 DATED 3/11/2022. CONTROL POINTS SHOWN ON PLAN, THE FIELD SURVEYS AND PROCESSING OF DATA WAS MADE IN THE MESA COUNTY LOCAL COORDINATE SYSTEM (MCLCS) GRAND VALLEY AREA (GVA) ZONE AND NAVD88 VERTICAL DATUM WITH GEOID 12A MODEL TO CONVERT ELLIPSOID HEIGHTS TO ORTHOMETRIC ELEVATIONS. THE MCLCS USED THE IN THE SAID WHS SURVEY ARE BASED UPON REFERENCE FROM:
MESA COUNTY CONTROL POINT P310 - PRECISION B-5PPM NORTH 28231.71 SFT (MCGVA) EAST 92054.57 SFT (MCGVA) NAVD 88, G12A ELEVATION: 4631.32 SFT LATITUDE: 39° 02' 47.60643" N LONGITUDE: 108° 33' 42.12299" W ELLIPSOID HEIGHT: 1394.760 METER COMMENT: NGS 9/16" STAINLESS STEEL ROD IN MONUMENT WELL
MESA COUNTY CONTROL POINT P318 - PRECISION B-5PPM NORTH 19671.32 SFT (MCGVA) EAST 110221.18 SFT (MCGVA) NAVD 88, G12A ELEVATION: 4793.43 SFT LATITUDE: 39° 01' 23.00622" N LONGITUDE: 108° 29' 51.95172" W ELLIPSOID HEIGHT: 1444.23 METERS COMMENT: NGS 9/16" STAINLESS STEEL ROD IN MONUMENT WELL
18.1 BEARINGS ARE SHOWN ON THE DRAWINGS SEE SHEET CO.0.
18.2 HORIZONTAL CONTROL INFORMATION: HORIZONTAL CONTROL COORDINATES ARE BASED ON THE REFERENCED SURVEY AND ARE PROVIDED ON SHEET CO.0 OF THE PLANS.
18.3 SURVEY UTILITY LOCATION INFORMATION PER THE SURVEYOR: SUBSURFACE UTILITIES ARE SHOWN IN APPROXIMATE HORIZONTAL AND VERTICAL LOCATIONS CONSISTENT WITH ASCE 38-02 QUALITY LEVEL "B" (INFORMATION OBTAINED BY THE APPLICATION OF APPROPRIATE SURFACE GEOPHYSICAL METHODS TO DETERMINE THE EXISTENCE AND HORIZONTAL POSITION OF VIRTUALLY ALL UTILITIES WITHIN THE PROJECT LIMITS. THE INFORMATION OBTAINED IN THIS MANNER IS SURVEYED TO PROJECT CONTROL) AND QUALITY LEVEL "C" (INFORMATION OBTAINED BY SURVEYING AND PLOTTING VISIBLE ABOVE-GROUND UTILITY FEATURES AND BY USING PROFESSIONAL JUDGMENT IN CORRELATING THIS INFORMATION TO QUALITY LEVEL "B" INFORMATION DERIVED FROM EXISTING RECORDS OR ORAL RECOLLECTIONS), AND BASED ON FIELD MEASUREMENTS PROVIDED BY THE OWNER AND THE CONTRACTOR. SUBSURFACE UTILITIES ARE NOT DETECTED TO THE EXTENT SET FORTH IN ASCE 38-02 QUALITY LEVELS "A" (INFORMATION OBTAINED THROUGH THE NONDESTRUCTIVE EXPOSURE OF UNDERGROUND UTILITIES, AND ALSO PROVIDES THE TYPE, SIZE, CONDITION, MATERIAL AND OTHER CHARACTERISTICS OF UNDERGROUND FEATURES), TO THE EXTENT DEEMED NECESSARY FOR THE PROTECTION OF PERSONS AND PROPERTY, POTHOLES OR OTHER PRECISE MAPPING MAY BE COMPLETED TO CONFIRM THE EXACT LOCATION OF ANY SUBSURFACE UTILITIES. NOTIFY OWNER AND ENGINEER WITH ALL UTILITY INFORMATION PRIOR TO CONSTRUCTION.VISIT HTTPS://WWW.FHWA.DOT.GOV/PROGRADMIN/SUEINDEX.CFM FOR MORE INFORMATION.
18.4 SERVICE TAP LOCATIONS ARE APPROXIMATE. CONTRACTOR IS RESPONSIBLE FOR LOCATING AND RESTORING ALL SERVICE CONNECTIONS DISTURBED BY PROJECT.
19. THE CONTRACTOR AT THE CONTRACTORS EXPENSE SHALL FURNISH THE OWNER AND ENGINEER OF RECORD A COMPLETE SET OF CONSTRUCTION RECORD DRAWINGS ("AS-BUILTS") FOR THE CONSTRUCTED IMPROVEMENTS. THE AS-BUILT SET SHALL SHOW SUFFICIENT DIMENSION TIES TO PERMANENT SURFACE FEATURES OR NORTHING/EASTING POINTS FOR ALL BURIED FACILITIES TO ALLOW FOR FUTURE LOCATING. THE AS-BUILT SET SHALL SHOW AS-BUILT CONTOURS AND ELEVATIONS OF ASPHALT AND CONCRETE FLATWORK, FLOWLINES, GRADE BREAKS, STAIRS, CROSS-SLOPES, HIGH AND LOW POINTS, AND ADDITIONAL ELEVATIONS TO DEMONSTRATE IMPROVEMENTS WERE CONSTRUCTED PER PLANS. THE AS-BUILT SET SHALL SHOW ELEVATIONS OF ALL DETENTION/WATER QUALITY FACILITIES, INCLUDING BUT NOT LIMITED TO BERMS, SPILLWAYS, BASIN BOTTOM, PIPE INVERTS, AND CONTROL STRUCTURE FEATURES (AS SURVEYED AND STAMPED BY A CERTIFIED P.L.S.). THE AS-BUILT SET SHALL ALSO INCLUDE ELEVATIONS OF MANHOLES, PIPES, INLETS, GRATES, AND SIZES OF ALL UTILITIES. THE AS-BUILT SET SHALL SHOW ANY AND ALL VARIATIONS FROM THE APPROVED PLAN. ENGINEER WILL PRODUCE FINAL RECORD DRAWINGS.




DETAIL TITLE



SECTION CALLOUT



DETAIL MARKER



SURVEY LEGEND

Table of survey legend symbols for water line abandoned, water line, overheard utility line, underground gas line, underground telephone line, storm sewer line, sanitary sewer line, right-of-way line, lot lines, fence line, edge of pavement, back of curb, fl of curb, back of sidewalk, control lines, bench mark, backflow preventer, catch basin / curb storm inlet, clean out (sanitary), curb stop, fire hydrant, guy wire anchor, mailbox, manhole (electric), manhole (gas), manhole (sanitary), manhole (storm), manhole (telephone), manhole (tv), manhole (water), meter (gas), meter (water), pedestal (telephone), pedestal (tv), property pin, street light, survey monument (city), survey monument (control point), survey monument (type noted), tree (dia. size), utility pole, valve (gas), valve (irrigation), valve (sprinkler head), valve (water).

Table with columns for description and date, containing revision history.

Table with columns for description and date, containing drawing approval information.

Table with columns for description and date, containing scale information.



2022 WATERLINE REPLACEMENT PROJECT - PHASE 2 LEGENDS, NOTES, AND ABBREVIATIONS GO.1

**STORMWATER MANAGEMENT PLAN (SWMP)**

THIS STORMWATER MANAGEMENT PLAN IS TO BE RETAINED AND MAINTAINED ONSITE INCLUDING FINAL LANDSCAPING PLANS AND ANY OTHER EROSION CONTROL DOCUMENTATION. A SWMP ADMINISTRATOR WILL BE DESIGNATED BY THE CONTRACTOR AND IS RESPONSIBLE FOR DEVELOPING, IMPLEMENTING, MAINTAINING, AND REVISING THIS SWMP. THE SWMP ADMINISTRATOR IS THE CONTACT FOR ALL SWMP-RELATED ISSUES AND IS RESPONSIBLE FOR ITS ACCURACY, COMPLETENESS, AND IMPLEMENTATION. THE FOLLOWING HAS BEEN DESIGNATED AS THE SWMP ADMINISTRATOR FOR THIS PROJECT:

NAME: \_\_\_\_\_  
 CONTACT INFO: \_\_\_\_\_

THE SITE IS LOCATED CONTAINED BY ORCHARD AVE AND ELM AVE ON THE NORTH AND SOUTH RESPECTIVELY AND BY N 17TH ST AND N 26TH ST ON THE WEST AND EAST RESPECTIVELY, AND AT APPROXIMATELY 39° 4' 51.5" N LATITUDE, 108° 32' 43.4" W LONGITUDE. THE PROPOSED PROJECT CONSISTS OF UTILITY INFRASTRUCTURE, UTILITY SERVICE CONNECTIONS, PAVING OF SIDEWALKS AND ROADWAYS, CONSTRUCTION IN THE CITY OF GRAND JUNCTION, COLORADO. THE TOTAL SITE AREA IS APPROXIMATELY 10.7 ACRES WITH A TOTAL DISTURBANCE OF 1.2 ACRES. NO AREAS GREATER THAN 40 ACRES SHALL BE DISTURBED AT ANY GIVEN TIME. NO CONSTRUCTION ACTIVITIES SHALL OCCUR OFFSITE OR OUTSIDE OF THE CONSTRUCTION LIMITS SHOWN ON THE CONSTRUCTION DOCUMENTS. THE SEQUENCE OF CONSTRUCTION STARTS IS AS FOLLOWS:

PHASE	ESTIMATED	ACTUAL
CONSTRUCTION START	AUGUST, 2022	_____
UTILITY CONSTRUCTION	AUGUST, 2022	_____
PAVING	OCTOBER, 2022	_____
SITE RESTORATION	DECEMBER, 2022	_____

THE EXISTING SITE CONSISTS OF DEVELOPED LAND AND VEGETATION AND IS APPROXIMATELY 1% COVERED WITH VEGETATIVE GROUND COVER. A DRAINAGE REPORT WAS NOT COMPLETED AS HISTORIC AND DEVELOPED RUNOFFS WERE NOT ALTERED.

OFFSITE RUNOFF FLOWS ONTO THE PROPERTY AT ORCHARD AVE FROM THE NORTH. ONSITE FLOWS ARE DIRECTED TO THE GUTTERS AND STORM DRAINS. THERE ARE NO ONSITE DETENTION SITES. STORMWATER IS DISCHARGED FROM THIS SITE TO INDIAN WASH WHICH ULTIMATELY DRAINS INTO THE COLORADO RIVER. A DRAINAGE REPORT FOR THIS DEVELOPMENT HAS BEEN SUBMITTED TO THE ENGINEER OF THE CITY OF GRAND JUNCTION.

OTHER POTENTIAL POLLUTION SOURCES SUCH AS VEHICLE FUELING, VEHICLE WASHING, LOADING/ UNLOADING AREAS ARE LOCATED ONSITE. NON-STORMWATER COMPONENTS OF THE DISCHARGE LANDSCAPE IRRIGATION RETURN FLOW ARE LOCATED ONSITE.

**BEST MANAGEMENT PRACTICES FOR STORMWATER MANAGEMENT**

NON STRUCTURAL BMP'S WILL BE IMPLEMENTED TO THE MAXIMUM EXTENT POSSIBLE. THE UTILIZATION OF NON STRUCTURAL BMP'S WILL BE AN ONGOING PROCESS DIRECTED AT PREVENTING EROSION. THE NON STRUCTURAL BMP'S WILL RECEIVE CONTINUOUS EMPHASIS THROUGHOUT CONSTRUCTION BECAUSE THEY AVERT PROBLEMS BEFORE THEY OCCUR AND REDUCE THE NEED FOR STRUCTURAL BMP'S. NON STRUCTURAL BMP'S WILL CONSIST PRIMARILY OF PRESERVATION OF EXISTING MATURE VEGETATION AND TREES, PLANNING AND SCHEDULING CONSTRUCTION ACTIVITIES AIMED AT ACHIEVING THE GOAL OF MINIMIZING EROSION. FURTHERMORE, CONSTRUCTION PERSONNEL WILL BE INSTRUCTED AND SUPERVISED IN CONSTRUCTION METHODS CONSISTENT WITH EROSION PREVENTION PRACTICES.

PLANNED STRUCTURAL BMP'S FOR EROSION AND SEDIMENT CONTROL ARE SHOWN ON THE EROSION AND SEDIMENTATION CONTROL PLAN. IMPLEMENTING THESE MEASURES SHOULD MINIMIZE NUISANCE SILT AND SEDIMENTATION EXITING THE SITE AND PREVENT CLOGGING EXISTING STORM SEWERS AND STREET GUTTERS.

APPLICATION OF THESE BMP'S FOR STORMWATER MANAGEMENT ARE FOR CONSTRUCTION PERIODS AND ARE CONSIDERED TEMPORARY. POST-DEVELOPMENT STORMWATER MANAGEMENT IS PROVIDED THROUGH STORM COLLECTION SYSTEM.

**VEHICLE TRACKING CONTROL (VTC):**

A STABILIZED CONSTRUCTION ENTRANCE WILL BE PROVIDED AT ALL ENTRANCES AND EXITS TO THE CONSTRUCTION SITES. THE CONSTRUCTION ACCESS AND PARKING WILL BE GRADED AND COVERED WITH A CRUSHED STONE BASE COURSE DURING CONSTRUCTION. THE VEHICLE TRACKING CONTROL WILL BE RELOCATED WITH THE CONSTRUCTION ACCESS AS NECESSARY.

**SEDIMENT CONTROL LOGS (SCL):**

SEDIMENT CONTROL LOGS SHALL BE INSTALLED WITH RESPECT TO PROPOSED DRAINAGE PATTERNS. SEDIMENT CONTROL LOGS SHALL BE CONSTRUCTED IN THE GUTTERS AND ALONG ANY DRAINAGE AREAS SUBJECT TO EROSION. THE SEDIMENT CONTROL LOGS SHALL BE INSTALLED AT THE DOWNHILL SIDE OF THE EXISTING SLOPES ACROSS THE SITE AND AT ALL POINT DISCHARGE AREAS WHETHER SHOWN OR NOT, SEDIMENT CONTROL LOGS SHALL BE MAINTAINED AS NEEDED THROUGHOUT THE CONSTRUCTION PROCESS. SEDIMENT CONTROL LOGS WILL REMAIN UNTIL THE STORM SEWER STRUCTURES ARE COMPLETED AND GROUND COVER IS EFFECTIVE.

**INLET PROTECTION (IP):**

THE INLET PROTECTION WILL BE INSTALLED AS THE STORM SEWER STRUCTURES ARE CONSTRUCTED. EACH INLET ON THE PROPOSED STORM SEWER SYSTEM WILL HAVE A TEMPORARY INLET SEDIMENT TRAP CONSTRUCTED AROUND IT. IN PAVED AREAS, THIS TRAP CONSISTS OF WIRE MESH SOCKS, CONCRETE BLOCKS, AND GRAVEL BAGS TO FILTER THE STORM RUNOFF AND ALLOW ANY SILT TO SETTLE OUT.

**CONCRETE WASHOUT AREA:**

CONCRETE WASHOUTS SHALL BE USED ON SITE DURING THE CONSTRUCTION OF FLATWORK SHOWN ON THE PLANS. CONTRACTOR TO USE ONLY ROLL-OFF/PORTABLE STYLE WASHOUT CONTAINERS, PIT STYLE CLEANOUTS WILL NOT BE ACCEPTED ON THIS SITE.

**DUST CONTROL MEASURES:**

DISTURBED AREAS NOT YET READY TO BE SEEDED, LANDSCAPED, PAVED, OR OTHERWISE STABILIZED SHALL BE WATERED, OR RIPPED AS NECESSARY TO PRECLUDE VISIBLE DUST EMISSIONS.

ITEMS ARE SCHEDULED TO BE IMPLEMENTED ACCORDING TO THE CONSTRUCTION SCHEDULE. AS WORK PROCEEDS, IMPLEMENTATION OF INDIVIDUAL BMP'S IS TO COINCIDE WITH THE CONSTRUCTION THEREBY MINIMIZING THE EXPOSURE OF UNPROTECTED AREAS. INLET PROTECTION (FOR EXISTING INLETS), AND GRAVELING OF THE CONSTRUCTION ENTRANCE WILL BE PERFORMED WHEN THE GROUND IS DISTURBED AND THE PROJECT EXCAVATION BEGINS. FUGITIVE DUST EMISSIONS RESULTING FROM GRADING ACTIVITIES AND/OR WIND SHALL BE CONTROLLED USING THE BEST AVAILABLE CONTROL TECHNOLOGY AS DEFINED BY THE COLORADO DEPARTMENT OF HEALTH AT THE TIME OF GRADING. THE GRAVELING IS TO BE MAINTAINED AND EXTENDED CONSTRUCTION PROGRESSES ESPECIALLY AROUND THE BUILDING SITE. THE STRUCTURAL BMP'S ARE TO BE REMOVED, AS THE PERMANENT LANDSCAPING INSTALLATIONS ARE COMPLETED.

THE EROSION AND SEDIMENT CONTROL PLAN MAY BE MODIFIED BY THE DEPARTMENT OF HIGHWAYS AND TRANSPORTATION, OWNER'S ENGINEER, CITY OF GRAND JUNCTION OR ITS AUTHORIZED REPRESENTATIVE AS FIELD CONDITIONS WARRANT.

**STORMWATER DETENTION AND WATER QUALITY:**

STORMWATER DETENTION AND WATER QUALITY IS ACHIEVED THROUGH THE EXISTING STORMWATER COLLECTION SYSTEM.

**TEMPORARY SEEING AND MULCHING:**

ALL SEEDS FURNISHED SHALL BE FREE FROM NOXIOUS SEEDS SUCH AS RUSSIAN OR CANADIAN THISTLE, COURSE FESCUE, EUROPEAN BINDWEED, JOHNSON GRASS, KNAPWEED, AND LEAFY SPURGE. THE FORMULA USED FOR DETERMINING THE QUALITY OF PURE LIVE SEED (PLS) SHALL BE (POUNDS OF SEED) X (PURITY) X (GERMINATION) = POUNDS OF PURE LIVE SEED (PLS). SEEING RECOMMENDATIONS ARE PROVIDED BELOW, BUT MAY BE MODIFIED WITH THE OWNER'S APPROVAL TO MAKE THE BEST USE OF EXISTING CLEARINGS AND GRUBBINGS:

SPECIES	COMMON NAME	VARIETY	PLS RATE(%) / ACRE
AGROPYRON CRISTATUM	CRESTED WHEATGRASS	EPHRAIM	6
AGROPYRON SMITHI	WESTERN WHEATGRASS	ARRIBA	16
BROMIS INERMIS	SMOOTH BROME	LINCOLN	12
SPOROBOLUS AIROIDES	ALKALI SACATON		0.5
PLEURAPHIS JAMESII	VIVA GALLETIA GRASS		12
DACTYLIS GLOMERATA	ORCHARD GRASS	PAIUTE	4
ARRHENATHERUM ELATES	TALL OATGRASS		ADD IN
LILIUM PERENNE	PERENNIAL RYEGRASS	TETRAPLOID	8

ALL SEEDS SHALL BE DRILLED NOT HYDROSEEDED. ALL DISTURBED AREAS SHALL BE SEEDED AND CRIMP MULCHED IF PERMANENT VEGETATION IS NOT IMMEDIATELY INSTALLED. AFTER SEEING HAS BEEN COMPLETED, A RATE OF 4,000 LBS. OF STRAW PER ACRE SHALL BE APPLIED UNIFORMLY, CRIMPED IN WITH A CRIMPER OR OTHER APPROVED EQUIPMENT OR OTHERWISE ATTACHED. A TACKIFIER OR JUTE NETTING TO ATTACH MULCH MAY BE USED WITH THE OWNER'S APPROVAL. THE SEEDED AREA SHALL BE CRIMPED MULCHED AND THE MULCH ATTACHED WITHIN TWENTY-FOUR (24) HOURS AFTER SEEING. AREAS NOT MULCHED AND ATTACHED WITHIN TWENTY-FOUR (24) HOURS AFTER SEEING MUST BE RESEEDED WITH THE SPECIFIED MIX AT THE CONTRACTOR'S EXPENSE, PRIOR TO MULCHING AND ATTACHING. ON STEEP SLOPES OR OTHER SPECIFIED AREAS AS SHOWN ON THE PLANTING PLAN, WHICH ARE DIFFICULT TO MULCH AND ATTACH BY CONVENTIONAL METHOD, BURLAP OR OTHER BLANKETING MATERIALS PROPERLY ANCHORED AND SECURED MAY BE USED WHEN APPROVED BY THE CITY OF GRAND JUNCTION.

**PERMANENT STABILIZATION MEASURES:**

PERMANENT LANDSCAPING WILL INCLUDE SEEING TO OPEN AREAS. NATIVE PERENNIAL SEEING WILL BE ESTABLISHED IN NON-IRRIGATED AREAS AND SOD OR OTHER VEGETATIVE COVER WILL BE ESTABLISHED IN IRRIGATED OPEN AREAS. ALL PERMANENT STABILIZATION MEASURES WILL BE SPECIFIED BY THE LANDSCAPE ARCHITECT OR OWNER.

**MATERIALS AND SPILL PREVENTION:**

THE CONTRACTOR WILL STORE CONSTRUCTION MATERIALS AND EQUIPMENT IN CONFINED AREAS ON SITE FROM WHICH RUNOFF WILL BE CONTAINED AND FILTERED. MATERIALS WILL BE STORED OFF THE GROUND AND PROTECTED FROM THE WEATHER BY A COVER OR STORED IN A CONTAINER SUCH AS A VAN OR TRAILER. AN EARTHEN DIKE WILL BE CONSTRUCTED AROUND THE PERIMETER OF THE FUEL STORAGE AREA TO PREVENT MATERIALS FROM CONTACT WITH SURFACE RUNOFF. EQUIPMENT MAINTENANCE WILL BE PERFORMED IN A DESIGNATED AREA AND STANDARD MAINTENANCE PROCEDURES, SUCH AS THE USE OF DRIP PANS, WILL BE USED TO CONTAIN PETROLEUM PRODUCTS.

**INSPECTION AND MAINTENANCE:**

THE EROSION CONTROL MEASURES WILL BE INSPECTED DAILY DURING CONSTRUCTION BY THE CONTRACTOR AND AFTER EACH RAIN EVENT. ALL INSPECTIONS SHALL BE DOCUMENTED AND SHALL INCLUDE THE DATE OF INSPECTION, ANY INCIDENCE OF NON-COMPLIANCE, SIGNED CERTIFICATION THAT THE SITE IS IN COMPLIANCE, AND ANY NOTES, DRAWINGS, MAPS, ETC. PERTAINING TO REPAIRS. COPIES OF ALL DOCUMENTATION SHALL BE DISTRIBUTED TO MUNICIPALITIES AND OWNER ON A REGULAR BASIS AS SPECIFIED BY OWNER. STRAW BALE BARRIERS WILL BE CHECKED FOR UNDERMINING AND BYPASS AND REPAIRED OR EXPANDED AS NEEDED. SEDIMENT SHOULD BE REMOVED FROM INLET FILTERS BEFORE ONE HALF OF THE DESIGN DEPTH HAS BEEN FILLED. SEDIMENTS DEPOSITED IN THE PUBLIC RIGHTS-OF-WAY WILL BE REMOVED IMMEDIATELY. THE TEMPORARY VEGETATION OF BARE SOILS WILL BE CHECKED REGULARLY AND AREAS WHERE IT IS LOST OR DAMAGED WILL BE RESEEDED. AT MINIMUM THE CONTRACTOR OR HIS AGENT SHALL INSPECT ALL BMP'S EVERY 14 DAYS AND AFTER SIGNIFICANT PRECIPITATION OR SNOWMELT EVENTS. INSTALLATIONS AND MODIFICATIONS AS REQUIRED BY THE CITY OF GRAND JUNCTION WILL BE IMPLEMENTED WITHIN 48 HOURS OF NOTIFICATION. CONTRACTOR SHALL REMOVE TEMPORARY EROSION CONTROL MEASURES AND REPAIR AREAS AS REQUIRED AFTER VEGETATION IS ESTABLISHED AND ACCEPTED BY OWNER AND MUNICIPALITY.

**FINAL STABILIZATION AND LONG-TERM STORMWATER QUALITY:**

FINAL STABILIZATION IS REACHED WHEN ALL SOIL DISTURBING ACTIVITIES AT THE SITE HAVE BEEN COMPLETED, AND UNIFORM VEGETATIVE COVER HAS BEEN ESTABLISHED WITH A DENSITY OF AT LEAST 70% OR PRE-DISTURBANCE LEVELS OR EQUIVALENT PERMANENT, PHYSICAL EROSION REDUCTION METHODS HAVE BEEN EMPLOYED. FINAL STABILIZATION WILL BE ACHIEVED USING SOD, NATIVE SEEING, PERMANENT BMP'S, AND OTHER METHODS. CONTRACTOR SHALL BE RESPONSIBLE FOR FINAL STABILIZATION REGARDLESS OF ACCEPTANCE BY OWNER OF THE CONTRACTOR ITEM.

N:\071158\Drawings\Phase 2 - Drawings\071158 - 01-EGP-00.dwg, 3/13/2023 - 2:22 PM, NJM

REVISION	DESCRIPTION	DATE
REVISION $\Delta$	_____	_____
REVISION $\Delta$	_____	_____
REVISION $\Delta$	_____	_____
REVISION $\Delta$	_____	_____

DRAWN BY	ZCF	DATE	3/8/2023
DESIGNED BY	LAL/ZCF	DATE	3/8/2023
CHECKED BY	JJM	DATE	12/8/2022
APPROVED BY	_____	DATE	_____

SCALES:
PLAN & PROFILE




**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2 EROSION CONTROL NOTES**

CE1.0



EC-8 Temporary Outlet Protection (TOP)



TEMPORARY OUTLET PROTECTION PLAN




TABLE OP-1. TEMPORARY OUTLET PROTECTION SIZING TABLE

PIPE DIAMETER, D <sub>o</sub> (INCHES)	DISCHARGE, Q (CFS)	APRON LENGTH, L <sub>a</sub> (FT)	RIPRAP D50 DIAMETER MIN (INCHES)
8	2.5	5	4
	5	10	6
12	5	10	4
	10	13	6
	10	10	6
	20	16	9
	30	23	12
	40	26	16
24	30	16	9
	40	26	9
	50	26	12
	60	30	16

OP-1. TEMPORARY OUTLET PROTECTION


TOP-2 Urban Drainage and Flood Control District  
Urban Storm Drainage Criteria Manual Volume 3 November 2010

Temporary Outlet Protection (TOP) EC-8

- TEMPORARY OUTLET PROTECTION INSTALLATION NOTES**
- SEE PLAN VIEW FOR:
    - LOCATION OF OUTLET PROTECTION.
    - DIMENSIONS OF OUTLET PROTECTION.
  - DETAIL IS INTENDED FOR PIPES WITH SLOPE  $\leq$  10%. ADDITIONAL EVALUATION OF RIPRAP SIZING AND OUTLET PROTECTION DIMENSIONS REQUIRED FOR STEEPER SLOPES.
  - TEMPORARY OUTLET PROTECTION INFORMATION IS FOR OUTLETS INTENDED TO BE UTILIZED LESS THAN 2 YEARS.
- TEMPORARY OUTLET PROTECTION INSPECTION AND MAINTENANCE NOTES**
- INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION. MAINTENANCE OF BMPs SHOULD BE PROACTIVE, NOT REACTIVE. INSPECT BMPs AS SOON AS POSSIBLE (AND ALWAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE EROSION, AND PERFORM NECESSARY MAINTENANCE.
  - FREQUENT OBSERVATIONS AND MAINTENANCE ARE NECESSARY TO MAINTAIN BMPs IN EFFECTIVE OPERATING CONDITION. INSPECTIONS AND CORRECTIVE MEASURES SHOULD BE DOCUMENTED THOROUGHLY.
  - WHERE BMPs HAVE FAILED, REPAIR OR REPLACEMENT SHOULD BE INITIATED UPON DISCOVERY OF THE FAILURE.
- NOTE: MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN DIFFERENCES ARE NOTED.
- (DETAILS ADAPTED FROM AURORA, COLORADO AND PREVIOUS VERSION OF VOLUME 3, NOT AVAILABLE IN AUTOCAD)

November 2010 Urban Drainage and Flood Control District  
Urban Storm Drainage Criteria Manual Volume 3 TOP-3

SM-3 Construction Fence (CF)



CF-1. PLASTIC MESH CONSTRUCTION FENCE

- CONSTRUCTION FENCE INSTALLATION NOTES**
- SEE PLAN VIEW FOR:
    - LOCATION OF CONSTRUCTION FENCE.
  - CONSTRUCTION FENCE SHOWN SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIVITIES.
  - CONSTRUCTION FENCE SHALL BE COMPOSED OF ORANGE, CONTRACTOR-GRADE MATERIAL THAT IS AT LEAST 4' HIGH. METAL POSTS SHOULD HAVE A PLASTIC CAP FOR SAFETY.
  - STUDDED STEEL TEE POSTS SHALL BE UTILIZED TO SUPPORT THE CONSTRUCTION FENCE. MAXIMUM SPACING FOR STEEL TEE POSTS SHALL BE 10'.
  - CONSTRUCTION FENCE SHALL BE SECURELY FASTENED TO THE TOP, MIDDLE, AND BOTTOM OF EACH POST.


CF-2 Urban Drainage and Flood Control District  
Urban Storm Drainage Criteria Manual Volume 3 November 2010

Construction Fence (CF) SM-3

- CONSTRUCTION FENCE MAINTENANCE NOTES**
- INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION. MAINTENANCE OF BMPs SHOULD BE PROACTIVE, NOT REACTIVE. INSPECT BMPs AS SOON AS POSSIBLE (AND ALWAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE EROSION, AND PERFORM NECESSARY MAINTENANCE.
  - FREQUENT OBSERVATIONS AND MAINTENANCE ARE NECESSARY TO MAINTAIN BMPs IN EFFECTIVE OPERATING CONDITION. INSPECTIONS AND CORRECTIVE MEASURES SHOULD BE DOCUMENTED THOROUGHLY.
  - WHERE BMPs HAVE FAILED, REPAIR OR REPLACEMENT SHOULD BE INITIATED UPON DISCOVERY OF THE FAILURE.
  - CONSTRUCTION FENCE SHALL BE REPAIRED OR REPLACED WHEN THERE ARE SIGNS OF DAMAGE SUCH AS RIPS OR SACS. CONSTRUCTION FENCE IS TO REMAIN IN PLACE UNTIL THE UPSTREAM DISTURBED AREA IS STABILIZED AND APPROVED BY THE LOCAL JURISDICTION.
  - WHEN CONSTRUCTION FENCES ARE REMOVED, ALL DISTURBED AREAS ASSOCIATED WITH THE INSTALLATION, MAINTENANCE, AND/OR REMOVAL OF THE FENCE SHALL BE COVERED WITH TOPSOIL, SEEDS AND MULCHED, OR OTHERWISE STABILIZED AS APPROVED BY LOCAL JURISDICTION.
- NOTE: MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN DIFFERENCES ARE NOTED.
- (DETAIL ADAPTED FROM TOWN OF PARKER, COLORADO, NOT AVAILABLE IN AUTOCAD)


November 2010 Urban Drainage and Flood Control District  
Urban Storm Drainage Criteria Manual Volume 3 CF-3

SC-6 Inlet Protection (IP)



IP-1. BLOCK AND ROCK SOCK SUMP OR ON GRADE INLET PROTECTION

- BLOCK AND CURB SOCK INLET PROTECTION INSTALLATION NOTES**
- SEE ROCK SOCK DESIGN DETAIL FOR INSTALLATION REQUIREMENTS.
  - CONCRETE "CINDER" BLOCKS SHALL BE LAID ON THEIR SIDES AROUND THE INLET IN A SINGLE ROW, ABUTTING ONE ANOTHER WITH THE OPEN END FACING AWAY FROM THE CURB.
  - BRIVEL BASS SHALL BE PLACED AROUND CONCRETE BLOCKS, GLOSSELY ABUTTING ONE ANOTHER AND JOINTED TOGETHER IN ACCORDANCE WITH ROCK SOCK DESIGN DETAIL.




IP-2. CURB ROCK SOCKS UPSTREAM OF INLET PROTECTION

- CURB ROCK SOCK INLET PROTECTION INSTALLATION NOTES**
- SEE ROCK SOCK DESIGN DETAIL INSTALLATION REQUIREMENTS.
  - PLACEMENT OF THE SOCK SHALL BE APPROXIMATELY 30 DEGREES FROM PERPENDICULAR IN THE OPPOSITE DIRECTION OF FLOW.
  - SOCKS ARE TO BE FLUSH WITH THE CURB AND SPACED A MINIMUM OF 5 FEET APART.
  - AT LEAST TWO CURB SOCKS IN SERIES ARE REQUIRED UPSTREAM OF ON-GRADE INLETS.


IP-4 Urban Drainage and Flood Control District  
Urban Storm Drainage Criteria Manual Volume 3 August 2013

Inlet Protection (IP) SC-6



IP-3. ROCK SOCK SUMP/AREA INLET PROTECTION

- ROCK SOCK SUMP/AREA INLET PROTECTION INSTALLATION NOTES**
- SEE ROCK SOCK DESIGN DETAIL FOR INSTALLATION REQUIREMENTS.
  - STRAW WATTLES/SEDIMENT CONTROL LOGS MAY BE USED IN PLACE OF ROCK SOCKS FOR INLETS IN PERVIOUS AREAS. INSTALL PER SEDIMENT CONTROL LOG DETAIL.



IP-4. SILT FENCE FOR SUMP INLET PROTECTION

- SILT FENCE INLET PROTECTION INSTALLATION NOTES**
- SEE SILT FENCE DESIGN DETAIL FOR INSTALLATION REQUIREMENTS.
  - POSTS SHALL BE PLACED AT EACH CORNER OF THE INLET AND AROUND THE EDGES AT A MAXIMUM SPACING OF 3 FEET.
  - STRAW WATTLES/SEDIMENT CONTROL LOGS MAY BE USED IN PLACE OF SILT FENCE FOR INLETS IN PERVIOUS AREAS. INSTALL PER SEDIMENT CONTROL LOG DETAIL.

August 2013 Urban Drainage and Flood Control District  
Urban Storm Drainage Criteria Manual Volume 3 IP-5

SC-6 Inlet Protection (IP)

- GENERAL INLET PROTECTION INSTALLATION NOTES**
- SEE PLAN VIEW FOR:
    - LOCATION OF INLET PROTECTION.
    - TYPE OF INLET PROTECTION (IP.1, IP.2, IP.3, IP.4, IP.5, IP.6)
  - INLET PROTECTION SHALL BE INSTALLED PROMPTLY AFTER INLET CONSTRUCTION OR PAVING IS COMPLETE (TYPICALLY WITHIN 48 HOURS). IF A RAINFALL/RUNOFF EVENT IS FORECAST, INSTALL INLET PROTECTION PRIOR TO ONSET OF EVENT.
  - MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN DIFFERENCES ARE NOTED.
- INLET PROTECTION MAINTENANCE NOTES**
- INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION. MAINTENANCE OF BMPs SHOULD BE PROACTIVE, NOT REACTIVE. INSPECT BMPs AS SOON AS POSSIBLE (AND ALWAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE EROSION, AND PERFORM NECESSARY MAINTENANCE.
  - FREQUENT OBSERVATIONS AND MAINTENANCE ARE NECESSARY TO MAINTAIN BMPs IN EFFECTIVE OPERATING CONDITION. INSPECTIONS AND CORRECTIVE MEASURES SHOULD BE DOCUMENTED THOROUGHLY.
  - WHERE BMPs HAVE FAILED, REPAIR OR REPLACEMENT SHOULD BE INITIATED UPON DISCOVERY OF THE FAILURE.
  - SEDIMENT ACCUMULATED UPSTREAM OF INLET PROTECTION SHALL BE REMOVED AS NECESSARY TO MAINTAIN BMP EFFECTIVENESS, TYPICALLY WHEN STORAGE VOLUME REACHES 50% OF CAPACITY, A DEPTH OF 6" WHEN SILT FENCE IS USED, OR 1/4 OF THE HEIGHT FOR STRAW BALES.
  - INLET PROTECTION IS TO REMAIN IN PLACE UNTIL THE UPSTREAM DISTURBED AREA IS PERMANENTLY STABILIZED, UNLESS THE LOCAL JURISDICTION APPROVES EARLIER REMOVAL OF INLET PROTECTION IN STREETS.
  - WHEN INLET PROTECTION AT AREA INLETS IS REMOVED, THE DISTURBED AREA SHALL BE COVERED WITH TOP SOIL, SEEDS AND MULCHED, OR OTHERWISE STABILIZED IN A MANNER APPROVED BY THE LOCAL JURISDICTION.
- (DETAIL ADAPTED FROM TOWN OF PARKER, COLORADO AND CITY OF AURORA, COLORADO, NOT AVAILABLE IN AUTOCAD)
- NOTE: MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN DIFFERENCES ARE NOTED.
- NOTE: THE DETAILS INCLUDED WITH THIS FACT SHEET SHOW COMMONLY USED, CONVENTIONAL METHODS OF INLET PROTECTION IN THE DENVER METROPOLITAN AREA. THERE ARE MANY PROPRIETARY INLET PROTECTION METHODS ON THE MARKET. UDFCD NEITHER ENDORSES NOR DISCOURAGES USE OF PROPRIETARY INLET PROTECTION. HOWEVER, IN THE EVENT PROPRIETARY METHODS ARE USED, THE APPROPRIATE DETAIL FROM THE MANUFACTURER MUST BE INCLUDED IN THE SWEEP AND THE BMP MUST BE INSTALLED AND MAINTAINED AS SHOWN IN THE MANUFACTURER'S DETAILS.
- NOTE: SOME MUNICIPALITIES DISCOURAGE OR PROHIBIT THE USE OF STRAW BALES FOR INLET PROTECTION. CHECK WITH LOCAL JURISDICTION TO DETERMINE IF STRAW BALE INLET PROTECTION IS ACCEPTABLE.


IP-8 Urban Drainage and Flood Control District  
Urban Storm Drainage Criteria Manual Volume 3 August 2013

N:\107115a\Drawings\Phase 2 - Drawings\107115a - 01-EDP-00.dwg, 3/13/2023, 2:22 PM, NLM

REVISION	DESCRIPTION	DATE	DRAWN BY	DATE
REVISION			ZCF	3/8/2023
REVISION			LAL/ZCF	3/8/2023
REVISION			JJM	12/8/2022
REVISION				

SCALES:

PLAN & PROFILE
----------------




2022 WATERLINE REPLACEMENT PROJECT - PHASE 2 EROSION CONTROL NOTES

JVA, Inc.  
817 Colorado Avenue, Suite 301  
Glenwood Springs, CO 81601  
970.404.3100  
www.jvajva.com  
Boulder • Fort Collins • Winter Park  
Glenwood Springs • Denver

CE1.1



**Stabilized Staging Area (SSA) SM-6**



**SSA-1. STABILIZED STAGING AREA**

- STABILIZED STAGING AREA INSTALLATION NOTES**
- SEE PLAN VIEW FOR -LOCATION OF STAGING AREA(S). -CONTRACTOR MAY ADJUST LOCATION AND SIZE OF STAGING AREA WITH APPROVAL FROM THE LOCAL JURISDICTION.
  - STABILIZED STAGING AREA SHOULD BE APPROPRIATE FOR THE NEEDS OF THE SITE. OVERSIZING RESULTS IN A LARGER AREA TO STABILIZE FOLLOWING CONSTRUCTION.
  - STAGING AREA SHALL BE STABILIZED PRIOR TO OTHER OPERATIONS ON THE SITE.
  - THE STABILIZED STAGING AREA SHALL CONSIST OF A MINIMUM 3" THICK GRANULAR MATERIAL.
  - UNLESS OTHERWISE SPECIFIED BY LOCAL JURISDICTION, ROCK SHALL CONSIST OF DOT SECT. #703, AASHTO #3 COARSE AGGREGATE OR 6" (MINUS) ROCK.
  - ADDITIONAL PERIMETER BMPs MAY BE REQUIRED INCLUDING BUT NOT LIMITED TO SILT FENCE AND CONSTRUCTION FENCING.

- STABILIZED STAGING AREA MAINTENANCE NOTES**
- INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION. MAINTENANCE OF BMPs SHOULD BE PROACTIVE, NOT REACTIVE. INSPECT BMPs AS SOON AS POSSIBLE (AND ALWAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE EROSION, AND PERFORM NECESSARY MAINTENANCE.
  - FREQUENT OBSERVATIONS AND MAINTENANCE ARE NECESSARY TO MAINTAIN BMPs IN EFFECTIVE OPERATING CONDITION. INSPECTIONS AND CORRECTIVE MEASURES SHOULD BE DOCUMENTED THOROUGHLY.
  - WHERE BMPs HAVE FAILED, REPAIR OR REPLACEMENT SHOULD BE INITIATED UPON DISCOVERY OF THE FAILURE.
  - ROCK SHALL BE REAPPLIED OR REGRADED AS NECESSARY IF RUTTING OCCURS OR UNDERLYING SUBGRADE BECOMES EXPOSED.

November 2010 Urban Drainage and Flood Control District SSA-3  
Urban Storm Drainage Criteria Manual Volume 3


**SM-6 Stabilized Staging Area (SSA)**

**STABILIZED STAGING AREA MAINTENANCE NOTES**


- STABILIZED STAGING AREA SHALL BE ENLARGED IF NECESSARY TO CONTAIN PARKING, STORAGE, AND UNLOADING/LOADING OPERATIONS.
  - THE STABILIZED STAGING AREA SHALL BE REMOVED AT THE END OF CONSTRUCTION THE GRANULAR MATERIAL SHALL BE REMOVED OR, IF APPROVED BY THE LOCAL JURISDICTION, USED ON SITE, AND THE AREA COVERED WITH TOPSOIL, SEEDED AND MULCHED OR OTHERWISE STABILIZED IN A MANNER APPROVED BY LOCAL JURISDICTION.
- NOTE: MANY MUNICIPALITIES PROHIBIT THE USE OF RECYCLED CONCRETE AS GRANULAR MATERIAL FOR STABILIZED STAGING AREAS DUE TO DIFFICULTIES WITH RE-ESTABLISHMENT OF VEGETATION IN AREAS WHERE RECYCLED CONCRETE WAS PLACED.
- NOTE: MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN DIFFERENCES ARE NOTED.
- (DETAILS ADAPTED FROM DOUGLAS COUNTY, COLORADO, NOT AVAILABLE IN AUTOCAD)

SSA-4 Urban Drainage and Flood Control District November 2010  
Urban Storm Drainage Criteria Manual Volume 3

**SC-5 Rock Sock (RS)**



**ROCK SOCK SECTION ROCK SOCK PLAN**



**ROCK SOCK JOINTING**

**GRADATION TABLE**

SIEVE SIZE	MASS PERCENT PASSING SQUARE MESH SIEVES
NO. 4	100
2"	90 - 100
1 1/2"	20 - 55
1"	0 - 15
3/4"	0 - 5
3/8"	0 - 5

MATCHES SPECIFICATIONS FOR NO. 4 COARSE AGGREGATE FOR CONCRETE PER AASHTO M43. ALL ROCK SHALL BE FRACTURED FACE, ALL SIDES.

- ROCK SOCK INSTALLATION NOTES**
- SEE PLAN VIEW FOR -LOCATION(S) OF ROCK SOCKS.
  - CRUSHED ROCK SHALL BE 1/2" (MINUS) IN SIZE WITH A FRACTURED FACE (ALL SIDES) AND SHALL COMPLY WITH GRADATION SHOWN ON THIS SHEET (1/2" MINUS).
  - WIRE MESH SHALL BE FABRICATED OF 10 GAGE POULTRY MESH, OR EQUIVALENT, WITH A MAXIMUM OPENING OF 1/2", RECOMMENDED MINIMUM ROLL WIDTH OF 48"
  - WIRE MESH SHALL BE SECURED USING "HOG RINGS" OR WIRE TIES AT 6" CENTERS ALONG ALL JOINTS AND AT 2" CENTERS ON ENDS OF SOCKS.
  - SOME MUNICIPALITIES MAY ALLOW THE USE OF FILTER FABRIC AS AN ALTERNATIVE TO WIRE MESH FOR THE ROCK ENCLOSURE.

**RS-1. ROCK SOCK PERIMETER CONTROL**

RS-2 Urban Drainage and Flood Control District November 2010  
Urban Storm Drainage Criteria Manual Volume 3

**Rock Sock (RS) SC-5**

**ROCK SOCK MAINTENANCE NOTES**

- INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION. MAINTENANCE OF BMPs SHOULD BE PROACTIVE, NOT REACTIVE. INSPECT BMPs AS SOON AS POSSIBLE (AND ALWAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE EROSION, AND PERFORM NECESSARY MAINTENANCE.
- FREQUENT OBSERVATIONS AND MAINTENANCE ARE NECESSARY TO MAINTAIN BMPs IN EFFECTIVE OPERATING CONDITION. INSPECTIONS AND CORRECTIVE MEASURES SHOULD BE DOCUMENTED THOROUGHLY.
- WHERE BMPs HAVE FAILED, REPAIR OR REPLACEMENT SHOULD BE INITIATED UPON DISCOVERY OF THE FAILURE.
- ROCK SOCKS SHALL BE REPLACED IF THEY BECOME HEAVILY SOILED, OR DAMAGED BEYOND REPAIR.
- SEDIMENT ACCUMULATED UPSTREAM OF ROCK SOCKS SHALL BE REMOVED AS NEEDED TO MAINTAIN FUNCTIONALITY OF THE BMP, TYPICALLY WHEN DEPTH OF ACCUMULATED SEDIMENTS IS APPROXIMATELY 1/3 OF THE HEIGHT OF THE ROCK SOCK.
- ROCK SOCKS ARE TO REMAIN IN PLACE UNTIL THE UPSTREAM DISTURBED AREA IS STABILIZED AND APPROVED BY THE LOCAL JURISDICTION.
- WHEN ROCK SOCKS ARE REMOVED, ALL DISTURBED AREAS SHALL BE COVERED WITH TOPSOIL, SEEDED AND MULCHED OR OTHERWISE STABILIZED AS APPROVED BY LOCAL JURISDICTION.


(DETAIL ADAPTED FROM TOWN OF PARKER, COLORADO AND CITY OF AURORA, COLORADO, NOT AVAILABLE IN AUTOCAD)

NOTE: MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN DIFFERENCES ARE NOTED.

NOTE: THE DETAILS INCLUDED WITH THIS FACT SHEET SHOW COMMONLY USED, CONVENTIONAL METHODS OF ROCK SOCK INSTALLATION IN THE DENVER METROPOLITAN AREA. THERE ARE MANY OTHER SIMILAR PROPRIETARY PRODUCTS ON THE MARKET. UDFCD NEITHER ENDORSES NOR DISCOURAGES USE OF PROPRIETARY PROTECTION PRODUCTS; HOWEVER, IN THE EVENT PROPRIETARY METHODS ARE USED, THE APPROPRIATE DETAIL FROM THE MANUFACTURER MUST BE INCLUDED IN THE SWMP AND THE BMP MUST BE INSTALLED AND MAINTAINED AS SHOWN IN THE MANUFACTURER'S DETAILS.

November 2010 Urban Drainage and Flood Control District RS-3  
Urban Storm Drainage Criteria Manual Volume 3


**Vehicle Tracking Control (VTC) SM-4**



**VTC-1. AGGREGATE VEHICLE TRACKING CONTROL**

November 2010 Urban Drainage and Flood Control District VTC-3  
Urban Storm Drainage Criteria Manual Volume 3


**SM-4 Vehicle Tracking Control (VTC)**



**VTC-2. AGGREGATE VEHICLE TRACKING CONTROL WITH WASH RACK**

VTC-4 Urban Drainage and Flood Control District November 2010  
Urban Storm Drainage Criteria Manual Volume 3

**Vehicle Tracking Control (VTC) SM-4**



**VTC-3. VEHICLE TRACKING CONTROL W/ CONSTRUCTION MAT OR TURF REINFORCEMENT MAT (TRM)**

November 2010 Urban Drainage and Flood Control District VTC-5  
Urban Storm Drainage Criteria Manual Volume 3

**SM-4 Vehicle Tracking Control (VTC)**

**STABILIZED CONSTRUCTION ENTRANCE/EXIT INSTALLATION NOTES**

- SEE PLAN VIEW FOR -LOCATION OF CONSTRUCTION ENTRANCE(S)/EXIT(S). -TYPE OF CONSTRUCTION ENTRANCE(S)/EXIT(S) (WITH/WITHOUT WHEEL WASH, CONSTRUCTION MAT OR TRM).
- CONSTRUCTION MAT OR TRM STABILIZED CONSTRUCTION ENTRANCES ARE ONLY TO BE USED ON SHORT DURATION PROJECTS (TYPICALLY RANGING FROM A WEEK TO A MONTH) WHERE THERE WILL BE LIMITED VEHICULAR ACCESS.
- A STABILIZED CONSTRUCTION ENTRANCE/EXIT SHALL BE LOCATED AT ALL ACCESS POINTS WHERE VEHICLES ACCESS THE CONSTRUCTION SITE FROM PAVED RIGHT-OF-WAYS.
- STABILIZED CONSTRUCTION ENTRANCE/EXIT SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIVITIES.
- A NON-WOVEN GEOTEXTILE FABRIC SHALL BE PLACED UNDER THE STABILIZED CONSTRUCTION ENTRANCE/EXIT PRIOR TO THE PLACEMENT OF ROCK.
- UNLESS OTHERWISE SPECIFIED BY LOCAL JURISDICTION, ROCK SHALL CONSIST OF DOT SECT. #703, AASHTO #3 COARSE AGGREGATE OR 6" (MINUS) ROCK.

- STABILIZED CONSTRUCTION ENTRANCE/EXIT MAINTENANCE NOTES**
- INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION. MAINTENANCE OF BMPs SHOULD BE PROACTIVE, NOT REACTIVE. INSPECT BMPs AS SOON AS POSSIBLE (AND ALWAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE EROSION, AND PERFORM NECESSARY MAINTENANCE.
  - FREQUENT OBSERVATIONS AND MAINTENANCE ARE NECESSARY TO MAINTAIN BMPs IN EFFECTIVE OPERATING CONDITION. INSPECTIONS AND CORRECTIVE MEASURES SHOULD BE DOCUMENTED THOROUGHLY.
  - WHERE BMPs HAVE FAILED, REPAIR OR REPLACEMENT SHOULD BE INITIATED UPON DISCOVERY OF THE FAILURE.
  - ROCK SHALL BE REAPPLIED OR REGRADED AS NECESSARY TO THE STABILIZED ENTRANCE/EXIT TO MAINTAIN A CONSISTENT DEPTH.
  - SEDIMENT TRACKED ONTO PAVED ROADS IS TO BE REMOVED THROUGHOUT THE DAY AND AT THE END OF THE DAY BY SHOVELING OR SWEEPING. SEDIMENT MAY NOT BE WASHED DOWN STORM SEWER DRAINS.

NOTE: MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN DIFFERENCES ARE NOTED.

(DETAILS ADAPTED FROM CITY OF BROOMFIELD, COLORADO, NOT AVAILABLE IN AUTOCAD)

VTC-6 Urban Drainage and Flood Control District November 2010  
Urban Storm Drainage Criteria Manual Volume 3



N:\071156\Drawings\Phase 2 - Drawings\071156 - 01-EDP-00.dwg, 3/13/2023 - 2:22 PM, NLM

REVISION	DESCRIPTION	DATE	DRAWN BY	DATE
REVISION			ZCF	3/8/2023
REVISION			LAL/ZCF	3/8/2023
REVISION			JJM	12/8/2022
REVISION				

SCALES:  
PLAN & PROFILE




**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2 EROSION CONTROL NOTES**



CONTROL POINT TABLE				
CONTROL POINT	DESCRIPTION	NORTHING	EASTING	ELEVATION
3126	CP-10	41795.81	96954.13	4639.84
3127	CP-11	40743.08	97005.72	4629.66
3128	CP-12	41199.29	96968.52	4634.89
3129	CP-21	41452.44	96998.40	4637.72
3649	CP-13	42044.05	97356.14	4638.14
3650	CP-14	41444.52	97361.11	4634.73
3651	CP-15	41108.23	97336.13	4632.84
3652	CP-16	40743.39	97360.98	4629.29
4077	CP-17	40804.63	97669.01	4628.70
4078	CP-18	41274.72	97703.13	4630.45
4079	CP-19	41463.75	97655.80	4632.47
4080	CP-20	42053.54	97683.84	4635.88
4584	CP-22	42059.33	98005.91	4633.86
4585	CP-23	41774.35	98014.62	4631.56
4586	CP-24	41457.58	98008.14	4629.26
4587	CP-25	41256.51	98015.55	4627.75
4588	CP-26	40798.96	97989.08	4626.52
5166	CP-27	41744.25	98383.74	4630.40
5167	CP-28	41757.88	98689.03	4628.58
5375	CP-29	41445.61	99838.33	4622.85
5376	CP-30	41415.31	99548.11	4624.26
5377	CP-32	41418.00	98638.98	4627.47
5378	CP-33	41418.85	98303.94	4628.44

N:\071156\Drawings\Phase 2 - Drawings\071156 - 01-cSP-00.dwg, 3/13/2023 - 2:22 PM, NLM



REVISION	DESCRIPTION	DATE	DRAWN BY	DATE	CHECKED BY	DATE	APPROVED BY	DATE
REVISION			ZCF/NLM	3/8/2023				
REVISION			LAL/ZCF	3/8/2023				
REVISION			JJM	12/8/2022				
REVISION								



**2022 WATERLINE REPLACEMENT  
PROJECT - PHASE 2  
OVERALL UTILITY PLAN**

CO.0






KEY MAP  
NTS

CONSTRUCTION NOTES

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 3 202 - REMOVAL OF CONCRETE. SAW CUT AND REMOVE CONCRETE AS SHOWN. (INDICATED BY CROSS HATCH PATTERN) INCLUDES BUT NOT LIMITED TO CURB, GUTTER, SIDEWALK, DRIVEWAY, SLABS, V-PAN, CURB RAMPS, INTERSECTION CORNERS, APRONS, AND LANDSCAPE BORDERS.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8b/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 581 608.06 - CONCRETE DRAINAGE PAN (6' WIDE)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)





NOTES:

1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-PWP-01.dwg, 3/16/2023 - 8:09 AM, NJM



REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/JJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_




2022 WATERLINE REPLACEMENT  
PROJECT - PHASE 2  
HALL AVE WATER PLAN & PROFILE

C1.0



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 408 102.8/108.3 - CROSS (SIZE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)
- 826 PROTECT EXISTING UTILITY LINE IN PLACE





**NOTES:**

1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-Plan-06.dwg, 3/15/2023 - 6:30 PM, NLM

REVISION	DESCRIPTION	DATE



DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 18TH ST WATER PLAN & PROFILE**


**C2.0**





**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 3 202 - REMOVAL OF CONCRETE. SAW CUT AND REMOVE CONCRETE AS SHOWN. (INDICATED BY CROSS HATCH PATTERN) INCLUDES BUT NOT LIMITED TO CURB, GUTTER, SIDEWALK, DRIVEWAY, SLABS, V-PAN, CURB RAMPS, INTERSECTION CORNERS, APRONS, AND LANDSCAPE BORDERS.
- 22 202 - REMOVE EXISTING FIRE HYDRANT AND RETURN TO CITY SHOPS.
- 100 210 - RESET LANDSCAPE GROUND COVER. CONTRACTOR SHALL REMOVE GROUND COVER AND ANY UNDERLYING WEED BARRIER AS NEEDED AND STOCKPILE MATERIALS. CONTRACTOR SHALL RESET THESE MATERIALS AND PROVIDE ADDITIONAL MATERIALS AS NEEDED TO RESTORE LANDSCAPING.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 PVC DR-18) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 412 102.8A/108.3 - FIRE HYDRANT
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 569 608.06 - MONOLITHIC CURB, GUTTER AND SIDEWALK (5' WIDE)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)





**NOTES:**

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\07155a\Drawings\Phase 2 - Drawings\07155a - 02-HP-06.dwg, 3/15/2023 - 6:30 PM, NJM



REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_




**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 18TH ST WATER PLAN & PROFILE**

C2.1



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN).
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)





**NOTES:**

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-HP-06.dwg, 3/15/2023 - 6:30 PM, NJM




REVISION	DESCRIPTION	DATE	DRAWN BY	DATE
REVISION			ZCF	3/8/2023
REVISION			LAL/ZCF	3/8/2023
REVISION			CDB/JJM	12/8/2022
REVISION				



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 18TH ST WATER PLAN & PROFILE**

**C2.2**






KEY MAP  
NTS

**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDON BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)
- 826 PROTECT EXISTING UTILITY LINE IN PLACE
- 827 PROTECT EXISTING GAS.





**NOTES:**

1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-PWP-06.dwg, 3/15/2023 - 6:30 PM, NLM



REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_




**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 18TH ST WATER PLAN & PROFILE**

C2.3



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 PVC DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)
- 827 PROTECT EXISTING GAS.





**NOTES:**

1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-P&P-07.dwg, 3/13/2023 - 2:23 PM, NJM

REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/JJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_





**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 19TH ST WATER PLAN & PROFILE**

C3.0




N:\071156\Drawings\Phase 2 - Drawings\071156 - 02-PL-07.dwg, 3/13/2023 - 2:23 PM, NJM



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 3 202 - REMOVAL OF CONCRETE. SAW CUT AND REMOVE CONCRETE AS SHOWN. (INDICATED BY CROSS HATCH PATTERN) INCLUDES BUT NOT LIMITED TO CURB, GUTTER, SIDEWALK, DRIVEWAY, SLABS, V-PAN, CURB RAMPS, INTERSECTION CORNERS, APRONS, AND LANDSCAPE BORDERS.
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 22 202 - REMOVE EXISTING FIRE HYDRANT AND RETURN TO CITY SHOPS.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 100 210 - RESET LANDSCAPE GROUND COVER. CONTRACTOR SHALL REMOVE GROUND COVER AND ANY UNDERLYING WEED BARRIER AS NEEDED AND STOCKPILE MATERIALS. CONTRACTOR SHALL RESET THESE MATERIALS AND PROVIDE ADDITIONAL MATERIALS AS NEEDED TO RESTORE LANDSCAPING.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 PVC DR-18) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 412 102.8A/108.3 - FIRE HYDRANT
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 569 608.06 - MONOLITHIC CURB, GUTTER AND SIDEWALK (5' WIDE)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)





**NOTES:**

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE



REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/JJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 19TH ST WATER PLAN & PROFILE**


**C3.1**



KEY MAP  
NTS

CONSTRUCTION NOTES


- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)





- NOTES:
1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
  2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
  3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\107155\Drawings\Phase 2 - Drawings\107155 - 02-HP-07.dwg, 3/13/2023 - 2:23 PM, NJM

REVISION	DESCRIPTION	DATE	DRAWN BY	DATE
1			ZCF	3/8/2023
2			LAL/ZCF	3/8/2023
3			CDB/JJM	12/8/2022
4				




2022 WATERLINE REPLACEMENT PROJECT - PHASE 2  
N 19TH ST WATER PLAN & PROFILE



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 PVC DR-18) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)




**NOTES:**

1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\07155a\Drawings\Phase 2 - Drawings\07155a - 02-P&P-07.dwg, 3/13/2023 - 2:24 PM, NJM

REVISION	DESCRIPTION	DATE



DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 19TH ST WATER PLAN & PROFILE**


C3.3





**CONSTRUCTION NOTES**


- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 PVC DR-18) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)
- 826 PROTECT EXISTING UTILITY LINE IN PLACE



- NOTES:**
1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
  2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
  3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE



N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-PIP-06.dwg, 3/13/2023 - 2:24 PM, NJM

REVISION	DESCRIPTION	DATE	DRAWN BY	DATE
1			ZCF	3/8/2023
2			LAL/ZCF	3/8/2023
3			CDB/WJM	12/8/2022
4				



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 20TH ST WATER PLAN & PROFILE**


**C4.0**



KEY MAP  
NTS

CONSTRUCTION NOTES

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 355 104.40 - CAP TOP HALF OF SEWER IN CONCRETE PER STD. DETAIL GU-04. (WATER LINE LESS THAN 18" ABOVE SEWER LINE)
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)
- 826 PROTECT EXISTING UTILITY LINE IN PLACE
- 827 PROTECT EXISTING GAS.




NOTES:

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE



N:\071515a\Drawings\Phase 2 - Drawings\071515a - 02-Plan-04.dwg, 3/13/2023 - 2:24 PM, NJM

REVISION	DESCRIPTION	DATE	DRAWN BY	DATE
1			ZCF	3/8/2023
2			LAL/ZCF	3/8/2023
3			CDB/JJM	12/8/2022
4				




**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**MESA AVE WATER PLAN & PROFILE**

C4.1



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 3 202 - REMOVAL OF CONCRETE. SAW CUT AND REMOVE CONCRETE AS SHOWN. (INDICATED BY CROSS HATCH PATTERN) INCLUDES BUT NOT LIMITED TO CURB, GUTTER, SIDEWALK, DRIVEWAY, SLABS, V-PAN, CURB RAMPS, INTERSECTION CORNERS, APRONS, AND LANDSCAPE BORDERS
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 22 202 - REMOVE EXISTING FIRE HYDRANT AND RETURN TO CITY SHOPS.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 100 210 - RESET LANDSCAPE GROUND COVER. CONTRACTOR SHALL REMOVE GROUND COVER AND ANY UNDERLYING WEED BARRIER AS NEEDED AND STOCKPILE MATERIALS. CONTRACTOR SHALL RESET THESE MATERIALS AND PROVIDE ADDITIONAL MATERIALS AS NEEDED TO RESTORE LANDSCAPING.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 412 102.8A/108.3 - FIRE HYDRANT
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 569 608.06 - MONOLITHIC CURB, GUTTER AND SIDEWALK (5' WIDE)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75.) (TWO 2" LIFTS)
- 827 PROTECT EXISTING GAS.





**NOTES:**

1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-PIP-04.dwg, 3/13/2023 - 2:24 PM, NLM

REVISION	DESCRIPTION	DATE



DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 21ST ST WATER PLAN & PROFILE**


C4.2





**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDON BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 427 DEFLECT PIPE AS SHOWN.
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)



**NOTES:**

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE



N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-PWP-08.dwg, 3/13/2023 - 2:24 PM, zcf

REVISION	DESCRIPTION	DATE	DRAWN BY	DATE	SCALES:
REVISION			ZCF	3/8/2023	PLAN
REVISION			LAL/ZCF	3/8/2023	HORIZONTAL
REVISION			CDB/WJM	12/8/2022	VERTICAL
REVISION					




**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 20TH ST WATER PLAN & PROFILE**

C5.0



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)





**NOTES:**

1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

X:\1071156\Drawings\Phase 2 - Drawings\1071156 - 02-Plan-08.dwg, 3/13/2023 - 2:24 PM, zcf



REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_




**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 20th St WATER PLAN & PROFILE**

C5.1



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)
- 826 PROTECT EXISTING UTILITY LINE IN PLACE
- 827 PROTECT EXISTING GAS.




**NOTES:**

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

A:\1071158\Drawings\Phase 2 - Drawings\1071158 - 02-Plan-05.dwg, 3/13/2023 - 2:24 PM, zcf



REVISION	DESCRIPTION	DATE	DRAWN BY	DATE
1			ZCF	3/8/2023
2			LAL/ZCF	3/8/2023
3			CDB/JJM	12/8/2022
4				



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 21ST ST WATER PLAN & PROFILE**


C6.0





**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAWCUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)
- 826 PROTECT EXISTING UTILITY LINE IN PLACE
- 827 PROTECT EXISTING GAS.





**NOTES:**

1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE



N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-PWP-05.dwg, 3/13/2023 - 2:25 PM, zcf

REVISION	DESCRIPTION	DATE	DRAWN BY	DATE
1			ZCF	3/8/2023
2			LAL/ZCF	3/8/2023
3			CDB/JJM	12/8/2022
4				



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**N 21ST ST WATER PLAN & PROFILE**


C6.1



KEY MAP  
NTS

**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 3 202 - REMOVAL OF CONCRETE. SAW CUT AND REMOVE CONCRETE AS SHOWN. (INDICATED BY CROSS HATCH PATTERN) INCLUDES BUT NOT LIMITED TO CURB, GUTTER, SIDEWALK, DRIVEWAY, SLABS, V-PAN, CURB RAMPS, INTERSECTION CORNERS, APRONS, AND LANDSCAPE BORDERS
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 22 202 - REMOVE EXISTING FIRE HYDRANT AND RETURN TO CITY SHOPS.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 100 210 - RESET LANDSCAPE GROUND COVER. CONTRACTOR SHALL REMOVE GROUND COVER AND ANY UNDERLYING WEED BARRIER AS NEEDED AND STOCKPILE MATERIALS. CONTRACTOR SHALL RESET THESE MATERIALS AND PROVIDE ADDITIONAL MATERIALS AS NEEDED TO RESTORE LANDSCAPING.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8b/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 412 102.8A/108.3 - FIRE HYDRANT
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 427 DEFLECT PIPE AS SHOWN.
- 569 608.06 - MONOLITHIC CURB, GUTTER AND SIDEWALK (5' WIDE)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)
- 827 PROTECT EXISTING GAS.





**NOTES:**

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

X:\1071158\Drawings\Phase 2 - Drawings\1071158 - 02-HP-02.dwg, 3/13/2023 - 2:25 PM, zcf



REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**HALL AVE WATER PLAN & PROFILE**


**C7.0**



KEY MAP  
NTS

**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)




**NOTES:**

1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

X:\1071158\Drawings\Phase 2 - Drawings\1071158 - 02-HP-02.dwg, 3/13/2023 - 2:25 PM, zcf

REVISION	DESCRIPTION	DATE



DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/JWM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**HALL AVE WATER PLAN & PROFILE**


C7.1





**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 3 202 - REMOVAL OF CONCRETE. SAW CUT AND REMOVE CONCRETE AS SHOWN. (INDICATED BY CROSS HATCH PATTERN) INCLUDES BUT NOT LIMITED TO CURB, GUTTER, SIDEWALK, DRIVEWAY, SLABS, V-PAN, CURB RAMPS, INTERSECTION CORNERS, APRONS, AND LANDSCAPE BORDERS
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 22 202 - REMOVE EXISTING FIRE HYDRANT AND RETURN TO CITY SHOPS.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 100 210 - RESET LANDSCAPE GROUND COVER. CONTRACTOR SHALL REMOVE GROUND COVER AND ANY UNDERLYING WEED BARRIER AS NEEDED AND STOCKPILE MATERIALS. CONTRACTOR SHALL RESET THESE MATERIALS AND PROVIDE ADDITIONAL MATERIALS AS NEEDED TO RESTORE LANDSCAPING.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 412 102.8A/108.3 - FIRE HYDRANT
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 569 608.06 - MONOLITHIC CURB, GUTTER AND SIDEWALK (5' WIDE)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)
- 827 PROTECT EXISTING GAS.





**NOTES:**

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-WP-03.dwg, 3/13/2023 - 2:25 PM, zcf



REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_




**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**MESA AVE WATER PLAN & PROFILE**

**C8.0**



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN)
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 408 102.8/108.3 - CROSS (SIZE AS SHOWN)
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)
- 827 PROTECT EXISTING GAS.





**NOTES:**

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

X:\1071156\Drawings\Phase 2 - Drawings\1071156 - 02-PLN-03.dwg, 3/13/2023 - 2:25 PM, zcf



REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_




**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**MESA AVE WATER PLAN & PROFILE**

**C8.1**



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)
- 827 PROTECT EXISTING GAS.




**NOTES:**

1. CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
2. ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
3. IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

X:\1071158\Drawings\Phase 2 - Drawings\1071158 - 02-WP-03.dwg, 3/13/2023 - 2:25 PM, zcf

REVISION	DESCRIPTION	DATE



DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**MESA AVE WATER PLAN & PROFILE**

**C8.2**






KEY MAP  
NTS

**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 3 202 - REMOVAL OF CONCRETE. SAW CUT AND REMOVE CONCRETE AS SHOWN. (INDICATED BY CROSS HATCH PATTERN) INCLUDES BUT NOT LIMITED TO CURB, GUTTER, SIDEWALK, DRIVEWAY, SLABS, V-PAN, CURB RAMPS, INTERSECTION CORNERS, APRONS, AND LANDSCAPE BORDERS.
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 22 202 - REMOVE EXISTING FIRE HYDRANT AND RETURN TO CITY SHOPS.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 100 210 - RESET LANDSCAPE GROUND COVER. CONTRACTOR SHALL REMOVE GROUND COVER AND ANY UNDERLYING WEED BARRIER AS NEEDED AND STOCKPILE MATERIALS. CONTRACTOR SHALL RESET THESE MATERIALS AND PROVIDE ADDITIONAL MATERIALS AS NEEDED TO RESTORE LANDSCAPING.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 412 102.8A/108.3 - FIRE HYDRANT
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 569 608.06 - MONOLITHIC CURB, GUTTER AND SIDEWALK (5' WIDE)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)
- 826 PROTECT EXISTING UTILITY LINE IN PLACE
- 827 PROTECT EXISTING GAS.





**NOTES:**

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

K:\071158\Drawings\Phase 2 - Drawings\071158 - 02-HP-03.dwg, 3/13/2023 - 2:25 PM, zcf



REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_




**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**MESA AVE WATER PLAN & PROFILE**

C8.3



**CONSTRUCTION NOTES**

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 3 202 - REMOVAL OF CONCRETE. SAW CUT AND REMOVE CONCRETE AS SHOWN. (INDICATED BY CROSS HATCH PATTERN) INCLUDES BUT NOT LIMITED TO CURB, GUTTER, SIDEWALK, DRIVEWAY, SLABS, V-PAN, CURB RAMPS, INTERSECTION CORNERS, APRONS, AND LANDSCAPE BORDERS.
- 20 202 - ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 410 102.8/108.3 - END CAP / PLUG (SIZE AS SHOWN).
- 412 102.8A/108.3 - FIRE HYDRANT
- 413 102.7C/108.4 - WATER SERVICE LINE (TYPE K COPPER) (SIZE AS SHOWN ON PLAN)
- 416 102.8J/108.4 - CORPORATION STOP (INSTALL ONLY) (SIZE AS SHOWN ON PLAN)
- 569 608.06 - MONOLITHIC CURB, GUTTER AND SIDEWALK (5' WIDE)
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)
- 826 PROTECT EXISTING UTILITY LINE IN PLACE





**NOTES:**

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-HP-03.dwg, 3/13/2023 - 2:26 PM, zcf




REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/WJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_



**2022 WATERLINE REPLACEMENT PROJECT - PHASE 2**  
**MESA AVE WATER PLAN & PROFILE**


**C8.4**



KEY MAP  
NTS

CONSTRUCTION NOTES

- 1 202 - REMOVAL OF ASPHALT MAT. SAW CUT AND REMOVE ASPHALT AS SHOWN. (INDICATED BY DOT HATCH PATTERN).
- 20 ABANDON PIPE. ABANDONED BY PLUGGING REMAINING ENDS WITH CONCRETE.
- 22 202 - REMOVE EXISTING FIRE HYDRANT AND RETURN TO CITY SHOPS.
- 25 202 - ABANDON EXISTING WATER VALVE. CLOSE VALVE, REMOVE TOP HALF OF EXISTING VALVE BOX, FILL CAVITY TO FINISHED SUBGRADE WITH FLOW FILL MATERIAL.
- 100 210 - RESET LANDSCAPE GROUND COVER. CONTRACTOR SHALL REMOVE GROUND COVER AND ANY UNDERLYING WEED BARRIER AS NEEDED AND STOCKPILE MATERIALS. CONTRACTOR SHALL RESET THESE MATERIALS AND PROVIDE ADDITIONAL MATERIALS AS NEEDED TO RESTORE LANDSCAPING.
- 400 102.7/108.2 - WATER MAIN PIPE (C-900 DR-18 PVC) (SIZE AS SHOWN). INCLUDES TYPE A BEDDING AND HAUNCHING MATERIAL AND BACKFILL OF TRENCH WITH NATIVE MATERIALS MEETING 103.16 EARTH BACKFILL MATERIAL.
- 403 102.8B/108.3 - GATE VALVE. (SIZE AS SHOWN)
- 407 102.8/108.3 - TEE (SIZE AS SHOWN)
- 409 102.8/108.3 - ELBOW (SIZE AND ANGLE AS SHOWN)
- 426 CONNECT TO EXISTING WATER PIPE/VALVE/FITTING. THE CONTRACT UNIT PRICE FOR WATER PIPE SHALL INCLUDE THE COST OF CONNECTION TO EXISTING PIPELINE
- 683 401.08 - HOT BITUMINOUS PAVEMENT (PATCHING) (4" THICK ON TOP OF 6" ABC) (GRADING SX, BINDER GRADE PG 64-22, GYR 75) (TWO 2" LIFTS)
- 775 208 - STORM DRAIN INLET PROTECTION (EROSION CONTROL LOG) (AS SHOWN AND PER DETAIL)
- 826 PROTECT EXISTING UTILITY LINE IN PLACE.




NOTES:

- CONNECT TO EXISTING SERVICE LINES OR EXTEND SERVICE LINES TO NEW 6" WATERLINE
- ALL CURB STOP AND SERVICE LINE LOCATIONS ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION
- IF CURB STOP WAS NOT LOCATED FIELD LOCATE CURB STOP AND REPLACE EXIST SRVC CONNECTION WITH NEW CONNECTION TO NEW 6" WATERLINE

N:\071158\Drawings\Phase 2 - Drawings\071158 - 02-PWP-09.dwg, 3/13/2023 - 2:26 PM, zcf

REVISION	DESCRIPTION	DATE

DRAWN BY ZCF DATE 3/8/2023  
 DESIGNED BY LAL/ZCF DATE 3/8/2023  
 CHECKED BY CDB/JJM DATE 12/8/2022  
 APPROVED BY \_\_\_\_\_ DATE \_\_\_\_\_



2022 WATERLINE REPLACEMENT  
 PROJECT - PHASE 2  
 N 26TH ST WATER PLAN & PROFILE

C9.0