



Asbestos Building Materials Inspection Services

Client: The City of Grand Junction, 250 N. 5th Street, Grand Junction,
CO 81501

Project Site: 649 25 Road, Grand Junction, CO 81506

(House & Metal Barn Structures)

Inspection Date: January 4, 2024

Phase Con Project #: 24-01-04D

2166 Peregrine Court
Grand Junction, CO 81507
970-260-3341 -- office@phasecon.com

649 25 Road, Grand Junction, CO -- House (SFRD) & Metal Barn Structures

Sampling Description

Phase Con provided asbestos building inspection services at 649 25 Road in Grand Junction, Colorado on January 4, 2024. The inspection was performed by Mr. Douglas Close, a Colorado State and EPA Asbestos Building Inspector/Management Planner. This house (SFRD) and metal barn building are scheduled for demolition in the near future. Suspect materials within the scope of work were sampled and analyzed as per Colorado State Regulation #8.

A random sampling scheme was utilized in choosing sampling locations. This scheme used a grid system and randomly generated numbers. The Inspector, Mr. Douglas Close, classified the suspect materials by type (Thermal System Insulation (TSI), Surfacing Materials, and Miscellaneous Materials), and obtained the appropriate number of samples of each material based upon material type, and quantity.

Tables are provided which detail the individual samples obtained, the laboratory analysis results for these samples, the quantity and condition of Asbestos Containing Building Materials (ACBM), the locations of each homogeneous area, and other material specific information. Potential for damage to materials information is provided in the following sampling information tables.

Discussion & Recommendations

House Structure

The following materials were positive for Colorado State and EPA regulated asbestos content (>1% asbestos):

- Window Glazing - present in association with the east and northeast windows on the house. There is an estimated 1 sf of this ACBM present.
- Cement Asbestos Board Siding Shingles - present on the entire house exterior perimeter. There is an estimated 1400 sf of this ACBM present.
- Interior Plaster - present on the upper level walls and ceilings. There is an estimated 500 sf of this ACBM present.
- Ceiling Tiles - present in the kitchen and dining room. There is an

- estimated 350 sf of this ACBM present.
- Non-Surfaced Gypsum Board Systems – present as the walls and ceilings in the west porch room. There is an estimated 400 sf of this ACBM present.
 - Interior Plaster – present on the ground level of the house as most walls and ceilings. There is an estimated 2500 sf of this ACBM present.
 - Tar Impregnated Felts – present as a black felt layer beneath the cement asbestos board siding on the exterior perimeter of the house. There is an estimated 1400 sf of this ACBM present.
 - Surfaced Celotex Panels – present as the walls and ceilings of the northwest room. There is an estimated 200 sf of this ACBM present.
 - Non-Surfaced Gypsum Board Systems – present as the walls and ceilings of the south bathroom and the south porch. There is an estimated 350 sf of this ACBM present.
 - Orange Peel Type Surfaced Gypsum Board Systems – present as the walls and ceilings of the Living Room, NE Bedroom and the SE Bedroom (ACBM plaster may also be present beneath this material). There is an estimated 800 sf of this ACBM present.
 - Green Vinyl Floor Tile & Associated Black Mastic – present in the west porch. There is an estimated 110 sf of this ACBM present.
 - Black Vinyl Floor Tile & Black Mastic – present in the kitchen area. There is an estimated 200 sf of this ACBM present.
 - Red Vinyl Floor Tile & Black Mastic – present in the kitchen and dining room areas. There is an estimated 160 sf of this ACBM present.
 - Brown Vinyl Floor Tile & Black Mastic – present in the living room. There is an estimated 250 sf of this ACBM present.

The prior listed ACBMs are regulated by the State of Colorado and the EPA and must be handled, removed and disposed of by a State of Colorado licensed asbestos abatement contractor (General Abatement Certificate holder) in accordance with Colorado State Regulation #8 prior to building demolition.

Metal Barn Building

No asbestos containing building materials are present in this structure. There are no building materials present which are suspect for potential asbestos content; only wood structural members and metal siding/roof panels.

If any previously unknown or undiscovered materials are found during

demolition activities which are suspect for asbestos content then these materials should be tested for potential asbestos content prior to continuing any further demolition work.

Disclaimer

The inspection services process consists of initial inspection/sampling and sampling of subsequently discovered hidden or inaccessible building materials as the inspection/abatement/demolition process occurs within the building. Discovery of hidden or inaccessible building materials by any interested parties can and will occur at any time during the inspection/abatement/demolition process and necessitates stopping demolition until the discovered materials can be properly inspected/sampled. The discovery of hidden materials during the building demolition process is common, should be expected by the client and is a normal part of the inspection process.


Identified asbestos containing materials may be in areas which are inaccessible or hidden due to their application during the construction process and their subsequent enclosure or covering with building and finish materials. Areas behind walls, inside chases, or other hidden, covered or enclosed areas should be inspected whenever renovation or demolition activities are scheduled which may disturb the materials within or beneath these barriers. Care to watch for hidden or undiscovered materials should be taken by the demolition contractor during the demolition process. A discovery of unknown materials will necessitate stopping demolition until the materials can be inspected by a certified asbestos building inspector. 'Overspray' or excess materials from the installation or application process of asbestos containing materials is common, should be expected in the vicinity of installed asbestos containing materials, and is often present either covered by other building materials or in hidden or unexpected locations.

Bulk material samples are obtained in accordance with applicable regulations, industry standard techniques and analyzed by a NVLAP accredited laboratory; however, due to the asbestos content fluctuations which may occur in a building material due to the application and/or initial mixing process no guarantee can be made as to an 'exact' percentage asbestos content (this includes 'no asbestos detected' and 'trace' contents) which represents the entirety of the material (asbestos content fluctuations can and will occur throughout a building material).

Abatement cost estimates and material quantity estimates are

approximate only (due to the hidden nature of many of the materials), and are provided only as a general guideline to the client. More than one licensed Colorado State asbestos abatement contractor should be consulted to determine actual abatement costs of the ACBMs described above. Actual material quantities can only be determined by complete removal of covering materials.

Please call us with any questions which you may have concerning this report and our recommendations. Thank you.

A handwritten signature in black ink, appearing to read 'Douglas A. Close', written over a horizontal line.

Douglas A. Close
Colorado State and EPA Certified Asbestos Building
Inspector/Management Planner #2930

Sample Description Table(s)

Table 1

Sampling & Materials Description Table -- 649 25 Rd, GJ, CO

SMP L #	HMGNS AREA	MATERIAL DESCRIPTION	MATERIAL LOCATION(S)	MTRL TYPE	QUANTITY	CONDITION ASSES	REASON for CONDN ASSESSMENT	F/NF	ASBESTOS (Y/N)
1	A	Cement board siding	Entire house perimeter	M	1400 sf	G	-	NF	Y
2	A	Cement board siding	Entire house perimeter	M	1400 sf	G	-	NF	Y
3	B	Asphalt roofing shingles	Entire roof	M	1500 sf	G	-	NF	N
4	B	Asphalt roofing shingles	Entire roof	M	1500 sf	G	-	NF	N
5	C	Window glazing	NE & E windows	M	1 sf	G	-	NF	Y
6	C	Window glazing	NE & E windows	M	1 sf	G	-	NF	Y
7	D	Plaster	Upper floor walls/ceiling	S	500 sf	G	-	F	N
8	D	Plaster	Upper floor walls/ceiling	S	500 sf	G	-	F	N
9	D	Plaster	Upper floor walls/ceiling	S	500 sf	G	-	F	Y
10	E	12x24 ceiling tiles	Kitchen/dining room	M	350 sf	G	-	F	Y
11	E	12x24 ceiling tiles	Kitchen/dining room	M	350 sf	G	-	F	Y
12	F	12x12 ceiling tile	South bathroom & porch	M	160 sf	G	-	F	N
13	F	12x12 ceiling tile	South bathroom & porch	M	160 sf	G	-	F	N
14	G	Non surfaced gypsum board systems	West porch walls/ceiling	M	400 sf	G	-	F	N
15	G	Non surfaced gypsum board systems	West porch walls/ceiling	M	400 sf	G	-	F	Y

Sampling & Materials Description Table -- 649 25 Rd, GJ, CO

SMP L #	HMGNS AREA	MATERIAL DESCRIPTION	MATERIAL LOCATION(S)	MTRL TYPE	QUANTITY	CONDITION ASSES	REASON for CONDN ASSESSMENT	F/NF	ASBESTOS (Y/N)
16	H	Interior plaster	Most rooms walls/ceilings	S	2500 sf	G	-	F	Y
17	H	Interior plaster	Most rooms walls/ceilings	S	2500 sf	G	-	F	Y
18	H	Interior plaster	Most rooms walls/ceilings	S	2500 sf	G	-	F	Y
19	H	Interior plaster	Most rooms walls/ceilings	S	2500 sf	G	-	F	Y
20	H	Interior plaster	Most rooms walls/ceilings	S	2500 sf	G	-	F	Y
21	I	Tar impregnated felts	Beneath siding shingles	M	1400 sf	G	-	NF	Y
22	I	Tar impregnated felts	Beneath siding shingles	M	1400 sf	G	-	NF	Y
23	J	Celotex panels	NW room walls & ceiling	M	200 sf	G	-	F	Y
24	J	Celotex panels	NW room walls & ceiling	M	200 sf	G	-	F	N
25	K	Non surfaced gypsum board systems	South bathroom & south porch walls/ceiling	M	350 sf	G	-	F	Y
26	K	Non surfaced gypsum board systems	South bathroom & south porch walls/ceiling	M	350 sf	G	-	F	Y
27	L	Coarse plaster	Dining room walls/ceiling	S	375 sf	G	-	F	Y
28	L	Coarse plaster	Dining room walls/ceiling	S	375 sf	G	-	F	Y
29	L	Coarse plaster	Dining room walls/ceiling	S	375 sf	G	-	F	Y

Sampling & Materials Description Table -- 649 25 Rd, GJ, CO

SMP	HMGN S AREA	MATERIAL DESCRIPTION	MATERIAL LOCATION(S)	MTRL TYPE	QUANTITY	CONDITION ASSES	REASON for CONDN ASSESSMENT	F/NF	ASBESTOS (Y/N)
30	M	Orange peel type surfacing texture	LR, NE BR, SE BR	S	800 sf	G	-	F	Y
31	M	Orange peel type surfacing texture	LR, NE BR, SE BR	S	800 sf	G	-	F	Y
32	M	Orange peel type surfacing texture	LR, NE BR, SE BR	S	800 sf	G	-	F	Y
33	N	Gypsum board core sample, Homogeneous Area M	LR, NE BR, SE BR	M	800 sf	G	-	F	Y
34	N	Gypsum board core sample, Homogeneous Area M	LR, NE BR, SE BR	M	800 sf	G	-	F	Y
35	O	White sheet vinyl flooring	West porch	M	110 sf	G	-	F	N
36	O	White sheet vinyl flooring	West porch	M	110 sf	G	-	F	N
37	P	Green 9x9 vinyl floor tile & black mastic	West porch	M	110 sf	G	-	NF	Y, both
38	P	Green 9x9 vinyl floor tile & black mastic	West porch	M	110 sf	G	-	NF	Y, both
39	Q	Black vinyl floor tile	Kitchen	M	200 sf	G	-	NF	Y, both
40	Q	Black vinyl floor tile & black mastic	Kitchen	M	200 sf	G	-	NF	Y, both
41	R	Red vinyl floor tile & black mastic	Kitchen	M	20 sf	G	-	NF	N
42	R	Red vinyl floor tile & black mastic	Kitchen	M	20 sf	G	-	NF	N
43	S	Green sheet vinyl flooring	NW room	M	80 sf	G	-	NF	N

Sampling & Materials Description Table -- 649 25 Rd, GJ, CO

SMP L #	HMGNS AREA	MATERIAL DESCRIPTION	MATERIAL LOCATION(S)	MTRL TYPE	QUANTITY	CONDITION ASSES	REASON for CONDN ASSESSMENT	F/NF	ASBESTOS (Y/N)
44	S	Green sheet vinyl flooring	NW room	M	80 sf	G	-	NF	N
45	T	White vinyl floor tile	SW bathroom	M	150 sf	G	-	NF	N
46	T	White vinyl floor tile	SW bathroom	M	150 sf	G	-	NF	N
47	U	Sheet vinyl flooring	South porch	M	70 sf	G	-	F	N
48	U	Sheet vinyl flooring	South porch	M	70 sf	G	-	F	N
49	V	Red vinyl floor tile & black mastic	Dining room	M	140 sf	G	-	NF	Y, both
50	V	Red vinyl floor tile & black mastic	Dining room	M	140 sf	G	-	NF	Y, both
51	W	Green sheet vinyl flooring	SE bedroom	M	100 sf	G	-	NF	N
52	W	Green sheet vinyl flooring	SE bedroom	M	100 sf	G	-	NF	N
53	X	Brown vinyl floor tile & mastic	LR	M	250 sf	G	-	NF	Y, both
54	X	Brown vinyl floor tile & mastic	LR	M	250 sf	G	-	NF	Y, both
55	Y	Blue sheet vinyl flooring	NE bedroom	M	100 sf	G	-	NF	N
56	Y	Blue sheet vinyl flooring	NE bedroom	M	100 sf	G	-	NF	N

Abbreviations

ACM: Asbestos Containing Material

Material Type:

S (Surfacing material), TSI (Thermal System Insulation), M (Miscellaneous)

Condition Assessment:

DTSI (Damaged TSI ACM)

SDTSI (Significantly Damaged TSI ACM)

SDFS (Significantly Damaged Friable Surfacing ACM)

DFM (Damaged Friable Miscellaneous ACM)

SDFM (Significantly Damaged Friable Miscellaneous ACM)

PD (ACM with potential for damage)

PSD (ACM with potential for significant damage)

ARF (Any Remaining Friable ACM)

F: Friable

NF: Non Friable

Trace: <1% asbestos

Tr-Comp: Trace by composite analysis


Field Sketch – Sampling Locations

Asbestos Sample Locations Diagram


Site Location: 649 25 Road - House,
Gr. Jct. Co

Ground Floor

↑
North



Upper Floor



* This diagram is not to scale and is intended solely for the general representation of asbestos-contaminated areas.

ACM Locations Diagram(s)


ACM Locations Diagram

Site Location: 649 25 Road,
Grand Junction, CO

↑
North


ACM Siding → Ground Floor

Shingles and
Black Tar
Impreg. Felts
(entire exterior)



▨ ACM: Plaster,
Gypsum Board
and Celotex
Wall and
Ceiling Panels
(all walls/ceilings)

◻◻◻◻ ACM Ceiling Tiles



Upper
Floor

◻◻◻◻ ACM Vinyl Floor Tile/mastic


* This diagram is not to scale and is intended solely for the general representation of Asbestos Containing Materials (ACMs).

★ ACM Window Glazing (NE and E windows)

Laboratory Analysis Results

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Materials Characterization - Bulk Asbestos Analysis

Laboratory Analysis Report - Polarized Light

Phase Con Environmental Consultants, LLC

2166 Peregrine Court
Grand Junction, CO 81507

Attn: Doug Close

Customer Project: 649 25 Rd.
Reference #: CBR24010195

Date: 1/15/2024

Analysis and Method

Summary of polarizing light microscopy (PLM / Stereomicroscopy bulk asbestos analysis) using the methods described in 40CFR Part 763 Appendix E to Subpart E (Interim and EPA 600 / R-93 / 116 (Improved). The sample is first viewed with the aid of stereomicroscopy. Numerous liquid slide preparations are created for analysis under the polarized microscope where identifications and quantifications are preformed. Calibrated liquid refractive oils are used as liquid mounting medium. These oils are used for identification (dispersion staining). A calibrated visual estimation is reported, should any asbestiform mineral be present. Other techniques such as acid washing are used in conjunction with refractive oils for detection of smaller quantities of asbestos. All asbestos percentages are based on calibrated visual estimation traceable to NIST standards for regulated asbestos. Traceability to measurement and calibration is achieved by using known amounts and types of asbestos from standards where analyst and laboratory accuracy are measured. As little as 0.001% asbestos can be detected in favorable samples, while detection in unfavorable samples may approach the detection limit of 0.50% (well above the laboratory definition of trace).

Discussion

Vermiculite containing samples may have trace amounts of actinolite-tremolite, where not found by PLM should be analyzed using TEM methods and / or water separation techniques. Suspected actinolite/vermiculite presence will be indicated through the sample comment section of this report.

Fibrous talc containing samples may even contain a related asbestos fiber known as anthophyllite. Under certain conditions the same fiber may actually contain both talc and anthophyllite (a phenomenon called intergrowth). Again, TEM detection methods are recommended. CA Labs PLM report comments will denote suspected amounts of asbestiform anthophyllite with talc, where further analysis is recommended.

Some samples (floor tiles, surfacings, etc.) may contain fibers too small to be detectable by PLM analysis and should be analyzed by TEM bulk protocols.

A "trace asbestos" will be reported if the analyst observes far less than 1% asbestos. CA Labs defines "trace asbestos" as a few fibers detected by the analyst in several preparations and will indicate as such under these circumstances.


Quantification of <1% will actually be reported as <=1% (allowable variance close to 1% is high). Such results are ideal for point counting, and the technique is mandatory for friable samples (NESHAP, Nov. 1990 and clarification letter 8 May 1991) under 1% percent asbestos and the "trace asbestos". **In order to make all initial PLM reports issued from CA Labs NESHAP compliant, all <1% asbestos results (except floor tiles) will be point counted at no additional charge.**

Qualifications

CA Labs is accredited by the National Voluntary Accreditation Program (NVLAP) for selected test methods for airborne fiber analysis (TEM), and for bulk asbestos fiber analysis (PLM). All analysts have a college degree in a natural science (geology, biology, or environmental science) or are recognized by a state professional board in one these disciplines. Extensive in-house training programs are used to augment education background of the analyst. The group leader of polarized light has received supplemental McCrone Research training for asbestos identification. This report is not covered by the scope of AIHA accreditation. Analysis performed at CA Labs, LLC 12232 Industriplex, Suite 32 Baton Rouge, LA 70809.

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Overview of Project Sample Material Containing Asbestos

Customer Project:	649 25 Rd.			CA Labs Project #:	CBR24010195
Sample #	Layer #	Analysts Physical Description of Subsample	Asbestos type / calibrated visual estimate percent	List of Affected Building Material Types	
1	1-1	Gray Transite	20% Chrysotile	Gray Transite Tan Surfaced Gray Sealant White Surfaced Gray Sealant White Surfaced Gray Plaster White Surfaced Brown Ceiling Tile White Surfaced White Compound Tan Surfaced Gray Plaster Tan Surfaced White Compound	
2	2-1	Gray Transite	20% Chrysotile		
5	5-1	Tan Surfaced Gray Sealant	2% Chrysotile		
6	6-1	White Surfaced Gray Sealant	2% Chrysotile		
9	9-1	White Surfaced Gray Plaster	2% Chrysotile		
10	10-1	White Surfaced Brown Ceiling Tile	2% Chrysotile		
11	11-1	White Surfaced Brown Ceiling Tile	2% Chrysotile		
15	15-1	White Surfaced White Compound	2% Chrysotile		


Glossary of abbreviations (non-asbestos fibers and non-fibrous minerals):

ca - carbonate gypsum - gypsum	pe - perlite qu - quartz	fg - fiberglass mw - mineral wool wo - wollastinite ta - talc sy - synthetic ce - cellulose br - brucite ka - kaolin (clay)	pa - palygorskite (clay)
bi - binder or - organic ma - matrix mi - mica ve - vermiculite ot - other			

This report relates to the items tested. This report is not to be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST, AIHA LAP, LLC, or any other agency of the federal government. This report may not be reproduced except in full without written permission from CA Labs. These results are submitted pursuant to CA Labs' current terms and sale, condition of sale, including the company's standard warranty and limitations of liability provisions and no responsibility or liability is assumed for the manner in which the results are used or interpreted. Unless notified in writing to return the samples covered by this report, CA Labs will store the samples for a period of ninety (90) days before discarding. A shipping or handling fee may be assessed for the return of any samples.

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Overview of Project Sample Material Containing Asbestos

Customer Project: 649 25 Rd.		CA Labs Project #: CBR24010195		
Sample #	Layer #	Analysts Physical Description of Subsample	Asbestos type / calibrated visual estimate percent	List of Affected Building Material Types

16	16-2	Gray Plaster	2% Chrysotile	
17	17-1	Gray Plaster	2% Chrysotile	
18	18-1	Tan Surfaced Gray Plaster	2% Chrysotile	
19	19-1	Tan Surfaced White Compound	2% Chrysotile	
20	20-1	Tan Surfaced Gray Plaster	2% Chrysotile	
21	21-1	Black Felt and Tar	2% Chrysotile	
22	22-1	Black Felt and Tar	2% Chrysotile	
23	23-1	White Textured Surfacing	2% Chrysotile	


Glossary of abbreviations (non-asbestos fibers and non-fibrous minerals):

ca - carbonate	pe - perlite	fg - fiberglass	pa - palygorskite (clay)
gypsum - gypsum	qu - quartz	mw - mineral wool	
bj - binder		wo - wollastonite	
or - organic		ta - talc	
ma - matrix		sy - synthetic	
ml - mica		ce - cellulose	
ve - vermiculite		br - brucite	
ot - other		ka - kaolin (clay)	

This report relates to the items tested. This report is not to be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST, AIHA LAP, LLC, or any other agency of the federal government. This report may not be reproduced except in full without written permission from CA Labs. These results are submitted pursuant to CA Labs' current terms and sale, condition of sale, including the company's standard warranty and limitations of liability provisions and no responsibility or liability is assumed for the manner in which the results are used or interpreted. Unless notified in writing to return the samples covered by this report, CA Labs will store the samples for a period of ninety (90) days before discarding. A shipping or handling fee may be assessed for the return of any samples.

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Overview of Project Sample Material Containing Asbestos

Customer Project:	649 25 Rd.		CA Labs Project #:	CBR24010195	
Sample #	Layer #	Analysts Physical Description of Subsample	Asbestos type / calibrated visual estimate percent	List of Affected Building Material Types	
26	26-1	Gray Ceiling Tile	2% Chrysotile		
27	27-1	Tan Surfaced Gray Plaster	2% Chrysotile		
28	28-1	Tan Surfaced White Compound	3% Chrysotile		
	28-2	Gray Plaster	2% Chrysotile		
29	29-1	Tan Surfaced Gray Plaster	2% Chrysotile		
30	30-1	Tan Surfaced White Compound	2% Chrysotile		
31	31-1	Tan Surfaced White Compound	2% Chrysotile		
32	32-1	Tan Surfaced White Compound	2% Chrysotile		


Glossary of abbreviations (non-asbestos fibers and non-fibrous minerals):

ca - carbonate gypsum - gypsum bi - binder or - organic ma - matrix mi - mica ve - vermiculite ot - other	pe - perlite qu - quartz	fg - fiberglass mw - mineral wool wo - wollastinite ta - talc sy - synthetic ce - cellulose br - brucite ka - kaolin (clay)	pa - palygorskite (clay)
--	-----------------------------	--	--------------------------

This report relates to the items tested. This report is not to be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST, AIHA LAP, LLC, or any other agency of the federal government. This report may not be reproduced except in full without written permission from CA Labs. These results are submitted pursuant to CA Labs' current terms and sale, condition of sale, including the company's standard warranty and limitations of liability provisions and no responsibility or liability is assumed for the manner in which the results are used or interpreted. Unless notified in writing to return the samples covered by this report, CA Labs will store the samples for a period of ninety (90) days before discarding. A shipping or handling fee may be assessed for the return of any samples.

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Overview of Project Sample Material Containing Asbestos

Customer Project: 649 25 Rd.

CA Labs Project #: CBR24010195

Sample #	Layer #	Analysts Physical Description of Subsample	Asbestos type / calibrated visual estimate percent	List of Affected Building Material Types
	39-2	Black Floor Tile	4% Chrysotile	
	39-3	Brown Mastic	2% Chrysotile	
40	40-2	Gray Floor Tile	3% Chrysotile	
	40-3	Black Mastic	2% Chrysotile	
49	49-1	Brown Floor Tile	3% Chrysotile	
	49-2	Black Mastic	2% Chrysotile	
50	50-1	Brown Floor Tile	3% Chrysotile	
	50-2	Black Mastic	2% Chrysotile	


Glossary of abbreviations (non-asbestos fibers and non-fibrous minerals):

ca - carbonate	pe - perlite	fg - fiberglass	pa - palygorskite (clay)
gypsum - gypsum	qu - quartz	mw - mineral wool	
bi - binder		wo - wollastinite	
or - organic		ta - talc	
ma - matrix		sy - synthetic	
ml - mica		ce - cellulose	
ve - vermiculite		br - brucite	
ot - other		ka - kaolin (clay)	

This report relates to the items tested. This report is not to be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST, AIHA LAP, LLC, or any other agency of the federal government. This report may not be reproduced except in full without written permission from CA Labs. These results are submitted pursuant to CA Labs' current terms and sale, condition of sale, including the company's standard warranty and limitations of liability provisions and no responsibility or liability is assumed for the manner in which the results are used or interpreted. Unless notified in writing to return the samples covered by this report, CA Labs will store the samples for a period of ninety (90) days before discarding. A shipping or handling fee may be assessed for the return of any samples.

CA Labs
 Dedicated to
 Quality

CA Labs, L.L.C.
 12232 Industriplex, Suite 32
 Baton Rouge, LA 70809
 Phone 225-751-5632
 Fax 225-751-5634



NVLAP #200772-0
 TDSHS #300370
 CDPHE #AL-18111
 LELAP #03069

Overview of Project Sample Material Containing Asbestos

Customer Project:	649 25 Rd.		CA Labs Project #:	CBR24010195
Sample #	Layer #	Analysts Physical Description of Subsample	Asbestos type / calibrated visual estimate percent	List of Affected Building Material Types

53	53-1	Tan Floor Tile	3% Chrysotile	
	53-2	Black Mastic	2% Chrysotile	
54	54-1	Tan Floor Tile	3% Chrysotile	
	54-2	Black Mastic	2% Chrysotile	


Glossary of abbreviations (non-asbestos fibers and non-fibrous minerals):

ca - carbonate	pe - perlite	fg - fiberglass	pa - palygorskite (clay)
gypsum - gypsum	qu - quartz	mw - mineral wool	
bi - binder		wo - wollastinite	
or - organic		ta - talc	
ma - matrix		sy - synthetic	
mi - mica		ce - cellulose	
ve - vermiculite		br - brucite	
ot - other		ka - kaolin (clay)	

This report relates to the items tested. This report is not to be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST, AIHA LAP, LLC, or any other agency of the federal government. This report may not be reproduced except in full without written permission from CA Labs. These results are submitted pursuant to CA Labs' current terms and sale, condition of sale, including the company's standard warranty and limitations of liability provisions and no responsibility or liability is assumed for the manner in which the results are used or interpreted. Unless notified in writing to return the samples covered by this report, CA Labs will store the samples for a period of ninety (90) days before discarding. A shipping or handling fee may be assessed for the return of any samples.

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024
Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Physical Description of Subsample	Homo- geneo us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
1		1-1	Gray Transite	Y	20% Chrysotile		80% qu, ma, ca
2		2-1	Gray Transite	Y	20% Chrysotile		80% qu, ma, ca
3		3-1	Black Shingle with Black Gravel	Y	None Detected	70% fg	30% qu, ma, bi
4		4-1	Black Shingle with White Gravel	Y	None Detected	70% fg	30% qu, ma, bi
5		5-1	Tan Surfaced Gray Sealant	N	2% Chrysotile		98% qu, ma, bi, ca
6		6-1	White Surfaced Gray Sealant	N	2% Chrysotile		98% qu, ma, bi, ca
7		7-1	Blue Surfaced Tan Plaster	N	None Detected		100% qu, ma, bi, ca

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bl - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz


Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages effecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024


Date Of Sampling:
Purchase Order #:


Sample #	Com ment	Layer #	Analysts Physical Description of Subsample	Homo- geneo us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
8		8-1	Blue Surfaced Tan Plaster	N	None Detected		100% qu, ma, bi, ca
9		9-1	White Surfaced Gray Plaster	N	2% Chrysotile		98% qu, ma, bi, ca
10		10-1	White Surfaced Brown Ceiling Tile	N	2% Chrysotile	80% ce	18% qu, ma, bi, ca
11		11-1	White Surfaced Brown Ceiling Tile	N	2% Chrysotile	80% ce	18% qu, ma, bi, ca
12		12-1	White Surfaced Tan Ceiling Tile	N	None Detected	80% ce	20% qu, ma, bi
13		13-1	White Surfacing	Y	None Detected		100% qu, bi, ca
		13-2	Gray Ceiling Tile	Y	None Detected	15% fg 50% ce	35% qu, ma, pe


Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for
Identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bl - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:


David Darby
Analyst


Senior Analyst
Alicia Stretz



Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages effecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024
Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Physical Description of Subsample	Homo- geneo- us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
14		14-1	White Surfaced White Compound	N	None Detected		100% qu, mi, bi, ca
		14-2	White Drywall with Paper	N	None Detected	10% ce	90% qu, gy
15		15-1	White Surfaced White Compound	N	2% Chrysotile		98% qu, mi, bi, ca
		15-2	White Drywall with Paper	N	None Detected	10% ce	90% qu, gy
16		16-1	White Surfacing	N	None Detected		100% qu, bi, ca
		16-2	Gray Plaster	Y	2% Chrysotile		98% qu, ma, ca
17		17-1	Gray Plaster	Y	2% Chrysotile		98% qu, ma, ca

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for
Identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bi - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz


Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damage affecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024
Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Subsample	Physical Description of	Homo- geneo us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
18		18-1		Tan Surfaced Gray Plaster	N	2% Chrysotile		98% qu, ma, bi, ca
19		19-1		Tan Surfaced White Compound	N	2% Chrysotile		98% qu, mi, bi, ca
		19-2		Gray Plaster	Y	None Detected		100% qu, ma, ca
20		20-1		Tan Surfaced Gray Plaster	N	2% Chrysotile		98% qu, ma, ve, bi, ca
21		21-1		Black Felt and Tar	N	2% Chrysotile	80% ce	18% qu, ma, bi
22		22-1		Black Felt and Tar	N	2% Chrysotile	80% ce	18% qu, ma, bi
23		23-1		White Textured Surfacing	N	2% Chrysotile		98% qu, mi, bi, ca

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bl - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz


Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages effecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024

Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Physical Description of Subsample	Homo- geneo us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
			23-2 White Drywall with Paper	N	None Detected	10% ce	90% qu, gy
24			24-1 White Surfaced Tan Floorboard	N	None Detected	80% ce	20% qu, ma
25			25-1 White Drywall with Paper	N	None Detected	10% ce	90% qu, gy
26			26-1 Gray Ceiling Tile	Y	2% Chrysotile	15% fg 50% ce	35% qu, ma, pe
			26-2 White Drywall with Paper	N	None Detected	10% ce	90% qu, gy
27			27-1 Tan Surfaced Gray Plaster	N	2% Chrysotile		98% qu, ma, bi, ca
28			28-1 Tan Surfaced White Compound	N	3% Chrysotile		97% qu, mi, bi, ca

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for
Identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bi - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz


Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages effecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024

Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Subsample	Physical Description of	Homo- gene- us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
		28-2		Gray Plaster	Y	2% Chrysotile		98% qu, ma, ca
29		29-1		Tan Surfaced Gray Plaster	N	2% Chrysotile		98% qu, ma, bi, ca
30		30-1		Tan Surfaced White Compound	N	2% Chrysotile		98% qu, mi, bi, ca
		30-2		White Drywall with Paper	N	None Detected	10% ce	90% qu, gy
31		31-1		Tan Surfaced White Compound	N	2% Chrysotile		98% qu, mi, bi, ca
		31-2		White Drywall with Paper	N	None Detected	10% ce	90% qu, gy
32		32-1		Tan Surfaced White Compound	N	2% Chrysotile		98% qu, mi, bi, ca

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for
Identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bi - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz


Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages effecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024


Date Of Sampling:
Purchase Order #:


Sample #	Com ment	Layer #	Analysts Physical Subsample	Description of	Homo- geneo us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
				32-2 White Drywall with Paper	N	None Detected	10% ce	90% qu, gy
33				33-1 Tan Surfaced White Compound	N	3% Chrysotile		97% qu, mi, bi, ca
				White Compound Beneath				
				33-2 Tape	Y	3% Chrysotile		97% qu, mi, ca
				33-3 White Drywall with Paper	N	None Detected	10% ce	90% qu, gy
34				34-1 Tan Surfaced White Compound	N	3% Chrysotile		97% qu, mi, bi, ca
				White Compound Beneath				
				34-2 Tape	Y	3% Chrysotile		97% qu, mi, ca
				34-3 White Drywall with Paper	N	None Detected	10% ce	90% qu, gy


Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bi - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:


David Darby
Analyst


Senior Analyst
Alicia Stretz



Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages effecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024

Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Physical Description of Subsample	Homo- geneo us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
35		35-1	Tan Linoleum	Y	None Detected	20% ce	80% qu, ma
		35-2	Tan Mastic	Y	None Detected		100% qu, bi
36		36-1	Tan Linoleum	Y	None Detected	20% ce	80% qu, ma
		36-2	Tan Mastic	Y	None Detected		100% qu, bi
37		37-1	Green Floor Tile	Y	3% Chrysotile		97% qu, ma, ca
		37-2	Black Mastic	Y	6% Chrysotile		94% qu, bi
38		38-1	Green Floor Tile	Y	3% Chrysotile		97% qu, ma, ca

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for
identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bl - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz


Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages effecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024
Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Subsample	Physical Description of	Homo- geneo us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
				38-2 Black Mastic	Y	6% Chrysotile		94% qu, bi
39				39-1 Tan Mastic	Y	None Detected		100% qu, bi
				39-2 Black Floor Tile	Y	4% Chrysotile		96% qu, ma, ca
				39-3 Brown Mastic	Y	2% Chrysotile		98% qu, bi
40				40-1 Tan Mastic	Y	None Detected		100% qu, bi
				40-2 Gray Floor Tile	Y	3% Chrysotile		97% qu, ma, ca
				40-3 Black Mastic	Y	2% Chrysotile		98% qu, bi

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for
Identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bi - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz


Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages affecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024

Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Physical Description of Subsample	Homo-geneous (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
41		41-1	Tan Mastic	Y	None Detected		100% qu, bi
		41-2	Red Linoleum	Y	None Detected	30% ce	70% qu, ma
42		42-1	Tan Mastic	Y	None Detected		100% qu, bi
		42-2	Red Linoleum	Y	None Detected	30% ce	70% qu, ma
43		43-1	Gray Foam	Y	None Detected		100% qu, ot
		43-2	Green Linoleum	Y	None Detected	20% ce	80% qu, ma
44		44-1	Gray Foam	Y	None Detected		100% qu, ot

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bi - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz


Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages effecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024
Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Physical Description of Subsample	Homo- geneo us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
45		45-1	White Floor Tile	Y	None Detected		100% qu, ca
		45-2	Tan Mastic	Y	None Detected		100% qu, bi
46		46-1	White Floor Tile	Y	None Detected		100% qu, ca
47		47-1	Tan Linoleum	Y	None Detected	20% ce	80% qu, ma
		47-2	Tan Mastic	Y	None Detected		100% qu, bi
48		48-1	Tan Linoleum	Y	None Detected	20% ce	80% qu, ma
		48-2	Tan Mastic	Y	None Detected		100% qu, bi

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for
Identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bi - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz


Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damage affecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024
Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Physical Description of Subsample	Homo- gene- us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
49		49-1	Brown Floor Tile	Y	3% Chrysotile		97% qu, ma, ca
		49-2	Black Mastic	Y	2% Chrysotile		98% qu, bi
50		50-1	Brown Floor Tile	Y	3% Chrysotile		97% qu, ma, ca
		50-2	Black Mastic	Y	2% Chrysotile		98% qu, bi
51		51-1	Blue Linoleum	Y	None Detected	20% ce	80% qu, ma, bi
52		52-1	Blue Linoleum	Y	None Detected	20% ce	80% qu, ma, bi
53		53-1	Tan Floor Tile	Y	3% Chrysotile		97% qu, ma, ca

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for
Identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bi - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz


Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages effecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

CA Labs
Dedicated to
Quality

CA Labs, L.L.C.
12232 Industriplex, Suite 32
Baton Rouge, LA 70809
Phone 225-751-5632
Fax 225-751-5634



NVLAP #200772-0
TDSHS #300370
CDPHE #AL-18111
LELAP #03069

Polarized Light Asbestiform Materials Characterization

Customer Info: Attn: Doug Close
Phase Con Environmental Consultants, LLC
2166 Peregrine Court
Grand Junction, CO 81507

Customer Project:
649 25 Rd.

CA Labs Project #:
CBR24010195

Phone # 970-241-6480
Fax # 970-241-6584

Turnaround Time: 3 day

Date: 1/15/2024
Samples Received: 1/11/2024

Date Of Sampling:
Purchase Order #:

Sample #	Com ment	Layer #	Analysts Physical Description of Subsample	Homo- geneo us (Y/N)	Asbestos type / calibrated visual estimate percent	Non-asbestos fiber type / percent	Non-fibrous type / percent
			53-2 Black Mastic	Y	2% Chrysotile		98% qu, bi
54			54-1 Tan Floor Tile	Y	3% Chrysotile		97% qu, ma, ca
			54-2 Black Mastic	Y	2% Chrysotile		98% qu, bi
55			55-1 Green Linoleum	Y	None Detected	20% ce	80% qu, ma
56			56-1 Green Linoleum	Y	None Detected	20% ce	80% qu, ma

Analysis Method: Interim (40CFR Part 763 Appendix E to Subpart E) / Improved (EPA-600 / R-93/116)
Preparation Method: HCL acid washing for carbonate based samples, chemical reduction for organically bound components, oil immersion for
identification of asbestos types by dispersion attaining / becke line method.

ca - carbonate	mi - mica	fg - fiberglass	ce - cellulose
gypsum - gypsum	ve - vermiculite	mw - mineral wool	br - brucite
bl - binder	ot - other	wo - wollastinite	ka - kaolin (clay)
or - organic	pe - perlite	ta - talc	pa - palygorskite (clay)
ma - matrix	qu - quartz	sy - synthetic	

Approved Signatories:

David Darby
Analyst

Senior Analyst
Alicia Stretz

Laboratory Director
Chris Williams

1. Fire Damage significant fiber damage - reported percentages reflect unaltered fibers
2. Fire Damage no significant fiber damages effecting fibrous percentages
3. Actinolite in association with Vermiculite
4. Layer not analyzed - attached to previous positive layer and contamination is suspected
5. Not enough sample to analyze

6. Anthophyllite in association with Fibrous Talc
7. Contamination suspected from other building materials
8. Favorable scenario for water separation on vermiculite for possible analysis by another method
9. < 1% Result point counted positive
10. TEM analysis suggested

Certificates



Colorado Department
of Public Health
and Environment

ASBESTOS CERTIFICATION*

This certifies that

Douglas A. Close

Certification No.: 2930


has met the requirements of 25-7-507, C.R.S. and Air Quality Control
Commission Regulation No. 8, Part B, and is hereby certified by the
state of Colorado in the following discipline:

Inspector/Management Planner*

Issued: October 27, 2023

Expires: October 25, 2024

*This certificate is valid only with the possession of a
current Division-approved training course certification
in the discipline specified above.*


Authorized APCD Representative
SEAL



Colorado Department
of Public Health
and Environment

ASBESTOS CERTIFICATION*

This certifies that

Douglas A. Close

Certification No.: 2930

has met the requirements of 25-7-507, C.R.S. and Air Quality Control
Commission Regulation No. 8, Part B, and is hereby certified by the
state of Colorado in the following discipline:

Project Designer*

Issued: October 27, 2023

Expires: October 25, 2024

**This certificate is valid only with the possession of a
current Division-approved training course certification
in the discipline specified above.*


Authorized APCD Representative

SEAL



Colorado Department
of Public Health
and Environment

ASBESTOS CERTIFICATION*

This certifies that

Douglas A. Close

Certification No.: 2930

has met the requirements of 25-7-507, C.R.S. and Air Quality Control
Commission Regulation No. 8, Part B, and is hereby certified by the
state of Colorado in the following discipline:

Air Monitoring Specialist*

Issued: October 27, 2023

Expires: October 25, 2024

**This certificate is valid only with the possession of a
current Division-approved training course certification
in the discipline specified above.*


Authorized APCD Representative

SEAL



Colorado Department
of Public Health
and Environment

ASBESTOS CONSULTING FIRM
Phase Con Environmental Consultants, LLC

This certifies that

Registration No.: ACF - 14801

has met the registration requirements of 25-7-507, C.R.S. and the Air Quality Control Commission Regulation No. 8, Part B, and is hereby authorized to perform asbestos consulting activities as required under Regulation No. 8, Part B, in the state of Colorado.

Issued: January 30, 2023
Expires: January 30, 2024

Authorized APCD Representative
SEAL



Colorado Department
of Public Health
and Environment

ASBESTOS LABORATORY

This certifies that

Phase Con Environmental Consultants, LLC

Registration No.: AL - 14801

has met the registration requirements of 25-7-507, C.R.S. and the Air Quality Control Commission Regulation No. 8, Part B, and is hereby authorized to perform asbestos laboratory testing activities, as required by Regulation No. 8, Part B, in the state of Colorado.

Issued: April 12, 2023

Expires: April 07, 2024

[Signature]
Authorized Representative
SEAL



Colorado Department
of Public Health
and Environment

ASBESTOS LABORATORY

This certifies that

CA Labs, LLC

Registration No.: AL - 27819


has met the registration requirements of 25-7-507, C.R.S. and the Air Quality Control Commission Regulation No. 8, Part B, and is hereby authorized to perform asbestos laboratory testing activities, as required by Regulation No 8, Part B, in the state of Colorado.

Issued: April 28, 2023

Expires: May 12, 2024

Authorized Representative
SEAL

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 200772-0

CA Labs L.L.C.
Baton Rouge, LA


is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:

Asbestos Fiber Analysis

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communiqué dated January 2009).

2024-01-01 through 2024-12-31

Effective Dates



A handwritten signature in black ink, appearing to read 'John S. Lamm', written over a horizontal line.

For the National Voluntary Laboratory Accreditation Program