

LUMINAIRE SCHEDULE (CONTINUED)						
TYPE	SYMBOL	LAMP	VA	VOLT	LUMINAIRE DESCRIPTION	EQUAL MANUFACTURERS
G		(1) CF126W/3500K 830	28	120/277	VANDAL RESISTANT LOW PROFILE WALL MOUNT FIXTURE - 1/8" GAGE ALUMINUM HOUSING - INJECTION MOLDED POLYCARBONATE FULL FACE LENS - HIGH POWER FACTOR ELECTRONIC BALLAST - UL LISTED	KENALL - H612FL-C-26P-1 DV-FS-9500 DAY-BRITE LIGHTOLIER LUMINAIRE
H		(1) CF174W/830	46	120	ENCLOSED VAPOR PROOF TYPE FIXTURE - COPPER FREE ALUMINUM HOUSING - 1-1/2" STANCHION MOUNTING - HIGH POWER FACTOR ELECTRONIC BALLAST - HEAT AND IMPACT RESISTANT GLASS GLOBE - 90 MINUTE EMERGENCY BATTERY BACK-UP - UL LISTED	CROUSE-HINDS - DMV-FB-042W- GP CANLET RAB LITHONIA
H1		(1) CF174W/830	46	120	ENCLOSED VAPOR PROOF TYPE FIXTURE - COPPER FREE ALUMINUM HOUSING - WALL MOUNTING - HIGH POWER FACTOR ELECTRONIC BALLAST - HEAT AND IMPACT RESISTANT GLASS GLOBE - 90 MINUTE EMERGENCY BATTERY BACK-UP - UL LISTED	CROUSE-HINDS - DMV-FB-21W- 042W-GP DAY-BRITE RAB LITHONIA
J		15.51 LM5FT LED 2800K	1.65 W/F	120/277	10" SEMI-RIGID LED LIGHT TUBING WITH 4" LED SPACING - CLEAR RIGID POLYCARBONATE MOUNTING CHANNEL - CLEAR TWO PIECE POLYCARBONATE MOUNTING CLAMP - FAST TUBE CONNECTOR KITS - MULTI-VOLT INTEGRAL ELECTRONIC DRIVER W/ 0-10V DIMMING - 120VAC-12VDC, 200W ELECTRONIC POWER SUPPLY - (2) 96W 12VDC - 12VDC DIMMER	TIVOLI - FTL-03-04-WW-10- 12 ADMN-200-3-5-12-D DM-12V-8A TEMPO SSL VISA
K		(2) F327B/835	62	120/277	4" PERIMETER TROUGH RECESSED ADJUSTABLE STAGGERED FIXTURE - ENCLOSURE DIE-FORMED 20 GA. STEEL - WHITE FINISH POLYESTER POWDER COAT PAINT - ELECTRONIC DIMMING BALLAST THD< 10% - PARABOLIC ROLL FORMED ALUMINUM REFLECTORS - UL LISTED	LIGHTOLIER - PTS8-2-S-2-4-AS DAYBRITE LITHONIA LIGHTOLIER
K1		(2) F177B/835	34	120/277	2" PERIMETER TROUGH RECESSED ADJUSTABLE STAGGERED FIXTURE - ENCLOSURE DIE-FORMED 20 GA. STEEL - WHITE FINISH POLYESTER POWDER COAT PAINT - ELECTRONIC DIMMING BALLAST THD< 10% - PARABOLIC ROLL FORMED ALUMINUM REFLECTORS - UL LISTED	LIGHTOLIER - PTS8-2-S-2-4-AS DAYBRITE LITHONIA LIGHTOLIER
L		3500K FT50W/ ZG11	160	277	6" CEILING MOUNTED WALL WASH FIXTURE - CLEAR ANODIZED ALUMINUM FINISH - (2) 1" SHIPPED MOUNTING BRACKETS - REMOTE ELECTRONIC DIMMING BALLAST - PROVIDE END FEED, END CAPS AND JOINER CONNECTIONS AS REQUIRED - UL LISTED	ELIPTAPAR - F282-L350-S-00- V-0 SSL PHILLIPS LITHONIA
L1		RGB LED	96	120	8" COLOR CHANGING ADJUSTABLE LED FIXTURE - LOW COPPER CONTENT EXTRUDED ALUMINUM HOUSING - ELECTROSTATICALLY APPLIED POWDERCOAT FINISH - VIDEO TYPE TRI-COLOR LED'S 287 LUMENS PER FOOT - DMX CONTROLLER, DATA BOX AND LEADER CABLE - UL LISTED	LUMENPULSE - LCS-HO-120-96- RGB-TF-SF-8F- WH-LD-CBOX- 120-LCSICD-6 SSL PHILLIPS POWERCORE
M		(4) CF323W/830	152	120/277	16" DECORATIVE PENDANT FIXTURE - GREY POWDER COATED HOUSING - WHITE GLASS SHADE - AIRCRAFT CABLE SUSPENSION WITH BLACK POWER FEED - LUTRON ECOSYSTEM DIMMING BALLAST - UL LISTED	LIGHTOLIER - 40471U3TM- 408WH4048KB- W02-2A HUBBEL HOLOPHANE LITHONIA
N		1-34W ONE ENGL 10-LED'S 4000K	24	120/277	-ARCHITECTURAL WALL SCENE (0% UPLIGHT) - DIE CAST ALUMINUM HOUSING - FULLY GASKETED DIE CAST DOOR FRAME - PRECISION MOLDED ACRYLIC LENS - 90 MINUTE BATTERY BACKUP - DARK BRONZE FINISH - LES TYPE II DISTRIBUTION - CLASS 2 ELECTRONIC DRIVER PF> 90% - UL LISTED FOR WET LOCATIONS.	LITHONIA #WSTLED2- 10A70040K-SR2- WVOLT-7-SF-ELCOW- DDBXD DAYBRITE NEO-RAY COOPER
W2E		(2) F327B/835 (1) F177B/835	75	120/277	4" STAIR LIGHT - CHANNEL, ENDS AND SOCKET BRACKETS 22 GA STEEL - ACRYLIC PRISMATIC DIFFUSER - (2) ELECTRONIC ENERGY SAVING BALLASTS < 10% THD - EMERGENCY BATTERY PAK 1400 LUMENS - INTEGRAL ULTRASONIC SENSOR - NIGHT LIGHT STAYS ON - UL LISTED	LITHONIA - FCW4-2-32-21- GEB10RS-EL14- MS1UNL DAY-BRITE LIGHTOLIER COLUMBIA
Z1		WARM WHITE LED (INCL.)	5	120	2.75" X 4.5" X 1.5" LOW LEVEL LED LUMINAIRE - DIE CAST ALUMINUM HOUSING - POWDER COAT BLACK FINISH - SOLID STATE INTEGRAL ELECTRONIC DRIVER - HIGH IMPACT POWER SUPPLY CASE - LINE VOLTAGE DIMMING - CLEAR POLYCARBONATE LENS - MOUNTED IN RECESSED SINGLE-GANG BACKBOX.	LIGHTOLIER - LP-2-S-BK-DIM- BLU PRUDENTIAL PRESCOLITE VISTA
Z2		BLUE LED (INCL.)	5	120	SAME AS TYPE Z1 EXCEPT WITH BLUE LIGHT ENGINE	LIGHTOLIER - LP-2-S-BK-DIM- BLU PRUDENTIAL PRESCOLITE VISTA

LUMINAIRE SCHEDULE (CONTINUED)						
TYPE	SYMBOL	LAMP	VA	VOLT	LUMINAIRE DESCRIPTION	EQUAL MANUFACTURERS
D1		(1) CF126W/3500K 830	28	120/277	6" OPEN DOWNLIGHT WITH VERTICAL LAMP - 2-STAGE CLEAR MATTE-DIFFUSE ALUMINUM REFLECTOR - WHITE FLANGE - 1/8" GAGE GALVANIZED STEEL MOUNTING FRAME - MAXIMUM 1" BUILT-IN DEPTH - FAST BLOW FUSE - (1) MULTI-VOLTAGE ELECTRONIC BALLAST.	GOTHAM - AFV-26TRT-6AR LD-MVOLT-GLR- TRW-EL CALCULITE OMEGA PORTFOLIO PRESCOLITE
D1E		(1) CF126W/3500K 830	28	120/277	SAME AS TYPE D1 EXCEPT WITH 90 MINUTE EMERGENCY BATTERY PACK AND INTEGRAL TEST SWITCH	GOTHAM - AFV-26TRT-6AR LD-MVOLT-GLR- TRW-EL CALCULITE OMEGA PORTFOLIO PRESCOLITE
D2		(1) CF126W/3500K 830	28	120/277	6" OPEN DOWNLIGHT WITH VERTICAL LAMP - 2-STAGE CLEAR MATTE-DIFFUSE ALUMINUM REFLECTOR - WHITE FLANGE - 1/8" GAGE GALVANIZED STEEL MOUNTING FRAME - MAXIMUM 1" BUILT-IN DEPTH - FAST BLOW FUSE - (1) MULTI-VOLTAGE LUTRON ECOSYSTEM ELECTRONIC BALLAST. - UL LISTED	GOTHAM - AFV-26TRT-6AR LD-MVOLT-GLR- TRW-EL CALCULITE OMEGA PORTFOLIO PRESCOLITE
D2A		(1) CF126W/3500K 830	20	120/277	SAME AS TYPE D2 EXCEPT WITH 18W CFL LAMP	GOTHAM - AFV-26TRT-4AR LD-MVOLT-ECOS- GLR-TRW CALCULITE OMEGA PORTFOLIO PRESCOLITE
D2B		(1) CF126W/3500K 830	28	120/277	SAME AS TYPE D2 EXCEPT WITH TEMPERED PRISMATIC LENS, ELECTRONIC DIMMING BALLAST AND UL LISTED FOR DAMP LOCATIONS	GOTHAM - AFV-26TRT-4AR LD-MVOLT-ECOS- GLR-TRW CALCULITE OMEGA PORTFOLIO PRESCOLITE
D2E		(1) CF126W/3500K 830	34	120/277	SAME AS TYPE D2 EXCEPT WITH 90 MINUTE EMERGENCY BATTERY PACK AND INTEGRAL TEST SWITCH	GOTHAM - AFV-32TRT-4AR LD-MVOLT-GLR- TRW-EL CALCULITE OMEGA PORTFOLIO PRESCOLITE
D3		(1) CF126W/3500K 830	28	120/277	6" LENSED DOWNLIGHT WITH HORIZONTAL LAMP - ALUMINUM UPPER REFLECTOR COATED WITH WHITE REFLECTIVE PAINT - PRISMATIC POLYCARBONATE LENS - REGRESSED ANODIZED DOOR FLANGE - 1/8" GAGE GALVANIZED STEEL MOUNTING FRAME - LOW PROFILE DEPTH & TAMPER RESISTANT SCREWS - SINGLE FAST BLOW FUSE - CLASS P THERMALLY PROTECTED HIGH PF ELECTRONIC BALLAST. - UL LISTED FOR WET LOCATIONS	GOTHAM - LGPLP-126TRT- GLR-PPC-MVOLT- GLR-TRUA CALCULITE OMEGA PORTFOLIO PRESCOLITE
D3E		(1) CF126W/3500K 830	30	120/277	SAME AS TYPE D3 EXCEPT WITH 90 MINUTE HIGH LUMEN OUTPUT EMERGENCY BATTERY PACK AND REMOTE TEST SWITCH	GOTHAM - LGPLP-126TRT- GLR-PPC-MVOLT- GLR-TRUA-ELRL CALCULITE PORTFOLIO PRESCOLITE
D4		(1) MR16 50W/ PAR	50	120/277	2" LOW VOLTAGE ROUND FIXED PINHOLE DOWNLIGHT - INTEGRAL TRANSFORMER - SEAMLESS CAST FACEPLATE WITH BLACK FINISH - INTERNAL HOUSING COMPONENTS PAINTED MATTE BLACK - ETCHED BLACK ANODIZED TUBE FROM FACILITY TO LAMPHOLDER - RE-LAMP CAPABILITY FROM ABOVE AND BELOW - UL LISTED	GOTHAM - DLV-01W-2B-277- DBL TRANSLITE CALCULITE KURT VERSEN PRESCOLITE
D5		(1) CF126W/3500K 830	34	120/277	4" SURFACE MOUNTED DOWNLIGHT - DURABLE HEAVY GAGE ALUMINUM HOUSING - SELF-FLANGE SEMI-SPECULAR REFLECTOR - TEMPERED PRISMATIC LENS - ECOSYSTEM ELECTRONIC DIMMING BALLAST - UL LISTED FOR DAMP LOCATIONS	GOTHAM - PDTF-32TRT-4AR- T73-MVOLT-ECOS- SS-NR-2M-WLP TRANSLITE CALCULITE KURT VERSEN PRESCOLITE
D6		(2) CF126W/3500K 830	28	120/277	6" 0 G RATED OPEN DOWNLIGHT - SELF FLANGED SPECULAR REFLECTOR - STEEL HOUSING - WHITE PAINTED FLANGE - BALLAST DISCONNECT PLUG - LUTRON ECOSYSTEM ELECTRONIC DIMMING BALLAST - UL LISTED	LITHONIS - LIF6-213DIT- MVOLT-GMF-AT- BDP EDISON PRICE KURT VERSEN LITHONIA
D7		(1) 38W PAR20/ HAL/ NFL	39	120	4" 9 ADJUSTABLE DOWNLIGHT WITH PAR LAMP - HIGH PURITY ALUMINUM ALZAK REFLECTOR - 277-120V TRANSFORMER - PAINTED ALUMINUM OUTER HOUSING - C-RATED - ADJUSTABLE TO 45 DEGREES WITH LOCKING PROVISIONS - MATTE WHITE DIE-CAST ALUMINUM TRIM - UL LISTED	PRESCOLITE - PHAC-TAMC- TRG EDISON PRICE KURT VERSEN LITHONIA
D8		LED 2700K 80 CRI	20	120	7" 0 LED DOWNLIGHT - HIGH PURITY ALUMINUM ALZAK REFLECTOR - JUL CLASS 2, FCC A7CER PART 1.5 CLASS B COMPLIANT LED DRIVER - 7 TUBE ASSEMBLY ACCESSIBLE FROM BELOW - NON-IC RATED - DUAL-LITE 100VA SURFACE WALL MOUNT EMERGENCY LIGHTING INVERTER - 5 YEAR WARRANTY - UL LISTED FOR WET LOCATIONS	PRESCOLITE - D2LED-277- 20LED-27K-8- WFL4S-WH-LG1S EDISON PRICE KURT VERSEN LITHONIA
E1		GREEN LED 5 / FACE	120/277		LED RECESSED SOLID STATE EMERGENCY EXIT SIGN - IMPACT RESISTANT, ALUMINUM DIE-CAST ALUMINUM HOUSING - GREEN LETTERING - WHITE PAINTED FINISH - PROVIDE FACES AS SHOWN ON PLANS - BATTERY BACK-UP WITH SELF-DIAGNOSTICS - UNIVERSAL MOUNTING - UL LISTED	SIGMATEX - RAPER - RPR-BB- S-W-TV SURE-LITES - TPX EVENLIGHT - RZR LIGHTOLIER - DX
E2		GREEN LED 1.25W	120/277		LED BRUSHED ALUMINUM EMERGENCY EXIT SIGN - PANEL IS BRUSHED ALUMINUM - GREEN LETTERING - BODY IS BRUSHED ALUMINUM FINISH - PROVIDE FACES AS SHOWN ON PLANS - BATTERY BACK-UP WITH SELF-DIAGNOSTICS - UNIVERSAL MOUNTING - UL LISTED	EMERGO-LITE - AA-DX-12-G DUAL LITE SURE LITES CHLORIDE
E3		GREEN LED 5	120/277		LED EMERGENCY EXIT SIGN - IMPACT AND SCRATCH RESISTANT THERMOPLASTIC HOUSING - GREEN LETTERING - WHITE PAINTED FINISH - PROVIDE FACES AS SHOWN ON PLANS - BATTERY BACK-UP WITH SELF-DIAGNOSTICS - UNIVERSAL MOUNTING - UL LISTED	EMERGO-LITE - LX-U-G-W-E-1 DUAL LITE - LPX SURE LITES - LPX CHLORIDE - SL
E4		GREEN LED 5	120/277		LED COMBINATION EMERGENCY EXIT SIGN / LIGHTS - IMPACT AND SCRATCH RESISTANT THERMOPLASTIC HOUSING - GREEN LETTERING - WHITE PAINTED FINISH - PROVIDE FACES AS SHOWN ON PLANS - BATTERY BACK-UP WITH SELF-DIAGNOSTICS - UNIVERSAL MOUNTING - UL LISTED	CHLORIDE - VCLGW DUAL LITE - LT SURE LITES - UNH EMERGO-LITE - PREMIERE
F		(2) F327B/3500K 835	62	120/277	4" STEEL CHANNEL STRIP - HEAVY DUTY COLD ROLLED STEEL CHANNEL - HIGH GLOSS BAKED WHITE ENAMEL FINISH - 11-GAUGE WIRE CAGE - INSTANT START ELECTRONIC BALLAST < 10% THD - UL LISTED	LITHONIA - C-2-32-MVOLT- GEB101S-WGOUN NST COLUMBIA DAY-BRITE LIGHTOLIER METALUX
FE		(2) F327B/3500K 835	62	120/277	SAME AS TYPE F EXCEPT WITH 90 MINUTE 1400 LUMEN EMERGENCY BATTERY PACK	LITHONIA - C-2-32-MVOLT- GEB101S-WGOUN NST-EL14 COLUMBIA DAY-BRITE LIGHTOLIER METALUX
F1		(2) F327B/3500K 835	62	120/277	4" WET LOCATION INDUSTRIAL - RUGGED LIGHT GRAY POLYCARBONATE HOUSING - CONTINUOUS Poured GASKETED - INSTANT START ELECTRONIC BALLAST < 10% THD - UL LISTED FOR WET LOCATIONS	LITHONIA - XWL232MV COLUMBIA DAY-BRITE LIGHTOLIER
F2		(2) F327B/3500K 835	62	120/277	4" TELESCOPING STAGGERED STRIP FIXTURE - HEAVY DUTY COLD ROLLED STEEL CHANNEL - HIGH GLOSS BAKED WHITE ENAMEL FINISH - INSTANT START ELECTRONIC BALLAST < 10% THD - UL LISTED	LITHONIA - SST-2-32-MVOLT- GEB101S-GLR COLUMBIA DAY-BRITE LIGHTOLIER METALUX
F3		(2) F327B/3500K 835	62	120/277	2" TELESCOPING STAGGERED STRIP FIXTURE - HEAVY DUTY COLD ROLLED STEEL CHANNEL - HIGH GLOSS BAKED WHITE ENAMEL FINISH - INSTANT START ELECTRONIC BALLAST < 10% THD - UL LISTED	LITHONIA - SST-2-17-MVOLT- GEB101S-GLR COLUMBIA DAY-BRITE LIGHTOLIER METALUX
F4		(2) F327B/3500K 835	64	120/277	4" STAGGERED STRIP FIXTURE - HEAVY DUTY COLD ROLLED STEEL CHANNEL - HIGH GLOSS BAKED WHITE ENAMEL FINISH - INSTANT START ELECTRONIC BALLAST < 10% THD - UL LISTED	LITHONIA - SS-2-32-MVOLT- GEB101S-GLR COLUMBIA DAY-BRITE LIGHTOLIER METALUX
F4E		(2) F327B/3500K 835	34	120/277	SAME AS TYPE F4 EXCEPT WITH 90 MINUTE 1400 LUMEN EMERGENCY BATTERY PACK	LITHONIA - SS-2-32-MVOLT- GEB101S-EL14-GLR COLUMBIA DAY-BRITE LIGHTOLIER

LUMINAIRE SCHEDULE						
TYPE	SYMBOL	LAMP	VA	VOLT	LUMINAIRE DESCRIPTION	EQUAL MANUFACTURERS
A		(2) F327B/3500K	62	120/277	DIRECT/INDIRECT 2 X 4 RECESSED FLUORESCENT FIXTURE - HOUSING GLOSS WHITE ENAMEL ON COLD ROLLED STEEL - OPTICS (2) MATTE WHITE POLYESTER POWDER COAT REFLECTORS - CENTER METAL DIFFUSER WITH .075" HOLES - INTERNAL FAST BLOW FUSE - ELECTRONIC DIMMING BALLAST THD< 10% - UL LISTED	LITHONIA - 2AV-G-2-17-MDR MVOLT-LUTRON ECOSYSTEM DIMMING-BALLAST-GLR COLUMBIA DAY-BRITE LIGHTOLIER
A1		(2) F327B/3500K	62	120/277	2 X 4 RECESSED FLUORESCENT FIXTURE - HOUSING GLOSS WHITE ENAMEL ON COLD ROLLED STEEL - ACRYLIC PRISMATIC LENS 0.125" THICK - FLUSH STEEL DOOR - INTERNAL FAST BLOW FUSE - ELECTRONIC BALLAST THD< 10% - UL LISTED	LITHONIA - 2G18-232-A12125- MVOLT-GE101S- GLR COLUMBIA DAY-BRITE LIGHTOLIER
A2		(2) F177B/3500K	33	120/277	DIRECT/INDIRECT 2 X 2 RECESSED FLUORESCENT FIXTURE - HOUSING GLOSS WHITE ENAMEL ON COLD ROLLED STEEL - OPTICS (2) MATTE WHITE POLYESTER POWDER COAT REFLECTORS - CENTER METAL DIFFUSER WITH .075" HOLES - INTERNAL FAST BLOW FUSE - DIMMING ELECTRONIC BALLAST - UL LISTED	LITHONIA - 2AV-G-2-17-MDR MVOLT-LUTRON ECOSYSTEM DIMMING-BALLAST-GLR COLUMBIA DAY-BRITE LIGHTOLIER
A2E		(2) F177B/3500K	33	120/277	SAME AS TYPE A1 EXCEPT WITH 90 MINUTE EMERGENCY BATTERY PACK	LITHONIA - 2AV-G-2-17-MDR MVOLT-LUTRON ECOSYSTEM DIMMING-BALLAST-GLR COLUMBIA DAY-BRITE LIGHTOLIER
B1		2000 LUMENS 2700K LED	35	120	6" 0 HOUSE LIGHT FIXTURE - SELF FLANGED SEMI SPECULAR DIFFUSE - 45 DEGREE CUT-OFF TO SOURCE AND SOURCE IMAGE - LIGHT ENGINE AND DRIVER ARE ACCESSIBLE FROM ABOVE AND BELOW - 16 GAUGE BLACK PAINTED STEEL MOUNTING FRAME WITH C CHANNEL MOUNTING TABS - 0-10V DIMMING - SOLID STATE LED LIGHT ENGINE 2700K, 85 CRI - 20 DEGREE SLOPED CEILING ADAPTOR	GOTHAM - CO-2720-6BR- SF-TBL-20D PHILLIPS/ SELECON
B2		3000 LUMENS 2700K LED	50	120	6" 0 HOUSE LIGHT FIXTURE - SELF FLANGED SEMI SPECULAR DIFFUSE - 45 DEGREE CUT-OFF TO SOURCE AND SOURCE IMAGE - LIGHT ENGINE AND DRIVER ARE ACCESSIBLE FROM ABOVE AND BELOW - 16 GAUGE BLACK PAINTED STEEL MOUNTING FRAME WITH C CHANNEL MOUNTING TABS - 0-10V DIMMING - SOLID STATE LED LIGHT ENGINE 2700K, 85 CRI - 20 DEGREE SLOPED CEILING ADAPTOR	GOTHAM - CO-2720-6BR- LD-65-277-DMXR- SF-TBL-20D PHILLIPS/ SELECON
B3		6500 LUMENS 2700K LED	95	120	6" 0 HOUSE LIGHT FIXTURE - SELF FLANGED SEMI SPECULAR DIFFUSE - 45 DEGREE CUT-OFF TO SOURCE AND SOURCE IMAGE - LIGHT ENGINE AND DRIVER ARE ACCESSIBLE FROM ABOVE AND BELOW - 16 GAUGE BLACK PAINTED STEEL MOUNTING FRAME WITH C CHANNEL MOUNTING TABS - 0-10V DIMMING - SOLID STATE LED LIGHT ENGINE 2700K, 85 CRI - 20 DEGREE SLOPED CEILING ADAPTOR	GOTHAM - CO-2720-6BR- LD-65-277-DMXR- SF-TBL-20D PHILLIPS/ SELECON
C		(1) F327B/3500K 85 CRI	34	120/277	4" X 4" SURFACE LINEAR FIXTURE - SURFACE MOUNTING - EXTRUDED ALUMINUM HOUSING - REFLECTORS WHITE POWDER COATED STEEL - SATIN LENSE - ECOSYSTEM DIMMING ELECTRONIC BALLAST - UL LISTED	AXIS LIGHTING - BEAM 4 - BBS-S-FE-4-EX- 18-1-W-UNV-D-1- DS-F-FW#
CE		(1) F327B/3500K 85 CRI	68	120/277	SAME AS TYPE C EXCEPT WITH 90 MINUTE EMERGENCY BATTERY PACK	AXIS LIGHTING - BEAM 4 - BBS-S-FE-4-EX- 18-1-W-UNV-D-1- DS-B90-F-FW#
CA		(2) F327B/3500K 85 CRI	68	120/277	SAME AS TYPE C EXCEPT WITH (2) T8 LAMPS	AXIS LIGHTING - BEAM 4 - BBS-S-FE-4-EX- 18-2-W-UNV-D-1- DS-B90-F-FW#
CAE		(2) F327B/3500K 85 CRI	68	120/277	SAME AS TYPE CA EXCEPT WITH 90 MINUTE EMERGENCY BATTERY PACK	AXIS LIGHTING - BEAM 4 - BBS-S-FE-4-EX- 18-2-W-UNV-D-1- DS-B90-F-FW#
C1		(3) F327B/3500K 85 CRI	102	120/277	12" X 4" SURFACE LINEAR FIXTURE - SURFACE MOUNTING - REFLECTORS WHITE POWDER COATED STEEL - CONTINUOUS SATIN LENS - STAGGERED LAMPING - ECOSYSTEM DIMMING ELECTRONIC BALLAST - 90 MINUTE EMERGENCY BATTERY IN 4" SECTION REFER TO PLAN DRAWINGS - UL LISTED	AXIS LIGHTING - BEAM 4 - BBS-S-FE-12-EX- 18-1-W-UNV-D-1- DS-B90-F-FW#
C1A		(6) F327B/3500K 85 CRI	204	120/277	12" X 4" SURFACE LINEAR FIXTURE - EXTRUDED ALUMINUM HOUSING - REFLECTORS WHITE POWDER COATED STEEL - CONTINUOUS SATIN LENS - STAGGERED LAMPING - ECOSYSTEM DIMMING ELECTRONIC BALLAST - 90 MINUTE EMERGENCY BATTERY IN 4" SECTION REFER TO PLAN DRAWINGS - UL LISTED	AXIS LIGHTING - BEAM 4 - BBS-S-FE-12-EX- 18-2-W-UNV-D-1- DS-B90-F-FW#
C2		(2) F327B/3500K 85 CRI	68	120/277	4" X 4" PENDANT DIRECT LINEAR FIXTURE - 4" PENDANT MOUNTING - EXTRUDED ALUMINUM HOUSING - REFLECTORS WHITE POWDER COATED STEEL - SATIN LENSE - ECOSYSTEM DIMMING ELECTRONIC BALLAST - UL LISTED	AXIS LIGHTING - BEAM 4 - BBS-S-FE-4-EX- 18-2-W-UNV-D-1- CA36-F
C3		(6) F547SHO/3500K 85CRI	345	120/277	12" X 4" SURFACE LINEAR FIXTURE - SURFACE MOUNTING - EXTRUDED ALUMINUM HOUSING - REFLECTORS WHITE POWDER COATED STEEL - STAGGERED LAMPING - CONTINUOUS SATIN LENSE - ECOSYSTEM DIMMING ELECTRONIC BALLAST - 90 MINUTE EMERGENCY BATTERY IN 4" SECTION REFER TO PLAN DRAWINGS - UL LISTED	AXIS LIGHTING - BEAM 4 - BBS-S-FE-12-EX- 18-2-W-UNV-D-1- DS-F
C4		100 LMFT 3000K	5 W/F	120/277	12" X 4" RECESSED LINEAR FIXTURE - EXTRUDED ALUMINUM HOUSING - REFLECTORS WHITE POWDER COATED STEEL - CONTINUOUS LENS DESIGNED FOR LED LIGHT SOURCE - 12VDC LED DRIVER, 99% PF, CLASS A SOUND RATING, EXTREME LOW TEMPERATURE RATED (-40 DEGREE) - 90 MINUTE EMERGENCY BATTERY IN 4" SECTION REFER TO PLAN DRAWINGS - UL LISTED FOR WET LOCATIONS	ALIGHTS- ACCOLADE- DS-12-L130-U-SH- G-W-(E)-Q
C4A		100 LMFT 3000K	5 W/F	120/277	SAME AS TYPE C4 EXCEPT 8" LENGTH	ALIGHTS- ACCOLADE- DS-8-L130-U-SH- G-W-(E)-Q

Issued / Revised		
No.	Date	Description
1	2/26/13	ISSUED FOR PERMIT
2	3/11/13	ADDENDUM NO. 1
3	3/21/13	ADDENDUM NO. 2

3/3/14 PR-006 Addition - Complete Build-Out

#### Luminaire Schedule Notes

- THE TERM "APPROVED EQUAL MANUFACTURER" SHALL BE DEFINED AS A PRODUCT THAT POTENTIALLY MAY BE EQUIVALENT TO THE "BASIS OF DESIGN MANUFACTURER". THE PRODUCT IS EXPECTED TO PERFORM IN AN EQUIVALENT MANNER IN AREAS SUCH AS QUALITY, PERFORMANCE, MANUFACTURING, AVAILABLE OPTIONS, PRICING, WARRANTY, WARRANTY RESOLUTION, DELIVERY, AND AFTER-SALE SUPPORT.
- THE ARCHITECT/ENGINEER RESERVES THE RIGHT TO DETERMINE WHETHER OR NOT THE DESIGNATED "APPROVED EQUAL MANUFACTURER" IS EQUAL TO THE "BASIS OF DESIGN MANUFACTURER" AND ACCEPTABLE FOR USE ON THIS PROJECT.
- LUMINAIRE SUBMITTALS WHICH ARE DESIGNATED AS "APPROVED EQUAL MANUFACTURER" AND DO NOT INCLUDE SPECIFIC CATALOG DESIGNATIONS SHALL BE ACCOMPANIED BY PERFORMANCE DATA FROM AN INDEPENDENT TESTING LAB, COLOR PHOTOGRAPHY, DIMENSIONAL DRAWINGS AND PROJECT SPECIFIC, ANTICIPATED FOOTCANDLE LEVELS, UPON REQUEST OF ARCHITECT/ENGINEER.
- LUMINAIRES LISTED IN SCHEDULE WITHOUT ANY "APPROVED EQUAL MANUFACTURER" LUMINAIRES ARE UNIQUE IN QUALITY AND AVAILABLE ONLY FROM SPECIFIED MANUFACTURER. LUMINAIRE SUBMITTALS FROM UNAPPROVED MANUFACTURERS TRYING TO COPY OR KNOCK-OFF THE ORIGINAL DESIGN ARE NOT ACCEPTABLE.
- FOR EXACT LOCATION OF RECESSED LUMINAIRES, SEE ARCHITECTURAL REFLECTED CEILING PLANS AND FOR EXACT LOCATION OF WALL MOUNTED LUMINAIRES, SEE ARCHITECTURAL ELEVATIONS AND DETAILS.
- LUMINAIRES SHOWN ON PLANS WITH CROSS HATCHING ARE DESIGNATED FOR EMERGENCY AND EGRESS REQUIREMENTS. LUMINAIRES SHALL BE CONNECTED TO EMERGENCY POWER SOURCE PER NEC, ARTICLE 700 BY MEANS OF AN INTEGRAL OR REMOTE SELF-CONTAINED EMERGENCY TRANSFER DEVICE THAT BYPASSES LOCAL SWITCHING AND LIGHTING CONTROL RELAYS. REFER TO SCHEDULES AND DETAILS FOR REQUIREMENTS.
- BURN IN ALL FLUORESCENT LAMPS AT 100% POWER FOR 48 HOURS PRIOR TO DIMMING.
- ALL 4" T8 FLUORESCENT LAMPS (INDICATED IN THE SCHEDULE AS "T3218/835") ARE TO BE "SUPER T8" TYPE WITH 3100 INITIAL LUMENS, 3500