

Ordinances of the City of Grand Junction, Colorado

ORDINANCE NO. 182.

AN ORDINANCE TO AMEND CERTAIN SECTIONS OF ORDINANCE NO. 167, ENTITLED "AN ORDINANCE DEFINING SIDEWALK AND CURB LINES AND PRESCRIBING MATERIALS FOR SIDEWALK CONSTRUCTION IN THE CITY OF GRAND JUNCTION, COLORADO."

Be it Ordained by the City Council of the City of Grand Junction, Colorado:

Section 1 of Ordinance No. 167 entitled "An Ordinance Defining Sidewalk and Curb Lines and Prescribing Materials for Sidewalk Construction in the City of Grand Junction," be, and the same is hereby amended so as to read as follows:

Section 1. That upon the following named portions of streets and avenues within the city of Grand Junction, the sidewalks shall be of the width specified herein and the curb line shall be a line along the outer edge of the sidewalk. All sidewalks shall be fifteen feet wide on Second Street from the right-of-way of the Denver and Rio Grande Railroad Company to Main Street; on Fourth Street between Ute Avenue and Rood Avenue; on Fifth Street from Colorado Avenue to White Avenue; on Sixth Street from Colorado Avenue to Rood Avenue; on Colorado Avenue from Second Street to Sixth Street. All sidewalks shall be sixteen (16) feet wide on Main Street from Second Street to Seventh Street.

Section 7 of said ordinance shall be and the same is hereby amended so as to read as follows:

Sec. 7. If the walk or crossing is constructed of concrete, it shall be laid in accordance with the following specifications: The mixture for the base shall be composed of 4 and 1/3 sacks of cement to one cubic yard of sand and gravel, or in the same proportion for smaller quantities. No gravel shall be used which will not pass through a 3 and 1/2 inch ring; concrete shall be laid not less than 3 and 1/4 inches thick after being well tamped on sidewalks, and not less than 7 inches thick after being well tamped on crossings. For the cap or top dressing, the concrete mixture shall be composed of one part standard grade cement to 1 and 1/2 parts fine sand of good quality, which has been screened through a screen of 3/16 inch mesh, and shall be not less than 3/4 inch in thickness at any point. The top dressing shall be finished with a smooth float finish, and must be laid immediately after the concrete has been tamped, to be cut with the jointer crosswise every 2 and 1/2 feet along the length of the walk; no crease or line shall be cut lengthwise along the center of the walk. Expansion joints of at least 1/2 inch shall be cut at least every fifty feet and an expansion joint of at least 1/2 inch shall be left at each end of alley or street crossings where they are joined to the sidewalks. All walks or crossings must be covered with sand or dirt and kept wet for 24 hours.

Adopted and approved this 6th day of September, A. D. 1910.

Thos M. Todd
Mayor.

Attest:

Charles K. Holmberg
City Clerk.

I hereby certify, that the foregoing ordinance, entitled "An Ordinance to Amend Certain Sections of Ordinance No. 167, entitled 'An Ordinance Defining Sidewalk and Curb Lines and Prescribing Materials for Sidewalk Construction in the City of Grand Junction, Colorado,'" was introduced and read at a regular meeting of the City Council of the City of Grand Junction, held on the 23d day of August, A. D. 1910, and that the same was published in full in the Daily News, a daily newspaper published and in general circulation in said city, at least ten days before its passage.

IN WITNESS WHEREOF, I have hereunto set my hand and affixed the official seal of said city this 6th day of September, A. D. 1910.

Charles K. Holmberg
City Clerk.

(SEAL)