		_					
Planning \$ 3,780 Draina 2806	20		DG PERMIT NO.				
TCP\$ TOP School Impact \$ N	/A		FILE # SPR-2005-140				
per Eric PLANNII	NG CLEA	RANCE					
(site plan review, multi-family development, non-residential development)							
THIS SECTION TO BE COMPLETED BY APPLICANT 95338 - 54							
BUILDING ADDRESS 2471 River Road		TAX SCHEDULE NO. 2945-094-19-003					
SUBDIVISION Bormac	SQ. FT	SQ. FT. OF EXISTING BLDG(S) 0 4000 \$12 12,570					
FILING BLK LOT 3	SQ. FT	OF PROPOSE	DBLDG(S)/ADDITONS 4000 ft^2				
McCallum Family LLC and OWNER Chris S. McCallum LLP	MULTI	I-FAMILY:	UNITS: BEFORE 0 AFTER 0				
ADDRESS 2471 River Rd Wit A		NSTRUCTION	ONITS. BEI ONEAITEN				
CITY/STATE/ZIP Grand Jot. CO 81505	NO. COŃ	NO. OF BLDGS ON PARCEL: BEFORE 2 AFTER 3 CONSTRUCTION					
APPLICANT TPI SHOWN Chris McCal	lum USE O	F ALL EXISTING	G BLDG(S) Office Warehouse				
ADDRESS 2471 River Rd-Unit	A DESCE	RIPTION OF WO	ORK & INTENDED USE:				
CITY/STATE/ZIP Grand July. CO 8150	<u> </u>	ns truction	n of 4000 ft2 office				
TELEPHONE 970 - 242-4454		irehouse	for lease				
Submittal requirements are outlined in the SSID (Submittal Standards for Improvements and Development) document. THIS SECTION TO BE COMPLETED BY COMMUNITY DEVELOPMENT DEPARTMENT STAFF							
	OF COMMISSIONALL LIDES	ACEOU MICHIU DEI WIT					
T			,				
ZONE			ENING REQUIRED: YES 1 NO				
ZONE	LANDS	SCAPING/SCRE	,				
SETBACKS: FRONT: 15 from Property Line (PL) from property Line (PL) from Pl REAR: 16 from F	LANDS	SCAPING/SCRE	ENT: Jans dated 6/20 \$				
SETBACKS: FRONT: from Property Line (PL) from SIDE: from PL REAR: from F	LANDS or PARKIN	SCAPING/SCRE	ENT: Jans dated 6/20 \$				
SETBACKS: FRONT: from Property Line (PL) from icenter of ROW, whichever is greater SIDE: from PL REAR: from F	LANDS or PARKIN	SCAPING/SCRE	ENT: Jans dated 6/20 \$				
SETBACKS: FRONT: from Property Line (PL) fromjcenter of ROW, whichever is greater SIDE: from PL REAR: from F MAX. HEIGHT MAX. COVERAGE OF LOT BY STRUCTURES	LANDS or PARKIN PL SPECIA	SCAPING/SCRE NG REQUIREME AL CONDITIONS	ENING REQUIRED: YES \(\sum \) NO ENT: \(\frac{100}{200} \)				
SETBACKS: FRONT: from Property Line (PL) from Property Line (PL) from PL REAR: from FMAX. HEIGHT	LANDS or PARKIN PL SPECIA	SCAPING/SCRE NG REQUIREME AL CONDITIONS	ENING REQUIRED: YES X_NO ENT: <u>fans dated 6/20 \$</u> S: \[\text{Yes d 8/4/05} \]				
SETBACKS: FRONT: from Property Line (PL) from Center of ROW, whichever is greater SIDE: from PL REAR: from FMAX. HEIGHT MAX. COVERAGE OF LOT BY STRUCTURES Modifications to this Planning Clearance must be approved, in authorized by this application cannot be occupied until a final issued by the Building Department (Section 307, Uniform Buguaranteed prior to issuance of a Planning Clearance. All bushance of a Certificate of Occupancy. Any landscaping requirement of any vegetation materials that die or are	LANDS or PARKIN PL SPECIA writing, by the Clinspection has aliding Code). her required siting in an unhealth	Community Deves been complete improvements not condition is re-	ENING REQUIRED: YES NO ENT:				
SETBACKS: FRONT: from Property Line (PL) from Center of ROW, whichever is greater SIDE: from PL REAR: from FMAX. HEIGHT MAX. COVERAGE OF LOT BY STRUCTURES MODIFICATION OF THE CONTROL OF THE CON	LANDS or PARKIN PL SPECIA writing, by the Clainspection has aliding Code). her required sitired by this permin an unhealth I and stamped to S. information is continuous contin	Community Deve s been complete Required improvements in the shall be maintally condition is re-	ENING REQUIRED: YES NO ENT: Auto data 6/20 4 For a 8/4/05 S: Vov a 8/4/0				
SETBACKS: FRONT: from Property Line (PL) from Center of ROW, whichever is greater SIDE: from PL REAR: from FMAX. HEIGHT MAX. COVERAGE OF LOT BY STRUCTURES MODIFICATION OF THE STRUCTURES	LANDS or PARKIN PL SPECIA writing, by the Clainspection has aliding Code). her required sitired by this permin an unhealth I and stamped to S. information is continuous contin	Community Deve s been complete Required improvements in the shall be maintally condition is re-	ENING REQUIRED: YES NO ENT: Auto data 6/20 4 For a 8/4/05 S: Vov a 8/4/0				
SETBACKS: FRONT: from Property Line (PL) from SIDE: from PL REAR: from FMAX. HEIGHT MAX. COVERAGE OF LOT BY STRUCTURES MAIL STRUCTURES MAX. COVERAGE OF LOT BY STRUCTURES MAX. COVERAGE OF LOT BY STRUCTURES MAIL STRUCTURES MAX. COVERAGE OF LOT BY STRUCTURES	LANDS or PARKIN PL SPECIA writing, by the Clainspection has aliding Code). her required sitired by this permin an unhealth I and stamped to S. information is continuous contin	Community Deve s been complete Required improvements in the shall be maintally condition is re-	ENING REQUIRED: YES NO				
SETBACKS: FRONT: from Property Line (PL) from Center of ROW, whichever is greater SIDE: from PL REAR: from FMAX. HEIGHT MAX. COVERAGE OF LOT BY STRUCTURES	LANDS or PARKIT PL SPECIA writing, by the Clinspection has ailding Code). her required sitired by this perm in an unhealth and stamped to the conference of	Community Deves been complete Required improvements in the shall be maint by City Engineer correct; I agree to railure to comply	ENING REQUIRED: YES NO ENT: Almo data 6/36 f Your d 8/4/05 S: Plopment Department Director. The structure d and a Certificate of Occupancy has been wements in the public right-of-way must be a must be completed or guaranteed prior to ained in an acceptable and healthy condition. equired by the Grand Junction Zoning and ring prior to issuing the Planning Clearance. I comply with any and all codes, ordinances, shall result in legal action, which may include				
SETBACKS: FRONT:	writing, by the Clinspection has aliding Code). her required sirred by this pering an unhealth and stamped to the conferstand that for the confers the conferstand that for the confers	Community Deves been complete Required improvements in the shall be maint by City Engineer correct; I agree to ailure to comply	ENING REQUIRED: YES \(\sum_{NO} \) Aster \(\lambda \) Aster \(\				
SETBACKS: FRONT:	LANDS or PARKIT PL SPECIA writing, by the Clainspection has aliding Code). her required sitired by this permin an unhealth and stamped to stand that for the standard that for	Community Development Service Improvements and condition is recorded to complete improvements and condition is recorded to comply and complete and comple	ENING REQUIRED: YES \(\) NO				



FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ELEVATION CERTIFICATE

AND

Instructions

NEW EDITION

NATIONAL FLOOD INSURANCE PROGRAM ELEVATION CERTIFICATE

PAPERWORK REDUCTION ACT NOTICE

Public reporting burden for the Elevation Certificate is estimated to average 2.25 hours per response. Burden means the time, effort, or financial resources expended by persons to generate, maintain, retain, disclose, or provide information to the Federal Emergency Management Agency (FEMA). You are not required to respond to the collection of information unless a valid OMB control number is displayed in the upper right corner of each form. You may send comments regarding the accuracy of the burden estimate and any suggestions for reducing the burden to: Information Collections Management, Federal Emergency Management Agency, 500 C Street, SW, Washington, DC 20472, Paperwork Reduction Project (3067-0077). Do not send completed form(s) to the above address. To obtain or retain benefits under the National Flood Insurance Program (NFIP), you must respond to this collection of information.

PURPOSE OF THE ELEVATION CERTIFICATE

The Elevation Certificate is an important administrative tool of the National Flood Insurance Program (NFIP). It is to be used to provide elevation information necessary to ensure compliance with community floodplain management ordinances, to determine the proper insurance premium rate, and to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR-F).

The Elevation Certificate is required in order to properly rate post-FIRM buildings, which are buildings constructed after publication of the Flood Insurance Rate Map (FIRM), for flood insurance Zones A1-A30, AE, AH, A (with BFE), VE, V1-V30, V (with BFE), AR, AR/A, AR/AE, AR/A1-A30, AR/AH, and AR/AO. The Elevation Certificate is not required for pre-FIRM buildings unless the building is being rated under the optional post-FIRM flood insurance rules.

As part of the agreement for making flood insurance available in a community, the NFIP requires the community to adopt a floodplain management ordinance that specifies minimum requirements for reducing flood losses. One such requirement is that the community obtain the elevation of the lowest floor (including basement) of all new and substantially improved buildings, and maintain a record of such information. The Elevation Certificate provides a way for a community to comply with this requirement.

Use of this certificate does not provide a waiver of the flood insurance purchase requirement. Only a LOMA or LOMR-F from the Federal Emergency Management Agency (FEMA) can amend the FIRM and remove the Federal mandate for a lending institution to require the purchase of flood insurance. However, the lending institution has the option of requiring flood insurance even if a LOMA/LOMR-F has been issued by FEMA. The Elevation Certificate may be used to support a LOMA or LOMR-F request. Lowest floor and lowest adjacent grade elevations certified by a surveyor or engineer will be required if the certificate is used to support a LOMA or LOMR-F request.

This certificate is used only to certify building elevations. A separate certificate is required for floodproofing. Under the NFIP, non-residential buildings can be floodproofed up to or above the Base Flood Elevation (BFE). A floodproofed building is a building that has been designed and constructed to be watertight (substantially impermeable to floodwaters) below the BFE. Floodproofing of residential buildings is not permitted under the NFIP unless FEMA has granted the community an exception for residential floodproofed basements. The community must adopt standards for design and construction of floodproofed basements before FEMA will grant a basement exception. For both floodproofed non-residential buildings and residential floodproofed basements in communities that have been granted an exception by FEMA, a floodproofing certificate is required.

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

O.M.B. No. 3067-0077 Expires July 31, 2002

ELEVATION CERTIFICATE

Important: Read the instructions on pages 1 - 7. **SECTION A - PROPERTY OWNER INFORMATION** For Insurance Company Use: Policy Number BUILDING OWNER'S NAME McCallum Family LLLP and Chris S. McCallum LLC BUILDING STREET ADDRESS (Including Apt., Unit, Suite, and/or Bidg. No.) OR P.O. ROUTE AND BOX NO. 2471 Kiver Road - Wait & C Company NAIC Number STATE ZIP CODE CITY Grand 81505 Junction PROPERTY DESCRIPTION (Lot and Block Numbers, Tax Parcel Number, Legal Description, etc.)
Lot 3 Barnac Subdivision, 2945-094-19-003 BUILDING USE (e.g., Residential, Non-residential, Addition, Accessory, etc. Use a Comments area, if necessary.) Warehouse Commercia HORIZONTAL DATUM: SOURCE: | GPS (Type): LATITUDE/LONGITUDE (OPTIONAL) (##° - ##' - ## ##" or ## .####°) MOther: FEMA Map NAD 1927 ____ NAD 1983 USGS Quad Map SECTION B - FLOOD INSURANCE RATE MAP (FIRM) INFORMATION B1. NFIP COMMUNITY NAME & COMMUNITY NUMBER B2. COUNTY NAME B3. STATE **Vlesa** 080115 Count Colorado Mesa County **B4. MAP AND PANEL B6. FIRM INDEX B7. FIRM PANEL** B8. FLOOD B9, BASE FLOOD ELEVATION(S) B5. SUFFIX ZONE(S) EFFECTIVE/REVISED DATE (Zone AO, use depth of flooding) NUMBER DATE July 1978 July 15, 1992 4542,75 080115-0460 B10. Indicate the source of the Base Flood Elevation (BFE) data or base flood depth entered in B9. X FIRM __ | Community Determined __| Other (Describe): B11. Indicate the elevation datum used for the BFE in B9: X NGVD 1929 | NAVD 1988 | Other (Describe): B12. Is the building located in a Coastal Barrier Resources System (CBRS) area or Otherwise Protected Area (OPA)? |__| Yes **Designation Date:** SECTION C - BUILDING ELEVATION INFORMATION (SURVEY REQUIRED) C1. Building elevations are based on: Construction Drawings* Building Under Construction* |Finished Construction *A new Elevation Certificate will be required when construction of the building is complete. C2. Building Diagram Number ____ (Select the building diagram most similar to the building for which this certificate is being completed - see pages 6 and 7. If no diagram accurately represents the building, provide a sketch or photograph.) C3. Elevations - Zones A1-A30, AE, AH, A (with BFE), VE, V1-V30, V (with BFE), AR, AR/A, AR/AE, AR/A1-A30, AR/AH, AR/AO Complete Items C3.a-i below according to the building diagram specified in Item C2. State the datum used. If the datum is different from the datum used for the BFE in Section B, convert the datum to that used for the BFE. Show field measurements and datum conversion calculation. Use the space provided or the Comments area of Section D or Section G, as appropriate, to document the datum conversion/ NA Datum NGVD 1929 Conversion/Comments Elevation reference mark used___RM #18 Does the elevation reference mark used appear on the FIRM? MINION REG 4548, a) Top of bottom floor (including basement or enclosure) 8 ft.(m) b) Top of next higher floor NA ft.(m) ☐ c) Bottom of lowest horizontal structural member (V zones only) NA ft.(m) NA ☐ d) Attached garage (top of slab) ft.(m) ☐ e) Lowest elevation of machinery and/or equipment 4548 servicing the building (Describe in a Comments area.) ft.(m) ☐ f) Lowest adjacent (finished) grade (LAG) ft.(m) Q g) Highest adjacent (finished) grade (HAG) 7_ft.(m) ☐ h) No. of permanent openings (flood vents) within 1 ft. above adjacent grade 0 i) Total area of all permanent openings (flood vents) in C3.h SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION This certification is to be signed and sealed by a land surveyor, engineer, or architect authorized by law to certify elevation information. I certify that the information in Sections A, B, and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001. CERTIFIER'S NAME LICENSE NUMBER COMPANY NAME CES ADDRESS STATE ZIP CODE ΩC TELEPHONE FFMA Form 81-31 .IIII 00 SEE REVERSE SIDE FOR CONTINUATION REPLACES ALL PREVIOUS EDITIONS

IMPORTANT: In these space				For insurance Company Use:			
BUILDING STREET ADDRESS (2471 River Ro	(Including Apt., Unit, Suite, and/or	Bldg. No.) OR P.O. F	ROUTE AND BOX NO.	Policy Number			
Grand Juncti	01	STATE CO	zip codi 81505	Company NAIC Number:			
SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION (CONTINUED)							
Copy both sides of this Elevation Certificate for (1) community official, (2) insurance agent/company, and (3) building owner.							
COMMENTS				- <u> </u>			
			· · · · · · · · · · · · · · · · · · ·				
							
				Check here if attachments			
		·		AND ZONE A (WITHOUT BFE)			
see pages 6 and 7. If no d	AR-F, Section C must be comp (Select the building dia iagram accurately represents	oleted. gram most similar the building, provi	to the building for which thi de a sketch or photograph.)	s certificate is being completed -			
E2. The top of the bottom floor (including basement or enclosure) of the building is ft.(m)							
E4. For Zone AO only: If no flo floodplain management or		• •		rdance with the community's his information in Section G.			
	TION F - PROPERTY OWNER						
The property owner or owner's	s authorized representative wh mmunity-issued BFE) or Zone	no completes Secti AO must sign her	ons A, B, C (Items C3.h an				
McCallum Family	LLC and Chris S. Mc	Callum LLP	STATE	ZIP CODE			
ADDRESS 2471 Rives Rox	ad Unit A	Grand Jun	ction Co	81505			
STGNATURE IN		DATE	TELEP	HONE			
COMMENTS			1				
			· · · · · · · · · · · · · · · · · · ·	Check here if attachments			
· · · · · · · · · · · · · · · · · · ·	SECTION G - COM	MUNITY INFORM	IATION (OPTIONAL)	Officer field if attachments			
The local official who is authoriz Sections A, B, C (or E), and G of G1. [] The information in Section engineer, or architect velevation data in the CG2. [] A community official cozone AO. G3. [] The following information	f this Elevation Certificate. Co ion C was taken from other do who is authorized by state or lo omments area below.) mpleted Section E for a buildi	omplete the applic ocumentation that I ocal law to certify e ng located in Zone	able item(s) and sign belown has been signed and embo- levation information. (Indic A (without a FEMA-issued	n. ssed by a licensed surveyor, ⇒ate the source and date of the or community-issued BFE) or			
G4. PERMIT NUMBER	G5. DATE PERMIT ISSUE	D		F COMPLIANCE/OCCUPANCY			
G7. This permit has been issued G8. Elevation of as-built lowest G9. BFE or (in Zone AO) depth	floor (including basement) of t	he building is:		ft.(m) Datum: ft.(m) Datum:			
LOCAL OFFICIAL'S NAME		TIT	LE				
COMMUNITY NAME TELEPHONE							
SIGNATURE DATE							
COMMENTS		·					
		· · · · · -					
				Check here if attachments			

INSTRUCTIONS FOR COMPLETING THE ELEVATION CERTIFICATE

The Elevation Certificate is to be completed by a land surveyor, engineer, or architect who is authorized by law to certify elevation information when elevation information is required for Zones A1-A30, AE, AH, A (with BFE), VE, V1-V30, V (with BFE), AR, AR/A, AR/AE, AR/A1-A30, AR/AH, or AR/AO. Community officials who are authorized by law or ordinance to provide floodplain management information may also complete this form. For Zones AO and A (without BFE), a community official, a property owner, or an owner's representative may provide information on this certificate, unless the elevations are intended for use in supporting a LOMA or LOMR-F. Certified elevations must be included if the purpose of completing the Elevation Certificate is to obtain a LOMA or LOMR-F.

In Puerto Rico only, elevations for building information and flood hazard information may be entered in meters.

SECTION A - PROPERTY OWNER INFORMATION

This section identifies the building, its location, and its owner. Enter the name(s) of the building owner(s), the building's complete street address, and the lot and block number. If the building's address is different from the owner's address, enter the address of the building being certified. If the address is a rural route or a Post Office box number, enter the lot and block numbers, the tax parcel number, the legal description, or an abbreviated location description based on distance and direction from a fixed point of reference. For the purposes of this certificate, "building" means both a building and a manufactured (mobile) home.

A map may be attached to this certificate to show the location of the building on the property. A tax map, FIRM, or detailed community map is appropriate. If no map is available, provide a sketch of the property location, and the location of the building on the property. Include appropriate landmarks such as nearby roads, intersections, and bodies of water. For building use, indicate whether the building is residential, non-residential, an addition to an existing residential or non-residential building, an accessory building (e.g., garage), or other type of structure. Use the Comments area of Section F if needed.

If latitude and longitude data are available, enter them in degrees, minutes, and seconds, or in decimal degrees, taken at the center of the front of the building. Enter arc seconds to two decimal places. Indicate the horizontal datum and the source of the measurement data (for example, taken with GPS, scaled from a USGS Quad Map, etc.).

SECTION B - FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Complete the Elevation Certificate on the basis of the FIRM in effect at the time of the certification.

The information for Section B is obtained by reviewing the FIRM panel that includes the building's location. Information about the current FIRM and a pamphlet titled "Guide to Flood Maps" are available from the Federal Emergency Management Agency (FEMA) website at http://www.fema.gov or by calling 1-800-427-4661. If a Letter of Map Amendment (LOMA) or Letter of Map Revision (LOMR-F) has been issued by FEMA, please provide the letter date and case number in the Comments area of Section D or Section G, as appropriate.

Item B1. NFIP Community Name & Community Number. Enter the complete name of the community in which the building is located and the associated 6-digit community number. For a building that is in an area that has been annexed by one community but is shown on another community's FIRM, enter the community name and 6-digit number of the annexing community. For a newly incorporated community, use the name and 6-digit number of the new community. Under the NFIP, a "community" is any State or area or political subdivision thereof, or any Indian tribe or authorized native organization, that has authority to adopt and enforce floodplain management regulations for the areas within its jurisdiction. To determine the current community number, see the NFIP Community Status Book, available on FEMA's website at http://www.fema.gov or by calling 1-800-427-4661.

Item B2. County Name. Enter the name of the county or counties in which the community is located. For an unincorporated area of a county, enter "unincorporated area." For an independent city, enter "independent city."

Item B3. State. Enter the 2-letter state abbreviation (for example, VA, TX, CA).

Item B4. Map and Panel Number. Enter the 10-digit number shown on the FIRM panel where the building or manufactured (mobile) home is located. The first six digits will not match the NFIP community number: 1) when the sixth digit is a "C," in which case the FIRM panel is in a countywide format; or 2) when one community has annexed land from another community but the FIRM panel has not been updated to reflect this annexation. If the sixth digit is a "C," it is followed by a four-digit map number. For maps not in countywide format, enter the "community panel number" shown on the FIRM.

Item B5. Suffix. Enter the suffix letter shown on the FIRM panel that includes the building's location.

Item B6. FIRM Index Date. Enter the effective date or map revised date shown on the FIRM Index.

Item B7. FIRM Panel Effective/Revised Date. Enter the map effective date or the map revised date shown on the FIRM panel. This will be the latest of all dates shown on the map. The current FIRM panel effective date can be determined by calling 1-800-427-4661.

Item B8. Flood Zone(s). Enter the flood zone, or flood zones, in which the building is located. All flood zones containing the letter "A" or "V" are considered Special Flood Hazard Areas. The flood zones are A, AE, A1-A30, V, VE, V1-V30, AH, AO, AR, AR/A, AR/AE, AR/A1-A30, AR/AH, and AR/AO. Each flood zone is defined in the legend of the FIRM panel on which it appears.

Item B9. Base Flood Elevation(s). Using the appropriate Flood Insurance Study (FIS) Profile, Flood Elevation Table, or FIRM panel, locate the property and enter the BFE (or base flood depth) of the building site. If the building is located in more than one flood zone in Item B8., list all appropriate BFEs in Item B9. BFEs are shown on a FIRM or FIS Profile for Zones A1-A30, AE, AH, V1-V30, VE, AR, AR/A, AR/AE, AR/A1-A30, AR/AH, and AR/AO; flood depth numbers are shown for Zone AO. Use the AR BFE if the building is located in any of Zones AR/A, AR/AE, AR/A1-A30, AR/AH, or AR/AO. In A or V zones where BFEs are not provided on the FIRM, the community may have established BFEs or obtained BFE data from other sources. For subdivisions and other developments of more than 50 lots or 5 acres, establishment of BFEs is required by the community's floodplain management ordinance. If the BFE is obtained from another source, enter the BFE in Item B9.

Item B10. Indicate the source of the BFE that you entered in Item B9.

Item B11. Indicate the elevation datum to which the elevations on the applicable FIRM are referenced.

Item B12. Indicate whether the building is located in a Coastal Barrier Resources System (CBRS) area or Otherwise Protected Area (OPA). Federal flood insurance is prohibited in designated CBRS areas for buildings or manufactured (mobile) homes built or substantially improved after the date of the CBRS designation. An information sheet explaining CBRS areas may be obtained on FEMA's website at http://www.fema.gov or by calling 1-800-427-4661.

SECTION C - BUILDING ELEVATION INFORMATION (SURVEY REQUIRED)

Complete Section C if the building is located in any of Zones A1-A30, AE, AH, A (with BFE), VE, V1-V30, V (with BFE), AR, AR/A, AR/AE, AR/A1-A30, AR/AH, or AR/AO, or if this certificate is being used to support a LOMA or LOMR-F. If the building is located in Zone AO or Zone A (without BFE), complete Section E instead.


Item C1. Indicate whether the elevations to be entered in this section are based on construction drawings, a building under construction, or finished construction. For either of the first two choices, a post-construction Elevation Certificate will be required when construction is complete. Select "finished construction" only when all machinery and/or equipment such as furnaces, hot water heaters, heat pumps, air conditioners, and elevators and their associated equipment have been installed and the grading around the building is completed.

Item C2. Select the diagram on pages 6 and 7 that best represents the building. Then enter the diagram number and use the diagram to identify and determine the appropriate elevations requested in Items C3.a-g. If you are unsure of the correct diagram, select the diagram that most closely resembles the building being certified, or provide a sketch or photograph of the building and enter all elevations in Items C3.a-g.

Item C3. Indicate whether the elevation reference mark (benchmark) used during the field survey is an elevation mark on the FIRM. If it is not, indicate the source and datum for the elevation. Vertical control benchmarks other than those shown on the

FIRM are acceptable for elevation determinations. Show the conversion from the field survey datum used to the datum used for the BFE(s) entered in Item B9. All elevations for the certificate must be referenced to the datum on which the BFE is based. Show the datum conversion, if applicable, in this section or in the Comments area of Section D. For property experiencing ground subsidence, the most recently adjusted reference mark elevations must be used for determining building elevations. However, when subsidence is involved, the BFE should not be adjusted. Enter elevations in Items C3.a-g to the nearest tenth of a foot (nearest tenth of a meter, in Puerto Rico).

Items C3.a-d. Enter the building elevations (excluding the attached garage) indicated by the selected building diagram (Item C2.) in Items C3.a-c. If there is an attached garage, enter the elevation for top of attached garage slab in Item C3.d. (Because elevation for top of attached garage slab is self-explanatory, attached garages are not illustrated in the diagrams.) If the building is located in a V zone on the FIRM, complete Item C3.c. If the flood zone cannot be determined, enter elevations for all of Items C3.a-g. For buildings in A zones, elevations a, b, d, and e should be measured at the top of the floor. For buildings in V zones, elevation c must be measured at the bottom of the lowest horizontal structural member of the floor (see drawing below). If any item does not apply to the building, enter "N/A" for not applicable.



Item C3.e. Enter the lowest elevation of machinery and/or equipment such as furnaces, hot water heaters, heat pumps, air conditioners, and elevators and their associated equipment in an attached garage or enclosure or on an open utility platform that provides utility services for the building. If the machinery and/or equipment is mounted to a wall, pile, etc., enter the platform elevation of the machinery and/or equipment. Indicate machinery/equipment type in the Comments area of Section G or Section D, as appropriate. If this item does not apply to the building, enter "N/A" for not applicable.

Items C3.f-g. Adjacent grade is defined as the elevation of the ground, sidewalk, patio slab, or deck support immediately next to the building. For Zone AO, use the natural grade elevation, if available. This measurement must be to the nearest tenth of a foot (nearest tenth of a meter, in Puerto Rico) if this certificate is being used to support a request for a LOMA or LOMR-F.

Items C3.h-i. Enter the number of permanent openings (flood vents) in the walls supporting the building that are no higher than 1.0 foot above the adjacent grade. Determine the total area of all such openings in square inches (square cm, in Puerto Rico), and enter the total in Item C3.i. If the building has no permanent openings (flood vents) within 1.0 foot above adjacent grade, enter "0" (zero) for each of Items C3.h and C3.i.

SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION

Complete as indicated. This section of the Elevation Certificate may be signed by only a land surveyor, engineer, or architect who is authorized by law to certify elevation information. Place embossed seal and signature in the box next to elevations in Section C. A flat stamp is acceptable only in states that do not authorize use of an embossed seal over the signature of a professional. You are certifying that the information in Sections A, B, and C on this certificate represents your best efforts to interpret the data available and that you understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001. Use the Comments area of Section D, on the back of the certificate, to provide datum, elevation, or other relevant information not specified on the front.

SECTION E - BUILDING ELEVATION INFORMATION (SURVEY NOT REQUIRED) FOR ZONE AO & ZONE A (WITHOUT BFE)

Complete Section E if the building is located in Zone AO or Zone A (without BFE). Otherwise, complete Section C instead.

Item E1. Select the diagram on pages 6 and 7 that best represents the building; then enter the diagram number. If you are unsure of the correct diagram, select the diagram that most closely resembles the building, or provide a sketch or photograph.

Item E2. Enter the height in feet and inches (meters and centimeters, in Puerto Rico) of the top of the bottom floor (as indicated in the applicable diagram) above or below the highest adjacent grade (HAG). For post-FIRM buildings in Zone AO, the community's floodplain management ordinance requires that this value equal or exceed the base flood depth on the FIRM. Buildings in Zone A (without BFE) may qualify for a lower insurance rate if an engineered BFE is developed at the site.

Item E3. For Building Diagrams 6-8 with "proper openings" (see page 7), enter the height in feet and inches (meters and centimeters, in Puerto Rico) of the next higher floor or elevated floor (as indicated in the applicable diagram) above the highest adjacent grade (HAG). Be sure that you have completed Items C3.h and C3.i on the front of the form to show the number of permanent, proper openings (flood vents) within 1 foot above adjacent grade and the total area of the openings.

Item E4. For those communities where this base flood depth is not available, the community will need to determine whether the top of the bottom floor is elevated in accordance with the community's floodplain management ordinance.

SECTION F - PROPERTY OWNER (OR OWNER'S REPRESENTATIVE) CERTIFICATION

Complete as indicated. This section is provided for certification of measurements taken by a property owner or property owner's representative when responding to Sections A, B, C (Items C3.h and C3.i only), and E. The address entered in this section must be the actual mailing address of the property owner or property owner's representative who provided the information on the certificate.

SECTION G - COMMUNITY INFORMATION (OPTIONAL)

Complete as indicated. The community official who is authorized by law or ordinance to administer the community's floodplain management ordinance can complete Sections A, B, C (or E), and G of this Elevation Certificate. If the authorized community official completes Sections C, E, or G, complete the appropriate item(s) and sign this section.

Check Item G1. if Section C is completed with elevation data from other documentation, including elevations obtained from the Community Rating System Elevation Software, that has been signed and embossed by a licensed surveyor, engineer, or architect who is authorized by law to certify elevation information. Indicate the source of the elevation data and the date obtained in the Comments area of Section G. If you are both a community official and a licensed land surveyor, engineer, or architect authorized by law to certify elevation information, and you performed the actual survey for a building in Zones A1-A30, AE, AH, A (with BFE), VE, V1-V30, V (with BFE), AR, AR/A, AR/A1-A30, AR/AE, AR/AH, or AR/AO, you must also complete Section D.

Check Item G2. if information is entered in Section E by the community for a building in Zone A (without a FEMA-issued or community-issued BFE) or Zone AO.

Check Item G3. if the information in Items G4.-G9. has been completed for community floodplain management purposes to document the as-built lowest floor elevation of the building. Section C of the Elevation Certificate records the elevation of various building components but does not determine the lowest floor of the building or whether the building, as constructed, complies with the community's floodplain management ordinance. This must be done by the community. Items G4.-G9. provide a way to document these determinations.

Item G4. Permit Number. Enter the permit number or other identifier to key the Elevation Certificate to the permit issued for the building.

Item G5. Date Permit Issued. Enter the date the permit was issued for the building.

- Item G6. Date Certificate of Compliance Issued. Enter the date that the Certificate of Compliance or Occupancy or similar written official documentation of as-built lowest floor elevation was issued by the community as evidence that all work authorized by the floodplain development permit has been completed in accordance with the community's floodplain management laws or ordinances.
- Item G7. New Construction or Substantial Improvement. Check the applicable box. "Substantial Improvement" means any reconstruction, rehabilitation, addition, or other improvement of a building, the cost of which equals or exceeds 50 percent of the market value of the building before the start of construction of the improvement. The term includes buildings that have incurred substantial damage, regardless of the actual repair work performed.
- Item G8. As-built lowest floor elevation. Enter the elevation of the lowest floor (including basement) when the construction of the building is completed and a final inspection has been made to confirm that the building is built in accordance with the permit, the approved plans, and the community's floodplain management laws or ordinances. Indicate the elevation datum used.
- Item G9. BFE. Using the appropriate FIRM panel, FIS, or other data source, locate the property and enter the BFE (or base flood depth) of the building site. Indicate the elevation datum used.

Enter your name, title, and telephone number, and the name of the community. Sign and enter the date in the appropriate blanks.

BUILDING DIAGRAMS

The following eight diagrams illustrate various types of buildings. Compare the features of the building being certified with the features shown in the diagrams and select the diagram most applicable. Enter the diagram number in Item C2. and the elevations in Items C3.a-C3.g.

In A zones, the floor elevation is taken at the top finished surface of the floor indicated; in V zones, the floor elevation is taken at the bottom of the lowest horizontal structural member (see drawing in instructions for Section C).

All slab-on-grade single- and multiple-floor buildings (other than split-level) and high-rise buildings, either detached or row type (e.g., townhouses); with or without attached garage. Distinguishing Feature – The bottom floor is at or above ground level (grade) on at least one side.* NEXT HIGHER FLOOR BOTTOM FLOOR (determined by existing grade)






DIAGRAM 2





^{*} A floor that is below ground level (grade) on all sides is considered a basement even if the floor is used for living purposes, or as an office, garage, workshop, etc.

Instructions – Page 6

DIAGRAM 5

All buildings elevated on piers, posts, piles, columns, or parallel shear walls. No obstructions below the elevated floor.

Distinguishing Feature – For all zones, the area below the elevated floor is open, with no obstruction to flow of flood waters (open lattice work and/or readily removable insect screening is permissible).




DIAGRAM 6

All buildings elevated on piers, posts, piles, columns, or parallel shear walls with full or partial enclosure below the elevated floor.

Distinguishing Feature – For all zones, the area below the elevated floor is enclosed, either partially or fully. In A Zones, the partially or fully enclosed area below the elevated floor is with or without openings** present in the walls of the enclosure. Indicate information about openings in Section C, Building Elevation Information (Survey Required).




DIAGRAM 7

All buildings elevated on full-story foundation walls with a partially or fully enclosed area below the elevated floor. This includes walkout levels, where at least one side is at or above grade. The principal use of this building is located in the elevated floors of the building.

Distinguishing Feature – For all zones, the area below the elevated floor is enclosed, either partially or fully. In A Zones, the partially or fully enclosed area below the elevated floor is with or without openings** present in the walls of the enclosure. Indicate information about openings in Section C, Building Elevation Information (Survey Required).





DIAGRAM 8

All buildings elevated on a crawl space with the floor of the crawl space at or above grade on at least one side, with or without an attached garage.

Distinguishing Feature – For all zones, the area below the first floor is enclosed by solid or partial perimeter walls. In all A zones, the crawl space is with or without openings** present in the walls of the crawl space. Indicate information about the openings in Section C, Building Elevation



** An "opening" (flood vent) is defined as a permanent opening in a wall that allows for the free passage of water automatically in both directions without human intervention. Under the NFIP, a minimum of two openings is required for enclosures or crawl spaces with a total net area of not less than one square inch for every square foot of area enclosed. Each opening must be on different sides of the enclosed area. If a building has more than one enclosed area, each area must have openings on exterior walls to allow floodwater to directly enter. The bottom of the openings must be no higher than one foot above the grade underneath the flood vents. Alternatively, you may submit a certification by a registered professional engineer or architect that the design will allow for the automatic equalization of hydrostatic flood forces on exterior walls. A window, a door, or a garage door is not considered an opening.