Table of Contents

Fil	e	FP-1996-114 Name: Grand View - Filing	#2	<u>– N</u>	orth of Hawthorne Avenue/East of 28 Rd Final Plan								
P r e s e n t	S c a n n e d	A few items are denoted with an asterisk (*), which means retrieval system. In some instances, items are found on the lis file because they are already scanned elsewhere on the system be found on the ISYS query system in their designated catego Documents specific to certain files, not found in the standard of Remaining items, (not selected for scanning), will be listed and the contents of each file.	st b n. T rie: che	ut The s. ckli	are not present in the scanned electronic development se scanned documents are denoted with (**) and will ist materials, are listed at the bottom of the page.								
X	X	Table of Contents											
		*Review Sheet Summary											
X	X	*Application form											
X		Review Sheets											
		Receipts for fees paid for anything			:								
X	X	*Submittal checklist											
		*General project report											
		Reduced copy of final plans or drawings											
X		Reduction of assessor's map.											
		Evidence of title, deeds, easements											
X	X												
		Public notice cards											
		Record of certified mail											
X	X	Legal description											
		Appraisal of raw land											
		Reduction of any maps – final copy											
]	*Final reports for drainage and soils (geotechnical reports)											
Ш		Other bound or non-bound reports											
Ш		Traffic studies			(2.1)								
X	X	*Review Comments											
X	X	*Petitioner's response to comments											
X	X	*Staff Reports											
Ш	_	*Planning Commission staff report and exhibits											
		*City Council staff report and exhibits											
		*Summary sheet of final conditions											
		DOCUMENT DESC	<u>:RI</u>	PΤ	TON:								
	X	Correspondence	X	X	Final Plat – not signed – signed copy – GIS Historical Maps - **								
X		Chicago Title Ins. Company – 1/14/94		X	Historical Maps - **								
X		Treasurer's Certificate of Taxes Due – 5/1/96		X	- GIS Historical Maps - **								
X		Stormwater Management Plan – 5/96		X	GIS Historical Maps - **								
X	X	Subsurface Soils Exploration – 6/29/96		X	Historical Maps - **								
	X	General Permit Application – Stormwater Discharges – 5/23/96		X									
X	X	Posting of Public Notice Signs – 6/18/96	X		First /Second Amendment to the Declaration of								
					Covenants, Conditions and Restrictions of Grand View Subdivision – Bk 2244 / Pg 39								
	X	Final Drainage Report – 6/21/96	X		Articles of Incorporation – not recorded, notarized								
X	\Box	E-mails			<u> </u>								

X	X	Planning Commission Minutes - ** 7/2/96, 8/6/96 Certification of Plat - 9/9/96 DIA - Bk 2268 / Pg 846 - ** Ordinance No. 3044 - ** - Bk 2413 / Pg 78			
X	X	Certification of Plat – 9/9/96			
X	X	DIA – Bk 2268 / Pg 846 - **			
X	X	Ordinance No. 3044 - ** - Bk 2413 / Pg 78			
\dashv				1	
一				\vdash	
		The state of the s	 	\vdash	
\dashv			-	┢	
				├-	
_			-	<u> </u>	
_			<u> </u>	ļ	
			\bot	<u> </u>	
				<u> </u>	
				ļ	
				L_	
				Γ	
		:			
\neg	\neg				
\neg	_				
一	_			T	
-	_	<u> </u>	1		
\dashv		the state of the s	\top		
\dashv	+	A Company of the Comp			
\dashv	-				
\dashv	-+				
-	\dashv			-	
\dashv	\dashv	, , , , , , , , , , , , , , , , , , , ,		-	The state of the s
+	-		+	 	
	\dashv		+		
_			- -	_	
_	_		+	_	
	ļ			<u> </u>	
	i				



DEVELOPMENT APPLICATION

Community Development Department 250 North 5th Street, Grand Junction, CO 81501 (303) 244-1430

Receipt				
Date		,	 	_
Rec'd By _	<u> </u>		 	 _
File No.				

	situated in Me		ndersigned, being the ow te of Colorado, as descri		reby petition this:	
PETITION	PHASE	SIZE	LOCATION	Z	ONE	LAND USE
Subdivision Plat/Plan	☐ Minor ☑ Major ☐ Resub	12.3 ac.	Nof Hauthorne & E of 28 Road	RSF - 5		
Rezone				From:	То:	
☐ Planned Development	□ ODP □ Prelim □ Final					
☐ Conditional Use	38 <u>-</u> 38					
☐ Zone of Annex						
☐ Variance		7.3		·		
☐ Special Use						
☐ Vacation						☐ Right-of Way
☐ Revocable Permit						
⊠ PROPERTY OWNER		·	DEVELOPER		•	ESENTATIVE
<i>Donada, Lnc.</i> Name		Na Na	me Owner	<u> </u>	Tom Loque Name	?
DONADA, Inc. Name 634 Avolon Dr. Address					1225 50. 74. Address	b Street
			dress		Address	
Grand Junction, City/State/Zip	CO 81504			· · · · · · · · · · · · · · · · · · ·	Grand Jet.	CO. 81501
		Cit	y/State/Zip		City/State/Z	ip
434-6224 Business Phone No.		Bu	siness Phone No.		242 - 53 70 Business Ph	one No.
NOTE: Legal property owi	ner is owner of r	ecord on date o	f submittal.	•		
We hereby acknowledge that information is true and comp comments. We recognize tha will be dropped from the age	we have familiar plete to the best of t we or our repre	ized ourselves w f our knowledge sentative(s) mus	ith the rules and regulation c, and that we assume the r t be present at all required	esponsibility to mo hearings. In the ev	nitor the status of the ent that the petitioner	application and the review is not represented, the item
Momas A To	AUE				5-1-96	
Signature of Person Complete	ing Application Mottle				Date	Y
Donald D. dela M	Notte, Pre	sident Do	NADA. Inc.		5-1-96	
Signature of Property Owner	(s) - attach addition	onal sheets if nee	cessary		Date	



MAJOR SUBDIVISION: FINAL

Location: Not Hauthorne	: Ave	ue E of 28 Road Project Name: GRAND VIEW FILING #2																													
ITEMS			DISTRIBUTION																												
		П		Ŧ	Т	T	П										7					_				_					
		Development							Auth.			rtment				GVID	915		79 70						Survey						
Date Received 5-1-94 Receipt # 3942	.,,	y Deve			\gent	reation		(8 sets)	n Dev.		j.	g Depa	€		51	1	١ ١		- (entra!					eers	ogic Su	١٥					
Receipt # 3942	ERENCI	Community	v. Eng.	lity Eng	perty /	rks/Rec	tornev	G.J.P.C. (wntow	ice	Plannir	Buildin	SAVVER	Field	Dist. #	n Distri	e Distri	District	District	est	service			of Engineers	lo Geologic	stal Se	WWW	ole			REQ'D.
File # <i>FP-<u>96-114</u></i>	SSID REFERENCE	City Co	City Dev. Eng.	City Utility Eng.	City Pro	City Parks/Recreation	City	City G.,	City Downtown Dev.	City Police	County Planning	County Building Department	E CYNANTS Dynamon	Walker Field	School	Irrigation District	Drainage District	Water District	Sewer District	U.S. West	Public Service	GVRP	CDOT	Corps of	Colorado	U.S. Postal Service	ARANSING WALLING THE	TCI Cat			TOTAL REG'D.
DESCRIPTION	SS		•		9	4		, C	0	2	•	Ø	_				Ü		7	Ť	5	0	0	d			Ž	5			21
Application Fee - see reverse	VII-1	1		٦	Т	Т												\neg	_	٦											
Submittal Checklist*	VII-3	1	П	ヿ	十	十	T	П	Г	П						T	7	┪	\neg	┪			Г					П	コ	П	
Review Agency Cover Sheet*	VII-3	1	1	1	1	1	1 1	П	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	\neg		21
Application Form*	VII-1	1	1	1	1	1	1 1	8	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	\dashv	П	
Reduction of Assessor's Map	VII-1	1	1	1	1	1	1 1	8	1	1	1.	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	\dashv		
Evidence of Title	VII-2	1	H	┪	1	+	1	Н		Н		\Box	\neg	Н		7	_	7	┪	┪	\dashv						Н	Н	\dashv		-
O Appraisal of Raw Land	VII-1	1	H	寸	1	1	╈	H		H		\dashv	Н	H	Н	\dashv	\dashv	7	ᅥ	┪	-	-	Н	H	Н	 	Н	Н	\dashv	\dashv	
Names and Addresses*	VII-2	1	H	+	十	+	1-	\vdash		Н	-	\dashv	\dashv	Н	\dashv	\dashv	┪	7	+	\dashv	ㅓ	\dashv	М				Н	Н	\dashv	\dashv	
*	VII-2	1	⊢╂	4	-	+	+	Н	_	Н		Н	\dashv	Н	_	-	-	-+	4	-	_	_	_	_		_	Н	-	-	\dashv	
Legal Description* O Deeds	VII-2	1	Н	┩	╣	+	+	Н		Н	_	\blacksquare	\vdash	Н	\dashv	\dashv		-	-	4	_	4				_	Н	Н	\dashv		
		<u></u>	╌┤	+	╬	+-		╀┤		Н	4		\dashv		-	\dashv	4	-+	4	4	1	1		_		_	Н	1	\dashv	\dashv	
O Easements	VII-2	1	-'	1	1	+	1 1	-		Н	-	-1	Щ	H	\dashv	-	-			-\	4	-	Н			⊢	Н	-	\rightarrow	Н	
O Avigation Easement	VII-1		닊	-	-	4-	1	Н		Н		Н	\perp	Щ	_	Н	-	-	-	ᅱ	_	٦	_		Ш	_	Н	1			
O ROW	VII-2	1	-;	1	4	4	1 1	Н		Н			_	Н	\blacksquare	\dashv		4	4	4	_	_	Ь.	_	Щ	<u> </u>	L		\dashv		
Covenants, Conditions & Restrictions	VII-1	1	1	4	4	_	1	Ш		Н			_	Ш	\dashv	_	_	-		4			Ш			_	Ш		_		<i></i> .
O Common Space Agreements	VII-1	1	1	4	4	+	1	Н		\square	-	Ш	\dashv	Н		_	4		4	4	_		_			<u> </u>	Н	Н	_		
County Treasurer's Tax Cert.	VII-1	1	니	4	4	4	1	Н	Ш	Ц	_			Ш	\Box		-	4		_	_	_	ш					Н	\dashv		
Improvements Agreement/Guarantee*	VII-2	1	1	1	4	4	1	Ш		Ш		Ц		Ц			_	4	_	4	_	_				_	Ш	Ш			
O CDOT Access Permit	VII-3	1	1	4	_	\perp	\bot	Ш		Ш			\Box	Ш		\Box	_	_	4	_							Ш	Ш	\dashv		
O 404 Permit	VII-3	1	$\perp 1$	_	_	_	┸	Ц	Ш	Ц				Ш			_	_		┙							Ш	Щ	\dashv		
O Floodplain Permit*	VII-4	1		_			_	Ц		Ш								_	_	┙							Ш	Ш	\dashv		
General Project Report	X-7	1	1	1	1	1	1 1	8	1	╚	_1	1	_1	1	_1	_1	1	_11	1	1	2	_1	1	1	1	1	1	1	$ \bot $		*
Composite Plan	IX-10	1	2	1	1	┸	┸	Ш		Ш								_1	_	_									\Box		
11"x17" Reduction Composite Plan	IX-10	1	Ш			1	1 1		1	1	1	1		Ш		1	1	1	1	1	1	1	_1	1	1		_ 1		Ш		
Final Plat	IX-15	1	2	1	1	1	1 1	8	1	1	1	1	1	_1	1	1	1	_1	_1	1	1	1	_1	_1	1	1	1				200
O 11"X17" Reduction of Final Plat	IX-15	1	Ш	_[8	1	1	1			ᄖ	1	1	1	1	1	1	1	1		Ш		1		1	↲		
Cover Sheet	IX-11	1	2	_	\perp	\perp	1_	Ш		Ш				Ш		\Box	_	⅃		_							Ш	Щ	↲	Ц	
Grading & Stormwater Mgmt Plan	IX-17	1	2	_	\bot		\perp	Ш		Ш		Ш		Ц	Ц	Ц	1	_	_	_	_	ب		1	1	_	Ц	1		Ц	Ye
Storm Drainage Plan and Profile	IX-30	1	2	_	ightharpoonup		1	Ш		Ш	Щ		Щ	Ш		Ш	_1		_	_	1	_		<u> </u>	<u> </u>	<u> </u>	Ļ	1	Щ	Ц	
Water and Sewer Plan and Profile	IX-34	1	2	1	_	\perp	1	Ш	L.,	Ш			Ш	Ш	Щ	Щ	_	4	1	_1	1	1	L	L	L	L	1	Ш	\sqcup	Ш	·
Roadway Plan and Profile	IX-28	1	2	\bot	_	\perp	1	Ш	L	Ш			Ц	Ш		Ц	_1		_	_			L	<u>L</u> .	L	_	\sqcup	Ц	Щ	Щ	
Road Cross-sections	IX-27	1	2	_	_	_	1	Ш	L	Ш			Ш	Ц	Щ	Ц	_	_	_	_	_		L			L	\sqcup	Ш	\dashv	_	
Detail Sheet	IX-12	1	2	_	4	4	1	Щ	L	Ш			Ш	Ш		Щ	_	_	ᆚ	_			Ц	L	L.	_	Ш	Щ	Щ		
Landscape Plan-For common open space		2	_	4		\perp	1_	8	L	Ш		Ш	Ш	Ш	Ц		_	_	_				L	Ш	Ļ	$ldsymbol{ldsymbol{ldsymbol{eta}}}$	Ш	Ш	Щ	Ш	
Geotechnical Report	X-8	1	⊷	_	\bot	\bot	┸	Ш	L	Ш			Ш	Ц	Ц	Ш	\Box	_	_	_			L	L	\Box	<u> </u>	\vdash	Ш	$oldsymbol{\sqcup}$	Ц	
O Phase I & II Environmental Report	X-10,11	1		_	4	\perp	1	Ш	L	Ш		Ш		Ш	Ш	Ш		_		_			L	_	L	_	<u> </u>		Ш	Ц	
Final Drainage Report	X-5,6	1	2	4		\perp	1	Ш	L	Ш	Щ	Ш		Ш		Ш	_1	_		_			L	L	<u> </u>	_		Ш	Щ	Ц	*
O Stormwater Management Plan	X-14	1	2		\perp			Ш		Ш		Ш	Ш	Ш		Ш	_1	_					L	_1	L	L	Ш	Ш	Ш	Ш	
O Sewer System Design Report	X-13	1	ட			\perp		Ш	L	Ш			Ш	Ш		Ш			1				L			_	┕	Ш	Ш	Ш	
O Water System Design Report	X-16	1		1				Ш		Ш		\Box		Ш				1					Ĺ	$ldsymbol{ldsymbol{ldsymbol{eta}}}$	L	L		Ш	Ш	Ш	
O Traffic Impact Study	X-15	1	2					\square		Ш				\square															Ш		
· Site Plan Revised Preliminary	IX-29	1	2	1	1		1	8										\Box					Ĺ			L				Ш	
Plan																							-						_		

Plan

NOTES: * An asterisk in the item description column indicates that a form is supplied by the City.

PRE-APPLICATION CONFERENCE Date: MARCATA 1096 Conference Attendance: T. Loque M. Drollinger Proposal: GRAND VIEW FILING#2 Location: Nof Hantborne Are & E of 28 Road Tax Parcel Number: 2343-063-00-088 Review Fee: \$720+\$15/acre or fraction + \$75 Public Nortes Fees (Fee is due at the time of submittal. Make check payable to the City of Grand Junction.) Additional ROW required? DN 28 Road as pen eng. Adjacent road improvements required? As per enc. & prelim plan approval Area identified as a need in the Master Plan of Parks and Recreation? Parks and Open Space fees required? Yes Estimated Amount: \$ 225 / UNI Recording fees required? Yes _____ Estimated Amount: ___ Half street improvement fees/TCP required? As per exc. _____ Estimated Amount: _____ Revocable Permit required? No State Highway Access Permit required? No On-site detention/retention or Drainage fee required? As per prelim plan & eng. Applicable Plans, Policies and Guidelines Level Code Located in identified floodplain? FIRM panel #____ Located in other geohazard area? Located in established Airport Zone? Clear Zone, Critical Zone, Area of Influence? Area of Influence? Avigation Easement required? As per airport While all factors in a development proposal require careful thought, preparation and design, the following "checked" items are brought to the petitioner's attention as needing special attention or consideration. Other items of special concern may be identified during the review process. O Access/Parking O Screening/Buffering O Land Use Compatibility O Landscaping O Traffic Generation Drainage O Geologic Hazards/Soils O Floodplain/Wetlands Mitigation O Availability of Utilities O Other Related Files: # 85 - 94 (2) &(3) It is recommended that the applicant inform the neighboring property owners and tenants of the proposal prior to the public hearing and preferably prior to submittal to the City. PRE-APPLICATION CONFERENCE WE RECOGNIZE that we, ourselves, or our representative(s) must be present at all hearings relative to this proposal and it is our responsibility to know when and where those hearings are. In the event that the petitioner is not represented, the proposed item will be dropped from the agenda, and an additional fee shall be charged to cover rescheduling expenses. Such fee must be paid before the proposed item can again be placed on the agenda. Any changes to the approved plan will require a re-review and approval by the Community Development Department prior to those changes being accepted. WE UNDERSTAND that incomplete submittals will not be accepted and submittals with insufficient information,

Signature(s) of Petitioner(s)

X

Monas A: Have

Signature(s) of Representative(s)

agenda.

identified in the review process, which has not been addressed by the applicant, may be withdrawn from the agenda.

WE FURTHER UNDERSTAND that failure to meet any deadlines as identified by the Community Development Department for the review process may result in the project not being scheduled for hearing or being pulled from the

FINAL APPROVAL CHECKLIST GRAND VIEW FILING #2

1. Development Improvements Agreement (DIA) #	
2. Improvements Guarantee (type used: NOTEMENT AGREEMENT) #	ţ
3. Final Plans #	
0 4. Articles of Incorporation of $HOANA$	
0 5. CCERS NA	
o 6. Plat	
o 7. Disk of Plat	
o 8. UCC Approval	
9. TCP Credit Request	
10. City Surveyor Certificate	
o 11.	
#: Minimum required for commencement of construction	
FEES	
Open Space Fees - \$	
TCP-\$/lot	
School Impact Fee - \$/lot	

h:\mdforms\finapch.doc

(Ed Loshbaugh David Schumacher Earl Cogdill 662 28 Road 3610 Beechwood St. 2715 Hawthorne Ave. City 81506 City 81506 City 81506 Norma Cozzette Amrei Ungaro James McConnell 664 28 Rd. 3620 Beechwood St. 2624 Hawthorne Ave. City 81506 City 81506 City 81506 Emma McCreanor Brian Haut Norman Hack 3630 Beechwood St. 654 28 Rd. 2635 Beech Ct. City 81506 City 81506 City 81506 Brent Uilenberg Elijah Hitchcock Norma Zeiler 2640 Beech Ct. 652 28 Rd. 3710 Beechwood St. City 81506 City 81506 City 81506 Charles Green 1st Church of the Nazarene Merle Harris 2630 Beech Ct. 1000 North 9th St. 3720 Beechwood St. City 81506 city 81501 City 81506 Adolfo Torrez B&G Investments Leroy Murray 3210 Beechwood St. P.O. Box 9088 3730 Beechwood St. City 81506 City 81502 City 81506 Paul Burris Kenneth Matchett Rudolph Hansen 2956 Pheasant Run Circle 2844 F Road 3220 Beechwood St. City 81506 City 81506 City 81506 Graig Burdette Steven Poust Paul Ouret 3230 Beechwood St. 2958 Pheasant Run Circle 1615 N. 18th St. City 81506 City 81506 City 81501 Daniel Lacy Jarrel Doudy Carolyn Glass 3310 Beechwood St. 2625 Hawthorne Ave. 3520 Beechwood St. City 81506 City 81506 City 81506 Terance Beyrer Tedford Hendrickson James Fleming 3330 Beechwood St. 3530 Beechwood St. P.O. BOx 361 City 81506

Grand Junction, CO 81502

City 81506

Carl Pinson 3410 Beechwood St. City 81506 David Horen 3425 Beechwood St. City 81506

Gilbert Martin 3420 Beechwood St. City 81506 Stephen Witsken 3415 Beechwood St. City 81506

F. Clemens 3430 Beechwood St. City -81506 V. Kohl 3405 Beechwood St. City 81506

Bill Ferguson 3215 Beechwood St. City 81506

Merlin Zimmet 3205 Beechwood St. City 81506

Pamela Fox 2517 I Rd. City 81505

Charles Riggs 3325 Beechwood St. City 81506 PAUL M OURET 3510 BEECHWOOD ST GRAND JUNCTION, CO 81506-4852

CAROLYN C GLASS 3520 BEECHWOOD ST GRAND JUNCTION, CO 81506-4852 JAMES F FLEMING 3530 BEECHWOOD ST GRAND JUNCTION, CO 81506-4852

N KEITH COOMBE 2510 RIDGE DR GRAND JUNCTION, CO 81506-8468

PATRICK M MILLS 3615 BEECHWOOD ST GRAND JUNCTION, CO 81506-4849 JOSEPH M TONOZZI 3605 BEECHWOOD ST GRAND JUNCTION, CO 81506-4849

WILLIAM M BLACKBURN 3535 BEECHWOOD ST GRAND JUNCTION, CO 81506-4851

DONALD MARK GUTENTAG 3525 BEECHWOOD ST GRAND JUNCTION, CO 81506-4851 PATRICIA A HILL 2614 HAWTHORNE AVE GRAND JUNCTION, CO 81506-4872

ROGER L FISCHER 2624 HAWTHORNE AVE GRAND JUNCTION, CO 81506-4872

JOHN J KAMMERER 2714 HAWTHORNE AVE GRAND JUNCTION, CO 81506-4886 DAVID W TERRY 3120 BEECHWOOD ST GRAND JUNCTION, CO 81506-4859

NORMAN H HACK 2635 BEECH CT GRAND JUNCTION, CO 81506-4842 BRENT R UILENBERG 2640 BEECH CT GRAND JUNCTION, CO 81506-4842 CHARLES E GREEN 2630 BEECH CT GRAND JUNCTION, CO 81506-4842

ADOLFO TORREZ 3210 BEECHWOOD ST GRAND JUNCTION, CO 81506-4833 JOHN L COOKE 3220 BEECHWOOD ST GRAND JUNCTION, CO 81506-4833 ARNOLD F KRETZMANN 3230 BEECHWOOD ST GRAND JUNCTION, CO 81506

DANIEL A LACY . 3310 BEECHWOOD ST GRAND JUNCTION, CO 81506-4856 TERANCE A BEYRER PO BOX 361 GRAND JUNCTION, CO 81502-0361 TEDFORD M HENDRICKSON 3330 BEECHWOOD ST GRAND JUNCTION, CO 81506-4856

CARL PINSON 3410 BEECHWOOD ST GRAND JUNCTION, CO 81506-4854 GILBERT L MARTIN 3420 BEECHWOOD ST GRAND JUNCTION, CO 81506-4854 STEPHEN E CLEMENS 4937 LA RAMADA DR SANTA BARBARA, CA 93111

DAVID G HJELSTROM 2311 APRICOT CT GRAND JUNCTION, CO 81506-8459 CHARLES S WHITE 2305 APRICOT CT GRAND JUNCTION, CO 81506-8459 STEPHEN J WITSKEN 3415 BEECHWOOD ST GRAND JUNCTION, CO 81506-4853

V WILLIAM KOHL 3405 BEECHWOOD ST GRAND JUNCTION, CO 81506-4853 LYMAN L VAN HORN 2310 WINTERGREEN DR GRAND JUNCTION, CO 81506-8404 FIRST CHURCH OF NAZARENE OF GJ 1000 N 9TH ST STE 8 GRAND JUNCTION, CO 81501-3107

111 apos



RICK LEE CATLIN 656 28 RD GRAND JUNCTION, CO 81506-4802

EMMA LOUISE MCCREANOR 654 28 RD GRAND JUNCTION, CO 81506-4802 ELIJAH HITCHCOCK 652 28 RD GRAND JUNCTION, CO 81506-4802

SKELTON CONSTRUCTION INC 706 IVY PL GRAND JUNCTION, CO 81506-8341

JEFFREY M MCCLELLAND 3351 C RD PALISADE, CO 81526-9533

HARRY R MCGUINESS 590 EASTWOOD ST GRAND JUNCTION, CO 81504

Donada, Inc. 634 Avalon Drive Grand Junction, CO 81504 Tom Logue 1225 S 7th St. Grand Junction, CO 81501 City of Grand Junction Community Development Dept. 250 N 5th Street Grand Junction, CO 81501



April 30, 1996

Planning Commission
Community Development Department
City of Grand Junction
250 North 5th. Street
Grand Junction, CO 81501

RE: GRAND VIEW SUBDIVISION, FILING TWO

Dear Members:

Accompanying is the Final Plat and Site Development Documents for the second filing at the Grand View Subdivision located east of 28 Road and Hawthorne Avenue.

Filing Two consists of 36 single family lots and on a total of 12.3 acres. The second phase of development follows the phasing plan which was included with the approved Preliminary Development Plan in May, 1994. Phase Two is part of an overall development plan consisting of 200 units. Most of the first 29 lots within phase one have been build upon.

This application responds to the conditions, where applicable, which were established during the Preliminary Plan review process. Conditions of acceptance for Filing Two follow:

- 1. A Landscaping Plan has been submitted to the Community Development Department. Staff recommendations for buffering along 28 Road frontage has been illustrated on the Landscape Plan.
- 2. Identification signage has been relocated as requested by staff and is shown on the Landscape Plan.
- 3. A Traffic Impact Analysis for the entire development was transmitted to the Community Development and Engineering Departments during the phase one review process.

The only change between Filing Two and the accepted Preliminary Development Plan is the elimination of the center median in Ridge Drive. The landscaping which was in the median has been relocated to a new area between the edge of the street and an expanded right-of-way line for Ridge Drive.

Other conditions of approval not consistent with this filing will be addressed with subsequent plats.

It is the applicant's desire to begin construction for Filing Two immediately upon the acceptance of the Final Plat and Plan by the City. It is anticipated that construction will last approximately 8 weeks.

The applicant, Mr. Don dela Motte, and myself will be in attendance at the scheduled public meeting to discuss the proposal and answer any questions which may arise.

Respectfully,

Thomas A. Logae

xc: Don dela Motte, President R.L. Atkins, P.E. & P.L.S

DRAINAGE - GRAND VIEW SUBDIVISION, FILING TWO Grand Junction, Colorado

Sheet Number 2, Grading Plan; and Sheet Numbers 3,4, and 5 Road and Storm Sewer Plan and Profiles, of the construction documents for Grand View Subdivision, Filing 2, dated 4-30-96 were completed under by supervision and are in substantial accordance with the, *Master Drainage Study of Grand View Subdivision*, prepared by LANDesign LTD., dated 07-29-94.

Date: 5-1-96

Richard L. Atkins

Colorado Registered Professional Engineer No. 1229/



STORMWATER MANAGEMENT PLAN

FOR

Grandview Subdivision, Filing No. 2

May, 1996

Prepared for: Donada, Inc, c/o Don Dela Motte 634 Avalon Drive Grand Junction, CO 81501

Reviewed and Approved by: 1 LAND X R.L. Atkins P.E & P.L.S. State of Colorado, # 12.29/



V. References

- 1. Mesa County Storm Drainage Criteria Manual, Final Draft, Mesa County, Colorado, March 1992.
- 2. <u>Flood Hazard Information, Colorado River and Tributaries, Grand Junction, Colorado,</u> prepared for the City of Grand Junction and Mesa County, by The Department Of The Army, Sacramento District, Corps Of Engineers, Sacramento, California, November, 1976.
- 3. <u>Flood Insurance Rate Map, Mesa County, Colorado, (Unincorporated Areas)</u>, Community Panel Number 080115 0480 C, Federal Emergency Management Agency, Map Revised July 15th, 1992.
- 4. <u>Soil Survey, Grand Junction Area, Colorado</u>, Series 1940, No. 19, U.S. Department of Agriculture, issued November, 1955.
- 5. <u>Urban Storm Drainage Criteria Manual</u>, Urban Drainage and Flood Control District, prepared by Wright-McLaughlin Engineers, March 1969, Revised May, 1984.
- 6. Interim Outline of Grading and Drainage Criteria, City of Grand Junction, July 1992.
- 7. <u>Douglas County Storm Drainage Design and Technical Criteria</u>, Addendum A, Erosion Control <u>Criteria</u>, prepared by HydroDynamics Incorporated, Parker, Colorado, October, 1992.
- 8. <u>Grandview Subdivision Filing No. One Hydraulic Calculations</u> prepared by HART GROUP, PC, Engineers Designers Planners, A Division of LANDesign, Grand Junction, Colorado, July, 1994.
- 9. <u>Master Drainage Report for Grandview Subdivision</u> prepared by HART GROUP, PC, Engineers Designers Planners, A Division Of LANDesign, Grand Junction, Colorado, July, 1994.
- 10. <u>Subsurface Soils Exploration, South Rim Subdivision, Grand Junction, Colorado</u>, prepared by Lincoln-DeVore, Inc., Grand Junction, Colorado, August 3, 1993.
- 11. Colorado Department of Transportation, Erosion Control and Stormwater Quality Guide, Draft version, November 27, 1992.
- 12. <u>Declaration Of Covenants, Conditions, And Restrictions Of South Rim Subdivision</u>, Recorded in Book 2055, Pages 317 to 414 of the Mesa County Clerk and Recorders Office.

As defined in the detailed drainage study entitled "Flood Hazard Information, Colorado River and Tributaries" Grandview Filing 2 is not within the 100 and 500 year floodplains.

B. Management During Construction

1. Anticipated Problems and Corrective (BMPs) Best Management Practices:

Structural Erosion Control Areas below the toe of fill slopes shall be isolated from fill areas by the installation of prefabricated silt fences along the east edge of the planned detention area adjent to 28 Road. Straw bales shall be installed at 200 foot intervals along the flowline of the detention area. Straw bale outlet barriers will also be installed immediately below discharge points and pipe outlets.

Non-Structural Erosion Control Disturbed areas not designated for immediate construction or permanent landscaping shall be temporarily re-vegetated. In the event construction activity ceases for a period of 60 calendar days disturbed areas including cut and fill slopes shall be revegitated with a annual and perennial seed mixture.

<u>Dust Abatement</u> The contractor shall be required to provide a consistent and reliable source of construction water. Watering to prevent dust shall be ongoing for the duration of the project. In the event high winds and heavy traffic loads create a situation where watering by itself is not sufficient the contractor is to apply an approved dust palliative other than or in addition to water.

<u>Soil Tracking</u> Access to Filing No. Two shall be from 28 Road which is currently 2 lane asphalt roadway. Where construction traffic enters or exits unimproved areas onto asphalted public roadways a crushed rock construction staging pad shall be installed to minimize soil tracking.

<u>Waste Disposal</u> Construction debris shall be stockpiled in a central location. Debris shall be removed from the site and disposed of at appropriate locations secured by the contractor.

<u>Sedimentation Control</u> The contractor shall be responsible for inspecting the entire site on a weekly basis to ensure compliance and identify existing or potential sedimentation problems. The Masster Drainage Reports For Grandview Subdivision identifies existing drainage ditches which will be used for stormwater runoff and detention. Based on field investigations the mannings (N) value for each approaches 0.08. These drainages will provide an excellent sediment control and filtering effect and are to be maintained in their natural state.

Final Stabilization and Long Term Management

The project's Covenants Conditions and Restrictions obligate each lot owner to fully landscape front yard within 60 days and the rear yard within 1 year from the issuance of a Certificate of Occupancy. Other areas including open-space are to be landscaped by the developer and maintained by the Homeowners Association.

Permanent structural BMP's include pipe outlet protection, rip-rap over filter fabric and grassed swales as shown on the Drainage and Grading Plan.

Inspection and Maintenance

The Contractor shall be ultimately responsible for compliance and maintenance during construction. The owners representative and the contractor shall make weekly inspections of the site to assure compliance and implementation of the proposed BMPs.

<u>Phase VII</u> Final landscaping of individual lots as required by the project Covenants, Conditions and Restrictions.

5. Estimate of Areas Subject to Clearing, Grubbing and Excavation:

Grandview Subdivision filing 2 contains a total of 12.3 acres. Construction Phases I through IV will consist of approximately 4.6 acres. Phases V through VII will consist of the residual area of 7.7 acres.

6. Preconstruction and Postconstruction Runoff Coefficients:

As defined in the Master Drainage Report For Grand View Subdivision "the historic runoff coefficients for the 2 year and 100 year storm events respectively are 0.22 and 0.28. With the construction of proposed roadways coefficients are expected to increase to 0.40 and 0.49 respectively".

7. Soil Erosion Potential:

The site soils are classified as (Bc) Billings Silty Clay loam, 0 to 2 percent slopes which falls within the hydrological soil group "C", (Rf), Ravola very fine sandy loam, 0 to 2 percent slopes which falls within the hydrological soil group "B", and (Fc) Fruita and Ravola loams, 2 to 5 percent slopes which falls in hydrological soil group "B". Erosion of these soils during construction may be moderate if allowed to remain open with no vegetation.

8. Existing Vegetation:

Vegetation consists primarily of row crops and pockets of grass ground cover. Isolated pockets of wetland vegetation is found to exist within the existing irrigation and drainage channel along the south boundary line of the project.

9. Storage of Fuel Oils, Chemicals, Fertilizers or Other Potential Pollution Sources:

The storage of fuel oils, chemicals, fertilizers or other potential pollutants is prohibited without prior written notice to the owner by the contractor, subcontractor or other persons doing work on the site. In the event in becomes necessary to store such items, storage areas shall be designated. Storage areas shall be located above and away from drainages, waterways and other apparent conveyance elements. Appropriate measures shall be taken to protect such areas from spills or vandalism including but not limited to spill control berms and fencing.

10. Anticipated Non-Stormwater Components of Discharge:

Irrigation facilities have been constructed and include a pressurized under ground system supplied by a storage pond located at the southeast corner of Filing One. Offsite residual irrigation runoff is collected and routed underground to the storage pond upon entering the site.

11. Name and Location of Receiving Waters:

Receiving waters of the runoff from the site is first an existing storm water conveyance system routed through Spring Valley Subdivision and eventually into one of the irrigation canals located south of the site.

A. Site and Project Description

1. Site Location:

Grandview Subdivision is located in the City of Grand Junction, County of Mesa, State of Colorado, more particularly being located in the W 1/2 of Section 6, T.1 S., R.1 E. of the Ute Meridian.

Existing streets within the area of the project include 28 Road to the west and Patterson Road to the south which runs west to east and is to be used as primary access to the site.

Grandview Subdivision is bounded to the west across 28 Road by the Spring Valley Subdivisionand to the east, north and south by undeveloped lands. One quarter mile to the south of the Subdivision is Patterson Road.

2. Description of Property:

The Grandview Subdivision Filing 2 contains approximately 12.3 and contains 36 single family residential lots.

3. Description of Proposed Construction Activity:

Activity shall include the construction of roadway, water, sanitary sewer, storm sewer, irrigation, dry utility infrastructures followed by the construction of 36 single family residential structures and associated landscaping.

4. Proposed Sequence of Major Construction Activities:

<u>Phase I</u> Clearing and grubbing of proposed roadway alignments, storm water detention facilities and disposal of construction debris.

<u>Phase II</u> Construction of roadways to proposed subgrade elevations including cut and fill activities as required. Excess embankment material to be stockpiled in designated areas.

<u>Phase III</u> Utility infrastructures to be installed including storm sewers and culverts, swales and permanent erosion control features.

Phase IV Curb, gutter and sidewalks installed.

<u>Phase V</u> Clearing, Grubbing and overlot grading of single or multiple lots as sales and market conditions allow.

Phase VI Construction of single family building structures as sales and market conditions allow.



Lincoln DeVore, Inc.
Geotechnical Consultants

1441 Motor St. Grand Junction, CO 81505 TEL: (970) 242-8968 FAX: (970) 242-1561

May 1, 1996

Don Dela Motte 634 Avalon Drive Grand Junction, CO 81501

Re:

Preliminary Information of Subsurface Soils Exploration Grand View Subdivision, Filing #2, Grand Junction, CO

Gentlemen:

Lincoln DeVore has been retained to perform a Subsurface Soils Exploration for the second filing of the Grand View Subdivision. This Subsurface Soils Exploration will include Recommended Pavement Sections for the interior residential roadways of this Information currently available on this project indifiling. subsurface soils profile and the anticipated residential road pavement sections will be very similar to those reported for Filing #1. For purposes of preliminary design and evaluation, it is believed the recommendations will be quite similar to those found in our report of the Subsurface Soils Exploration, Grand View Subdivision, Filing #1, Grand Junction Colorado, Lincoln DeVore Job #81273-J, June 29, 1994.

It is believed that all pertinent points have been addressed. If any further questions arise regarding this project or if we can be of any further assistance, please do not hesitate to contact this office at any time.

30590

Respectfully Submitted

LINCOLN DeVORE, Inc.

by: Edward M. Morris

Engineer/Western Slope Manager

LD Job No.: 85459-J

June 29, 1994

Mr. Don Dela Motte 634 Avalon Drive Grand Junction, CO.

Re:

SUBSURFACE SOILS EXPLORATION

GRAND VIEW SUBDIVISION, Fil. 1

Grand Junction, Colorado

Dear Sir:

Transmitted herein are the results of a Subsurface Soils Exploration for the proposed single family residential Grand View Subdivision, Filing #1.

If you have any questions after reviewing this report, please feel free to contact this office at any time. This opportunity to provide Geotechnical Engineering services is sincerely appreciated.

Respectfully submitted,

LINCOLN-DeVORE, INC.

Bv:

Edward M. Morris, E.I.T.

Western Slope Branch Manager

Grand Junction, Office

Reviewed by:

George D. Morris, P.E. Colorado Springs Office

LDTL Job No. 81273-J

EMM/ss

TABLE OF CONTENTS

	Page No.
INTRODUCTION	1
Project Description, Scope, Field Exploration & Laboratory Testing.	
FINDINGS	5
Site Description, General Geology and Subsurface Description	on
CONCLUSIONS AND RECOMMENDATIONS	10
General Discussion, Excavation Observation Site Preparation, Excavation, Fill Placement and Compaction, Drainage and Gradient	on
FOUNDATIONS	16
Shallow, Settlement Characteristics, Deep Foundations, Drilled Piers, Grade Beams, Drilled Pier Observation Frost Protection	
CONCRETE SLABS ON GRADE	23
EARTH RETAINING STRUCTURES	24
REACTIVE SOILS	25
PAVEMENTS	26
LIMITATIONS	31

INTRODUCTION

PROJECT DESCRIPTION

This report presents the results of our geotechnical evaluation performed to determine the general subsurface conditions of the site applicable to construction of 28 single family residential structures, in Filing #1 of the Grand View Subdivision. A vicinity map is included in the Appendix of this report.

To assist in our exploration, we were provided with a preliminary site development plan prepared by Thomas A. Logue, Land Development Consultant. The Boring Location Plan attached to this report is based on that plan provided to us.

We understand that the proposed structures may consist of one and possibly two story, wood framed structures with the possibility of a partial basement and concrete floor slab on grade. Lincoln DeVore has not seen a full set of building plans, but structures of this type typically develop wall loads on the order of 600 to 1800 plf and column loads on the order of 8 to 16 kips.

The characteristics of the subsurface materials encountered were evaluated with regard to the type of construction described above. Recommendations are included herein to match the described construction to the soil characteristics found. The information contained herein may or may not be valid for other purposes. If the proposed site use is changed or types of construction proposed, other than noted herein, Lincoln

DeVore should be contacted to determine if the information in this report can be used for the new construction without further field evaluations.

PROJECT SCOPE

The purpose of our exploration was to evaluate the surface and subsurface soil and geologic conditions of the site and, based on the conditions encountered, to provide recommendations pertaining to the geotechnical aspects of the site development as previously described. The conclusions and recommendations included herein are based on an analysis of the data obtained from our field explorations, laboratory testing program, and on our experience with similar soil and geologic conditions in the area.

The scope of our geotechnical exploration consisted of a surface reconnaissance, a geophoto study, subsurface exploration, obtaining representative samples, laboratory testing, analysis of field and laboratory data, and a review of geologic literature.

Specifically, the intent of this study is to:

- 1. Explore the subsurface conditions to the depth expected to be influenced by the proposed construction.
- 2. Evaluate by laboratory and field tests the general engineering properties of the various strata which could influence the development.
- 3. Define the general geology of the site including likely geologic hazards which could have an effect on site development.

- 4. Develop geotechnical criteria for site grading and earthwork.
- 5. Identify potential construction difficulties and provide recommendations concerning these problems.
- 6. Recommend an appropriate foundation system for the anticipated structure and develop criteria for foundation design.

FIELD EXPLORATION AND LABORATORY TESTING

A field evaluation was performed on June14, 1994, and consisted of a site reconnaissance by our geotechnical personnel and the drilling of 3 shallow exploration borings. These 3 exploration borings were drilled within the proposed building sites near the locations indicated on the Boring Location Plan. The exploration borings were located to obtain a reasonably good profile of the subsurface soil conditions. All exploration borings were drilled using a CME 45B, truck mounted drill rig with continuous flight auger to depths of approximately 18 to 25 feet. Samples were taken with a standard split spoon sampler, thin wall Shelby tubes, and by bulk methods. Logs describing the subsurface conditions are presented in the attached figures.

Laboratory tests were performed on representative soil samples to determine their relative engineering properties. Tests were performed in accordance with test methods of the American Society for Testing and Materials or other accepted standards. The results of our laboratory tests are included in this report. The in-place moisture content and the standard penetration test values are presented on the attached drilling logs.

FINDINGS

SITE DESCRIPTION

The project site is located in the Northwest Quarter of the Southwest Quarter of Section 6, Township 1 South, Range 1 East of the Ute Principal Meridian, Mesa County, Colorado. More specifically the site is located West of 28 Road and will include the Eastward extension of Hawthorne Avenue from the Spring Valley Subdivision. The site is located approximately 1/4 mile North of Patterson Road and is approximately 2 miles Northeast of the main downtown business district of Grand Junction, Colorado.

The topography of the site is relatively flat, with a slight overall gradient to the South. The exact direction of surface runoff on this site will be controlled by the proposed construction and therefore will be variable. In general, surface runoff is expected to travel to the drain ditch along the South boundary, continuing along established drain ditches in the area, eventually entering the Colorado River to the Southwest. Surface and subsurface drainage on this site would be described as poor.

GENERAL GEOLOGY AND SUBSURFACE DESCRIPTION

The geologic materials encountered under the site consist of low density alluvial soils which overlie the Mancos Shale Formation which is considered to be bedrock in this area. The geologic and engineering properties of the materials found in our 3 exploration borings will be discussed in the following sections.

The surface soils on this site consist of an alluvial deposit placed by the action of the ancient debris fans which originate in the Bookcliffs to the North. This stratification of upper soils results in a layered system of silts and clays with thin, interbedded sand lenses overlying the Mancos Shale Formation. Generally, the silts and clays are soft, wet and of low density. Soil density decreases and the moisture content increases with increasing depth. The upper 2 feet of the soil profile are stiffer and relatively dry due to surface desiccation.

The upper 2 feet of the surface soils have been extensively re-worked by agricultural activity and have been subjected to flood and furrow irrigation for many years.

The surface soils were found to be quite consistent and have been grouped together and designated Soil Type I. This Soil Type was classified as a silty clay (CL) under the Unified Classification System. This material is of low to very low plasticity, of low to moderate permeability, and was encountered in a low to very low density, wet condition. If this soil is found in a relatively dry condition, it may undergo mild expansion with the entry of small amounts of moisture, but will undergo long-term consolidation upon the addition of larger This soil will settle after being loaded. amounts of moisture. The maximum allowable bearing capacity for this soil was found to be 800 psf, with 100 minimum dead load pressure required. finer grained portion of Soil Type I contains sulfates in detrimental quantities.

The Mancos Shale Formation is considered

to be bedrock in this area. The Mancos Shale is described as a thinbedded, drab, light to dark gray marine shale, with thinly interbedded fine grain sandstone and siltstone layers. Some portions of the Mancos Shale are bentonitic, and therefore, are highly expansive. The majority of the shale, however, has only a moderate expansion potential. Formational shale was encountered in Test Boring No. 1 at a depth of 32 feet. It is anticipated that this formational shale will not affect the construction and the performance of any shallow foundations placed on the site. If a deep foundation system, such as drilled piers, is utilized the Mancos Shale will affect the construction and performance of foundations on this site.

The lines defining the change between soil types or rock materials on the attached boring logs and soil profiles are determined by interpolation and therefore are approximations. The transition between soil types may be abrupt or may be gradual.

The boring logs and related information show subsurface conditions at the date and location of this exploration. Soil conditions may differ at locations other than those of the exploratory borings. If the structure is moved any appreciable distance from the locations of the borings, the soil conditions may not be the same as those reported here. The passage of time may also result in a change in the soil conditions at the boring locations.

GROUND WATER:

A free water table came to equilibrium

during drilling at 5 to 7 feet below the present ground surface. This is probably not a true phreatic surface but is an accumulation of subsurface seepage moisture (perched water). In our opinion the subsurface water conditions shown are a permanent feature on this site. The depth to free water would be subject to fluctuation, depending upon external environmental effects.

Because of capillary rise, the soil zone within a few feet above the free water level identified in the borings will be quite wet. Pumping and rutting may occur during the excavation process, particularly if the bottom of the foundations are near the capillary fringe. Pumping is a temporary, quick condition caused by vibration of excavating equipment on the site. If pumping occurs, it can often be stopped by removal of the equipment and greater care exercised in the excavation process. In other cases, geotextile fabric layers can be designed or cobble sized material can be introduced into the bottom of the excavation and worked into the soft soils. Such a geotextile or cobble raft is designed to stabilize the bottom of the excavation and to provide a firm base for equipment.

Data presented in this report concerning ground water levels are representative of those levels at the time of our field exploration. Groundwater levels are subject to change seasonally or by changed environmental conditions. Quantitative information concerning rates of flow into excavations or pumping capacities necessary to dewater excavations is not included and is beyond the scope of this report. If this information is desired, permeability and field pumping tests will be required.

This area has been extensively irrigated in the past for agricultural purposes. It is possible that after agricultural irrigation has ceased in the area, the water table may drop somewhat. It is not anticipated the free water table will rise in the future however, the water table should not be expected to drop more than 2 feet during the Summer and Fall months after area-wide irrigation has ceased or been diminished.

CONCLUSIONS AND RECOMMENDATIONS

GENERAL DISCUSSION

No geologic conditions were apparent during our reconnaissance which would preclude the site development as planned, provided the recommendations contained herein are fully complied with. Based on our investigation to date and the knowledge of the proposed construction, the site condition which would have the greatest effect on the planned development is the soft soils and the relatively high water table.

Since the exact magnitude and nature of the foundation loads are not precisely known at the present time, the following recommendations must be somewhat general in nature. Any special loads or unusual design conditions should be reported to Lincoln DeVore so that changes in these recommendations may be made, if necessary. However, based upon our analysis of the soil conditions and project characteristics previously outlined, the following recommendations are made.

OPEN FOUNDATION OBSERVATION

Since the recommendations in this report are based on information obtained through random borings, it is possible that the subsurface materials between the boring points could vary. Therefore, prior to placing forms or pouring concrete, an open excavation observation should be performed by representatives of Lincoln DeVore. The purpose of this observation is to determine if the subsurface soils directly below the proposed foundations are similar to those encountered in our exploration borings. If the materials below the proposed foundations differ from those encountered, or in our opinion, are not

capable of supporting the applied loads, additional recommendations could be provided at that time.

EXCAVATION & STRUCTURAL FILL:

Subgrade

Site preparation in all areas to receive structural fill should begin with the removal of all topsoil, vegetation, and other deleterious materials. Prior to placing any fill, the subgrade should be observed by representatives of Lincoln DeVore to determine if the existing vegetation has been adequately removed and that the subgrade is capable of supporting the proposed fills. The subgrade should then be scarified to a depth of 10 inches, brought to near optimum moisture conditions and compacted to at least 90% of its maximum modified Proctor dry density [ASTM D-1557]. The moisture content of this material should be within + or - 2% of optimum moisture, as determined by ASTM D-1557.

Structural Fill

In general, we recommend all structural fill in the area beneath any proposed structure or roadway be compacted to a minimum of 90% of its maximum modified Proctor dry density (ASTM D1557). We recommend that fill be placed and compacted at approximately its optimum moisture content (+/-2%) as determined by ASTM D 1557. Structural fill should be a granular, coarse grained, non-free draining, non-expansive soil. This structural fill should be placed in the overexcavated portion of this site in lifts not to exceed 6 inches after compaction. This

Structural Fill must be brought to the required density by mechanical means. No soaking, jetting or puddling techniques of any type should be used in placement of fill on this site.

Non-Structural Fill

We recommend that all backfill placed around the exterior of the building, and in utility trenches which are outside the perimeter of the building and not located beneath roadways or parking lots, be compacted to a minimum of 80% of its maximum modified Proctor dry density (ASTM D-1557).

Fill Limits

To provide adequate lateral support, we recommend that the zone of overexcavation extend at least 3 feet beyond the perimeter of the building on all sides. The Structural Fill should be a minimum of 3 feet in final compacted thickness.

No major difficulties are anticipated in the course of excavating into the surficial soils on the site. It is probable that safety provisions such as sloping or bracing the sides of excavations over 4 feet deep will be necessary. Any such safety provisions shall conform to reasonable industry safety practices and to applicable OSHA regulations. The OSHA classification for excavation purposes on this site is Soil Class C.

Field Observation & Testing:

During the placement of any structural fill, it is recommended that a sufficient amount of field tests

and observation be performed under the direction of the geotechnical engineer. The geotechnical engineer should determine the amount of observation time and field density tests required to determine substantial conformance with these recommendations. It is recommended that surface density tests be taken at maximum 2 foot vertical interval.

The opinions and conclusions of a geotechnical report are based on the interpretation of information obtained by random borings. Therefore the actual site conditions may vary somewhat from those indicated in this report. It is our opinion that field observations by the geotechnical engineer who has prepared this report are critical to the continuity of the project.

Slope Angles

Allowable slope angle for cuts in the native soils is dependent on soil conditions, slope geometry, the moisture content and other factors. Should deep cuts be planned for this site, we recommend that a slope stability analysis be performed when the location and depth of the cut is known.

DRAINAGE AND GRADIENT:

Adequate site drainage should be provided in the foundation area both during and after construction to prevent the ponding of water and the saturation of the subsurface soils. We recommend that the ground surface around the structure be graded so that surface water will be carried quickly away from the building. The minimum gradient within 10 feet of the building

will depend on surface landscaping. We recommend that paved areas maintain a minimum gradient of 2%, and that landscaped areas maintain a minimum gradient of 8%. It is further recommended that roof drain downspouts be carried across all backfilled areas and discharged at least 10 feet away from the structure. Proper discharge of roof drain downspouts may require the use subsurface piping in some areas. Planters, if any, should be so constructed that moisture is not allowed to seep into foundation areas or beneath slabs or pavements.

If adequate surface drainage cannot be maintained, or if subsurface seepage is encountered during excavation for foundation construction, a full perimeter drain is recommended for this building. It is recommended that this drain consist of a perforated drain pipe and a gravel collector, the whole being fully wrapped in a geotextile filter fabric. We recommend that this drain be constructed with a gravity outlet. If sufficient grade does not exist on the site for a gravity outlet, then a sealed sump and pump is recommended. Under no circumstances should a dry well be used on this site.

If a half basement type structure is planned on any of these sites, the high water level found across the tract should be controlled to prevent large upward fluctuations of this water surface. For this purpose, we recommend that this be accomplished by construction of an area drain beneath the building area. To control water surface movement, it is recommended that the drain outfall in a free gravity drain. If a gravity outfall is not possible, a sealed sump and pump is recommended to remove the water.

Should an automatic lawn irrigation systems be used on this site, we recommend that the sprinkler heads be installed no less than 5 feet from the buildings. In addition, these heads should be adjusted so that spray from the system does not fall onto the walls of the buildings and that such water does not excessively wet the backfill soils.

It is recommended that lawn and landscaping irrigation be reasonably limited, so as to prevent complete saturation of subsurface soils. Several methods of irrigation water control are possible, to include, but not limited to:

^{*} Metering the Irrigation water.

^{*} Sizing the irrigation distribution service piping to limit on-site water usage.

^{*} Encourage efficient landscaping practices.

^{*} Enforcing reasonable limits on the size of high water usage landscaping for each lot and any park areas.

FOUNDATIONS

Footing and Stemwall

Assuming that some amount of differential movement can be tolerated, then a conventional shallow foundation system, either resting on the native alluvial soils or underlain by a structural fill, placed in accordance with the recommendations contained within this report may be utilized. The foundation would consist of continuous spread footings beneath all bearing walls and isolated spread footings beneath all columns and other points of concentrated load. Such a shallow foundation system, resting on the native alluvial soils may be designed on the basis of an allowable bearing capacity of 800 psf maximum. If the shallow foundation system is founded on a properly constructed structural fill at least two feet thick below the foundation, the foundation system may be designed on the basis of an allowable bearing capacity of 1600 psf maximum. Recommendations pertaining to balancing, reinforcing, drainage, and inspection are considered extremely important and must be Contact stresses beneath all continuous walls should followed. be balanced to within + or - 200 psf at all points. Isolated interior column footings should be designed for contact stresses of about 150 psf less than the average used to balance the continuous walls. The criteria for balancing will depend somewhat on the nature of the structure. Single-story, slab-on-grade structures may be balanced on the basis of dead load only. Multi story structures may be balanced on the basis of dead load plus one half live load, for up to three stories.

Stem walls for a shallow foundation

system should be designed as grade beams capable of spanning at least thirteen feet. These "grade beams" should be horizontally reinforced both near the top and near the bottom. The horizontal reinforcement required should be placed continuously around the structure with no gaps or breaks. A foundation system designed in this manner should provide a rather rigid system and, therefore, be better able to tolerate differential movements associated with consolidation of the underlying soft soils.

If increased bearing capacity is required, the Structural Fill recommendations given for Structural Slab Foundation systems could be utilized. When The structural fill is completed, an allowable bearing capacity of 1600 psf maximum may be assumed for proportioning the footings.

Structural Slab

If the design of the upper structure is such that loads can be balanced reasonably well, a floating structural slab type of foundation could be used on this site. Such a slab would require heavy reinforcing to resist differential bending along the rim wall. It is possible to design such a slab either as a thickened edge only, a solid or a ribbed slab. A rim wall must be used for confinement purposes. Any such slab must be specifically designed for the anticipated loading.

Such a foundation system may settle to some degree however, the use of a structural fill beneath the slab and rim wall will help reduce settlement and hold differential movement to a minimum. Relatively large slabs will tend to experience minor cracking and heave of lightly loaded interior

portions, unless the slabs are specifically designed with this movement in mind.

The existing low density, metastable soils should be removed to a depth of 2 feet below the proposed bottom footing or rimwall elevation. Once it is felt that adequate soil removal has been achieved, it is recommended that the excavation be closely examined by a representative of Lincoln-DeVore to ensure that an adequate overexcavation depth has indeed occurred and that the exposed soils are suitable to support the proposed structural man-made fill.

Once this examination has been completed, it is recommended that a coarse-grained, non-expansive, nonfree draining man-made structural fill be imported to the site. The native soils may be utilized as structural fill, if specifically approved by the Geotechnical Engineer. This imported fill should be placed in the overexcavated portion of this site in lifts not to exceed 6 inches after compaction. A minimum of 90% of the soils maximum Modified Proctor dry density (ASTM D-1557) must be maintained during the soil placement. These soils should be placed at a moisture content conducive to the required compaction (usually Proctor optimum moisture content \pm 2%). The granular material must be brought to the required density by mechanical means. No soaking, jetting or puddling techniques of any type should be used in placement of fill on this site. To ensure adequate lateral support, we must recommend that the zone of overexcavation extend at least 2 feet around the perimeter of the proposed footing. To confirm the quality of the compacted fill product, it is recommended that surface density tests be taken at

maximum 2 foot vertical intervals.

The placement of a geotextile fabric for separation between the native soils and the structural fill is may be recommended to aid the fill placement and to improve the stability of the completed fill.

When The structural fill is completed, an allowable bearing capacity of 1600 psf maximum may be assumed for proportioning the footings.

The placement of the structural fill a minimum of two feet beyond the edge of the structural slab should provide additional support for the eccentrically placed wall loads on the slab edges.

SETTLEMENT:

We anticipate that total and/or differential settlements for the proposed structures may be considered to be within tolerable limits, provided the recommendations presented in this report are fully complied with. In general, we expect total settlements for the proposed structure to be less than 1-1/2 inch.

FROST PROTECTION

We recommend that the bottom of all foundation components rest a minimum of 1-1/2 feet below finished grade or as required by the local building codes. Foundation components must not be placed on frozen soils.

DRILLED PIERS:

Under some loading conditions, we recommend that a deep foundation system, consisting of drilled piers be used to carry the weight of the proposed structure. Deep foundations must extend through the low density upper low plastic clay materials and into the underlying clays and shales of the Mancos Shale Formation. The upper soils are very soft and wet with a water table being encountered at approximately 5 feet below the ground surface. Squeezing, caving and seepage moisture are anticipated during installation of these drilled piers, requiring that casing and dewatering equipment be on the site available for use during construction.

We recommend that drilled piers have a minimum shaft length of 38 feet and be embedded at least 6 feet into the relatively unweathered clays of the Mancos Shale Formation. At this level, these piers may be designed for a maximum end bearing capacity of 25000 psf, plus 2000 psf side support considering only the side wall area embedded in the bedrock. Due to the expansive potential of the bedrock, a minimum dead load uplift is required, consisting of a point uplift of 2200 psf and 300 psf side uplift, based on the side wall embedded in the bedrock. The overburden is soft and no supporting or uplift values are assigned to this material. The weight of the concrete in the pier may be incorporated into the required dead load.

It is recommended that the bottoms of all piers be thoroughly cleaned prior to the placement of concrete. The amount of reinforcing in each pier will depend on the

magnitude and nature of loads involved. As a rule of thumb, reinforcing equal to approximately 1/2 of 1% of the gross cross-sectional concrete area should be used. Additional reinforcing should be used if structural conditions warrant. We recommend that reinforcing extend through the full length of pier.

To minimize the possibility of voids developing in the drilled piers, concrete with a slump of 5 to 6 inches is recommended. We recommend that piers be dewatered and thoroughly cleaned of all loose material prior to placing the steel cage and concrete. The pier excavation should contain no more than 2 inches of free water unless the concrete is placed by means of a tremie extending to the bottom of the pier. A free fall in excess of 5 feet is not recommended when placing concrete in drilled piers. We recommend that casing be pulled as the concrete is being placed and that a 5 foot head of concrete be maintained while pulling the casing. It is recommended that drilled piers be plumb with 2% of their length and that the shaft maintain a constant diameter for the full length of the pier and not allowed to "mushroom" at the top.

DRILLED PIER OBSERVATION:

The foundation installation for drilled piers should be continuously observed by a representative of Lincoln DeVore to determine that the recommended bearing material has been adequately penetrated and that soil conditions are as anticipated by the exploration. This observation will aid in attaining an adequate foundation system. In addition, abnormalities in the subsurface conditions encountered during foundation

installation can be identified and corrective measures taken as required. Lincoln DeVore requires a minimum of one working day's notice, and a copy of the foundation plan, to schedule any field observation.

GRADE BEAMS:

A reinforced concrete grade beam is recommended to carry the exterior wall loads in conjunction with the deep foundation system. We recommend that this grade beam be designed to span from bearing point to bearing point and not be calculated to rest on the ground surface between these points.

CONCRETE SLABS ON GRADE

Slabs could be placed directly on the natural soils or on a structural fill. We recommend that all slabs on grade be constructed to act independently of the other structural portions of the building. One method of allowing the slabs to float freely is to use expansion material at the slabstructure interface.

It is recommended that slabs on grade be constructed over a capillary break of approximately 6 inches in thickness. We recommend that the material used to form the capillary break be free draining, granular material and not contain significant fines. A free draining outlet is also recommended for this break so that it will not trap water beneath the slab. A vapor barrier is recommended beneath the floor slab and above the capillary break. To prevent difficulty in finishing concrete, a 2 inch sand layer should be placed above the break. An alternate method of reducing finishing problems would be to place the vapor barrier beneath approximately 6 inches of a minus 3/4 inch gravel fill. This method must be very carefully accomplished to minimize excessive puncturing and tearing of the vapor barrier.

It is recommended that floor slabs on grade be constructed with control joints placed to divide the floor into sections not exceeding 360 to 400 square feet, maximum. Also, additional control joints are recommended at all inside corners and at all columns to control cracking in these areas.

EARTH RETAINING STRUCTURES

The active soil pressure for the design of earth retaining structures may be based on an equivalent fluid pressure of 51 pounds per cubic foot. The active pressure should be used for retaining structures which are free to move at the top (unrestrained walls). For earth retaining structures which are fixed at the top, such as basement walls, an equivalent fluid pressure of 63 pounds per cubic foot may be used. It should be noted that the above values should be modified to take into account any surcharge loads, sloping backfill or other externally applied forces. The above equivalent fluid pressures should also be modified for the effect of free water, if any.

The passive pressure for resistance to lateral movement may be considered to be 183 pcf per foot of depth. The coefficient of friction for concrete to soil may be assumed to be .24 for resistance to lateral movement. When combining frictional and passive resistance, the latter must be reduced by approximately 1/3.

We recommend that the backfill behind any retaining wall be compacted to a minimum of 85% of its maximum modified Proctor dry density, ASTM D-1557. The backfill material should be approved by the Soils Engineer prior to placing and a sufficient amount of field observation and density tests should be performed during placement. Placing backfill behind retaining walls before the wall has gained sufficient strength to resist the applied lateral earth pressures is not recommended.

REACTIVE SOILS

Since groundwater in the Grand Junction area typically contains sulfates in quantities detrimental to a Type I cement, a Type II or Type I-II or Type II-V cement is recommended for all concrete which is in contact with the subsurface soils and bedrock. Calcium chloride should not be added to a Type II, Type I-II or Type II-V cement under any circumstances.

PAVEMENTS

Samples of the surficial native soils at this property that may be required to support pavements have been evaluated using the Hveem-Carmany method (ASTM D-2844) to determine their support characteristics. The results of the laboratory testing are as follows:

AASHTO Classification - A-4(8) Unified Classification - CL

R = 11 Expansion @ 300 psi = 1.3 Displacement @ 300 psi = 4.28

Displacement values higher than 4.00 generally indicate the soil is unstable and may require confinement for proper performance.

No estimates of traffic volumes have been provided to Lincoln DeVore. However, we assume that the roads will be classified as residential. The design procedures utilized are those recognized by the Colorado Department of Highways and the 1986 AASHTO design procedure.

Based upon the existing topography, the anticipated final road grades and the anticipated future irrigation practices in the local area, a Drainage Factor of 0.6 (1986 AASHTO procedure) has been utilized for the section analysis.

PROPOSED PAVEMENT SECTIONS

Based on the soil support characteristics outlined above, the following pavement sections are recommended:

Residential Roadway, 18k EAL = 5:

The terminal Serviceability Index of 2.0, a Reliability of 70 and a design life of 20 years have been utilized, based on recommendations by the Highway Department. An 18 kip EAL of 5, also recommended by the Highway Department, was used for the analysis.

Asphalt-Base Coarse

3 inches of asphaltic concrete pavement on 8 inches of aggregate base coarse on 8 inches of recompacted native material

Full Depth Asphalt:

5 inches of asphaltic concrete pavement on 12 inches of recompacted native material

Due to anticipated problems of compacting the native subgrade soils and probable soil 'pumping' the use of a Full Depth Asphalt Section is $\underline{\text{NOT}}$ Recommended.

Rigid Concrete:

Doweled, not tied to shoulder slabs or curbing

6 inches of portland cement pavement on 4 inches of aggregate base coarse on 8 inches of recompacted native material

Collector Roadway, 18k EAL = 25:

The terminal Serviceability Index of 2.5, a Reliability of 70 and a design life of 20 years have been utilized, based on recommendations by the Highway Department. An 18 kip EAL of 25, also recommended by the Highway Department, was used for the analysis.

Asphalt-Base Coarse

3 inches of asphaltic concrete pavement on 18 inches of aggregate base coarse on 8 inches of recompacted native material OR

4 inches of asphaltic concrete pavement on 12 inches of aggregate base coarse on 8 inches of recompacted native material

Full Depth Asphalt:

6 inches of asphaltic concrete pavement on 12 inches of recompacted native material

Due to anticipated problems of compacting the native subgrade soils and probable soil 'pumping' the use of a Full Depth Asphalt Section is <u>NOT</u> Recommended.

Rigid Concrete:

Doweled, not tied to shoulder slabs or curbing

6 inches of portland cement pavement on 4 inches of aggregate base coarse on 8 inches of recompacted native material

Due to the possibility of very high soil moisture in the subgrade soils, the use of a Geotextile Fabric for separation and minor reinforcement (such as Mirafi 500-X or 140-N), placed beneath the Aggregate Base Course, may be required in some areas on this site.

PAVEMENT SECTION CONSTRUCTION

We recommend that any asphaltic concrete pavement meet the State of Colorado requirements for a Grade C mix. In addition, the asphaltic concrete pavement should be compacted to a minimum of 95% of its maximum Hveem density. The aggregate base coarse should meet the requirements of State of Colorado Class 5 or Class 6 material, and have a minimum R value of 78. We recommend that the base coarse be compacted to a minimum of 95% of its maximum Modified Proctor dry density (ASTM D-1557), at a moisture content within + or -2% of optimum moisture. The native subgrade shall be scarified and recompacted to a minimum of 90% of their maximum Modified Proctor day density (ASTM D-1557) at a moisture content within + or -2% of optimum moisture.

All pavement should be protected from moisture migrating beneath the pavement structure. If surface drainage is allowed to pond behind curbs, islands or other areas of the site and allowed to seep beneath pavement, premature deterioration or possibly pavement failure could result.

<u>Concrete</u> <u>Pavement</u>

We recommend that any rigid concrete pavement have a minimum flexural strength (F_t) of 650 psi at 28 days. This strength requirement can be met using Class P or AX or A or B Concrete as defined in Section 600 of the Standard Specifications for Road and Bridge Construction, Colorado DOT. It is recommended that field control of the concrete mix be made utilizing compressive strength criteria.

for the design process. Concrete with a lower flexural strength may be allowed by the agency having jurisdiction however, the design section thicknesses should be confirmed. In addition, the final durability of the pavement should be carefully considered.

Control joints should be placed at a minimum distance of 12 feet in all directions. If it is desired to increase the spacing of control joints, then 66-66 welded wire fabric should be placed in the mid-point of the slab. If the welded wire fabric is used, the control joint spacing can be increased to 40 feet. Construction joints designed so that positive joint transfer is maintained by the use of dowels is recommended.

The concrete should be placed at the lowest slump practical for the method of placement. In all circumstances, the maximum slump should be limited to 4 inches. Proper consolidation of the plastic concrete is important. The placed concrete must be properly protected and cured.

LIMITATIONS

This report is issued with the understanding that it is the responsibility of the owner, or his representative to ensure that the information and recommendations contained herein are brought to the attention of the individual lot purchasers for the subdivision. In addition, it is the responsibility of the individual lot owners that the information and recommendations contained herein are brought to the attention of the architect and engineer for the individual projects and the necessary steps are taken to see that the contractor and his subcontractors carry out the appropriate recommendations during construction.

The findings of this report are valid as of the present date. However, changes in the conditions of a property can occur with the passage of time, whether they be due to natural processes or the works of man on this or adjacent properties. In addition, changes in acceptable or appropriate standards may occur or may result from legislation or the broadening of engineering knowledge. Accordingly, the findings of this report may be invalid, wholly or partially, by changes outside our control. Therefore, this report is subject to review and should not be relied upon after a period of 3 years.

The recommendations of this report pertain only to the site investigated and are based on the assumption that the soil conditions do not deviate from those described in this report. If any variations or undesirable conditions are encountered during construction or the proposed construction will differ from that planned on the day of this

report, Lincoln DeVore should be notified so that supplemental recommendations can be provided, if appropriate. .

Lincoln DeVore makes no warranty, either expressed or implied, as to the findings, recommendations, specifications or professional advice, except that they were prepared in accordance with generally accepted professional engineering practice in the field of geotechnical engineering.

SOILS	DESC	RIPTIONS:	ROCK	DESCRIPTIONS:	SYMBOLS & NOTES:
SYMBOL	<u>uscs</u>	DESCRIPT!ON	SYMBOL	DESCRIPTION	SYMBOL DESCRIPTION
22		- Topsoil	0.000	DIMENTARY ROSKS CONGLOMERATE	9/12 Standard penetration drive
		-Mar-madê Fill		SANDSTONE	Numbers indicate 9 blows to drive the spoon 12" into ground.
0000 0000 0000 0000	GW	Well-graded Gravei		SILTSTONE	ST 2-1/2" Shelby thin wall sample
00000	GP	Poorly-graded Gravel		SHALE	III. Al-tural Mainture Content
0000	GM	Silty Grave!	XXX	CLAYSTONE	Wo Natural Moisture Content
000	GC	Clayey Grovel		COAL	W _X Weathered Material
	SW	Weil-greded Sand	写	LIMESTONE	Free water table
	SP	Pacriy-graded Sand		DOLOMITE	Y ^o Natural dry density
	SM	Siity Sand		MARLSTONE	T.B. — Disturbed Bulk Sample
	SC	Clayey Sand	7/7777	GYPSUM	② Soil type related to samples in report
	ML	Low-plasticity Sitt		Other Sedimentary Rocks	
	CL	Low-plasticity Clay	迎	GRANITIC ROCKS	15' Wx Top of formation
	OL	Low-plasticity Organic Silt and Clay	+++	DIORITIC ROCKS	Test Boring Location
	МН	High-plasticity Sitt		GABBRO	Test Pit Location
ووو	СН	High-plasticity Clay		RHYOLITE	Seismic or Resistivity Station.
- /- / - /-	ОН	High-plasticity Organic Clay	***	ANDESITE	Lineation indicates approx. length a orientation of spread (S=Seismic, R=Resistivity)
nun	Pt	Peat		BASALT	
000	GŴ/GM	Well- graded Gravel, Silty	4464	TUFF & ASH FLOWS	Standard Penetration Drives are made by driving a standard 1.4" split spoon sampler into the ground by dropping a
0000	GW/GC	Well-graded Gravel, Clayey	0.0	BRECCIA & Other Volcanics	140 lb. weight 30". ASTM fest des. D-1586.
00000	GP/GM	Poorly-graded Gravel, Silty	1 C Y 1	Other Igneous Rocks	Samples may be bulk, standard split spoon (both disturbed) or 2-1/2" I.D.
0000 0000 0000	GP/GC	Poorly-graded Gravel, Clayey		GNEISS	thin wall ("undisturbed") Shelby tube samples. See log for type.
1000		Silty Gravel, Clayey		SCHIST	The boring logs show subsurface conditions at the dates and locations shown, and it is
		Clayey Gravel, Silty		PHYLLITE	not warranted that they are representative of subsurface conditions at other locations and times.
	SW/SM	Well - graded Sand, Silty		SLATE	
	SW/SC	Clayey	000	METAQUARTZITE	
	SP/SM	Poorly-graded Sand, Silty	000	MARBLE	
	SP/SC	Poorly-graded Sand, Clayey	24 - 25 15t	HORNFELS	
	SM/SC	Silty Sand, Clayey	5115	SERPENTINE	
	SC/SM	Clayey Sand, Silty	1557	Other Metamorphic Rocks	
MIM	CL/ML	Silty Clay	DEVUKE	COLORADO: Colorado Springs, Pueblo, Gienwood Springs, Montrose, Gunnison, Grand Junction. — WYO. – Rock Springs	EXPLANATION OF BOREHOLE LOGS AND LOCATION DIAGRAMS

SUMN	MARY SHEET
Location GRAND VIEW SUB- G-J. Boring No Depth 3' Sample No J Natural Water Content (w) 22.0 %	
Specific Gravity (Gs)	In Place Density (7 0) <u>98, 6</u> pcf
SIEVE ANALYSIS: Sieve No. % Passing 1 1/2" 1" 3/4" 1/2" 4 10 20 99 40 99	Plastic Limit P.L. 16 % Liquid Limit L. L. 24 % Plasticity Index P.I. 8 % Shrinkage Limit % Flow Index Shrinkage Ratio % Volumetric Change % Lineal Shrinkage %
100	MOISTURE DENSITY: ASTM METHOD Optimum Moisture Content - wo% Maximum Dry Density - Tdpcf California Bearing Ratio (av)% Swell:Days% Swell againstpsf Wo gain%
Grain size (mm) %	BEARING:
-02 53 32	Housel Penetrometer (av) 800 psf Unconfined Compression (qu) psf Plate Bearing: psf Inches Settlement Consolidation 2.4% under 930 psf PERMEABILITY: K (at 20°C) Void Ratio Sulfates 1000 ppm.
	LINCOLN-DeVORE TESTING LABORATORY
soil analysis	COLORADO SPRINGS, COLORADO

SAM	PLE: AASHTO ,	4-4 (8.)	UCS (C	(4)		
	TEST SPECIMAN		A	В	С	D	E
	DATE TESTED		4/17	4/17	4/17		
7	Compactor Air Pressure	psi					
10 6	Initial Moisture	%	8-2%	-8-2	8-7		
18 2	Moisture at Compaction	%	18.2	17.2	16-2		
SPECI	Briquette Height	in.	7.58	Z.53	2.51		
0 3	Density	pcf	107-9	109.0	111-1		
	EXUDATION PRESSURE	psi	84	13.5	3/8		
	EXPANSION PRESSURE	DIAL	0.2	0.6	14		
. a	Ph at 1000 pounds	psi	66	64	60		
	Ph at 2000 pounds	psi	138	147	132		
STABIL-	Displacement	turns	4-05	4-14	4-30		
8 5	"R" Value		9	5	1)		<u> </u>
	CORRECTED "R" VALUE		8				

EXPANSION @ 300 PSI EXUDATION PRESSURE | 1.3 |
DISPLACEMENT @ 300 PSI EXUDATION PRESSURE | 4.28 |
"R: VALUE @ 300 PSI EXUDATION PRESSURE | 11

1월"	
1"	
3/4"	
1/2"	
3/8"	
4	100
10	99
20	99
40	99
100	94
200	82
.02 mm	50
.005 mm	32

LIQUID LIMIT	24
PLASTIC LIMIT	17
PLASTICITY INDEX	7
SAND EQUIVALENT	

100) [[]	H	\mathbb{H}	H	\mathbb{H}	H	H	+	\pm	± 1	Ŧ	H	Œ	H	1	H	H	Π	H	П	IF.	1	Fi	\pm	Ti	111	T				: [T:	::
	IIII I	ŦŦ	-	Ŧ	H	F	H	88	+	++	H	+++	Η.	H	ł+	Н	11	Н	Н	-1		++	Ð	ŧŧ:	11	• • •	-1!	ii:	Œ	1	1		Ŀ	: •
	\Box	ш	#	#	\Box	7	н	щ	ш		7	-	μ.	ш	17	П	Ι	-		==	μ.	71	Ħ	_	7		+-	-	4		-		1	
	###	#	##	#	#	#	П	\pm	ш	⇉	1	Ξ	Ħ	Π.	ļΙ	Ħ	17.	#	щ		Τ.	11:	11	::.	1:	:::	1:	:::	1	:::	: 1:		. []	٠.
	1	₩	11	H	++	t	H	Н		•	\pm	Н	+	H	ŧŧ.	H	łΞ	+ + -	++	••	ŧυ	4 *	ŧ٤	: : !	1:	: ::	1:	:::	1:	:::	: 1:		1:	1.1
90)	#	4	₽	\Box	4	-	Н	Ŧ	_	Ŧ	Ξ,	=	Π.	H	Н	F	-	-	-	μ.		F	-	+-		+-		+		+			
		1:		1:	==	#		#	ш		1	:#:	=	H		Ħ		11		=	! ::		t:	: -	1:	:::	1:	:::	: # :		: 1:		1	: '
	1111	++	-+	t	+++	Н	+	+		-	+	4-	+	+	•	+	+-		h::	- +	1:	:::	1:	• • •	1:	:::	1:	• • •	1:	• • • •	: 1:	: : : :	1:	
		#		₩	1	Ŧ	=	щ	#	-	7	=	-	Ξ	1	ц	-	-	Н.	==	-		F	-	+		7.		4		4		4	-
	1	11	-	1:		\pm	#	=	П	-:1	1	=	=	Ι.	#	‡‡	;=	:::	1.	-;	1	:::	1:	:	1:	: ::	1:	:::	: ‡:		: : :	::::		: :
	Hit	Ŧ÷:		H	+	+	+	-	++		+	-	-	+	++	H	-	+	++	1:	<u>†:</u> :		1:	. : :	: † :	:::	ł.:	:::	: 1:		:1:	::::	::	-:
80)	#	=	F	-	7	Н	П	-	_	7	-		-	ц	1	-	-	-	1.	F		Į-		4-		Τ.		4		4		<u> </u>	
	1	1	==	#	П	垏	12	Η	===	=	#		-	1:	::	11	11	-	Н	#	#		1:	:	:::	:::	1:	:::	: 1:	:::	: ; :		1	
	1	++-	-	Ħ	++	Н.	1		•	_	1	+	1	t÷.	:±	<u>: I</u>	+-	++		1:	t٠	: : :	I.		: t:	: ::	1:	:::	1:	:	: 1:		1:	: -
	1111	H	-	Ħ	Η	7	-	П		-	+	-	_	-	Ή.	ц	-	4	Н	Į.	Τ.		F		4		+-		4		4		<u> </u>	
	1111	11		۲.		吐		===	::	-1	1	-	1	t:	ヸ	Ħ	=	П	7.7	1:	1		1-	: : :	:1:	:::	1:	:::	1	:::	: 1 :		: .	: :
	111	++	++	ŧ÷	1	н		-			t	-	LT.	ŀ÷:	:+	±ŧ	:::	11	<u> </u>	1:	+-		1::	• • •	1:		1:	:::	1:	::::	: 1:		10	: :
70) 	#	+	₩	=	7	-	H			Ŧ	=	-	F	-	П	=	=	-	Ŧ	Η-		1:		+		Τ.		4		4		1	_
70		#	##	Ħ	-	#		≕	-		#	=		1	::	##	==	=	Н	⇉	1		17		1		1:		1:		: 1 :		.1.	
	++++	++	++	#	++	+	н	-	+ **	+	+	-	H	H	++	H	-	-	+•	++	+-	-+	+-	-	+:		+	-+-	+-		-+-		1:	
	-	#		Ħ	=	Π.	=	H	=	=	7	=	н	П	=	7	=	-	-	==	-		Ψ.	=	7.	==	7		Ŧ	Ξ.	-41		7	
		#	**	Ħ	\equiv		IT	H	\Box		1	=	#	1:	7	⇉	Ξ		-	=	1:	-	11	=	#	:	4=		4		#:		-4:	-:
	1	++		†÷	•	t	۲+	ш	++		÷	_	+	1:		: 1	: -	11	1		1=	-++	1:		:1:	- : :	1:	:::	: † :	: : :	: 1:		1:	
60)	#	==	Ŧ		7	-	_		-	+	_	-	F			_	-	-		μ.		F		+-		+-		+		-1-		<u> </u>	-
		#	-	#	::	1	::	==		7	7	=	:::	17	==	#	:-		-	::	#		1:	=	7:		1.		1	- : :	: [::.:	. 1 -	
	1	11	T	+		t	+	=	-:		1		÷	t:		11	<u>:</u> :	•	1:	++	±.		t:		:1:		t:		1:		: 1:		1:	::
	Hint	Ŧ		H	-	4	-		-	-	+	4	-	-		4	-	-	-	-	+-		+	-	+-		+-		+				4	_
		#	==	#	==	1	=	П	-		7.	Ξ.	; =	Ľ.	-:	=1		=			-	-:	#	_			П		4		: 4:		. ‡:	
	1:1:1	++	+	Ħ	+±	1	+		=:	-	±	1	-	<u> </u>	• •	: 1			-		<u>†:</u> :		<u> </u>	_	:1:		t:		: †:	-:	: ł :	: : : :	. t :	: :
50)	#	=	₩	-	+	-	H	Ī	_	Ŧ	-	-	H		+	++	-	-	-	Ŧ		F	-	+		+		4		-		-1-	_
	#	#	Ħ	#	\equiv	П	#	Н	н	_	1	: -	-;	Ľ.	コ	Ħ	Ц.		-		1:	===	11.		:1:		1-	:	: ‡.		: 1.		1.	:::
	11:1:	++	1	Ħ	t	H	t	ш		1	1	1	:t	1:	: 1	tt	:1	11			1:	11	Ħ	* *-	:1:		1.		-t	• • •	-1:	: :	: t -	
	H111	Ψ.	-	Ŧ	-	4	1	H	Ŧ	-	7	-	Τ.	μ.	4	П	#	-			1		H	-	7		7		-		4		-	
	###	#	\mathbf{H}	#	==	H	:	\mp	Н	=	4		Π,	Ħ	::	⇉	#	=	=		#	===	##	=:	-		1		7	:	: ‡.	::::	: 1:	:::
	ш:	#	##	Ħ	t	ш	Ħ		ш		d:	#	١.	Ħ	#	Ħ	#	ш.	1::	==	#		#	::	##	:::	1	:::	: 1:	. 4. 	: 1:	::::	: : :	::
40) 	ш	111	Ħ	\pm	н	H	ш	ш	ш		4	ш	н	Ħ	Ħ	11	±	ш	11	#	ш	±	IÌ.	ш	11:	1		::		-		:::	
	$\Pi\Pi\Pi$	H		H	+	H	H	-	Н	-	H	ł±	Ħ	H	Ħ	Ħ	H	H	Н	++	+	++	ŧ÷	11	++	1 1	+ :		1		٠ [• • • •	1:	- 1
	HH	#	Π	17	+	H	1	\pm	щ		4	Ŧ	Ħ.	H	Ħ	П	ŦŦ	H	H	77	+	77	F	ij.	41	111	7	щ,	7	ΞΞ.	. ; .		7	
	****	#	##	#	=		т		н	=	1	=	1:	Ħ	Ħ	11	::	#	#	#	#	**	1:	=	#	:::	1		1				:::	
	!!!!!	#	11	₩	1	tt	H	Ψ	Ш	-	ŧŁ.	: :	iż.	Н.	#	it	##	t:	H.	*	ቷ	1	±	+	1	+++	1:		: †:		: ł:	::::	: † :	::
20	VIIII	H	щ	₩	1	Н	H.		Н	Н	H	ij.	. :	Н	11	₩	H	Į.	+	++	H-		Ŧ÷		4		+		Ę.		- Į.		- † -	
30	'	Τ.	7	Ŧ	☵	П	H	-	\mp	- 4	7	=	• +	+	;;	듸	7	☵		Ξ.	ŢŦ	==	1-	=			Т.		.7					
	<u> </u>	#	##	11	I	#	∷	=	11:	1	Ц.	: =		Ħ	₽	⇉	11	11:	1::	++	#	-	#		:::		1:		:::	:	: 1:	: : : :	: 1:	:::
	1-11	++	+++	₩	++	Н	+	•	1		H	t t-	+	H	††	t t	:†	÷÷.	+-	++	++-		++	•	+		+.	• • •	4	٠.,	٠ إ	• • • •	. Į -	• • •
	H	#	-	77	Ŧ	7	+	7	Ŧ	-	FF	:=	H	H	H	77	77	-	-	77	+		7	#	7		Ŧ		7	===			7	==
	###	#		#	#	#	#	7.		7	ч			#	#	##	##	ΙŢ	1	#	#	==	1:	:-	:::	:::	#:		: 1	• • •	: ::		: ::	
20	\ LLL.	#	+++	Ħ		Н	+	÷	Ξ	•-	Lt.	-1-	=	<u>+</u> +	#	₩	++	++-	Ŀ	#	#	+	t		:1:	* * *	1:	• • •	<u>- L</u>		<u>· (:</u>		:±-	-
20	'	++		₩	-	7	 -	-	Ŧ	+	++	+	-	H	•	+7	-	_	₽				Ŧ÷	• • •	Τ-		∓-		7		- 7		Τ.	
		77		Ħ	-	ч	H	-	-		Ŧ	-	;=	#	Ц.	₽	μ.	=	μ.		Π.		H		: 1:	:::	1		: ‡		. 1	;:	: 1 :	
	thit:	Ħ	1	#		\pm	#	-	Η	-	<u>tt</u>	-	Ŀ	t t	#	Ħ	#	#	-	\pm	#:		#		+	+++	1:		• +		• 1:	• • • •	1:	_
		ŦŦ		₩	+	7	-	#	Ξ	٠,	H		F	Ŧ	+ +	₽	7:	ŦŦ	+	++	Ŧ+-	-	77	•	Π.	• • • •	Τ.		-7	• • •			-	
		1	H	H	7	H	H	-	$^{+}$	-	1	#	-	11	::	Ħ	14	щ	-		#	==	1:	; : :	μ:		4:		4	:::	:1			
10		1+	111	11	ш	ш	υ.	н	ш	_	Η.	+	**	Ħ	::	Ħ	**		#	-	±±	*	±	-	#	+++	1:		:1		• •		<u>: t:</u>	
~		#	Ħ	Ħ		Ħ	۰	ш	tri	-	tτ	Ė	tř	±٠	11	Н	÷	٠.	th	ΞŤ	dt.	ΞĪ	1:	ı.	ı J		+	_	+		<u>.</u> F		÷	_
	HH	H	H	H	++	H	1	F	H	-	H	H	H	H		H	#		Ŧ	#	#	+	1-	-	Η-		7	11	: ‡	++-	П		4:	==
		#	#	##	-	#	ш	ш	₽	=	Ħ	#	Ħ	#	#	Ħ	7#	::	Ħ	#	#	#	士	∺	#:	##	#		: +	-+-	_		#	
	1::11	Ш	ш	#	Ħ	벞	ш	Η.	ш	#	Н	Ħ	Ħ	Ħ	H	H	Ħ	#	H	+	ŦŤ	Н	++	Ħ.	+		+		: 1		• [- F	
_	Щ	Ŧ		Ħ	H	П	H	I	H	1	H	H	H	17	щ	71	17	#	1	-:	#		#	++	1	\Box	47	7.	11	::-	:1	117.	: : :	:::
0	ЩЩ	#	ш	Ŧ	tt	: 1	t t	щ	ш	-	tt,	t.t	ţţ	<u>t</u> t	##	t l	11	Ħ	tt.	#	1:		نا	##	ш	ш	1		Н	•••	:±:	<u>:::</u> :	±:	
8	⊞		7	$\overline{\alpha}$)			60	ŏ				5	$\overline{\alpha}$)			4	$\overline{\infty}$			-3	ά) [2	Ò	כ כ		_	10	o ¯		
_	_								٠,				-					- '	_				-			_						-		



GR	AND VI	EW SUB	FIL	#1	6-7-
DON	DELA	MOTTE		DATE 7	-/-94
JOB N	10. 91273-J	DRAWN	YM		

									γ	,
	,				BORING N	o. 1				
			BORIN	G ELEVATION:					SOIL	
РТН	SOIL			a LLL IXIII OXI.	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·		BLOW	DENSITY	WATER
.)	LOG				DESCRIPT	ION		COUNT	pcf	%
_			Surface	Soils reworked by	Agriculture					
_			Surface	is dessicated			±			
_			Debris	Fan Deposits		Increasing Mo	oisture			
_	/ [CL	Low Plas	stic, Silty Clay		Sulfates	ST		95.2	19.8%
5			9	Sandy Strata	Gray-brow	n compressib	le5		98.6	22.0%
					Saturated,	capillary frings	 -	4		
_	/	Free	Water	<u> </u>			•	_		
_				Very Soft				_		
•		CL	Silty Cla	ıy			SP*			
10 _			Some si	It and sand strata		Compressible	10	-		23.5%
_								3/18		
_					Hole is squ	eezing shut		4		
_								4		
_			Silty Cla	у				4		
15 _					Very Soft			4		
_								_		
_								4		
_							·	4		
_								4		
20 _							20	ᆜ		
_								4		
_								_		
								_		
_							BULK	4		22.1%
25 _			Very Sof	ft Silty Clay	alluvial/Del	oris Fan deposits	_25			
_]							4	1	
_								- -		
_	4		TD @ 25	5'				-		
_	-							\exists		
30 _	4				D1 O	ts are cumulative	30	<u>-</u>		
-								-		
-	4					'sampier penetrat e Water @	7 ′	-		
-	1						6-14-94	\dashv		
						ing brining	0 1 7 0 7		L	
							LOG OF SUBS	URFACE	EXPLO	RATION
							GRAND VII			
							Grand Jun		•	
										Date
		N1	\sim	N Dave		Ino		_l_ &#</td><td>•</td><td>7 4 04</td></tr><tr><td></td><td></td><td>LI IV</td><td>UUL</td><td>N - DeV</td><td>UNE,</td><td>mc.</td><td>Mr. Don C</td><td>Drawn</td><td></td><td>7-1-94</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>Job No.</td><td></td><td></td><td></td></tr></tbody></table>		

					BORING N	o. 2					
ЕРТН	SOIL		BORING	ELEVATION:						SOIL	
:P1H [.)	LOG				DESCRIPTI	ION			BLOW	DENSITY	WATER %
•			Surface Sc	ils reworked by					00011	POI	~ _
_			Surface is	dessicated		Debris Far	Deposits		1		
_					Sulfates	Increasing N	foisture		1		ļ
		CL	Low Plastic	, Silty Clay		Gray-brown		ST		105.1	17.9%
5 _			Saturated,	capillary frings				5]		Ì
_		Free	Water	<u>V</u>		compressi	bie				
_			Some silt a	and sand strata							ĺ
_			Ve	ery Soft							
_		CL	Silty Clay					SPT	1/6		
10 _			Very Stratif	fied		Compressibl	•	10	4 '		-21.4%
-									4/18		
-			Very Soft		Hole is sque	ezing shut			-		
-	/		Cilt. Ol						-		
15			Silty Clay TD @ 13'						1		
'3 -			10 @ 13					15	4		
-											
-									1		
				•					i		
20								20			
7								-	1		
25								. 25			
_											
4											
4										·	
<u></u>								30			
30					Blow Count	s are cumulative	for each				
4						sampler penetra					
7						Water @	6'				
-						ng Drilling					
·									L		
								F SUBSU			
							1	AND VIET			•
							- Gra			2101440	Date
		LIN	COLN	- DeVC	DRE.	Inc.	M-	Don De	la Mot		7-1-94
	•		- -: \		;		Job No.	JJ., DC	Drawn	-	, , , , , ,
			C=	and Junction	Colores	to	ì	73-J		ЕММ	

			BORING NO. 3					
		BORING ELEVATION:					SOIL	
PTH	SOIL	*				BLOW	DENSITY	WATER
Τ.)	LOG		DESCRIPTION			COUNT	pcf	%
-		Surface Soils reworked by						1
_		Surface is dessicated	Debris Fan	•				
_			Sulfates Increasing M	oisture				ļ
_		CL Low Plastic, Silty Clay	Saturated, capillary frings		ST		99.0	18.8%
5.		Free Water ∇	Gray-brown		5		99.3	20.1%
-		compressible]	
-		Very Soft						
-		CL Silty Clay			SPT	1/6		
10		Some silt and sand strata	Compressible		10	2/12		24.7%
	1 7	Come and and sund summ				3/18		}
-	/		Hole is squeezing shut					
•			, -					
-		Silty Clay						
15			Very Soft		15			
•							1	İ
-								
-								}
•								
20					20		į į	
-							!	
-							<u> </u>	
				BULK			İ	23.9%
25		Very Soft Silty Clay	alluvial/Debris Fan deposits		25			Ì
	}							ĺ
] .
_	<u>]</u>	TD @ 25'	•					}
_								1
30.	-			h	30			
-	4		Blow Counts are cumulative					1
-	4		6 inches of sampler penetral Free Water @	5'				
-	4		_					
			During Drilling	0-14-34	1			L., ——
				LOG OF SU				
			~				DIVISIO	
				Grand	June	tion, (Colorado	
								Date
		LINCOLN - DeV	ORE. Inc.	Mr. Do	n De	la Moi	tte	7-1-94
				Job No.		Drawn		
				04070	. [

Grand Junction, Colorado

81273-J

EMM



TEL: (303) 242-8968 FAX: (303) 242-1561

June 29, 1994

Mr. Don Dela Motte 634 Avalon Drive Grand Junction, CO.

Re:

SUBSURFACE SOILS EXPLORATION

GRAND VIEW SUBDIVISION, Fil. 1

Grand Junction, Colorado

Dear Sir:

Transmitted herein are the results of a Subsurface Soils Exploration for the proposed single family residential Grand View Subdivision, Filing #1.

If you have any questions after reviewing this report, please feel free to contact this office at any time. This opportunity to provide Geotechnical Engineering services is sincerely appreciated.

Respectfully submitted,

LINCOLN-DeVORE, INC.

By:


Edward M. Morris, E.I.T. Western Slope Branch Manager Grand Junction, Office

Reviewed by:

George D. Morris, P.E. Colorado Springs Office

LDTL Job No. 81273-J '

EMM/ss



REVIEW COMMENTS

Page 1 of 4

FILE #FP-96-114

TITLE HEADING: Grand View Subdivision, Filing #2

LOCATION:

N of Hawthorne, E of 28 Road

PETITIONER:

Donada, Inc.

PETITIONER'S ADDRESS/TELEPHONE:

634 Avalon Drive

Grand Junction, CO 81504

434-6224

PETITIONER'S REPRESENTATIVE:

Tom Logue

STAFF REPRESENTATIVE:

Michael Drollinger

NOTE: THE PETITIONER IS REQUIRED TO SUBMIT FOUR (4) COPIES OF WRITTEN RESPONSE AND REVISED DRAWINGS ADDRESSING ALL REVIEW COMMENTS ON OR BEFORE 5:00 P.M., MAY 23, 1996.

CENTRAL GRAND VALLEY SANITATION

5/6/96

M. Meyer

434-2276

This is not in our District

GRAND JUNCTION DRAINAGE

5/7/96

John Ballagh

242-4343

- 1. This subdivision which is outside the boundaries of the Drainage District, does drain into the Buthorn Drain, a Grand Junction Drainage District facility which is at capacity during storm events. On-site or regional detention is <u>strongly</u> recommended. The surface runoff <u>does not</u> flow through Spring Valley and into one of the irrigation canals, as the Stormwater Management Plan for Grand View Subdivision, Filing No. 2 indicates on page 5, point #11.
- 2. No overall drainage plans were submitted for review by this office. We need plans to look at in order to comment.

CITY POLICE DEPARTMENT

5/7/96

Dave Stassen

244-3587

No additional comments.

WALKER FIELD AIRPORT AUTHORITY

5/6/96

Dennis Wiss

244-9100

- 1. This development lies within the Airport Area of Influence, as well as underlying a common aircraft traffic pattern (runway 4/22), so may be affected by overflight of aircraft.
- 2. An Avigation Easement is required to be recorded at or before filing of the subdivision plat. Please send a copy of the recorded document to the Walker Field Airport Authority following its recording.
- 3. It is our recommendation that, due to this (residential) development's proximity to aircraft flight paths and the airport proper, that additional soundproofing insulation as well as planned landscape features be designed into each residence and site to help mitigate potential sound-level perceptions.

FP-96-114 / REVIEW COMMENTS / page 2 of 4

UTE WATER

5/8/96

242-7491

Gary R. Mathews

- The water lines in Ridge Drive and Grand View Drive will be 8" and a 6" in Grand View Circle. Ute Water has an 18" water main in 28 Road.
- 2. Water mains shall be C-900, class 150. Installation of pipe fittings, valves and services including testing and disinfection shall be in accordance with Ute Water standard specifications and drawings.
- 3. Developer is responsible for installing meter pits and yokes. Ute will furnish the meter pits and yokes.
- 4. Construction plans required before development begins.
- 5. Policies and fees in effect at the time of application will apply.

CITY FIRE DEPARTMENT

5/9/96

Hank Masterson

244-1414

Move the hydrant proposed for Lot 26, Block 4 to Lot 24, Block 4. Move the hydrant proposed for Lot 21, Block 4 to Lot 18, Block 4 at Lot 18's northwest corner.

CITY PROPERTY AGENT

5/9/96

Steve Pace

256-4003

- 1. Re-plat this filing #2 to show the remainder of property being subdivided, see attached reduced copy of the assessor map with are to be platted shown thereon.
- 2. All lots & blocks in each filing to be numbered consecutively.
- 3. Provide long chord information with all curves.
- 4. Address only those easements that are shown on the plat (see red-lined plat).
- In the Surveyors Certificate also stat the this plat conforms to the requirements for subdivision plats specified in the City of Grand Junction Development Code.
- 6. Need to show that interior lot corners are going to be set.

PUBLIC SERVICE COMPANY

5/9/96

John Salazar

244-2781

GAS & ELECTRIC: No objections. Will require some side-lot easements - exact locations will be determined when power line for project is engineered.

U.S. WEST

5/13/96

Max Ward

244-4721

For timely telephone service, as soon as you have a plat and power drawing for your housing development, please......

MAIL COPY TO:

AND

CALL THE TOLL-FREE NUMBER FOR:

U.S. West Communications

Developer Contact Group

Developer Contact Group

Developer Contact Group

1-800-526-3557

P.O. Box 1720

Denver, CO 80201

We need to hear from you at least 60 days prior to trenching.

FP-96-114 / REVIEW COMMENTS / page 3 of 4

T C I CABLEVISION

5/13/96

245-8777

Glen Vancil

See attached comments.

CITY DEVELOPMENT ENGINEER

5/15/96

Jody Kliska

244-1591

See attached comments.

GRAND VALLEY WATER USERS

5/15/96

Richard Proctor

242-5065

Grand Valley Water Users' Association has no comments to offer concerning this second filing of Grand View Subdivision.

CITY UTILITY ENGINEER

5/15/96

Trent Prall

244-1590

WATER: Ute

- 1. Provide a signoff block for Ute on all water related plans.
- 2. Please obtain Ute Water's standard specifications rather than the City of Grand Junction's Water specifications.

SEWER: City of Grand Junction

- 3. Please reconfigure sewer service lines for lot 1, blk 8 and lot 1, blk 9 to drain to sewers rather than manholes.
- 4. Please eliminate sewer line B1 to B5. Reconfigure sewer service lines for: Lot 1, Blk 8 to between B2-B3; Lot 6, Blk 1 to between A1-B1; Lot 5 Blk 1 to between A1-B1 via an easement along back of Lot 6, Blk 1.
- 5. How is MH B1 to be set in relation to concrete curb-gutter-sidewalk?
- 6. Please indicate that all sewer/water crossings shall be encased per City of Grand Junction specifications.
- 7. In addition to the notes already on the sewer plans, please incorporate the following notes to the sewer plan and profile.
 - A. Contractor shall have one signed copy of plans and a copy of the City of Grand Junction's Standard Specifications at the job site at all times.
 - B. No 4" services shall be connected directly into manholes.
 - C. The contractor shall notify the City inspection 48 hours prior to commencement of construction.
 - D. The Contractor is responsible for all required sewer line testing to be completed in the presence of the City Inspector. Pressure testing will be performed after all compaction of street subgrade and prior to street paving. Final lamping will also be accomplished after paving is completed. These tests shall be the basis of acceptance of the sewer line extension.
 - E. The Contractor shall obtain City of Grand Junction Street Cut Permit for all work within existing City road right-of-way prior to construction.
 - F. A clay cut-off wall shall be placed 10 feet upstream from all new manholes unless otherwise noted. The cut-off wall shall extend from 6 inches below to 6 inches above granular backfill material and shall be 2 feet wide. If native material is not suitable, the contractor shall import material approved by the engineer.

G.V.-MD

FP-96-114 / REVIEW COMMENTS / page 4 of 4

G. Stub out north of Grand View Drive shall be capped and plugged north of development property line. Stub out shall be identified with a steel fence post buried 1' below finished grade. As-built surveying of stub out required PRIOR to backfill.

H. Benchmark _____

CITY PARKS & RECREATION

5/17/96

Shawn Cooper

244-3869

Parks & Open Space fees - 36 units @ \$225 = \$8,100.

CITY COMMUNITY DEVELOPMENT

5/16/96

Ronnie Edwards

244-1430

The name "Grand View Circle" is discouraged. A different prefix is advised due to the proximity in relation to Grand View Drive and its length. It is getting increasingly more difficult for the Postal Service to deliver mail when the same prefix is used over and over in the same subdivision.

CITY COMMUNITY DEVELOPMENT

5/16/96

Michael Drollinger

244-1439

See attached comments.

LATE COMMENTS

MESA COUNTY SCHOOL DISTRICT #51

5/20/96

Lou Grasso

242-8500

SCHOOL - CURRENT ENROLLMENT / CAPACITY - IMPACT

Orchard Avenue Elementary - 389 / 375 - 9

East Middle School - 415 / 465 - 4

Grand Junction High School - 1674 / 1630 - 6

TO DATE, COMMENTS NOT RECEIVED FROM:

City Attorney Mesa County Planning Grand Valley Irrigation Colorado Geological Survey U.S. Postal Service May 10, 1996

Grand View, Fil. 2
Tom Logue
% Community Development Department
250 North 5th Street
Grand Junction, CO 81501

Ref. No. CON19622

Dear Mr. Logue;

We are in receipt of the plat map for your new subdivision, **Grand View, Fil. 2**. We will be working with the other utilities to provide service to this subdivision in a timely manner.

I would like to take this opportunity to bring to your attention a few details that will help both of us provide the services you wish available to the new home purchasers. These items are as follows:

- 1. We require the developers to provide, at no charge to TCI Cablevision, an open trench for cable service where underground service is needed and when a roadbore is required, that too must be provided by the developer. The trench and/or roadbore may be the same one used by other utilities so long as there is enough room to accommodate all necessary lines.
- 2. We require developers to provide, at no charge to TCI Cablevision, fill-in of the trench once cable has been installed in the trench.
- 3. We require developers to provide, at no charge to TCI Cablevision, a 4" PVC conduit at all utility road crossings where cable TV will be installed. This 4" conduit will be for the sole use of cable TV.
- 4. Should your subdivision contain cul-de-sac's the driveways and property lines (pins) must be clearly marked prior to the installation of underground cable. If this is not done, any need to relocate pedestals or lines will be billed directly back to your company.
- 5. TCI Cablevision will provide service to your subdivision so long as it is within the normal cable TV service area. Any subdivision that is out of the existing cable TV area may require a construction assist charge, paid by the developer, to TCI Cablevision in order to extend the cable TV service to that subdivision.
- 6. TCI will normally not activate cable service in a new subdivision until it is approximately 30% developed. Should you wish cable TV service to be available for the first home in your subdivision it will, in most cases, be necessary to have you provide a construction assist payment to cover the necessary electronics for that subdivision.

Should you have any other questions or concerns please feel free to contact me at any time. If I am out of the office when you call please leave your name and phone number with our office and I will get back in contact with you as soon as I can.

Sincerely.

Glen Vancil,

Construction Supervisor 245-8777

Our Vancil

GENERAL PERMIT APPLICATION

STORMWATER DISCHARGES ASSOCIATED WITH:

CONSTRUCTION ACTIVITY

(Permit No. COR-030000)

FOR AGENCY USE	ONLY
Certification Num	iber
C O R - 0 3	
Date Received	Fee Category
Year Month Day	

Please print or type. All items must be completed accurately and in their entirety or the application will be deemed incomplete and processing of the permit will not begin until all information is received. Please refer to the instructions for information about the required items. An original signature of the applicant is required.

Other:
ing Two

-1-

Anticipated construction scheme:	\smile
Commencement date: June 1996	Completion date: <u>Sept. 1996</u>
Area of the construction site: Total area 12.3 ac.	
Area to undergo excavation or grading: 11.5	-
The name of the receiving stream(s). (If discharge is to a ditch ultimate receiving water): Buthorne Drain to Cold	
Other environmental permits held for this construction activity.	•
Stormwater Management Plan Certification:	
I certify under penalty of law that a complete Stormwater Manage	ement Plan, as described in Appendix A of this
I certify under penalty of law that a complete Stormwater Manage application, has been prepared for my facility. Based on my inquisystem, or those persons directly responsible for gathering the infithe best of my knowledge and belief, true, accurate, and complete for falsely certifying the completion of said SWMP, including the violations.	iry of the person or persons who manage the formation, the Stormwater Management Plan is . I am aware that there are significant penalts
application, has been prepared for my facility. Based on my inquisystem, or those persons directly responsible for gathering the infithe best of my knowledge and belief, true, accurate, and complete for falsely certifying the completion of said SWMP, including the violations.	iry of the person or persons who manage the formation, the Stormwater Management Plan is a. I am aware that there are significant penaltic possibility of fine and imprisonment for known
application, has been prepared for my facility. Based on my inquisystem, or those persons directly responsible for gathering the infithe best of my knowledge and belief, true, accurate, and complete for falsely certifying the completion of said SWMP, including the violations. Signature of Applicant	tiry of the person or persons who manage the formation, the Stormwater Management Plan is a. I am aware that there are significant penaltic possibility of fine and imprisonment for known and imprisonment for known and imprisonment for known and imprisonment for known and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic possibility of fine and imprisonment for known are also as a significant penaltic pe
application, has been prepared for my facility. Based on my inquisystem, or those persons directly responsible for gathering the infithe best of my knowledge and belief, true, accurate, and complete for falsely certifying the completion of said SWMP, including the violations. Anald I. Mannotte	tiry of the person or persons who manage the formation, the Stormwater Management Plan is a. I am aware that there are significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic possibility of fine and imprisonment for known as a significant penaltic
application, has been prepared for my facility. Based on my inquisystem, or those persons directly responsible for gathering the infithe best of my knowledge and belief, true, accurate, and complete for falsely certifying the completion of said SWMP, including the violations. Signature of Applicant	tiry of the person or persons who manage the formation, the Stormwater Management Plan is a. I am aware that there are significant penaltic possibility of fine and imprisonment for known and imprisonment for known and imprisonment for known are signed. S-23-96 Date Signed
application, has been prepared for my facility. Based on my inquisivem, or those persons directly responsible for gathering the infithe best of my knowledge and belief, true, accurate, and complete for falsely certifying the completion of said SWMP, including the violations. Signature of Applicant Donald D. Della Moffe president Della Name (printed)	iry of the person or persons who manage the formation, the Stormwater Management Plan is a. I am aware that there are significant penalty possibility of fine and imprisonment for known and Espain Date Signed Date Signed Title I am familiar with the information submitted in those individuals immediately responsible for occurate and complete. I am aware that there is
application, has been prepared for my facility. Based on my inquisystem, or those persons directly responsible for gathering the infinite best of my knowledge and belief, true, accurate, and complete for falsely certifying the completion of said SWMP, including the violations. Signature of Applicant Denald D. Della Motte president Della Name (printed) Signature of applicant: I certify under penalty of law that I have personally examined and application and all attachments and that, based on my inquiry of the obtaining the information, I believe that the information is true, a significant penalties for submitting false information, including the	iry of the person or persons who manage the formation, the Stormwater Management Plan is a. I am aware that there are significant penaltic possibility of fine and imprisonment for known and the Signed Title I am familiar with the information submitted in those individuals immediately responsible for occurate and complete. I am aware that there are possibility of fine or imprisonment.
application, has been prepared for my facility. Based on my inquisivem, or those persons directly responsible for gathering the infinite best of my knowledge and belief, true, accurate, and complete for falsely certifying the completion of said SWMP, including the violations. Signature of Applicant Denald D. Della Moffe president Denald Printed Signature of applicant: I certify under penalty of law that I have personally examined and application and all attachments and that, based on my inquiry of to obtaining the information, I believe that the information is true, a	iry of the person or persons who manage the formation, the Stormwater Management Plan is it. I am aware that there are significant penaltic possibility of fine and imprisonment for known Date Signed Date Signed Title I am familiar with the information submitted in those individuals immediately responsible for occurate and complete. I am aware that there a
application, has been prepared for my facility. Based on my inquisystem, or those persons directly responsible for gathering the infinite best of my knowledge and belief, true, accurate, and complete for falsely certifying the completion of said SWMP, including the violations. Signature of Applicant Denald D. Della Motte president Della Name (printed) Signature of applicant: I certify under penalty of law that I have personally examined and application and all attachments and that, based on my inquiry of the obtaining the information, I believe that the information is true, a significant penalties for submitting false information, including the	iry of the person or persons who manage the formation, the Stormwater Management Plan is a. I am aware that there are significant penaltic possibility of fine and imprisonment for known and the Signed Title I am familiar with the information submitted in those individuals immediately responsible for occurate and complete. I am aware that there are possibility of fine or imprisonment. S-23-96 Date Signed

£0.9

STAFF COMMENTS

FILE:

#FP-96-114

DATE:

May 16, 1996

STAFF:

Michael T. Drollinger

PROJECT:

Grand View Filing #2

REQUEST:

Major Subdivision Plat-Final

LOCATION: N. of Hawthorne Ave./E of 28 Road

ZONING:

RSF-5

COMMENTS:

- 1. Landscaping of private open space must be made part of Development Improvements Agreement (DIA).
- 2. The Preliminary Plan approved for this project shows that adequate ROW exists for the completion of Ridge Drive at the 28 Road intersection. This does not appear to be the case on the Final Plat for Filing #2. Please explain.
- 3. Please provide a detail for the "rail fence" identified on the Landscape Plan. Also, please detail how the proposed landscape treatement along 28 Road conforms with the requirements of the Preliminary Plan approval.
- 4. Please remove the reference to the Mesa County Code in the landscaping notes.

Please contact the Community Development Department (244-1430) if you have any questions or require further explanation of any item.

h:\cityfil\1996\96-114.rvc

RESPONSE TO REVIEW COMMENTS

May 23, 1996

Title: GRAND VIEW FILING TWO, Final Plan and Plat

File No: FP-96-114

Location: NW of 28 Road and Hawthorne Ave.

The following agency comments were informational in nature and do not require a specific response:

CENTRAL GRAND VALLEY SANITATION
CITY POLICE DEPARTMENT
PUBLIC SERVICE COMPANY
U.S. WEST
TCI CABLEVISION
GRAND VALLEY WATER USERS
CITY PARKS AND RECREATION

RESPONSE TO GRAND JUNCTION DRAINAGE DIST.:

Overall drainage plans were submitted to the district as part of Filing One review in July of 1994. The drainage plan were submitted with modifications request by the City Engineering Department and responded to the issues raised by the Drainage District at that time.

RESPONSE TO WALKER FIELD:

An Aviation Easement has been transmitted to the Community Development Department for recording with the Final Plat.

The following statement is included in the previously recorded Covenants, "Grand View Subdivision lies within the Walker Field Airport of Influence, it is suggested that additional soundproofing insulation be incorporated within the construction of each dwelling".

RESPONSE TO UTE WATER:

With the exception of a 6 inch line in Grand View Circle all other new lines will be 8 inch in diameter.

RESPONSE TO FIRE DEPARTMENT:

The hydrant located at Lot 26, Block 4 has been relocated to Lot 24, Block 4 and the hydrant located at Lot 21, Block 4 has been relocated to Lot 24, Block 4.

A new overall utility composite has been submitted to the department for review.

RESPONSE TO PROPERTY AGENT:

All of the requested modifications to the Final Plat have been made and a new document has been transmitted to the Community Development Department for distribution to the Property Agent.

RESPONSE TO DEVELOPMENT ENGINEER:

- 1. Prior to rerunning the HEC program a meeting between the Development Engineer and the preparer of the Master Drainage Plan will be held to discuss in detail the nature of the requested modification to the plan.
- 2. The sidewalk extension south of Hawthorne Avenue along 28 Road was not installed as part of Filing One in order to allow space for any grade adjustments for future improvements to 28 Road south of Grand View. However, the Street Plans have been modified to include construction a 7 foot curbwalk extending south of Hawthorn Avenue to the south boundary of Grand View.
- 3. A copy of the Construction Permit Application to the State Health Department for stromwater management has been transmitted to the Community Development Department.
- 4. A 25 foot right of way was dedicated as part of the Garfield View Subdivision for what now is known as Ridge Drive.
- 5. The Final Plat has been revised to indicate a drainage easement within the private open space along 28 Road.
- 6. The Street Plans have been segmented showing the plan and profile in accordance with the SSID Manual requirements.
- 7. A notation for the 7 foot curbwalk has been added to the street plans.
- 8. Inlet sizes are indicated on the Storm Sewer profiles. If the HEC program must be rerun, a new summary will be provided indicating the sizing of the drainage facilities in filing two.
- 9. The location of street lighting and signs have been added to the Street Plans.
- 10. Street structural sections have been changed on the Detail Sheet to reflect the design by the geotechnical consultant.

- 11. A copy of a revised Exhibit B of the Improvements Agreement has been transmitted to the Community Development Department.
- 12. A note has been added to the Final Plat that no access to Ridge Drive will be permitted.

RESPONSE TO UTILITY ENGINEER:

Requested modifications have been made to the Sewer and Water Plans.

RESPONSE TO COMMUNITY DEVELOPMENT:

- 1. Costs for landscaping the Private Open Space has been added to Exhibit B of the Development Improvements Agreement.
- 2. A detail for the "rail fence" has been added to the Landscape Plan.

(Addendum #1)

MASTER DRAINAGE STUDY OF GRAND VIEW SUBDIVISION

JUNE, 1996

Prepared For:

DONADA INC, c/o DON DELA MOTTE 634 Avalon Drive Grand Junction, Colorado 81501 (303)-434-5224

Prepared By:

LANDesign LLC. 259 Grand Avenue Grand Junction, Colorado 81501 (303)-245-4099

"I hereby certify that this (Addendum #1) to the Master Drainage Study of Grand View Subdivision was prepared under my direct supervision".

Reviewed by:

Philip M. Hart P.E. // State of Colorado, # 19346

I. SCOPE OF ADDENDUM

The purpose of this addendum is to re-evaluate selected HEC1 input parameters based on the City of Grand Junction's latest current drainage criteria.

II. BACKGROUND INFORMATION

The original "Master Drainage Study for Grand View Subdivision", dated July 29, 1994, was prepared using the "Mesa County Storm Drainage Criteria Manual", dated March 1992. At the time of preparation the Mesa County manual contained the most complete and comprehensive hydrologic data and approved methodology for the Grand Junction and Mesa County areas. With the submittal of phase two (Filing No. Two) in June, 1996, came a re-review of the original Master Drainage Study. A comparison of the original study against design guidelines contained in the City of Grand Junction's "Stormwater Management Manual", adopted August 17, 1994, two input parameter discrepancies were note. The City Engineering staff has requested an analysis of the impact of these discrepancies as it would relate to the "total peak" discharge from the site and the adequacy of the originally proposed detention volumes.

Based on conversations between LANDesign staff and the City Development Engineer the scope of this analysis shall be limited to the evaluation of the Developed 100 Year Storm Event based on revisions to the following input parameters:

NMIN INPUT VALUE:

The original study used a minimum computation interval of 2 minutes. The HEC1 program allows and absolute minimum of 1 minute. The City of Grand Junction's recommended minimum is 5 minutes (see Exhibit 1.0). This addendum increases the NMIN value to 5 minutes.

SCS CURVE NUMBERS (CN):

Upon further review of the City's Stormwater Management Manual it is apparent that the (CN) values used in the original study for the developed condition were in conflict with those specified in the manual. The original study used those values presented in the Mesa County manual. These values are based on a Antecedent Runoff Condition (ARC) of III. The values prescribed by the City's manual are based on a (ARC) of II. The (CN) values presented herein are derived from the City manual and are based on actual field conditions using a percent of impervious area of 59% and a percent of pervious area of 41%. These values were derived by evaluating typical house, garage, landscaping and one-half roadway improvements as found to be constructed in Filing No. One.

III. CONCLUSIONS AND RESULTS

The result increasing the NMIN value is a long storm duration to peak discharge which increases the peak runoff.

The result of decreasing the (CN) values was to lower the peak runoff value from the entire site. The original 100 Year Storm Event runoff value was originally estimated to be 84 CFS. The revised estimate by this addendum is 41 CFS. The net decrease in calculated flow is 51%. In addition the maximum water surface elevations for the 100 Year maximum water surface are reduced to the levels as shown on the HEC1 output data sheets in the appendix.

Based on these results, the actual required detention volumes would be less than those proposed with the original study. A copy of the original study narrative is found in the appendix.

APPENDIX

ORIGINAL STUDY NARRATIVE

PURPOSE AND SCOPE OF STUDY

The purpose of this study is to evaluate the affects of development of the Grand View Subdivision and to provide a basis for subsequent analysis and design of proposed phases of the development. A hydrologic analysis of the project's tributary watersheds for historic and developed conditions has been performed and is presented in this report.

II. PROJECT LOCATION AND DESCRIPTION

Location:

Grand View Subdivision is located West 1/2 of Section 6, T.1 S., R.1 E., of the Ute Meridian.

Streets in the vicinity include 28 Road running from the south to the north defining the west boundary line. Approximately 1/4 mile south is Patterson Road running from the east to the west.

Development in the vicinity includes Spring Valley to the west a single family development of moderate density. Additionally some acreage sized parcels with single family dwellings adjoin the parcel adjacent to 28 Road. To the north lies undeveloped agricultural lands. To the east is Matchett Village a new development which is currently in the County Subdivision process. The Matchett Village area is planned for mixed use consisting of single family, multifamily and non-residential uses. To the south lies undeveloped agricultural lands.

Description:

The project contains approximately 64.9 acres of land and is planned for 200 single family building sites. Lots range in size from 8,000 to 10,000 square feet.

Presently there is one single family dwelling and two out-buildings on the subject property. Agricultural production has occurred on the property for a number of years and is presently readied for seasonal production.

III. HYDROLOGIC CALCULATIONS

References and Constraints:

The policies outlined in the "Interim Outline of Grading and Drainage Criteria, City of Grand Junction" were used as a basis to determine the study methodologies, techniques and hydrologic data presented herein.

The US Army Corps of Engineers "HEC1 Flood Hydrograph Package" was used to estimate the flowrates within the tributary watershed as a result of development of the property.

Watershed Description:

The tributary watershed contains an estimated 91.31 acres or 0.1426 square miles being entirely located east of 28 Road. The watershed length is approximately 3,200 feet or 0.61 miles. The elevation at the headwater is approximately 4,760 and the elevation at the southwest corner of the project is approximately 4,711. This results in a average slope of approximately 1.53%. Hydrologic conditions are considered "good".

Lands within the watershed are best described as flat agricultural and pasture lands tilled to support straight row crops.

Watershed Vegetation:

Vegetation consists primarily of row crops and pockets of grass ground cover. Isolated pockets of wetland vegetation is found to exist within the existing irrigation and drainage channel along the south boundary line of the project.

Watershed Soils:

The "Soil Survey, Grand Junction Area" defines soils within the watershed as being (Bc), Billings silty clay loam, 0 to 2 percent slopes, hydrological soils group "C", (Rf), Ravola very fine sandy loam, 0 to 2 percent slopes, hydrological soils group "B" and (Fc) Fruita and Ravola loams, 2 to 5 percent slopes, hydrological soils group "B".

As indicated on the "Area Soils Map" the watershed soils are classified as being in the Hydrologic Soils Group "B" and "C". Based on this information (CN) Curve Numbers assigned to sub-areas within the watershed range from 88 to 96 based on existing and proposed land use and are tabulated on the Sub-Basin Summary forms contained in the appendix of this report. These (CN)s represent a soil Antecedent Moisture Condition III for use with the "24 Hour Storm" (DDF) Depth-Duration- Frequency data. Runoff Curve Number Tables 408 and 409 for Mesa County are provided in the appendix of this report show relative changes in curve numbers based on site specific conditions.

Watershed Geometry:

Historic topography divides the watershed into 6 distinct sub-basins defined as offsite sub-basins OF1, OF2 and OF3 and onsite sub-basins A, B and C as shown on the "Historic Watershed and Routing Map" contained in the Appendix of this report.

Runoff from all of these sub-basins is conveyed via well defined irrigation and drainage ditches from the north to the south directly to the southwest corner of the site at 28 Road. From this point runoff is directed south along 28 Road within a deep drainage ditch to an existing drainage infrastructure within Spring Valley Ranch and subsequently underground west to an existing major drainageway west of 28 1/2 Road.

The propose land plan divides the onsite watershed into 16 sub-basins defined as A1 thru A3, B1 thru B5, C1 thru C3, D1 thru D4 and E1.

Runoff from these sub-basins will continue to be directed to the southwest corner of the site via proposed lot grading, roadways, swales and storm sewer as shown on the "Master Drainage Study Grading, Basin and Routing Plan".

IV. HEC1 METHODOLOGY

Precipitation Method:

2 Year and 100 Year Synthetic Storms were simulated based on rainfall (DDF) Depth-Duration-Frequency data for the Grand Junction Urbanized, Area (Table 403b, Reference 2).

Loss Rate Method:

The effects of interception and infiltration were analyzed using the SCS Curve Number Method.

Basin Model:

Flow from each of the sub-basins is analyzed as it converges with southwest corner of the site using the Muskingum-Cunge Routing Method.

Runoff Transformation Method:

Based on watershed geometry the SCS Dimensionless Unit Hydrograph method was used.

Element Application:

Each sub-basin was analyzed using 3 elements, overland flow, shallow concentrated flow and channel flow. Travel times (Tt) for each of these elements were calculated individually and combined to define the Time of Concentration (Tc) for each sub-basin. The Lag Time (TLAG) for each basin was calculated based on the relationship of TLAG = 0.6 * Tc as defined in Reference 3

V. HEC1 RESULTS

Historic Condition:

The resultant runoff hydrograph for the historic condition at southwest corner of the site (CP4) indicates a Peak Flow (Q2) of 8 CFS and a (Q100) of 87 CFS as shown on the computer printouts labeled Run #1 and Run #2.

Developed Condition:

The resultant runoff hydrograph for the developed condition at same location (CP11) indicates a Peak Flow (Q2) of 7 CFS and a (Q100) of 84 CFS as shown on the computer printouts labeled Run #3 thru Run #6.

Detention Requirements:

The proposed outflow hydrograph is obtained by routing runoff through a series of detention ponds defined as Res1 thru Res5 on the printouts. Res1 thru Res3 are located adjacent to 28 Road within sub-basins B1, B2 and B3 respectively and combine to form "System 1". Res4 is to be located in the southeast corner of the site within sub-basin D4. Res5 is located along the south boundary line of the site within sub-basin E1. Res4 and Res5 combine to form "System 2".

Detention Summary

I.D.	2 YEAR C.F.	*W.S. ELEV.	100 YEAR C.F.	**W.S. ELEV	
Res1	N/A	N/A	19,940	23.60	Spillway crest
Res2	N/A	N/A	12,704	21.00	Spillway crest
Res3	14,374 14,374	15.75	<u>28,889</u> 61,533	17.20	Outlet structure-dual stage Ex. Channel 28 Road
Syste	m 1 Totals		01,000		LA. Chamier 20 Road

^{*}Water surface elevation at maximum stage prior to 100 Year discharge.

^{**}Maximum water surface elevation including head above outlet element.

Detention Summary

1.D.	2 YEAR C.F.	*W.S. ELEV.	100 YEAR C.F.	**W.S. ELEV.	TYPE OF DISCHARGE ELEMENT
Res4	39,640	23.50	47,189	24.00	Outlet structure-dual stage
Res5	22,651	16.00	<u>34,365</u>	17.00	Outlet structure-dual stage
	62,291		81,554		Ex. Channel 28 Road
Syste	m 2 Totals				
	76,665 C.F.		143	3,087 C.F.	Ex. Channel 28 Road
	=1.76 Ac.Ft.		=3.	28 Ac.Ft.	
Cita T	atala.				

Site Totals

VI. DETENTION ELEMENT ALTERNATIVES:

As requested by the City of Grand Junction the potential use of a "Infiltrator" underground retention storage system has be evaluated as an alternative to above ground detention as follows:

Cost

The estimated cost for construction of Res1, Res2 and Res3 = \$30,000 including landscaping.

Total Required Storage Volume System 1 = 61,533 C.F.

Number of "Infiltrator" Units = 61,533 C.F. / 21.75 C.F./ Unit = 2,829 Units

Estimated Construction Cost = 2,829 Units X \$64.00 / Unit = \$181,056.00

The use of underground retention versus surface detention increase construction cost by a factor of 6.

Maintenance

Underground retention systems are prone to clogging due to sedimentation and other debris. Manufacture recommendations are that storm water delivered to the underground system be free of suspended solids. This would require the installation of sedimentation basins upstream of the infiltration system. Sedimentation basins would in effect emulate the above ground detention ponds resulting in redundancy. Further, the manufacture recommends that the system be inspected after each storm event to assure functional reliability.

Ground Water

The "Subsurface Soils Exploration" report for the site indicates the presence of ground water at depths of 5 to 6 feet. This would eliminate the effectiveness of a underground infiltration system below these depths. The result is a net increase in the infiltration bed area by 30% which equates to loss of buildable land and yet additional cost.

^{*}Water surface elevation at maximum stage prior to 100 Year discharge.

^{**}Maximum water surface elevation including head above outlet element.

In summary the use of underground storage as a viable option is not feasible and is not recommended for future consideration.

VII. IRRIGATION IMPACTS AND THE 2 YEAR STORM EVENT

Historic Conditions:

The site is bound along it's west and east lines by irrigation ditches originating at the Highline Canal. These ditches flow from the north to the south and are the source of irrigation water for lands surrounding the project as well as the project itself. The existing drainage ditch adjacent to the south boundary line of the site is the sole conveyance element for tailwater from these ditches. The ditch is currently owned and maintained by the Grand Valley Water Users Association (GVWUA). The association has agreed to grant to Grand View Subdivision the right to detain water within this ditch (aka Res5), with the stipulation that the conveyance of irrigation tailwater by the ditch continue perpetually.

The 2 Year Storm:

Analysis of the minor storm event presented herein is based on attenuation and release at historic levels excluding irrigation water. Maintaining the historic release rate during the 2 Year event from Res3, Res4 and Res5 will require the construction of a 3-inch by 3-inch square orifice blockout in each of the pond's dual stage release structures. This extremely small orifice creates the potential for continual maintenance problems due to clogging. The practical application of screening devices or filters capable of maintaining continuous flow through such a small conveyance element is in itself marginal.

For the reasons indicated above the proposed detention ponds, lowflow conveyance elements and release structures shall be designed to accommodate the aforementioned irrigation tailwater. The ultimate size of the lowflow discharge elements shall be based on the sum of 2 year historic release rates and calculated irrigation flow rates.

VIII. CONCLUSIONS

The calculated developed runoff hydrographs and required minimum detention volumes presented herein are to be used as the basis for design of individual phases within the total development. The proposed detention elements defined herein will attenuate developed flows to historic rates. The final size and configuration of individual detention and conveyance elements shall be verified by hydrologic and hydraulic design for each phase as development proceeds.

References

- 1. Interim Outline of Grading and Drainage Criteria, City of Grand Junction, July, 1992.
- 2. Mesa County Storm Drainage Criteria Manual, Final Draft, Mesa County, Colorado, March 1992.
- <u>3. HEC1 Flood Hydrograph Package</u>, Hydrologic Engineering Center, US Army Corps of Engineers, Davis, CA., September, 1990.
- <u>4. Soil Survey, Grand Junction Area, Colorado,</u> Series 1940, No. 19, U.S. Department of Agriculture, issued November, 1955.
- <u>5. Concrete Pipe Design Manual</u>, American Concrete Pipe Association, Fifth Printing (revised) June, 1980.
- 6. Flowmaster I, Version 3.16, Haestad Methods, Inc., Copyright 1990.
- 7. Subsurface Soils Exploration, Grand View Subdivision, Filing 1, Lincoln-DeVORE, Inc., Grand Junction, CO., June 29, 1994.

JOB# 96035.40 GRANG VIEW MASTER DRAINAGE STUDY (AddENdum)

APPENDIX "C" SCS CURVE NUMBERS

- 1. <u>General Discussion</u> The SCS-CN method and limitations have been discussed in Section VI-F-2a. In this Appendix, guidelines in the use of CN values are provided to assist in CN value selection. Also provided are SCS published SCS curve numbers.
- 2. <u>Antecedent Moisture/Runoff Conditions</u> In order to account for varying soil moisture conditions prior to a storm event, three "antecedent moisture conditions" (AMC) or "antecedent runoff conditions" (ARC) as they are now called, were developed.

ARCs are classified by the conditions shown in Table "C-1" below.


Class	Table "C-1" ification of Antecedent Runoff	Conditions
	Total 5-day Antece	edent Rainfall (in.)
ARC	Dormant Season	Growing Season
I	Less than 0.5	Less than 1.4
II	0.5-1.1	1.4-2.1
III	Over 1.1	Over 2.1

In arid and semi-arid regions, it is fair to say that most of the time soils fit the ARC category of I. Having more than 1.4 inches of rain in a 5-day period in arid and semi-arid areas would not be common, and statistically could be shown to be an extremely rare event. Therefore, one might justify using an ARC of I, particularly with the added SCS description that soils which are dry enough for satisfactory plowing or cultivation have an ARC of I.

Notwithstanding the above, use of an ARC of I is not recommended when selecting CN values for design storm analyses. This is because higher intensity storms tend to seal the soil, a phenomenon discussed in the next section.

3. <u>Impact of Storm Intensity</u> Published CN values are most applicable for storms of 2-year intensity or less. As expressed in Limitations, Chapter 2, SCS TR-55, modeling accuracy decreases with historical storms, or storms of greater intensity. Also stated is the fact that the CN equation does not account for rainfall intensity. This would indicate that, while CN values provided in SCS TR-55 are very useful for estimating peak flows for frequent storms or for volume and annual yield calculations, they may not be as applicable for typical deign storms used in peak runoff analysis. This is because water absorption rates for soils are limited and,

EXHIBIT 1.0



19-Jun-96

Project:

GRAND VIEW SUBDIVISION MASTER DRAINAGE STUDY (ADDENDUM)

Job No.:

Subject:

RESERVOIR #5 DEDUCTION OF POND VOLUME FOR ROADWAY

EXTENTION GRAND VIEW DRIVE

	ELEVATION FEET	CONTOUR AREA <u>SF.</u>	VOLUME CF.	STORAGE CF.
•	12.00	0.00		0.00
	13.00	419.00	209.50	209.50
·	14.00	495.00	457.00 594.00	666.50
	15.00	693.00	706.50	1,260.50
	16.00	720.00	882.00	1,967.00
WS. MAX	17.00	1,044.00	002.00	2.849.00
DEDUCTION OF PO	ND VOLUME D	HE TO ROADWAY C	ONST =	2 849 00

DEDUCTION OF POND VOLUME DUE TO ROADWAY CONST.= 2,849.

CREDIT FOR FULL STORM SEWER PIPE IN GRAND VIEW DRIVE

	DIAINCHES	LENGHT-FT	YOLUME -CF.	,
	12.00	31.00	24.35	
	18.00	31.00	54.78	
e esta e	24.00	199.00	625.19	
	SUM OF CREDIT =		704.32	g det
TOTAL DEDUCTI	ON IN CUBIC FEET=			<u>2.144.68</u>
ORIGINAL REQUIR	RED POND VOLUME		34,365.00	
CURRENT VOLUM	IE AVAILABLE=			32.220.32

EXHIBIT 3.0

DO NOT USE THIS TABLE ALONE. USE IN CONJUNCTION WITH FIGURES "C-2" AND "C-3"¹

Cover Description	Average Percent	Curve Numbers for Hydrologic Soil Group				
Cover Type and Hydrologic Condition	Impervious Area ²	A	В	С	D	
Fully developed urban areas (vegetation established)			HIN			
Open space (lawns, parks, golf courses, cemeteries, etc.)3:			KNS 60 PT	\frac{1}{2}	**	
Poor condition (grass cover < 50%)		68		₹ 86	89	
Fair condition (grass cover 50% to 75%)		49	 € 69	79	84	
Good condition (grass cover > 50%)		39	61	→ 74	80	
Impervious areas:						
Paved parking lots, roofs, driveways, etc. (excluding right-of-way)	* .	98	98	98	98	
Streets and roads:						
Paved; curbs and storm sewers (excluding right-of-way)		98	98	98	. 98	
Paved; open ditches (including right-of-way)		83	89	92	93	
Gravel (including right-of-way)	** ** .	76	85	89	91	
Dirt (including right-of-way)		72	82	87	89	
Western desert urban areas:	** *****					
Natural desert landscaping (pervious areas only)4		63	77	85	- 88	
Artificial desert landscaping (impervious weed barrier, desert shrub with 1- to 2-inch sand or gravel mulch and basin borders)		96	96	96	96	
Urban districts:				90		
Commercial and business	85 .	89	92	94	95	
Industrial	. 72	81	88	91	93	
Residential districts by average lot size:			$ \omega $	1.00		
1/8 acre or less (town houses)	65	77	C 85	90	92	
1/4 acre	38	61	75	83	87	
1/3 асте	30	57	72	81 .	86	
1/2 асте	25	54	70	80	85	
1 acre	20	51	68	79	·· 84	
2 acres	12	46	65	77	82	
Developing urban areas						
Newly graded areas (pervious areas only, no vegetation) ⁵		77	86	91	94	
Idle lands (CNs are determined using cover types similar to those in Table "C-2C"		68	79	86	89	

¹Average runoff condition (ARC = II), and $I_3 = 0.28$.



²The average percent impervious area shown was used to develop the composite CNs. Other assumptions are as follows: impervious areas are directly connected to the drainage system, impervious areas have a CN of 98, and pervious areas are considered equivalent to open space in good hydrologic condition. CNs for other combinations of conditions may be computed using Figure "C-3A" or "C-3B". See Figure "C-2" for more direction.

³CNs shown are equivalent to those of pasture. Composite CNs may be computed for other combinations of open space cover type. ⁴Composite CNs for natural desert landscaping should be computed using Figures "C-3A" or "C-3B" based on the impervious area percentage (CN = 98) and the pervious area CN. The pervious area CNs are assumed equivalent to desert shrub in poor

hydrologic condition.

5 Composite CNs to use for the design of temporary measures during grading and construction should be computed using Figures "C-3A" or "C-3B", based on the degree of development (impervious area percentage) and the CNs for the newly graded pervious

[Reproduced from TR-55 (SCS 1986)]


SCS CURVE NUMBERS:
Preliminary Values for Urban Areas

TABLE "C-2a"

EXHIBIT 4.0


MASTER DRAINAGE STUDY

USE THIS FIGURE ONLY IN ACCORDANCE WITH FIGURE "C-2"



A - COMPOSITE CN WITH CONNECTED IMPERVIOUS AREA.

AVERAGE LOT INCLUDING STREET = 10,870 \$ 6,370/10,870 = 59% IMERVIOUS AREA = 6,370 \$



B - COMPOSITE CN WITH UNCONNECTED IMPERVIOUS AREAS AND TOTAL IMPERVIOUS AREA LESS THAN 30%.

CN ADJUSTMENT DUE TO DIFFERENT CONDITIONS
OF IMPERVIOUS AREAS
(REPRODUCED FROM TR-55 (SCS 1986))

FIGURE C-3

Project:

GRAND VIEW SUBDIVISION MASTER DRAINAGE STUDY (ADDENDUM 1)

Job No.:

Subject:

COMPOSITE RUNOFF CURVE NUMBER (CN) CALCULATIONS

Condition: Developed

SUB-BASINS A1, A2 & A3

COVER DESCRIPTION

(cover type, treatment, and

hydrologic condition;

SOIL NAME AND HYDROLOGIC <u>GROUP</u>	percent impervious; unconnected / connected impervious area ratio)	Table C - 3a CURVE NUMBER (CN)	AREA % PERCENT	PRODUCT OF CN×AREA
(Rf) Ravola, very fine sandy sandy loam, HSG "B"	Residential lots and roadways, 41% pervious, 59% impervious.	83	33	2739
(Bc) Billings silty clay loam. HSG "C"	Residential lots and roadways, 41% pervious, 59% impervious.	88	67	5896
		TOTALS=	100	8635
	CN (WEIGHTED) = TOTAL PRODUCT / TOTA	L AREA = 8635/100	=	<u>86</u>

EXHIBIT 6.0

21-Jun-96

GRAND VIEW SUBDIVISION MASTER DRAINAGE STUDY (ADDENDUM 1)

Project: Job No.: Subject:

COMPOSITE RUNOFF CURVE NUMBER (CN) CALCULATIONS

DEVELOPED SUB-BASIN SUMMARY

SUB-BASIN I.D.	AREA AC.	AREA SM.	HYDRO. SOIL GROUP	SCS CN ARC II
OF1	11.22	0.0175	B x	79
OF2	12.00	0.0188	. B. ∴	79
OF3	3.09	0.0048	В	75
A1	18.62	0.0291	B&C	86
A2	3.27	0.0051	B&C	86
A3	3.38	0.0053	B & C	86
B1	0.31	0.0005	С	88
B2	0.29	0.0005	,,,C	88
B3	4.36	0.0068	С	88
B4	3.73	0.0058	С	88
B5	0.40	0.0006	С	88
C1	11.99	0.0187	С	88
C2	3.15	0.0049	C	88
C3	1.24	0.0019	С	88
D1	1.58	0.0025	C	88
D2	9.60	0.0150	С	88
D3	0.75	0.0012	С	88
D4	2.33	0.0036	С	88
E1	0.55	0.0009	С	83
			a.	
TOTALS	91.86	0.1435		

GRAND VIEW SUB.

FLOOD HYDROGRAPH PACKAGE (HEC-1)
SEPTEMBER 1990
VERSION 4.0

RUN DATE 06/20/1996 TIME 18:13:36

U.S. ARMY CORPS OF ENGINEERS
HYDROLOGIC ENGINEERING CENTER
609 SECOND STREET
DAVIS, CALIFORNIA 95616
(916) 756-1104

X	X	XXXXXXX	XX	XXX		X
X	X	X	X	X		XX
X	X	X	X			Χ
XXX	XXXX	XXXX	X		XXXXX	X
X	. X	χ	X	en i en	era e e e	X
X	X	X	X	X		X
X.	. Х	XXXXXXX	XX	XXX		XXX

THIS PROGRAM REPLACES ALL PREVIOUS VERSIONS OF HEC-1 KNOWN AS HEC1 (JAN 73), HEC1GS, HEC1DB, AND HEC1KW.

THE DEFINITIONS OF VARIABLES -RTIMP- AND -RTIOR- HAVE CHANGED FROM THOSE USED WITH THE 1973-STYLE INPUT STRUCTURE. THE DEFINITION OF -AMSKK- ON RM-CARD WAS CHANGED WITH REVISIONS DATED 28 SEP 81. THIS IS THE FORTRAN77 VERSION NEW OPTIONS: DAMBREAK OUTFLOW SUBMERGENCE, SINGLE EVENT DAMAGE CALCULATION, DSS:WRITE STAGE FREQUENCY, DSS:READ TIME SERIES AT DESIRED CALCULATION INTERVAL LOSS RATE:GREEN AND AMPT INFILTRATION KINEMATIC WAVE: NEW FINITE DIFFERENCE ALGORITHM

DEVELOPED 100 YEAR STORM
BASINS "OF1, OFZ, OF3, A ANDB
RUN #1

```
LINE
             ID......1.....2.....3.....4......5.....6......7.....8.....9.....10
                GRAND VIEW SUBDIVISION
  1
                  DEVELOPED CONDITION
             ID
                  100 YEAR 24 HOUR STORM (GRAND JUNCTION URBANIZED AREA D-D-F DATA)
             IT
                     5 20JUN96
                                 1200
                                         300
             10
                                    0
             KΚ
                   OF1
  7
             KM.
                 Basin runoff calculation for
  8
                                    0
             KO.
                 . 3
                            1
  9
             BA
                 0.0175
 10
             PH
                                 0.39
                                                                            1.69
                                                                                    2.01
                            0
                                        0.76
                                               1.34
                                                       1.40
                                                              1.44 1.56
 11
             LS
                           79
 12
             UD 0.304
             * ********
 13
                                                                  CP3
 14
             ΚM
                                                       CP1 to-
                 Muskingum-Cunge channel routing from
 15
             KO
                     3
                           1
                                  0
                                          1
                                               21
 16
             RD
                   760 0.0118 0.025
                                               TRAP
                                                                3
             * ********
 17
             KK
                    A2
 18
             ΚM
                 Basin runoff calculation for
 19
             ΚĐ
                     3
                            1
                                   0
                                         1
                                                 21
 20
                0.0051
             BΑ
 21
             PH
                            0
                                0.39
                                        0.76
                                               1.34
                                                      1.40
                                                                     1.56
                                                                            1.69
                                                                                   2.01
                                                              1.44
 22
            LS
                           86
             UD 0.293
             * ********
 24
            KK
 25
            ΚM
                 Combining two hydrographs at control point
                    0
                                                21
 26
            ΚĐ
                                         1
 27
                     2
            * ********
                   ST1
 29
            ΚM
                 Muskingum-Cunge channel routing from
                                                       CP3 to
                                                                  CP4
30
            KO
                        1
                                0
                                        1
31
            RD
32
            RC
                 0.020
                        0.020
                               0.020
                                        966 0.0084
33
                                        105
                                             106.5
                                                     112.5
                  100
                          104
                                 105
                                                            118.5
                                                                   120.5
34
                                             34.53
                 34.86
                        34.78
                              34.53
                                      34.40
                                                     34.65
                                                                   34.81
                                                            34.77
            * ********
35
            KK
36
            KM Basin runoff calculation for
                                              A3
37
            KΟ
                3
                           1 0
38
            BA 0.0053
39
            PH
                           0
                               0.39
                                       0.76
                                             1.34
                                                      1.40
                                                                                   2.01
            LS
                          86
40
41
            UD 0.316
                                                                                 R1-Z
            * ********
```

```
LINE
 42
 43
              Combining two hydrographs at control point
           KM
                                                     CP4
                       1 0 1 21
 44
                  3
 45
                  2
           * ********
 46
                 OF2
 47
           ΚM
              Basin runoff calculation for
 48
               3 1 0 1
 49
           BA 0.0187
 50
                        0
                            0.39
                                   0.76 1.34
                                                1.40
                                                      1,44
                                                                   1.69
                                                                         2.01
 51
           LS
                        79
 52
           UD 0.478
           * ********
 53
 54
                                                CP2 to
               Muskingum-Cunge channel routing from
 55
                3 1 0 1 21
                630 0.013 0.025
                                         TRAP
           * *******
57
                DF3
58
           KM Basin runoff calculation for
59
           ΚO
              3
                       1 0 1
60
           BA 0.0048
61
           PH
                        0
                            0.39
                                  0.76
                                         1.34
62
63
           UD 0.478
           * ********
64
65
           ΚM
             Combining two hydrographs at control point
                                                    CP4
               3 1 0 1 21
66
           ΚO
                  2
           * ********
68
69
              Combining two hydrographs at control point
70
          K0
                 3 1 0 1 21
          * *******
72
          KK
                A1
73
             Basin runoff calculation for
          ΚŪ
                 3
                       1
                            0
                                          21
75
            0.0291
          BA
76
          PH
                       0.
                            0.39
                                  0.76
                                        1.34
                                               1.40
                                                     1.44
                                                           1.56
                                                                  1.69
77
          LS
                       86
             0.510
```

```
LINE
 79
             KK
                 Combining two hydrographs at control point
                                                           CP4
 80
             ΚM
                                                21
 81
             KO
                     3
                           1
                                0
                                        1
 83
             ΚK
                   _P1
                                                      CP4 to
                                                                 CP5
 84
                 Muskingum-Cunge channel routing from
                    3
                           1
                                0
 85
                   525 0.0060 0.015
                                              CIRC
                                                      3.0
 86
             * ********
 87
             KK
                    Bi
 88
             KM
                 Basin runoff calculation for
                    3
                           1
                                  0
 89
                0.0005
 90
                                                                    1.56
                                                                          1.69
                                                                                 2.01
                                       0.76
                                              1.34
                                                     1.40
                                0.39
             PH
 91
 92
             LS
                           88
 93
                 0.037
             * ********
 94
             KK
                                                           CP5
                 Combining two hydrographs at control point
             ΚM
 95
                               0
                                        1
                     3
                           1
 96
             KΟ
                     2
 97
             HC
                  RES1
 98
                 Reservoir routing operation
 99
                                 0
                          2
 100
                   1
                                18.6
                    1
                         ELEV
 101
               0.0092 0.0613 0.1637 0.3107 0.4578
 102
                         20.6
                                21.6
                                       22.6
                                              23.6
103
             SE
                  19.6
                                 0.6
                                        0.5
                         0.79
104
                  18.6
                               . 2.7
                                        1.5
                  22.6
                         19.0
105
             * ********
             KK
106
                                                                 CP6
                 Muskingum-Cunge channel routing from
                                                      CP5 to
107
             KM
                                                21
                                  0
 108
             K0
                           1
                                                               3
                                              TRAP
 109
                   310 0.0052 0.025
             * ********
             KK
                    B2
110
                 Basin runoff calculation for
                                              B2
111
                                                21
112
                    3
                            1
                                   0
                0.0005
113
                                                                    1.56
                                                                          1.69
                                                                                  2.01
                                                     1.40
                                                            1.44
             PH
                            0
                                0.39
                                       0.76
                                              1.34
114
                           88
             LS
115
               0.037
 116
             * ********
```

```
ID......1,.....2......3......4......5......6......7.....8.......9.....10
LINE
117
             KK
                                                             CP6
                 Combining two hydrographs at control point
118
             KM
                                                 21
119
             KO.
                     3
                          1 0 1
                     2
 120
             * ********
                  RES2
121
             KK
             ΚM
                 Reservoir routing operation
122
                          2
                                0
 123
             KO
                     1
             RS
                     1
                         ELEV
                                 17.0
124
                 0.0150 0.0768
                                0.184 0.2916
             SV
125
                                        21.0
                          19.0
                                 20.0
126
                  18.0
                                 0.6
                                         0.5
127
             SL
                  17.0
                          0.79
                                         1.5
             SS
                  20.0
                          19.0
                                  2.7
128
             * ********
129
             KK
                   CH4
                                                       CP6 to
                  Muskingum-Cunge channel routing from
             KM
130
                         1 0 1 21
                   - 3
131
             ΚO
                                                                3
                                               TRAP
                   400 0.0079 0.025
132
             * ********
                  B345
133
             KK
             ΚM
                 Basin runoff calculation for
134
                                   0
135
             KΟ
                 3
                            1
136
             BA
                0.0132
                                                                     1.56
                                                                            1.69
                                                                                   2.01
             PH
                            0
                                 0.39
                                        0.76 1.34
                                                       1.40
137
                           88
             LS
138
             .UD
                 0.323
 139
             * ********
140
                 Combining two hydrographs at control point - CP7
141
             ΚM
                          1 0 1
             KO
                     3
142
                     2
             HC
143
             * ********
144
             KK
                  RES3
145
             KM
                 Reservoir routing operation
                                                 21
146
             K0
                     1
                         2
                                0 1
             RS
                     1
                         ELEV
                                12.83
147
                0.0817 0.2218 0.4160
                                     0.6632
148
                                 16.2
                                        17.2
             SE
                  14.2
                          15.2
149
                                         0.5
                                  0.6
             SL
                 13.83 0.0625
150
                                  2.7
                                         1.5
                 15.75
                          14.0
             * ********
152
             ZZ
```

FLOOD HYDROGRAPH PACKAGE (HEC-1) SEPTEMBER 1990 VERSION 4.0 RUN DATE 06/20/1996 TIME 18:13:36 *

U.S. ARMY CORPS OF ENGINEERS HYDROLOGIC ENGINEERING CENTER 609 SECOND STREET . DAVIS, CALIFORNIA 95616 (916) 756-1104

GRAND VIEW SUBDIVISION DEVELOPED CONDITION 100 YEAR 24 HOUR STORM (GRAND JUNCTION URBANIZED AREA D-D-F DATA)

5 IO **OUTPUT CONTROL VARIABLES**

> **IPRNT** 5 PRINT CONTROL

IPLOT 2 PLOT CONTROL

QSCAL O. HYDROGRAPH PLOT SCALE

IT HYDROGRAPH TIME DATA

> NMIN 5 MINUTES IN COMPUTATION INTERVAL

IDATE 20JUN96 STARTING DATE ITIME 1200 STARTING TIME

300 NUMBER OF HYDROGRAPH ORDINATES NQ

NDDATE 21JUN96 ENDING DATE NDTIME 1255 ENDING TIME **ICENT** 19 CENTURY MARK

COMPUTATION INTERVAL .08 HOURS TOTAL TIME BASE 24.92 HOURS

ENGLISH UNITS

SQUARE MILES DRAINAGE AREA

PRECIPITATION DEPTH INCHES LENGTH, ELEVATION FEET

FLOW CUBIC FEET PER SECOND

STORAGE VOLUME ACRE-FEET SURFACE AREA **ACRES**

TEMPERATURE DEGREES FAHRENHEIT

***** 6 KK

8 KO **OUTPUT CONTROL VARIABLES**

IPRNT 3 PRINT CONTROL

IPLOT 1 PLOT CONTROL QSCAL O. HYDROGRAPH PLOT SCALE

1 PUNCH COMPUTED HYDROGRAPH I PNCH IOUT

21 SAVE HYDROGRAPH ON THIS UNIT

121-6

```
SUBBASIN RUNOFF DATA
  9 BA
             SUBBASIN CHARACTERISTICS
                  TAREA
                         .02 SUBBASIN AREA
              PRECIPITATION DATA
 10 PH
                                 DEPTHS FOR O-PERCENT HYPOTHETICAL STORM
                                        ..... TP-40 .....
              .... HYDRO-35 .....
                                                                  TP-49 .....
             5-MIN 15-MIN 60-MIN 2-HR
                                         3-HR
                                                6-HR 12-HR 24-HR
                                                                  2-DAY 4-DAY
                                                                                7-DAY 10-DAY
                                         1.44 1.56 1.69 2.01 - .00
               .39 .76 1.34
                                1.40
                                                                        .00
                                                                               .00
                                         STORM AREA =
                                                        .02
 11 LS
             SCS LOSS RATE
                            .53 INITIAL ABSTRACTION
                  STRTL
                            79.00 CURVE NUMBER
                 CRVNBR
                  RTIMP
                              .00 PERCENT IMPERVIOUS AREA
12 UD
             SCS DIMENSIONLESS UNITGRAPH
                   TLAG
                              .30 LAG
                                               UNIT HYDROGRAPH
                                           20 END-OF-PERIOD ORDINATES
                                     24.
                                           23.
                                                   18. 12.
                                                                       8.
                    11.
                                                     0.
                                                              0.
             2.
                     2.
                                     1.
                                             1.
                                                                       0.
                                                         ***
                   HYDROGRAPH AT STATION
                                          OF1
  TOTAL RAINFALL = 2.01, TOTAL LOSS = 1.48, TOTAL EXCESS =
PEAK FLOW
                                    MAXIMUM AVERAGE FLOW
           TIME
 (CFS)
           (HR)
                                   24-HR 72-HR
                                                         24.92-HR
                             6-HR
                                                         0.
          12.42
                    (CFS)
                                      0.
                                                 ..0.
    6.
                             1.
                                       .528
                                                  .528
                                                            .528
                              .432
                  (INCHES)
                                      0.
                   (AC-FT)
                                                  0.
                             0.
                                     .02 SQ MI
                  CUMULATIVE AREA =
13 KK
               CH1 *
```

1 FIRST ORDINATE PUNCHED OR SAVED

300 LAST ORDINATE PUNCHED OR SAVED

.083 TIME INTERVAL IN HOURS

ISAV1

ISAV2

TIMINT

OUTPUT CONTROL VARIABLES
IPRNT 3

IPLOT

QSCAL

IPNCH IOUT 3 PRINT CONTROL 1 PLOT CONTROL

O. HYDROGRAPH PLOT SCALE

1 PUNCH COMPUTED HYDROGRAPH

21 SAVE HYDROGRAPH ON THIS UNIT

15 KO

R1-7

	٠.	ITMINI	.083	IIME IN	HERVAL IN	HUUKS					
								ALCO TO			
	- HYDRO	GRAPH ROUT	ING DATA								
16 RD	MUS	KINGUM-CUN	GE CHANNEL	ROUTING				: •			
		L	760.	CHANNEL	LENGTH						
		S		SLOPE							
		N	.025		ROUGHNESS	COEFFICI	ENT				
		CA	.00		UTING AREA						
		SHAPE		CHANNEL		T AMETER					
		WD Z	2.00	SIDE SL	WIDTH OR DI	IAMETER					
	ř		3.00	סומב פני	UFC						
						***			•		
	· · · ·		COMPU		INGUM-CUNGE ATION TIME		ERS	. •	٠.		
		ELEMENT	ALPHA	M	DT	DX	PEAK	TIME TO	VOLUME	MAXIMUM	ere i sa se
					/MTM3	/CT\	1000	PEAK	£ 7515	CELERITY	
			2 (** *		(MIN)	(FT)	(CFS)	(MIN)	(IN)	(FPS)	
		MAIN	2.60	1.34	2.00	253.33	6.20	750.00	.53	3.66	
			-							1	
				INTERPO	ATED TO SP	ECIFIED C	COMPUTATION	INTERVAL			
	-	•				•					
		MAIN	2.60	1.34	5.00		6.20	750.00	.53		
* 1 .			2100		2.77					n et et en en en en	
***		***	***		***		***		7.5		
		HYDROGE	RAPH AT STA	TION	CH1						
					2.75		A # 124 .				•
PEAK FLOW	TIME			MAXIM	ium average	FLOW				•	
(CFS)	(HR)		6-HR	24		72-HR	24.92-HR				
6.	12.50	(CFS)	1.	2.1.	0.	0.,	0.				
		(INCHES)	.432		528	.528	.528				
•		(AC-FT)	0.		0.	0.	0.				, see a
		CUMULATI	VE AREA =	.02	SQ MI		•	and the second second	e de la companya de la companya de la companya de la companya de la companya de la companya de la companya de		
								•			
	*										
	*** *** *	** *** ***	*** *** **		* *** *** 7		KK XXX XXX	*** *** **			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
******	XXV KKY X	रूत प्रकल्प सहस	*** *** **	* ***	* *** *** *		N	*** *** ***		*** *** ***	
		*									ė ·
	******	****									
	* "	*	* * *				• • • •				
17 KK		42 *	ergent in		- 151.5	÷	ray , refer at the			• •	
	*	*									
	*****	****	age agent								
10.70	Ortro	IT CONTRA!									
19 KO	UU 1 Pl	JT CONTROL		יים דאוד פרי	ITDNI						
		IPRNT IPLOT			ITROL IROJ						
		מקרטו זרנטו			INUL PH PLOT SCA	15				11	^

R1-8

1 FIRST ORDINATE PUNCHED OR SAVED
300 LAST ORDINATE PUNCHED OR SAVED

.083 TIME INTERVAL IN HOURS

ISAV1

ISAV2

TIMINT

QSCAL

IPNCH

IOUT

0. HYDROGRAPH PLOT SCALE

1 PUNCH COMPUTED HYDROGRAPH

21 SAVE HYDROGRAPH ON THIS UNIT

```
SUBBASIN RUNOFF DATA
  20 BA
                SUBBASIN CHARACTERISTICS
                                   .01 SUBBASIN AREA
                     TAREA
                PRECIPITATION DATA
  21 PH
                                      DEPTHS FOR O-PERCENT HYPOTHETICAL STORM
                                             ..... TP-40 .....
                5-MIN 15-MIN 60-MIN
                                       2-HR
                                               3-HR
                                                      6-HR
                                                            12-HR
                                                                    24-HR
                                                                            2-DAY 4-DAY
                                                                                           7-DAY 10-DAY
                         .76
                               1.34
                                       1.40
                                               1.44
                                                      1.56
                                                             1.69
                                                                     2.01
                                                                              .00
                                                                                    .00
                                                STORM AREA = .01
                SCS LOSS RATE
  22 LS
                     STRTL
                                   .33 INITIAL ABSTRACTION
                    CRVNBR
                                86.00 CURVE NUMBER
                     RTIMP
                                   .00 PERCENT IMPERVIOUS AREA
  23 UD
                SCS DIMENSIONLESS UNITGRAPH
                      TLAG
                                   .29 LAG
                                                      UNIT HYDROGRAPH
                                                 20 END-OF-PERIOD ORDINATES
                                                                        3.
               1.
                         3.
                                  6.
                                           7.
                                                   7.
                                                              5.
                                                                                 2.
                                                                                          1.
                                           0.
                                                     Û.
                                                              0.
                                                                        0.
                                                                                 0.
                                                                 ***
     ***
                       HYDROGRAPH AT STATION
                                                 A2
                                        1.15, TOTAL EXCESS =
   TOTAL RAINFALL =
                      2.01, TOTAL LOSS =
                                                                  .86
PEAK FLOW
                                         MAXIMUM AVERAGE FLOW
             TIME
                                            24-HR
  (CFS)
             (HR)
                                                   72-HR
                                                                24.92-HR
                                6-HR
                                                        0.
                                                                 0.
            12.42
                                             0.
      3.
                        (CFS)
                                  0.
                     (INCHES)
                                  .728
                                             .856
                                                        .856
                                                                     .856
                      (AC-FT)
                                              0.
                                                       ··· 0.
                      CUMULATIVE AREA =
                                           .01 SQ MI
*** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** ***
 24 KK
          **********
```

1 FIRST ORDINATE PUNCHED OR SAVED

300 LAST ORDINATE PUNCHED OR SAVED

.083 TIME INTERVAL IN HOURS

ISAV1 ISAV2

TIMINT

26 KO

OUTPUT CONTROL VARIABLES
IPRNT 3

IPLOT

QSCAL

IPNCH

IOUT

3 PRINT CONTROL

1 PLOT CONTROL

O. HYDROGRAPH PLOT SCALE

1 PUNCH COMPUTED HYDROGRAPH

21 SAVE HYDROGRAPH ON THIS UNIT

R1-9

27 HC HYDROGRAPH COMBINATION ICOMP 2 NUMBER OF HYDROGRAPHS TO COMBINE HYDROGRAPH AT STATION PEAK FLOW TIME MAXIMUM AVERAGE FLOW (HR) (CFS) 6-HR 24-HR 72-HR 24.92-HR 9. 12.42 (CFS) 0. 0. 0. 1. (INCHES) .498 .602 .602 .602 (AC-FT) 1. 1. 1. CUMULATIVE AREA = .02 SQ MI ******* 28 KK ST1 **OUTPUT CONTROL VARIABLES** 30 KD **IPRNT** 3 PRINT CONTROL **IPLOT** 1 PLOT CONTROL QSCAL O. HYDROGRAPH PLOT SCALE IPNCH 1 PUNCH COMPUTED HYDROGRAPH IOUT 21 SAVE HYDROGRAPH ON THIS UNIT ISAV1 1 FIRST ORDINATE PUNCHED OR SAVED ISAV2 300 LAST ORDINATE PUNCHED OR SAVED TIMINT .083 TIME INTERVAL IN HOURS HYDROGRAPH ROUTING DATA 31 RD MUSKINGUM-CUNGE CHANNEL ROUTING 32 RC NORMAL DEPTH CHANNEL ANL .020 LEFT OVERBANK N-VALUE ANCH .020 MAIN CHANNEL N-VALUE anr .020 RIGHT OVERBANK N-VALUE RLNTH 966. REACH LENGTH SEL .0084 ENERGY SLOPE **ELMAX** .O MAX. ELEV. FOR STORAGE/OUTFLOW CALCULATION CROSS-SECTION DATA --- LEFT OVERBANK --- + ----- MAIN CHANNEL ---- + --- RIGHT OVERBANK ---34 RY **ELEVATION** 34.86 34.78 34.53 34.40 34.53 34.65 34.77 34.81 33 RX DISTANCE 100.00 104.00 105.00 105.00 106.50 112.50 118.50 120.50 ***

FIRST ORDINATE PUNCHED OR SAVED

300 LAST ORDINATE PUNCHED OR SAVED

.083 TIME INTERVAL IN HOURS

ISAV1

ISAV2

TIMINT

STORAGE	.00	.00	.00	.00	.00	.00	.00	.00	.01	.01
OUTFLOW	.00	.00	.01	.02	.05	.08	.12	.19	.32	.50
ELEVATION	34.40	34.42	34.45	34.47	34.50	34.52	34.55	34.57	34.59	34.62
STORAGE	.01	.02	.02	.03	.04	.04	.05	.06	.07	.08
OUTFLOW	.76	1.16	1.68	2.30	3.04	3.90	4.86	5.95	7.32	8.87
ELEVATION	34.64	34.67	34.69	34.71	34.74	34.76	34.79	34.81	34.84	34.86

****** WARNING ****** THE FLOW RATE THAT YOU ARE ROUTING IS GREATER THAN WHAT CAN BE CALCULATE FROM THE 8 POINT CROSS SECTION YOU ENTERED ON RC, RX, AND RY RECORDS. THE PROGRAM HAD TO EXTRAPOLATE BEYOND THE MAXIMUM STORAGE-DISCHARGE VALUE CALCULATED. INCREASE ELMAX ON THE RC RECORD OR MAKE THE CROSS SECTION LARGER.

COMPUTED MUSKINGUM-CUNGE PARAMETERS

		COMPL	JTATION TIME	STEP		and the second second		
ELEMENT	ALPHA	М	DT	DX	PEAK	TIME TO PEAK	VOLUME	MAXIMUM CELERITY
			(MIN)	(FT)	(CFS)	(MIN)	(IN)	(FPS)
MAIN			3.25	241.50	9.11	754.00	.60	2.67

INTERPOLATED TO SPECIFIED COMPUTATION INTERVAL

MAIN 5.00 9.02 750.00 .60

CONTINUITY SUMMARY (AC-FT) - INFLOW= .7259E+00 EXCESS= .0000E+00 DUTFLOW= .7260E+00 BASIN STORAGE= .7201E-03 PERCENT ERROR= -.1

HYDROGRAPH AT STATION ST

PEAK FLOW MAXIMUM AVERAGE FLOW TIME 24-HR 72-HR (CFS) (HR) 6-HR 12.50 .0. 0. (CFS) 1. 0. ..602 (INCHES) .497 .602 .602 (AC-FT)

CUMULATIVE AREA = .02 SQ MI .--

*** ***

37 KO OUTPUT CONTROL VARIABLES

IPRNT 3 PRINT CONTROL
IPLOT 1 PLOT CONTROL

QSCAL 0. HYDROGRAPH PLOT SCALE
IPNCH 1 PUNCH COMPUTED HYDROGRAPH
IOUT 21 SAVE HYDROGRAPH ON THIS UNIT
ISAV1 1 FIRST ORDINATE PUNCHED OR SAVED

ISAV2 300 LAST ORDINATE PUNCHED OR SAVED

R1-11

```
SUBBASIN RUNOFF DATA
              SUBBASIN CHARACTERISTICS
                  TAREA
                        .01 SUBBASIN AREA
              PRECIPITATION DATA
 39 PH
                                DEPTHS: FOR O-PERCENT HYPOTHETICAL STORM
                                ..... TP-40
                                                                 ..... TP-49
              .... HYDRO-35 .....
             5-MIN 15-MIN 60-MIN 2-HR 3-HR
                                               6-HR 12-HR 24-HR
                                                                  2-DAY 4-DAY 7-DAY 10-DAY
                         1.34 1.40
                                               1.56 1.69
                                                            2.01
                                                                    .00
                     .76
                                         1.44
                                         STORM AREA = .01
 40 LS
             SCS LOSS RATE
                 STRTL
                             .33 INITIAL ABSTRACTION
                 CRVNBR
                           86.00 CURVE NUMBER
                            .00 PERCENT IMPERVIOUS AREA
                  RTIMP
 41 UD
             SCS DIMENSIONLESS UNITGRAPH
                   TLAG
                        .32 LAG
                                               UNIT HYDROGRAPH
                                           21 END-OF-PERIOD ORDINATES
                     3.
                                             7.
                                                              4.
                                                                      3.
                                                                               2.
             1.
                             0.
                    i.
                                      0.
                                              ٥.
                                                      0.
                                                              0.
                                                                       0.
                                                                               0.
             1.
             0.
                   HYDROGRAPH AT STATION
  TOTAL RAINFALL =
                  2.01, TOTAL LOSS = 1.15, TOTAL EXCESS =
                                                         .86
PEAK FLOW
         TIME
                                    MAXIMUM AVERAGE FLOW
 (CFS)
          (HR)
                             6-HR
                                      24-HR 72-HR
                                                        24.92-HR
                             0.
                                      0.
                                                0.
   3.
          12.42
                    (CFS)
                                                        0.
                             .728
                                      .856
                                                .856
                  (INCHES)
                                                           .856
                  (AC-FT)
                                       0.
                             0.
                                    .01 SQ MI
                  CUMULATIVE AREA =
        **********
               A3 *
42 KK
        *********
44 KO
            OUTPUT CONTROL VARIABLES
                 IPRNT
                           3 PRINT CONTROL
                 IPLOT
                             1 PLOT CONTROL
                 QSCAL
                             O. HYDROGRAPH PLOT SCALE
                                                                                      R1-12
                 IPNCH
                             1 PUNCH COMPUTED HYDROGRAPH
```

21 SAVE HYDROGRAPH ON THIS UNIT

1 FIRST ORDINATE PUNCHED OR SAVED

TIMINT

TUUT

ISAV1

.083 TIME INTERVAL IN HOURS

45 HC HYDROGRAPH COMBINATION ICOMP 2 NUMBER OF HYDROGRAPHS TO COMBINE *** *** *** HYDROGRAPH AT STATION MAXIMUM AVERAGE FLOW PEAK FLOW TIME (CFS) (HR) 6-HR 24-HR 72-HR 24.92-HR 12. 12.50 (CFS) .2. 0. 0. 0. (INCHES) .540 .650 .650 .650 (AC-FT) 1. 1. 1. 1. .03 SQ MI CUMULATIVE AREA = ***** 46 KK ***** 48 KO **OUTPUT CONTROL VARIABLES IPRNT** 3 PRINT CONTROL IPLOT 1 PLOT CONTROL QSCAL O. HYDROGRAPH PLOT SCALE IPNCH 1 PUNCH COMPUTED HYDROGRAPH IOUT 21 SAVE HYDROGRAPH ON THIS UNIT ISAV1 1 FIRST ORDINATE PUNCHED OR SAVED ISAV2 300 LAST ORDINATE PUNCHED OR SAVED TIMINT .083 TIME INTERVAL IN HOURS SUBBASIN RUNOFF DATA 49 BA SUBBASIN CHARACTERISTICS TAREA .02 SUBBASIN AREA PRECIPITATION DATA 50 PH DEPTHS FOR O-PERCENT HYPOTHETICAL STORM HYDRO-35 TP-40 3-HR 4-DAY 7-DAY 10-DAY 5-MIN 15-MIN 60-MIN 2-HR 6-HR 12-HR 24-HR 2-DAY .39 .76 1.34 1.40 1.44 1.56 1.69 2.01 .00 .00 .00 STORM AREA = .02 51 LS SCS LOSS RATE .53 INITIAL ABSTRACTION STRTL CRVNBR 79.00 CURVE NUMBER .00 PERCENT IMPERVIOUS AREA SCS DIMENSIONLESS UNITGRAPH 52 UD R1-13

300 LAST ORDINATE PUNCHED OR SAVED

.083 TIME INTERVAL IN HOURS

ISAV2

TIMINT

TLAG

.48 LAG

UNIT HYDROGRAPH 31 END-OF-PERIOD ORDINATES 17. 17. 13. 4. 8. 13. 16. 15. 3. 3. 2. 2. 1. 1. 6. 4. 0. 0. 0. 0. . 0. 0. 0. ***

10.

1.

0.

HYDROGRAPH AT STATION

0F2

TOTAL RAINFALL = 2.01, TOTAL LOSS = 1.48, TOTAL EXCESS = .53

PEAK FLOW	TIME		MAXIMUM AVERAGE FLOW							
(CFS)	(HR)		6-HR	24-HR	72-HR	24.92-HR				
5.	12.67	(CFS)	1.	0.	0.	0.				
		(INCHES)	.431	.528	.528	.528				
		(AC-FT)	0.	1.	1.	1.				

CUMULATIVE AREA = .02 SQ MI

*** ***

7.

1.

0.

53 KK * CH2 *

55 KO OUTPUT CONTROL VARIABLES

IPRNT 3 PRINT CONTROL
IPLOT 1 PLOT CONTROL

QSCAL O. HYDROGRAPH PLOT SCALE

I PNCH 1 PUNCH COMPUTED HYDROGRAPH

IOUT 21 SAVE HYDROGRAPH ON THIS UNIT

ISAV1 1 FIRST ORDINATE PUNCHED OR SAVED

ISAV2 300 LAST ORDINATE PUNCHED OR SAVED TIMINT .083 TIME INTERVAL IN HOURS

HYDROGRAPH ROUTING DATA

56 RD MUSKINGUM-CUNGE CHANNEL ROUTING

L 630. CHANNEL LENGTH

S .0130 SLOPE

N .025 CHANNEL ROUGHNESS COEFFICIENT

CA .00 CONTRIBUTING AREA

SHAPE TRAP CHANNEL SHAPE

WD 2.00 BOTTOM WIDTH OR DIAMETER

Z 3.00 SIDE SLOPE

......

COMPUTED MUSKINGUM-CUNGE PARAMETERS

COMPUTATION TIME STEP

		COLLEGE	ULION LINE	UILI				
ELEMENT	ALPHA	M	DT	DX	PEAK	TIME TO	VOLUME	MAXIMUM
• •			(MIN)	(FT)	(CFS)	PEAK (MIN)	(IN)	CELERITY (FPS)
MAIN	2,72	1.34	2.75	315.00	5.09	761.75	-53	3.60

R1-14

MAIN 2.72 1.34 5.00 5.08 760.00 .53

CONTINUITY SUMMARY (AC-FT) - INFLOW= .5263E+00 EXCESS= .0000E+00 DUTFLOW= .5260E+00 BASIN STORAGE= .5692E-03 PERCENT ERROR= -.1

*** *** *** ***

HYDROGRAPH AT STATION CH

PEAK FLOW TIME MAXIMUM AVERAGE FLOW 24-HR 72-HR (CFS) (HR) 6-HR 24.92-HR 12.67 (CFS) 1. 0. 0. O. (INCHES) .430 .527 .527 .527 1. (AC-FT) 0.

CUMULATIVE AREA = .02 SQ MI

57 KK * 0F3 1

59 KO OUTPUT CONTROL VARIABLES

IPRNT 3 PRINT CONTROL

IPLOT 1 PLOT CONTROL

QSCAL 0. HYDROGRAPH PLOT SCALE

IPNCH 1 PUNCH COMPUTED HYDROGRAPH

IOUT 21 SAVE HYDROGRAPH ON THIS UNIT

ISAVI 1 FIRST ORDINATE PUNCHED OR SAVED

ISAV2 300 LAST ORDINATE PUNCHED OR SAVED

TIMINT .083 TIME INTERVAL IN HOURS

SUBBASIN RUNOFF DATA

60 BA SUBBASIN CHARACTERISTICS

TAREA .00 SUBBASIN AREA

PRECIPITATION DATA

61 PH DEPTHS FOR O-PERCENT HYPOTHETICAL STORM

..... TP-40 HYDRO-35 6-HR 12-HR 24-HR 7-DAY 10-DAY 5-MIN 15-MIN 60-MIN 2-HR 3-HR 2-DAY 4-DAY 1.34 1.40 1,44 1.56 1.69 2.01 .00 .00

STORM AREA = .00

62 LS SCS LOSS RATE

63 UD

STRTL67 INITIAL ABSTRACTION

CRVNBR 75.00 CURVE NUMBER

RTIMP .OO PERCENT IMPERVIOUS ÁREA

SCS DIMENSIONLESS UNITGRAPH

RI-15

A6 .48 LI

UNIT HYDROGRAPH 31 END-OF-PERIOD ORDINATES 4. 3. 0. 1. 2. 3. 4. 4. 4. 2. 1. 0. 0. . 0. 1. 1. 1. 1. Ō. 0. 0. 0. 0. 0. 0. 0. 0. 0. *** *** *** HYDROGRAPH AT STATION TOTAL RAINFALL = 2.01, TOTAL LOSS = 1.62, TOTAL EXCESS = PEAK FLOW TIME MAXIMUM AVERAGE FLOW (CFS) 24-HR 72-HR 24.92-HR (HR) 6-HR 0. (CFS) 0. . 0. . 0. .385 (INCHES) .385 .385 .305 (AC-FT) 0. 0. 0. 0. CUMULATIVE AREA = .00 SQ MI ********** 0F3 64 KK 66 KO **OUTPUT CONTROL VARIABLES IPRNT** 3 PRINT CONTROL

FROM SOUTPUT CONTROL VARIABLES

IPRNT 3 PRINT CONTROL

IPLOT 1 PLOT CONTROL

QSCAL 0. HYDROGRAPH PLOT SCALE

IPNCH 1 PUNCH COMPUTED HYDROGRAPH

IOUT 21 SAVE HYDROGRAPH ON THIS UNIT

ISAV1 1 FIRST ORDINATE PUNCHED OR SAVED

ISAV2 300 LAST ORDINATE PUNCHED OR SAVED

TIMINT .083 TIME INTERVAL IN HOURS

67 HC HYDROGRAPH COMBINATION

ICOMP 2 NUMBER OF HYDROGRAPHS TO COMBINE

HYDROGRAPH AT STATION OF3

PEAK FLOW TIME MAXIMUM AVERAGE FLOW (CFS) (HR) 6-HR 24-HR 72-HR 24.92-HR 6. 12.67 (CFS) 1. O. 0. 0. .498 .498 .498 (INCHES) .405 (AC-FT) 1. 1. i. 1.

CUMULATIVE AREA = .02 SQ MI

R1-16

2.

0.

٥.

```
**********
  68 KK
  70 KD
                OUTPUT CONTROL VARIABLES
                      IPRNT
                                     3 PRINT CONTROL
                      IPLOT
                                     1 PLOT CONTROL
                      QSCAL
                                     O. HYDROGRAPH PLOT SCALE
                      IPNCH
                                     1 PUNCH COMPUTED HYDROGRAPH
                       IOUT
                                     21 SAVE HYDROGRAPH ON THIS UNIT
                      ISAV1
                                     1 FIRST ORDINATE PUNCHED OR SAVED
                      ISAV2
                                   300 LAST ORDINATE PUNCHED OR SAVED
                     TIMINT
                                   .083 TIME INTERVAL IN HOURS
  71 HC
                HYDROGRAPH COMBINATION
                      ICOMP
                                     2 NUMBER OF HYDROGRAPHS TO COMBINE
     ***
                                                                   ***
                        HYDROGRAPH AT STATION
                                           MAXIMUM AVERAGE FLOW
 PEAK FLOW
              TIME
              (HR)
   (CFS)
                                                         72-HR
                                   6-HR
                                              24-HR
                                                                   24.92-HR
             12.58
                         (CFS)
     17.
                                     3.
                                               1.
                                                          1.
                                                                      1.
                      (INCHÉS)
                                                                       .581
                                    .478
                                               .581
                                                          .581
                       (AC-FT)
                                                 2.
                                                            2.
                                                                        2.
                      CUMULATIVE AREA =
                                            .05 SQ MI
*** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** ***
           ********
 72 KK
                   A1
           ******
 74 KO
               OUTPUT CONTROL VARIABLES
                                   3 PRINT CONTROL
                     IPRNT
                     IPLOT
                                     1 PLOT CONTROL
                     OSCAL
                                   O. HYDROGRAPH PLOT SCALE
```

SUBBASIN RUNOFF DATA

IPNCH

IOUT

ISAV1

ISAV2

TIMINT

SUBBASIN CHARACTERISTICS

TAREA

.03 SUBBASIN AREA

1 PUNCH COMPUTED HYDROGRAPH

.083 TIME INTERVAL IN HOURS

21 SAVE HYDROGRAPH ON THIS UNIT

1 FIRST ORDINATE PUNCHED OR SAVED

300 LAST ORDINATE PUNCHED OR SAVED

R1-17

	PREL	IFITALIUN :	VATA												
76 PH			n	FPTHS FI	ne o-P	FRCFNT H	IYPOTHET	ICAL STO	RM						
70 111,		. HYDRO-35								TP	-49				
		N 15-MIN		2-HR	3-HR	6-HR	12-HR	24-HR	2-DAY	4-DAY		10-DAY			
	.3		1.34	1.40	1.44	1.56	1.69	2.01	.00	.00	.00	.00			
		1 .70	I s GT	1,70	1.477	1.00	1.0,	2.01	•••	•00	•••	•••			
					стлом	AREA =	.03				-				
				-	D I DIVIT	HILLH -	100								
77 LS	ere i	LOSS RATE													
// L3	J(J) 1	STRTL	.33	TMITTIAL	ABSTRA	אחדד									
		CRVNBR	86.00	CURVE N		DI TUIN									
		RTIMP			IMPERV	TOLIC ARE	Δ								
		WITTH.	.00	LINGER	I III LIVY.	TODO NINE	п								
78 UD	see i) IMENSIONLE	SS INITER	ΔΡΗ											
70 00	200 1	TLAG	.51						•	•					
		TENO "		LNO											
						*.	***								
														*	
						IINTT H	YDROGRAI	°H							
umb u		N. AF			33 E			RDINATES							
	2.	5.	10.	17.		22.	25.	25.	24		21.	17.			
	13.	10.	8.	6.		5.		3.	2		2.	1.			
	1.	1.	1.	1.		0.		0.	0		0.	0.			
	0.	0.	0.	••		•••			_	•		• • •			
	**	w*	**												
***		***	***		***	, ,	*1	.	-						
-															
-		HYDROGR	APH AT ST	ATION	A1										
					**				. "						
TOTAL R	RAINFALL =	2.01, TO	TAL LOSS :	= 1.1	5, TOTAL	EXCESS	= ,	86						eggen .	
-	** •														
PEAK FLOW	TIME				MUM AVER										
(CFS)	(HR)		6-HR	2	4-HR	72-HF		.92-HR							
13.	12.58	(CFS)	2.		·1.	1.		1.							
		(INCHES)	.726		.855	.85		.855							
		(AC-FT)	1.		1.	1.	•	1.							
		CUMULATI	ve area =	.03	SQ MI										
				. •											
						2									
*** *** ***	*** *** **	* *** ***	*** *** **	** *** *	** *** *	** *** *	** ***	*** *** :	*** ***	*** ***	*** ***	*** *** 1	** **	* *** ***	*-
*** ***															
	******	***	0												
	* 1	*													
79 KK	* A	į *	4 1 to 1												
	*	** ** **							1		este .				
	******	***													
												-			
81 KO	OUTPU'	T CONTROL \	/ARIABLES												
		IPRNT	3	PRINT CO	NTROL										
		IPLOT	1	PLOT COM	ITROL										
		QSCAL	0.	HYDROGRA	APH PLOT	SCALE									
2.43		IPNCH	1	PUNCH CO	IMPUTED I	HYDROGRA	PH								
		IOUT	21											•	
* ·		ISAV1			RDINATE I			D							
		ISAV2			INATE PL		r saved			*				•	
*	1	TIMINT	.083	TIME INT	ERVAL IN	HOURS						O		10	
												1 /		1 4	

R1-18

```
HYDROGRAPH AT STATION
 PEAK FLOW
              TIME
                                           MAXIMUM AVERAGE FLOW
   (CFS)
              (HR)
                                                          72-HR
                                   6-HR
                                              24-HR
                                                                   24.92-HR
     31.
             12.58
                         (CFS)
                                    5.
                                                1.
                                                           1.
                                                                        1.
                      (INCHES)
                                             .680
                                    .567
                                                           .680
                       (AC-FT)
                                     2.
                                                 3.
                                                                         3.
                       CUMULATIVE AREA =
                                            .08 SQ MI
*** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** ***
 83 KK
                   P1
 85 KO
               OUTPUT CONTROL VARIABLES
                     IPRNT
                               3 PRINT CONTROL
                                1 PLOT CONTROL
                     IPLOT
                     OSCAL
                                    O. HYDROGRAPH PLOT SCALE
                     IPNCH
                                    1 PUNCH COMPUTED HYDROGRAPH
                                   21 SAVE HYDROGRAPH ON THIS UNIT
                     IOUT
                     ISAV1
                                    1 FIRST ORDINATE PUNCHED OR SAVED
                     ISAV2
                                  300 LAST ORDINATE PUNCHED OR SAVED
                    TIMINT
                                  .083 TIME INTERVAL IN HOURS
             HYDROGRAPH ROUTING DATA
 86 RD
               MUSKINGUM-CUNGE CHANNEL ROUTING
                                 525. CHANNEL LENGTH
                        S
                                .0060 SLOPE
                                 .015 CHANNEL ROUGHNESS COEFFICIENT
                       CA
                                  .00 CONTRIBUTING AREA
                     SHAPE
                                 CIRC CHANNEL SHAPE
                       WD
                                 3.00 BOTTOM WIDTH OR DIAMETER
                        7
                                  .00 SIDE SLOPE
                                 COMPUTED MUSKINGUM-CUNGE PARAMETERS
                                        COMPUTATION TIME STEP
                                                                            TIME TO
                                                                                       VOLUME
                 ELEMENT
                            ALPHA
                                                 DT
                                                           DX
                                                                    PEAK
                                                                                                 MAXIMUM
                                                                             PEAK
                                                                                                 CELERITY
                                                (MIN)
                                                          (FT)
                                                                   (CFS)
                                                                             (MIN)
                                                                                        (IN)
                                                                                                  (FPS)
                   MAIN
                              4,99
                                                          262.50
                                                                     30.36
                                                                             756.58
                                                                                                   7.79
                                        1.25
                                                   1.12
                                                                                          .68
                                       INTERPOLATED TO SPECIFIED COMPUTATION INTERVAL
                   MAIN
                              4.99
                                        1.25
                                                  5.00
                                                                     30.28
                                                                             755.00
```

***		***	***	**	X	***
		HYDROGRAF	H AT STATIO	ON P1		
PEAK FLOW	TIME			MAXIMUM AVE	RAGE FLOW	
(CFS)	(HR)		6-HR	24-HR	72-HR	24.92-HR
30.	12.58	(CFS)	5.	1.	1.	1.
		(INCHES)	.567	.680	.680	.680
**		(AC-FT)	2.	3.	3.	3.

CUMULATIVE AREA = .08 SQ MI

-87 KK

89 KO OUTPUT CONTROL VARIABLES

> IPRNT 3 PRINT CONTROL **IPLOT** 1 PLOT CONTROL QSCAL O. HYDROGRAPH PLOT SCALE 1 PUNCH COMPUTED HYDROGRAPH IPNCH IOUT 21 SAVE HYDROGRAPH ON THIS UNIT ISAV1 1 FIRST ORDINATE PUNCHED OR SAVED ISAV2 300 LAST ORDINATE PUNCHED OR SAVED TIMINT .083 TIME INTERVAL IN HOURS

SUBBASIN RUNOFF DATA

SUBBASIN CHARACTERISTICS 90 BA

.00 SUBBASIN AREA

PRECIPITATION DATA

91 PH DEPTHS FOR O-PERCENT HYPOTHETICAL STORM

> 5-MIN 15-MIN 60-MIN 2-HR 3-HR 6-HR 12-HR 24-HR 2-DAY 4-DAY 7-DAY 10-DAY .39 1.40 1.44 1.56 1.69 2.01

> > .00 STORM AREA =

92 LS SCS LOSS RATE

> STRTL .27 INITIAL ABSTRACTION

CRVNBR 88.00 CURVE NUMBER

.00 PERCENT IMPERVIOUS AREA

SCS DIMENSIONLESS UNITGRAPH 93 UD

TLAG .04 LAG

UNIT HYDROGRAPH 5 END-OF-PERIOD ORDINATES

3. 0. R1 - 20

*** *** *** ***

B1

HYDROGRAPH AT STATION

TOTAL RAINFALL = 2.01, TOTAL LOSS = 1.04, TOTAL EXCESS = .97

PEAK FLOW TIME MAXIMUM AVERAGE FLOW (CFS) (HR) 24-HR 72-HR 24.92-HR 6-HR 12.08 0. · 1. 0. 0. 0. (CFS) .973 (INCHES) .836 .973 .973 (AC-FT) 0.

CUMULATIVE AREA = .00 SQ MI

*** ***

94 KK * B1 *

96 KO OUTPUT CONTROL VARIABLES

IPRNT 3 PRINT CONTROL
IPLOT 1 PLOT CONTROL

QSCAL O. HYDROGRAPH PLOT SCALE

I PNCH 1 PUNCH COMPUTED HYDROGRAPH
IOUT 21 SAVE HYDROGRAPH ON THIS UNIT

ISAV1 1 FIRST ORDINATE PUNCHED OR SAVED
ISAV2 300 LAST ORDINATE PUNCHED OR SAVED

TIMINT .083 TIME INTERVAL IN HOURS

97 HC HYDROGRAPH COMBINATION

ICOMP 2 NUMBER OF HYDROGRAPHS TO COMBINE

.

*** *** *** ***

HYDROGRAPH AT STATION BI

PEAK FLOW MAXIMUM AVERAGE FLOW TIME (CFS) 24-HR 72-HR (HR) 6-HR 24.92-HR 30. 12.58 (CFS) 5. 1. 1. 1. (INCHES) .569 .682 .682 .682 (AC-FT) 2. 3. 3. 3.

CUMULATIVE AREA = .08 SQ MI

*** ***

98 KK * RES1

R1-21

LOI COMILION	AHVIHDEED	
IPRNT	1	PRINT CONTROL
IPLOT	2	PLOT CONTROL
QSCAL	0.	HYDROGRAPH PLOT SCALE
IPNCH	1.	PUNCH COMPUTED HYDROGRAPH
IOUT	21	SAVE HYDROGRAPH ON THIS UNIT
ISAV1	1	FIRST ORDINATE PUNCHED OR SAVED
ISAV2	300	LAST ORDINATE PUNCHED OR SAVED
TIMINT	.083	TIME INTERVAL IN HOURS

HYDROGRAPH ROUTING DATA

OUTFLOW

100 KD

101 RS	STORAGE ROUTIN NSTPS ITYP RSVRIC X	1 ELEV 18.60	TYPE OF I	SUBREACH INITIAL CON CONDITION AND D COE	NDITION	
102 SV	STORAGE	.0	.1	.2	.3	.5
103 SE	ELEVATION	19.60	20.60	21.60	22.60	23.60
104 SL	LOW-LEVEL OUTL ELEVL CAREA COQL EXPL	18.60 .79	CROSS-SEC	CTIONAL ARE		
105 SS	SPILLWAY CREL SPWID COQW EXPW	22.60 19.00 2.70 1.50	SPILLWAY WEIR COEF	FICIENT	ATION	

4.03

4.28

4.56

COMPUTED OUTFLOW-ELEVATION DATA

4.89

5.26

5.70

6.22

ELEVATION	19.60	19.72	19.87	20.04	20.25	20.52	20.85	21.28	21.84	22.60
OUTFLOW	7.69	8.12	9.20	11.23	14.50	19.30	25.94	34.70	45.89	59.80
ELEVATION	22.61	22.64	22.70	22.77	22.86	22.97	23.10	23.24	23.41	23.60
·			COMPUTE	D STORAGE-(OUTFLOW-EL	EVATION DA	TA			
STORAGE	.01	.02	.02	.03	.04	.06	.06	.09	.13	.16
OUTFLOW	3.80	4.03	4.28	4.56	4.89	5.26	5.38	5.70	6.22	6.58
ELEVATION	19.60	19.72	19.87	20.04	20.25	20.52	20.60	20.85	21.28	21.60
STORAGE	.20	31	.31	.32	.32	.34	.35	.36	.38	.41
OUTFLOW	6.84	7.60	7.69	8.12	9.20	11.23	14.50	19.30	25.94	34.70
ELEVATION	21.84	22.60	22.61	22.64	22.70	22.77	22.86	22.97	23.10	23.24
STORAGE	.43	.46								
OUTFLOW	45.89	59.80								
ELEVATION	23.41	23.60		* 1 * 1 * 1 * 1 * 1 * 1 * 1 * 1 * 1 * 1		A real				

^{***} WARNING *** MODIFIED PULS ROUTING MAY BE NUMERICALLY UNSTABLE FOR OUTFLOWS BETWEEN 14. TO 60.

THE ROUTED HYDROGRAPH SHOULD BE EXAMINED FOR OSCILLATIONS OR OUTFLOWS GREATER THAN PEAK INFLOWS.

THIS CAN BE CORRECTED BY DECREASING THE TIME INTERVAL OR INCREASING STORAGE (USE A LONGER REACH.)

RES1

**	**	***	(*** ;	****	*****	*******	******* *		****	****	(***	*******	*****	******	****	***	****	****	*******	*****	******
D	A I	MON	HRMN	ORD	OUTFLOW	STORAGE		DA	MON	HRMN	ORD	OUTFLOW	STORAGE	STAGE		MON	i HRMN	ORD	OUTFLOW	STORAGE	STAGE
2	n :	TIN	1200	1	0.	0	19.6 *		JUN	2020	101	4.	.0	19.6		JUI	V 0440	201	4.	.0	19.6
			1205	2	4.	.0	19.6 *					4.	0	19.6					4.	.0	19.6
			1210	3	4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
2	0	JUN	1215	4	4.	.0	19.6 *					4.	.0				V 0455		4.	.0	19.6
			1220	5	4.	.0	19.6 *					4.	.0	19.6			V 0500 V 0505		4.	.0 .0	19.6 19.6
			1225	6	4.	.0	19.6 * 19.6 *					4. 4.	.0 .0	17.6					4.	.0	19.6
			1230 1235	7 8	4. 4.	.0 .0	17.6 *					4.	.0				V 0515		4.	.0	19.6
			1240		4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
			1245		4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
			1250		4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
			1255		4.	.0	19.6 *					4.	.0				V 0535		4.	.0 .0	19.6 19.6
			1300			.0	19.6 *					4.	.0	19.6			V 0540		4. 4.	.0	17.6
			1305		4.	.0	19.6 * 19.6 *					4. 4.	.0 .0	17.6					4.	.0	19.6
			1310 1315		4. 4.	.0	17.6 *					4.	.0				V 0555		4.	.0	19.6
			1320		4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
			1325		4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
			1330		4.	,0	19.6 *					4.	.0						4.	.0	19.6
			1335		4.	<u>.</u>	19.6 *						.0				V 0615		4.	.0	19.6 19.6
			1340		4.	.0	19.6 *					4,	.0	19.6 19.6					4. 4.	.0	17.6
			1345		4.	.0	19.6 *					4. 4.	.0	17.6					4.	.0	19.6
			1350		4. 4.	.0	17.6 *					4.	.0	19.6					4.	.0	19.6
			1355 1400		4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
			1405		4		19.6 *					4.	.0	19.6	* 21	JUI	0645	226	4.	.0	17.6
			1410		4.	.0	19.6 *	20	JUN	2230	127	4.	.0	19.6					4.	.0	19.6
2	0	JUN	1415	28	4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
			1420		4.	.0	19.6 *					4.	.0	19.6					4. 4.	.0	19.6 19.6
			1425		4.	.0	17.6 *					4. 4.	.0	19.6 19.6					4.	.0	19.6
			1430		4. 4.	.0 .0	19.6 * 19.6 *					4.	.0	19.6					4.	.0	19.6
			1435 1440		4.	.0	17.6 *					4.	0	19.6					4.	.0	19.6
			1445		4.	• -	19.6 *					4.	.0				V 0725		4.	.0	19.6
			1450		4.	.0	19.6 *					4.	0	19.6					4.	.0	19.6
2	0	JUN	1455	36	4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
			1500		4.	.0	19.6 *					4.	.0	19.6 19.6					4. 4.	.0. .0	19.6 19.6
			1505		4.	.0	. 19.6 *					4. 4.	.0 .0	17.6					4.	.0	19.6
			1510		4. 4.	.0	19.6 * 19.6 *					4.	.0				V 0755		4.	.0	19.6
			1515 1520		4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
			1525		4.	.0	19.6 *					4.	.0				0805		4.	.0	19.6
			1530		4.	.0	19.6 *					4.	.0	19.6					4.	.0	19.6
			1535		4.	.0	19.6 *					4.	.0				0815		4. 4.	.0 .0	19.6 19.6
			1540		4.	.0	19.6 *					4.	.0 .0	19.6 19.6					4.	.0	17.6
			1545		4.	.0	19.6 * 19.6 *					4. 4.	.0	19.6					4.	.0	19.6
			1550 1555		4. 4.	.0	19.6 *					4.	.0	19.7					4.	.0	19.6
			1600		4	.0	19.6 *					6.	.1	20.8					4.	.0	19.6
. ,			1605		4.	.0	19.6 *					7.	.2	21.7					4.	.0	19.6
2	0 ;	JUN	1610	51	4.	.0	19.6 *					8.	.3	22.6					4.	.0	19.6
			1615		4.	0	19.6 *					29.	.4.	23.1					4.	.0 .0	19.6 19.6
			1620		4.	.0	19.6 *					30. 28.	.4 .4	23.2 23.1					4.	.0	17.6
			1625		4. 4.	.0 .0	19.6 * 19.6 *					26. 26.	.4	23.1					4.	.0	19.6
			1630 1635		4.	.0	17.6 *					22.	.4	23.0					4.	.0	19.6
			1640		4.	.0	19.6 *	21	JUN	0100	157	18.	.4	22.9					4.	.0	19.6
			1645		4.	.0	19.6 *	21	JUN	0105	158	15.	.4	22.9						.0	19.6
			1650		4.	.0	19.6 *					13.	.3	22.8			1 0935		K	- 20	Z 19.4
2	ο.	JUN	1655	60	4.	.0	19.6 *	21	JUN	0115	160	10.	.3	22.1	* 41	10[1 0733	, 40V	· "4",	•0	1/10

ZU JUN 1700	ΦĬ	4.	۰۷	17.6 * ZI JUN VIZO 16.	7.	•0	ZZ./ * ZI JUN C		7.8	10	1710
20 JUN 1705		4.	.0	19.6 * 21 JUN 0125 16	2 8.	.3	22.6 * 21 JUN (4.	.0	19.6
20 JUN 1710		4.	.0	19.6 * 21 JUN 0130 163		.3	22.5 * 21 JUN 0		4.	.0	19.6
20 JUN 1715	64	4.	.0	19.6 * 21 JUN 0135 16	4 7.	.3	22.4 * 21 JUN (4.	.0	19.6
20 JUN 1720	65	4.	.0	19.6 * 21 JUN 0140 16	5 7.	.3	22.2 * 21 JUN 1		4.	.0	19.6
20 JUN 1725		4.	.0	19.6 * 21 JUN 0145 166		.2	22.0 * 21 JUN 1		4.	.0	19.6
20 JUN 1730	67	4.	.0	19.6 * 21 JUN 0150 167	7 7.	.2	21.8 * 21 JUN 1		4.	.0	19.6
20 JUN 1735		4.	.0	19.6 * 21 JUN 0155 168		.2	21.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1740	69	4.	.0	19.6 * 21 JUN 0200 16	7 6.	.1	21.3 * 21 JUN 1		4.	0	19.6
20 JUN 1745		4.	.0	19.6 * 21 JUN 0205 170		.1	21.1 * 21 JUN 1		4.	.0	19.6
20 JUN 1750		4.	.0	19.6 * 21 JUN 0210 171		.1	20.8 * 21 JUN 1		4.	.0	19.6
20 JUN 1755		4.	.0	19.6 * 21 JUN 0215 17		.1	20.5 * 21 JUN 1		4.	.0	19.6
20 JUN 1800	73	4.	.0	19.6 * 21 JUN 0220 173		.0	20.1 * 21 JUN 1		4.	.0	19.6
20 JUN 1805	74	4.	.0	19.6 * 21 JUN 0225 174	4 4.	.0	19.7 * 21 JUN 1		4.	.0	19.6
20 JUN 1810	75	4.	.0	19.6 * 21 JUN 0230 175		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1815	76	4.	.0	19.6 * 21 JUN 0235 176		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1820	77	4.	.0	19.6 * 21 JUN 0240 177		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1825	78	4.	.0	19.6 * 21 JUN 0245 178		.0	19.6 * 21 JUN 1		4.	.0	17.6
20 JUN 1830	79	4.	.0	19.6 * 21 JUN 0250 179		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1835	80	4.	.0	19.6 * 21 JUN 0255 180		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1840	81	4.	.0	19.6 * 21 JUN 0300 18		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1845	82	4.	.0	19.6 * 21 JUN 0305 18		.0	19.6 * 21 JUN 1		4.	0	19.6
20 JUN 1850	83	4.	.0	19.6 * 21 JUN 0310 183		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1855	84	4.	.0	19.6 * 21 JUN 0315 18		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1900	85	4.	.0	19.6 * 21 JUN 0320 18		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1905	86	4.	.0	19.6 * 21 JUN 0325 186		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1910	87	4.	.0	19.6 * 21 JUN 0330 187		.0	19.6 * 21 JUN 1		4.	.0	19.6 19.6
20 JUN 1915		4.	.0	19.6 * 21 JUN 0335 188		.0	19.6 * 21 JUN 1		4	.0	17.6
20 JUN 1920	89	4.	.0	19.6 * 21 JUN 0340 189		.0	19.6 * 21 JUN 1		4.	.0	17.6
20 JUN 1925	90	4.	.0	19.6 * 21 JUN 0345 190		.0	19.6 * 21 JUN 1		4.	.0	17.6
20 JUN 1930		4.	.0	19.6 * 21 JUN 0350 191		.0	19.6 * 21 JUN 1		4.	.0 .0	17.6
20 JUN 1935		4.	.0	19.6 * 21 JUN 0355 197		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1940		4.	.0	19.6 * 21 JUN 0400 193		.0	19.6 * 21 JUN 1		4. 4.	.0	17.6
20 JUN 1945		4.	.0	19.6 * 21 JUN 0405 194		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1950		4.	.0	19.6 * 21 JUN 0410 19:		.0	19.6 * 21 JUN 1		4.	.0	19.6
20 JUN 1955		4.	.0	19.6 * 21 JUN 0415 196		.0	19.6 * 21 JUN 1		4.	.0.	17.6
20 JUN 2000		4.	.0	19.6 * 21 JUN 0420 197		0	19.6 * 21 JUN 1		4. 4.	.0	17.6
20 JUN 2005		4.		19.6 * 21 JUN 0425 198		.0	19.6 * 21 JUN 1 19.6 * 21 JUN 1				17.6
20 JUN 2010		4.		19.6 * 21 JUN 0430 199					4.	.0	
20 JUN 2015	100	4.	.0	19.6 * 21 JUN 0435 200	0 4.	.0	* * * * * * * * * * * * * * * * * * *	200 3 00	7:		17.0
********	*****	*******	******	**************************************	********	*******	************	*******	********	******	*****
PEAK FLOW	TIM	F		MAXIMUM AVERAGE	E FLOW						
I LOW I LUM	1 41 11	_		, a =							

PEAK FLOW	TIME			MAXIMUM AVEF	RAGE FLOW	
(CFS)	(HR)		6-HR	24-HR	72-HR	24.92-HR
30.	12.67	(CFS)	7.	5.	4.	4.
		(INCHES)	.761	2.070	2.133	2.133
		(AC-FT)	3.	9.	9.	9.
PEAK STORAGE	TIME			MAXIMUM AVERA	age storage	
(AC-FT)	(HR)		6-HR	24-HR	72-HR	24.92-HR
0.	12.67		0.	0.	0.	0.
PEAK STAGE	TIME			MAXIMUM AVEF	AGE STAGE	
(FEET)	(HR)		6-HR	24-HR	72-HR	24.92-HR
23.17	12.67		20.49	19.82	19.81	19.81

CUMULATIVE AREA = .08 SQ MI

						(I) INFLOW,	(0)	OUTFLOW									
Design D			0.	4					20.	24.			0.	0.	0		0.
DARPHN PER										_						۸	۸
201200 11	w 18			•	0	.0	.0	• 0 •••	0	2	.0	.2	.4	.0		0	٠.٧
201205 21 0	- 60 - 60 - 10			1.							S-						
201210 31					n		•		•		S	•			,		
201215 41	7964					•	•									•	
201220 51						•								•		• .	•
201225 61 0 0 5. 201235 81 0 0 5. 201240 91 0 0 5. 201245 101 0 0 5. 201250 111 0 0 5. 201250 111 0 0 5. 201250 111 0 0 5. 201250 111 0 0 5. 201250 111 0 0 5. 201300 131 0 5. 201300 131 0 5. 201301 151 0 0 5. 201310 151 0 0 5. 201311 161 0 5. 201313 161 0 5. 201313 161 0 5. 201325 181 0 5 5. 201325 181 0 5 5. 201325 181 0 5 5. 201325 211 0 5 5. 201335 201 0 5 5. 201340 211 0 5 5. 201340 211 0 5 5. 201340 211 0 5 5. 201340 211 0 5 5. 201340 211 0 5 5. 201340 211 0 5 5. 201340 211 0 5 5. 201340 211 0 5 5. 201340 211 0 5 5. 201340 211 0 5 5. 201340 211 0 5 5. 201340 231 0 5 5. 201340 231 0 5 5. 201340 231 0 5 5. 201402 231 0 5 5. 201403 231 0 5 5. 201403 231 0 5 5. 201403 231 0 5 5. 201403 231 0 5 5. 201403 231 0 5 5. 201403 231 0 5 5. 201403 231 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201403 311 0 5 5. 201404 331 0 5 5. 201404 331 0 5 5. 201404 331 0 5 5. 201405 311 0 5 5. 201405 311 0 5 5. 201405 311 0 5 5. 201405 311 0 5 5. 201505 311 0 5 5. 201505 311 0 5 5. 201505 311 0 5 5. 201505 311 0 5 5. 201505 311 0 5 5. 201505 311 0 5 5. 201505 311 0 5 5. 201505 311 0 5 5. 201505 411 0 5 5. 201505					0				•		S.	*				•	
201225 81 0 0 S. 201240 91 0 S. 201240 91 0 S. 201240 91 0 S. 201250 111 0 S. 201250 111 0 S. 201255 121 0 S. 201300 131 0 S. 201300 131 0 S. 201300 141 0 S. 201310 151 0 S. 201310 171 0 S. 201320 171 0 S.	-44				0	•		•		•		•		•	. ,	•	•
201240 91 0 0 S. 201245 101 0 S. 201245 101 0 S. 201255 121 0 S. 201250 111 0 S. 201250 131 0 S. 201300 131 0 S. 201300 141 0 S. 201300 141 0 S. 201310 151 0 S. 201310 151 0 S. 201311 161 0 S. 201312 171 0 S. 201325 181 0 S. 201325 181 0 S. 201325 181 0 S. 201325 181 0 S. 201325 201 0 S. 201325 201 0 S. 201340 211 0 S. 201340 211 0 S. 201340 211 0 S. 201340 211 0 S. 201402 251 0 S. 201402 251 0 S. 201403 251 0 S. 201403 251 0 S. 201403 251 0 S. 201404 271 0 S. 201403 311 0 S. 201404 311 0 S. 201404 311 0 S. 201404 311 0 S. 201404 311 0 S. 201404 311 0 S. 201404 311 0 S. 201404 311 0 S. 201404 311 0 S. 201404 311 0 S. 201405 311 0 S. 201405 311 0 S. 201503 311 0 S. 201503 311 0 S. 201503 311 0 S. 201503 311 0 S. 201503 311 0 S. 201503 311 0 S. 201503 311 0 S. 201503 411 0 S. 201504 411 0 S. 201504 411 0 S. 201504 411 0					0	•		•	•	. •	•	•				•	•
201250 101 0 0 S	۳				_	•		• "	•	•		•	•	•	1	•	•
201250 111					_		•	•		* ***		•		. •		•	
201355 121 0					0	•	•	•		•	5. C	•	•	•			•
201300 131 0					U .		• • •				S						•
201305 141					_		•	•	•					•			
201310 151 0	***5				_		•	•									
201315 161				+ 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	n	•	•	•									
201320 171 0 S. S. S. S. S. S. S. S. S. S. S. S. S.					0		·				S.					• .,	•
201325 181 0	17:0				0	· ·					S.			•			11.
201330 19				, e	0	and the second of										•	•
201340 211			19I		0			• .		•		•	•	•		•	
201345 22		201335		•	0	•	•	• '	•	•	S.	•	•	1		•	•
201350 231 0					0.						5						
201355	_				0	The second of the second	•	•	•	•		•	•	•	~ (• • • • • • • • • • • • • • • • • • • •	•
201400 251 0					_	•	•	•					•	•			•
201405 281 0					_	•	•	•	. •	. •		granten b					:
201410 271 0	-				_		•	•	•					•			
201415 28I 0	14					•	•	•							•		
201420 291 0	Services.				-	•	:								,		
201425 30I	-				_						S.					•	• .
201430 31 0	· · · · · · · · · · · · · · · · · · ·				0						S.,					• •	
201445 32I	4.9			1	0.			. Na ang ang ang ang ang ang ang			5						
201445 34I 0			321		0	•		•		•	_	•		•		•	•
201450 35I 0	986 T				_	•		•		** * * •		•	•	•	,	•	•
201455 36I 0						•			•	•		•	•		•	•	•
201500 37I					_	•	•		•	•		•		/ · ·			• •
201505 38I	ne C					•	•	•	•	•						•	
201510 39I 0	1.5					•	•										
201515 40I					_	•									•	•	
201520 41I 0					0	•					S.				ì	•	
201525 42I					Ο.						S						
201535 44I					0	•						•		•		•	•
201540 45I					0		•	•	•	•		•	•	•		•	• • .
201545 46I	44				_		•		.• .			•	. •	•	•	•	•
201550 47I					_	•	•	•	•	•			•	•		•	•
201555 48I					_	•	•			•		•		•	•	•	•
201600 49I 0					_	•	. •	•	•	•			•			•	
201605 50I					_	•	•	•				•				• .	
201610 51I 0				1	0	•	:	•	•	•		•				•	
					Ō.						<u>§</u>						
201615 52I 0	-	201615	521				•	•	•	•	S.	•	•	DI	-7	4	•
201620 531 0	_	201620	53 I			•	•		•	•		•	•	トト		. 1	٠
201625 54I 0		201625	54 I		0	•		•		<u> </u>			. •		· '	• 	

201435 58J 0		201630	55 I		0		•		1		1 .	ı	5.	•	•	•	,
201446 531 0 5 5 5 5 5 5 5 5 5											,						
201455 581 0 5 5 201455 587 201455 597 0 0 5 5 201455 597 0 0 5 5 201455 597 0 0 5 5 201706 621 0 0 5 5 201706 621 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 641 0 0 5 5 201715 701 0 5 5 201715										•	•				•	•	
201455 991 0																	
201395 501 0 5 5 5 5 5 5 5 5 5							•								•		
Description Description							•			•							,
201705 621					D		•	•			•		S				
201710 631 0 5 5 5 201727 641 0 5 5 201727 641 0 5 5 5 201727 641 0 5 5 5 201727 641 0 5 5 5 201727 641 0 5 5 5 201727 641 0 5 5 5 201727 641 0 5 5 5 201727 641 0 5 5 201727 641 0 5 5 201727 641 0 5 5 201727 641 0 5 5 201727 641 0 5 5 201727 711 0 5 201727 711 0 5 201727 711 0 5 201727 711 0 5 201727 711 0 5 201727 711 0 5 201727 711 0 5 201727 711 0 5 201727 711 0 5 201727 711 0 5 201727 711 0 5 201727 711 0 201727 711 0 201727 711 0 201727 711 0 201727 711				• • •	U	• • • •		• •					 c				
201715 441 0							•			1	•			•	•	•	_
201720 651					_		•		• '	•	• '			•	•		•
201773 641 0							•	•		1	•			•	•	•	•
201730 672 0 0 S. 201730 673 0 0 S. 201740 674 0 0 S. 201747 701 0 C S. 201747 701 0 C S. 201747 701 0 C S. 201757 721 0 C S. 20150 731 0 C S. 20160 731 0 S					_		•		•	•	• '			•	•	•	•
201735 681 0 S. S. 201745 701 0 S. 201747 701 0 S. 201747 701 0 S. 201747 701 0 S. 201747 701 0 S. 201747 701 0 S. 201807 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201808 701 0 S. 201908 701 0 S.					_		•	1		•				•	•	•	•
Doc Doc					0		•		• .	•	•			•	•	•	•
201745 701					0		•	1			•			•		•	•
201750 711		201740	69 I		0		•			•				•	•	•	•
201755 721 0		201745	70 I		0		•			•	•	,	S	*	•	•	•
Deligno Tail D		201750	71I .		0								S				
201805 741		201755	72I		0		•		,	3					•		•
201805 741 0 S. 201815 751 0 S. 201820 771 0 S. 201825 761 0 S. 201825 861 0 S. 201825 861 0 S. 201826 821 0 S. 201826 831 0 S. 201826 831 0 S. 201826 841 0 S. 201826 841 0 S. 201905 861 0 S. 201905 861 0 S. 201905 861 0 S. 201905 861 0 S. 201910 871 0 S. 201912 871 0 S. 201913 871 0 S. 201913 871 0 S. 201915 871 0 S. 201915 871 0 S. 201925 971 0 S. 201935 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S. 201936 971 0 S		201800	73 I		0										•	•	•
201810 751			74I		0					•					•		
201815 761			75I		0									•			
201820 771 0 S. 201825 781 0 S. 201835 801 0 S. 201835 801 0 S. 201845 821 0 S. 201845 821 0 S. 201850 841 0 S. 201850 841 0 S. 201900 851 0 S. 201900 851 0 S. 201910 871 0 S. 201925 901 0 S. 201925 901 0 S. 201925 901 0 S. 201925 901 0 S. 201935 921 0 S. 201935 931 0 S. 201935 941 0 S. 201935 951 0 S. 201935 961 0 S. 201935 961 0 S. 202000 971 0 S. 202001 091 0 S. 202010 991 0 S. 202020 1011 0 S. 202120 1151 0 S. 202120 1151 0 S. 202130 1151 0 S. 202130 1151 0 S. 202145 1161 0 S. 202150 1151 0 S. 202					0				. ,	3	,		S.	•	•	•	•
201825 791					0							,	S.	•	• .,	•	
201835 801					0			- ,				. !	S		•	•	•
201845 801 0 S. S. S. S. S. S. S. S. S. S. S. S. S.					D								S.			• ,	
201845 821 0 S. 201855 831 0 S. 201855 841 0 S. 201905 851 0 S. 201905 861 0 S. 201905 861 0 S. 201910 871 0 S. 201910 871 0 S. 201910 871 0 S. 201910 871 0 S. 201925 901 0 S. 201925 901 0 S. 201935 921 0 S. 201936 931 0 S. 201936 931 0 S. 201937 931 0 S. 201939 931 0 S. 201930 931 0 S. 201930 931 0 S. 201941 0 S. 201940 931 0 S. 201950 951 0 S. 201950 951 0 S. 201950 951 0 S. 202000 971 0 S. 202000 1011 0 S. 202001 1011 0 S. 202001 1011 0 S. 202005 1021 0 S. 202005 10					n		-					, ;	S.	ī	•		
201845 82I					n								S				
201850 831 0				• • •	n					•	<u>.</u>	, ;	S.	y 25%	■ ***·		
201855 841 0								•					S.				
201900 851 0				*	_					•	•		S.	•	•		
201905 861 0							•		_							•	
201910 871 0							•			•					.		
201915 881 0							•			-							•
201920 891 0										•							
2019735 901 0							•			_				•			
201730 911 0 0							•		•	•				•			
201935 92I					n		•						S				
201940 931 0					0		• • •	• •					S.		•		
201945 941 0							•	,		_				•			
201950 951 0 0							•							•	•		
201955 961 0							• .	,	•		•			•			
202000 97I							•			174	•						
202005 98I							•	1			•				•	•	
202010 991 0							•			•	•				•	•	
202015 100I							•	1		_	•			•			
202020 101I					_		•			•							
20205 102I					n								S				
202030 103I				• • •	n.			• •					s.				
202035 104I							_									•	
202040 1051										•						•	
202045 106I															•		
202055 108I							-				,					•	1
202055 108I							-									• 1.7 S	
202100 109I							<u>.</u>			•						•	•
202105 110I							-			•					in a second		
202110 111I 0					_					•					•		• •
202115 112I					n								S				
202120 113I					n					•		,	s.				•
202125 114I							-						s.		•		•
202130 115I	-						_			•						•	
202135 116I							•			. *						• .	•
202140 117I									,						•	•	ŧ
202145 1181 0 S. S											. ,			•		•	
202130 1171							•				, ,				. 0	1 _ 1	フニ
202.00							·		,	•					. K	1 - 4	
474177									,	1	. ,						•
		****			_												

																			_												
	200 1211			0		•	• •					•		• •	• •	• • •	٠	• • •	.5 S	• •		• •		•	• • •	• •	• •		• • •		٠
	205 1221			0		•	•		•	•		•	•		•		•		S			•			•		•		• .		•
	210 123I			0			•		•	•		•	•		•		•		S			•			•		•		•		•
	215 1241			0		•	•		,	•		•	•		•		•		S			•			• -						•
	220 1251			0			•								•		•		S			•			•		•		•		•
	25 1261			0		•	•		•	•		•	•		•		•		S			•	- 0	1	•		•		•		•
	230 1271			0			•			•		•	•		•		•		S.			•		,	•	* • •	•		•		•
	35 1281			0		•	•		•	•		•	•		•		•		5			•		•	•		•		•		•
	240 1291			0		•	•		•	•		•	•		•		•		S.			•			•		•		•		•
	45 130I			0		٠	•		. •	•		•	1		•		•		ى د	•		•		. '	•		•		•		•
	250 1311	. • •	• •	U.		•	• •	• •	* 1		* *	• •		• •	• •		•		. S	• •	•	• •	• •	•		• •					•
	55 1321			Ü		•	•			•		•	•		•		•		S			•							•		•
	300 1331			0		1	•		•	•		•	•		•		•		S.			•							•		
	05 134I			0		•	•		•	•		. •			•		•		S		. , 5	•			•		•		•	•	•
	310 135I			0		1	•		•	•		•	•		• .		•		S.					'	•		•		•		•
	15 1361			0		•	•		•	•		•	•		•		٠		S			•			•		•		•		•
	320 137I			0			•			•		•	•		•		•		S			•			•				•		
	25 1381			0		•	•			8 125		•	•		•		•		S			•							•		•
	330 1391			0		1				•		•	•		•		٠		S			•							_		
	35 140I			0		•	•		,	1		•	•		•		•		0	•		•									•
	340 141I		• •	U .		•	• •	• •	•	• •	• •	•		• •	• •		•		.s		• •	• •	• •	•		• •					
	45 142I			0		•	•		•	•		•	•		•		•		S			•			_						
	550 143.			0		1	•		1	•		٠	•		•		•		S			•									
	55 144.			0		•	•		•	•		•	•		•		•		5			•									,
	000 145.			0			•		,	•		•	•		•		,*		S			•					•		•		
	05 146.		I	0	т	. •	•		•	•		•	•		•		•		S			•									
	010 147.			0	1		•	t	'	•		•	•		•		•			.s					_						
)15 148.			0	ο.	•	•	i		•.			·		•		•		. '		S	•			•				er Handaria		
	20 149.			•	0	0	•			•			• •		•		I				_	s.									
	25 150.			•	i	יט ה	• • • •		•	•		•	•		•				_	. T			. S								
	30 151.			•		.0		• •		• •	• . •			• •	• •		•	• • •	•	. 0	1		• •	•	3						
	35 152.			•		•	•		•	•			•		•		•				10	•			_						
)40 153.			•			•			• .		1	•		•		•		I	.n		•		S	_						٠.
	45 154.					•	•		,	•		٠	•		•		.I	0	•					S							
)50 155.			•		,	•			•		,	•			0	•	_						S							
)55 156.			•		. '	•		,	•		•	. T	Λ		•								S							
	100 157. 105 158.			•			•			•	I	0.			•		·							S.							
	100 150. 110 159.			•		,	•		I	-	•				:							ar.		S							
	15 160.						. I	0	•															S.							
	120 161.			•		Ţ	. n			•													. 9								
	25 162.		• •	•	· · ·	0.		•	•														S								
	30 163.				7	0.																	S						•		,
	35 164.			Ī	_	0																	S	1							
	40 165.		1			0																	5				•		•		•
	45 166.		I			0 .																.s							•		٠
	50 167.		I			0 .							•				•			•		S			•		•		•		
	55 168.		I		0				,	•,										• ,	9				•		•		•		•
	200 169,		I		0										•		•			• ,	S	. •			•		•		•		
2102	205 170.		I		0								•		•		•			•	ម	•			•		*		•		•
	210 171.		I		. 0 .				•			•		• •	• •		•		•	• •	ъ., `	• •	• •	•		• •					•
	215 172.	I		•	0		•		,	•					•	•	•			٠, ١)	٠			•		* .		•		*
	220 173.			. (0		•			•			• ,				•			. 5		•			•		•				٠
	225 174.			0					1			•	•		•		•			.5		•		. "	•		•		•		•
	230 175.			0			•								•		٠			S					• • •	v .	•	÷ *	•		٠
	35 176.			0		•	•			•					•		•		S S		1.00	. • .			•		•		•		•
	240 177.			0			•			•			•		•		•		S						•		•		•		•
	245 178.			0			•			•		•	•		•		•		S			•			•		•				•
	250 179.			0			•			•			•		•		•		5 S			•			•		•		•		٠
	255 180.			0		•	•			•			•		•		•		.s	•				-	•		•		•		•
	300 181.			U		•	• •	• •	•	• •	• •	•			• •		•	• • •	S	• •	• • •		• •	•		• •	• •				
	305 182.			0		•	•		1	•		1	•		•		•		S			•									
	310 183.			Ö			•			•			•		•		•		S					-					_		
	315 184. 320 185.	I I		0		٠	•		,	•		•	•				•		S			•				K	71	-	21		
				U								,			-		-		_			-								_	
	120 10J. 175 184	Ţ		n															S							,	•				-

	210330	187.	Ι		0			ı			•			5.		•	•	•	•
	210335	188.	I		0				•	•		*		S.	•	•	• ,		•
	210340				0		•		•	•	•	•		S. S.		•	•		•
	210345 210350				0 n	ı	•		•			•		S.					
	210355			• •	. 0		٠.							s.					. **
	210400				0	1								S.	i	•	•		
	210405	194.	I		0		•			•		•		S.			. 1	•	•
	210410				0		. •	i	•	•	•			s. s.	•	•	•	•	•
	210415 210420				0		•		•	•				s.				•	
-	210420				0		•							S.	,	<u>.</u>	•	•	
	210430				0)								s.		-		•	
	210435				. 0	l					•			S.	1	•	•	•	
	210440				. 0							• • • • •		.s. S.					
	210445 210450				0		•		•	•	•			s. S.					
	210450				0				•	. •		i saaba	,	S.		•			
	210500				0	· }		•		•				s.		•			
	210505				0		٠.		•	•				5.	•	•	·		
	210510				0		. •	•		•				S. S.	,		•	•	•
	210515				0		•	. J	•	•	•	•		s.	•		•		
	210520 210525				0	•				•				s.		•	•		•.
	210520				. 0			·						s.					
	210535				. 0	1		,		•				s.			•	• .	•
	210540				0		•		•	•	•	•		S. S.	1	•	•	•	
	210545				0 0		•	•	•					s. S.	•		•		•
	210550 210555				n U	•			•					s.		•			
	210600				0				•	•				S.				•	
	210605	218.	I		0	1.50				• •				S.		•	•	•	•
	210610				0		•	•	•	•	•			S. S.			•		
	210615 210620				0		•		•					.S.					
	210625			• •	. 0					•				S.					
	210630				0	e 1 .	٠.		*	•				S.			• 2.00		•
	210635				0		•		•	•	•			S.		•	•	•	•
	210640				0		•	• • • •	•	•	•	•		S. S.			•	• •	
	210645 210650				0		•		•		•	•		s.		•	•		
	210655				0							, •		S.	, a many	• • •			
	210700				0)	•		•	•	•			S.		•	•	•	•
	210705				0) `	•	•	•	•	•	. •		S.					
	210710 210715		. i) 	•				•			S.					
	210720		_		0			 •	•	•				5.		•	•	•	•
	210725				0		•	•		•	•			S.	,	•	•	•	
	210730	235.	I		0		. •		•		•			S. S.			•	•	•
	210735 210740				0		•	•			,			S.		•	•	•	
	210745				0	•								s.					
	210750	239.			0)	•	•	•	•				S.			•	•	•
	210755		I		0		٠.	,	•	•	•	•		S.	,	· ·······	•	•	•
	210800 210805					; 1	• •	· • • • • • • • • • • • • • • • • • • •			• •			S.					•
:	210810								· ,. · · ·	of wyskiis •				5.		•		•	
	210815	244.	I		0			•	• .	•	. •			s.		•	•		•
	210820				0		•		•					S.		•		•	
	210825 210830				0		•		•	• .	j., •	. •		S. S.				•	•
	210830				-0				:					s.					•
	210840	249.	I		0									s.			· 0	1-0	. 7
	210845	250.	I		0		•		•	•	•			S.	•	•	. 1	.1 - 2	- /
	210850			• •	. 0)	• •		• • • • •		• •		1 1 1 1	.s. s.					
	210855	, ZOZ.	Ţ		ົປ	1	•	•	•	•		•		W1		•	-	-	

	210900	253	ī		Ũ			_		_		_			S.						
	210705				0			•		•		•	•	•	S.						
					-			•		•		•	•	•			•	•	•		•
. •	210910	255.	1		0			•		•		•	•	•	s.		•	•	•	•	•
	210915	256.	I		0								•		s.		•	•	•	. ,	
	210920				n								_	_	s.						
					-			•		•		•	•	•			•	-		-	
	210925				0					•			•	•	S.		•	•	•		•
	210930	259.	I		0							•			S.			• .,	•		
	210935				0							_		_	S.					i i	
								•		•		•	•	•	.s.				1.6		
	210940				U,		• •														•
	210945	262.	I		0				**				•		5.		•	•			
	210950	263.	Ŧ		0										S.					,	
					n			-		•		-			s.		_	-			
	210955				_			•		•		•	•	•	s.		•				
	211000	265.	I		0					•			•	•			•	•	•		•
	211005	266.	I		0										s.		•	• [• •	•	•
	211010				0					_		_			S.						
					_			•		•		•	-		S.						
	211015				0			1				•	•	•			•		•		•
	211020	269.	1		0					•			•	1	S.		1	•	• .	•	•
	211025	270.	Ī		O		,								S.				•		
	211030				0			•							.s.						
					· ·	• •	• •	• •			• • •				S.						
	211035				0							•	•				•	•	•	•	•
	211040	273.	I		0		,.			•			s ·	•	S.		•	•	• • • • • •	•	•
	211045				n										S.						
					n			•				-			s.	* ** ** *	_				
	211050				_			•		•		•	•				•	•			
	211055	276.	Ι		0			•		•		1	•	•	S.		•	•	• '		٠
	211100	277.	I		0										s.		1	•	•	•	
	211105				n								_		S.						
					_			•		•		•	•	-	s.		_	_			
	211110				0			•		•		•	•	•			•	•	•		-
	211115	280.	I		0							•	•	•	s.		.	•	• •	•	•
	211120	281.	Ι.		0.										.5.						
	211125				n								_	_	S.			•			•
					_			•		•		•	•	•	S.				_		
	211130				0			•		•		•		•			•	•	•	•	•
	211135	284.	I		0							•	•	•	s.		•	•	•	• ,	*
	211140	285.	Ţ		0										S.			• *	•		٠
	211145				ñ								_		S.				. 1		
					_			•		•		•	•	•	S.			_		_	
	211150				0			•		•		•	•					•	•		٠
	211155	288.	I		0							•	1	•	s.		•	•	•	•	•
	211200	289.	I		0										s.				•	•	
	211205				0								_		S.						
								•		•		•	•	•	C.						
	211210			. :	0							# * # · # · # · # · # ·									•
	211215	292.	I		0					•		•	•	•	s.		•	•	• '	• '	*
	211220				0					4				•	S.						
					_			•		•			_	_	s.			•			
	211225				0					•		•	•	•	s.			_			
	211230				0			•				•	•	•			• " "	•	•	•	•
	211235	296.1			0									•	S.		•	•			•
	211240				0										s.		•				
					Ö			•		-					s.						
	211245				_			•		•		•	•	•	s.			_		***, **	
	211250				0			•		•		•	•	•	a.		•		· '	· 	-
	211255	300I-			-0			,							-5			,		,	*

```
106 KK
                    CH3 *
  108 KD
                 OUTPUT CONTROL VARIABLES
                       IPRNT
                                       3 PRINT CONTROL
                       IPLOT
                                      1 PLOT CONTROL
                       QSCAL
                                      O. HYDROGRAPH PLOT SCALE
                       IPNCH
                                      1 PUNCH COMPUTED HYDROGRAPH
                        IOUT
                                      21 SAVE HYDROGRAPH ON THIS UNIT
                       ISAV1
                                      1 FIRST ORDINATE PUNCHED OR SAVED
                       ISAV2
                                     300 LAST ORDINATE PUNCHED OR SAVED
                      TIMINT
                                    .083 TIME INTERVAL IN HOURS
               HYDROGRAPH ROUTING DATA
                MUSKINGUM-CUNGE CHANNEL ROUTING
                          L
                                   310. CHANNEL LENGTH
                          S
                                   .0052 SLDPE
                          Ν
                                    .025 CHANNEL ROUGHNESS COEFFICIENT
                          CA
                                    .00 CONTRIBUTING AREA
                       SHAPE
                                   TRAP CHANNEL SHAPE
                                   2.00 BOTTOM WIDTH OR DIAMETER
                                   3.00 SIDE SLOPE
                                   COMPUTED MUSKINGUM-CUNGE PARAMETERS
                                          COMPUTATION TIME STEP
                    ELEMENT
                              ALPHA
                                                    DT
                                                                               TIME TO
                                                                                          VOLUME
                                                                                                    MAXIMUM
                                                                                PEAK
                                                                                                    CELERITY
                                                  (MIN)
                                                             (FT)
                                                                      (CFS)
                                                                                (MIN)
                                                                                           (IN)
                                                                                                     (FPS)
                     MAIN
                                1.72
                                          1.34
                                                     1.28
                                                             155.00
                                                                        29.98
                                                                                 761.52
                                                                                            2.13
                                                                                                      4.04
                                         INTERPOLATED TO SPECIFIED COMPUTATION INTERVAL
                     MAIN
                                1.72
                                          1.34
                                                     5.00
                                                                       29.86
                                                                                760.00
                                                                                            2.13
CONTINUITY SUMMARY (AC-FT) - INFLOW= .9218E+01 EXCESS= .0000E+00 OUTFLOW= .9206E+01 BASIN STORAGE= .1282E-01 PERCENT ERROR=
```

HYDROGRAPH AT STATION

6-HR

PEAK FLOW

(CFS)

TIME

(HR)

CH3

. MAXIMUM AVERAGE FLOW

72-HR

24.92-HR

24-HR

```
(INCHES)
                                  .761
                                           2.070
                                                      2.131
                                                                 2,131
                      (AC-FT)
                                             9.
                                                        9.
                     CUMULATIVE AREA =
                                         .08 SQ MI
*** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** ***
          **********
110 KK
          **********
 112 KO
               OUTPUT CONTROL VARIABLES
                    IPRNT
                               3 PRINT CONTROL
                    IPLOT
                                 1 PLOT CONTROL
                    QSCAL
                                 O. HYDROGRAPH PLOT SCALE
                    IPNCH
                                 1 PUNCH COMPUTED HYDROGRAPH
                     IOUT
                                21 SAVE HYDROGRAPH ON THIS UNIT
                    ISAV1
                                1 FIRST ORDINATE PUNCHED OR SAVED
                    ISAV2
                                300 LAST ORDINATE PUNCHED OR SAVED
                   TIMINT
                                .083 TIME INTERVAL IN HOURS
             SUBBASIN RUNOFF DATA
113 BA
              SUBBASIN CHARACTERISTICS
                          .00 SUBBASIN AREA
               PRECIPITATION DATA
                                   DEPTHS FOR O-PERCENT HYPOTHETICAL STORM
114 PH
                                    ..... TP-40 .....
               ..... HYDRO-35 .....
              5-MIN-15-MIN 60-MIN
                                    2-HR 3-HR
                                                   6-HR 12-HR 24-HR
                                                                       2-DAY
                                                                               4-DAY
                                                                                      7-DAY 10-DAY
                       .76
                            1.34 1.40
                                          1.44
                                                   1.56
                                                        1.69 2.01
                                                                          .00
                                                                                 .00
                                             STORM AREA =
115 LS
            SCS LOSS RATE
                   STRTL
                              .27 INITIAL ABSTRACTION
                   CRVNBR
                              88.00 CURVE NUMBER
                   RTIMP
                                .00 PERCENT IMPERVIOUS AREA
116 UD
              SCS DIMENSIONLESS UNITGRAPH
                    TLAG
                                .04 LAG
                                                        ***
                                                  UNIT HYDROGRAPH
                                               5 END-OF-PERIOD ORDINATES
                     HYDROGRAPH AT STATION
  TOTAL RAINFALL =
                    2.01, TOTAL LOSS =
                                      1.04, TOTAL EXCESS =
                                       MAXIMUM AVERAGE FLOW
PEAK FLOW
            TIME
                                                                                           R1-30
                                                    72-HR
 (CFS)
            (HR)
                                6-HR
                                          24-HR
           12.08
                      (CFS)
                                          0.
                                                       0.
                                0.
                                                                  0.
    1.
```

30.

12.67

(CFS)

7.

```
**********
117 KK
             OUTPUT CONTROL VARIABLES
119 KO
                             3 PRINT CONTROL
                  IPRNT
                  IPLOT
                              1 PLOT CONTROL
                  QSCAL
                              O. HYDROGRAPH PLOT SCALE
                  IPNCH
                              1 PUNCH COMPUTED HYDROGRAPH
                   IOUT
                              21 SAVE HYDROGRAPH ON THIS UNIT
                  ISAV1
                              1 FIRST ORDINATE PUNCHED OR SAVED
                  ISAV2
                             300 LAST ORDINATE PUNCHED OR SAVED
                 TIMINT
                             .083 TIME INTERVAL IN HOURS
120 HC
             HYDROGRAPH COMBINATION
                  ICOMP
                               2 NUMBER OF HYDROGRAPHS TO COMBINE
                 HYDROGRAPH AT STATION
PEAK FLOW
           TIME
                                    MAXIMUM AVERAGE FLOW
  (CFS)
         (HR)
                                                72-HR
                             6-HR
                                      24-HR
    30.
          12.67
                   (CFS)
                             7.
                                                4.
                                       5.
                                                          4.
                             .761
                  (INCHES)
                                      2.063
                                                2.124
                                                          2.124
                  (AC-FT)
                                        9.
                  CUMULATIVE AREA =
                                     .08 SQ MI
        **********
121 KK
              RES2 *
123 KD
            OUTPUT CONTROL VARIABLES
                 IPRNT
                           1 PRINT CONTROL
                 IPLOT
                              2 PLOT CONTROL
                 QSCAL
                             O. HYDROGRAPH PLOT SCALE
                 IPNCH
                             1 PUNCH COMPUTED HYDROGRAPH
                             21 SAVE HYDROGRAPH ON THIS UNIT
                 IOUT
                                                                                     121-31
                 ISAV1
                             1 FIRST ORDINATE PUNCHED OR SAVED
                            300 LAST ORDINATE PUNCHED OR SAVED
                 ISAV2
```

.973

.00 SQ MI

Û.

.836

(INCHES)

(AC-FT)

TIMINT

.083 TIME INTERVAL IN HOURS

CUMULATIVE AREA =

.973

0.

.973

0.

HYDROGRAPH ROUTING DATA

20 JUN 1210 3

	124	RS	STC	RAGE ROUTIN NSTPS ITYP RSVRIC X	1 ELEV 17.00	NUMBER OF TYPE OF I INITIAL O WORKING R	NITIAL CON CONDITION	IDITION				·	
	125	SV	S	TORAGE	.0	.1	.2	.3			• •		
	126	SE	ELE	VATION	18.00	19.00	20.00	21.00					
si	127	SL	LOW	-LEVEL OUTLI	ΞT				•				
į.				ELEVL	17.00	ELEVATION	AT CENTER	OF OUTLET					
				CAREA	.79	CROSS-SEC	TIONAL ARE	Α					
				COOL	.60	COEFFICIE				, to			
		,		EXPL	.50	EXPONENT							
									, v				
-	128	SS	SPI	LLWAY									
7				CREL	20.00	SPILLWAY	CREST ELEV	ATION					
-55 FEE	~			SPWID	19.00	SPILLWAY !	WIDTH						
٥.				COQW	2.70	WEIR COEF							
				EXPW	1.50	EXPONENT (
						* - *							
				d.				***			•		
			2 · • ·					*					
			u.			CO	MPUTED OUT	FLOW-ELEVAT	TION DATA		·		
			ÓUTFLOW	.00	3.99	4.20	4.42	4.68	4.97	5.29	5.66	6.09	6.58
			ELEVATION	18.00	18.10	18.22	18.35	18.52	18.71	18.94	19.22	19.57	20.00
			CELVATION	10.00	10.10	10,22	10100	10102	10.71	10177	1/122	17107	20.00
			OUTFLOW	6.67	7.12	8.22	10.26	13.55	18.38	25.03	33.80	45.00	58.90
			ELEVATION	20.01	20.04	20.10		20.26	20.37	20.50	20.64	20.81	21.00
7													
						COMPUTE	ED STORAGE-	-OUTFLOW-EL	EVATION DA	TA			
			STORAGE	.01	.02	.03	.04	.05	.06	.07	.08	.10	.14
			OUTFLOW	3.80	3.99	4.20	4.42	4.68	4.97	5.29	5.38	5.66	6.09
			ELEVATION	18.00	18.10	18.22	18.35	18.52	18.71	18.94	19.00	19.22	19.57
946 1.3			CCCVHITOR	10.00	10.10	10.22	10:00	10.02	101/1	19177	17.00	1/*22	17.07
			STORAGE	.18	.19	.19	.19	.20	.21	.22	.24	.25	.27
			OUTFLOW	6.58	6.67	7.12	8.22	10.26	13.55	18.38	25.03	33.80	45.00
1/4			ELEVATION	20.00	20.01	20.04	20.10	20.17	20.26	20.37	20.50	20.64	20.81
1				70100	20101	T010;	20120	2411/					
			STORAGE	.29			, and a second of				•		. •
9			OUTFLOW	58.90							s	. 19 m	
76			ELEVATION	21.00		**						* "	
			NO XXX MONTE		17 TMD 4444		.a	PIE EDD 011	TELOUE DET	irrki	10 70	50	

*** WARNING *** MODIFIED PULS ROUTING MAY BE NUMERICALLY UNSTABLE FOR OUTFLOWS BETWEEN 10. TO 59.

THE ROUTED HYDROGRAPH SHOULD BE EXAMINED FOR OSCILLATIONS OR OUTFLOWS GREATER THAN PEAK INFLOWS.

THIS CAN BE CORRECTED BY DECREASING THE TIME INTERVAL OR INCREASING STORAGE (USE A LONGER REACH.)

18.0 * 20 JUN 2030 103

.0

HYDROGRAPH AT STATION DA MON HRMN ORD OUTFLOW STORAGE STAGE * DA MON HRMN ORD OUTFLOW STORAGE STAGE * DA MON HRMN ORD OUTFLOW STORAGE STAGE 18.0 * 20 JUN 2020 101 .0 18.0 * 21 JUN 0440 201 20 JUN 1200 1 .0 18.0 18.0 * 21 JUN 0445 202 18.1 * 20 JUN 2025 102 18.0 20 JUN 1205 2 .0 .0 .0

.0

18.0 * 21 JHN 0450 203

10 A

·	-		_	
20 JUN 1215 4 40 18.0 * 20 JUN 2035 104 4.	.0	18.0 * 21 JUN 0455 204	4.	.0 18.0
20 JUN 1220 5 40 18.0 * 20 JUN 2040 105 4.	.0	18.0 * 21 JUN 0500 205	4.	.0 18.0
20 JUN 1225 6 40 18.0 * 20 JUN 2045 106 4.	.0	18.0 * 21 JUN 0505 206	4.	.0 18.0
20 JUN 1230 7 40 18.0 * 20 JUN 2050 107 4.	.0	18.0 * 21 JUN 0510 207	4.	.0 18.0
20 JUN 1235 8 40 18.0 * 20 JUN 2055 108 4.	.0	18.0 * 21 JUN 0515 208	4.	.0 18.0
20 JUN 1240 9 40 18.0 * 20 JUN 2100 109 4.	.0	18.0 * 21 JUN 0520 209	4.	.0 18.0
20 JUN 1245 10 40 18.0 * 20 JUN 2105 110 4.	.0	18.0 * 21 JUN 0525 210	4.	.0 18.0
20 JUN 1250 11 40 18.0 * 20 JUN 2110 111 4.	.0	18.0 * 21 JUN 0530 211	4.	.0 18.0
20 JUN 1255 12 40 18.0 * 20 JUN 2115 112 4.	.0	18.0 * 21 JUN 0535 212	4.	.0 18.0
20 JUN 1300 13 40 18.0 * 20 JUN 2120 113 4.	.0	18.0 * 21 JUN 0540 213	4.	.0 18.0
20 JUN 1305 14 40 18.0 * 20 JUN 2125 114 4.	.0	18.0 * 21 JUN 0545 214	4.	.0 18.0
20 JUN 1310 15 40 18.0 * 20 JUN 2130 115 4.	.0	18.0 * 21 JUN 0550 215	4.	.0 18.0
20 JUN 1315 16 40 18.0 * 20 JUN 2135 116 4.	.0	18.0 * 21 JUN 0555 216	4.	.0 18.0
20 JUN 1320 17 40 18.0 * 20 JUN 2140 117 4.	.0	18.0 * 21 JUN 0600 217	4.	.0 18.0
20 JUN 1325 18 40 18.0 * 20 JUN 2145 118 4.	.0	18.0 * 21 JUN 0605 218	4.	.0 18.0
20 JUN 1330 19 40 18.0 * 20 JUN 2150 119 4.	.0	18.0 * 21 JUN 0610 219	4.	.0 18.0
20 JUN 1335 20 40 18.0 * 20 JUN 2155 120 4.	.0	18.0 * 21 JUN 0615 220	4.	.0 18.0
20 JUN 1340 21 40 18.0 * 20 JUN 2200 121 4.	.0	18.0 * 21 JUN 0620 221	4.	.0 18.0
20 JUN 1345 22 40 18.0 * 20 JUN 2205 122 4.	.0	18.0 * 21 JUN 0625 222	4.	.0 18.0
20 JUN 1350 23 40 18.0 * 20 JUN 2210 123 4.	.0	18.0 * 21 JUN 0630 223	4.	.0 18.0
20 JUN 1355 24 40 18.0 * 20 JUN 2215 124 4.	.0	18.0 * 21 JUN 0635 224	4.	.0 18.0
20 JUN 1400 25 40 18.0 * 20 JUN 2220 125 4.	.0	18.0 * 21 JUN 0640 225	4.	.0 18.0
20 JUN 1405 26 40 18.0 * 20 JUN 2225 126 4.	.0	18.0 * 21 JUN 0645 226	4.	.0 18.0
20 JUN 1410 27 40 18.0 * 20 JUN 2230 127 4.	.0	18.0 * 21 JUN 0650 227	4.	.0 18.0
20 JUN 1415 28 4 0 18.0 * 20 JUN 2235 128 4.	.0.	18.0 * 21 JUN 0655 228	4.	.0 18.0
20 JUN 1420 29 40 18.0 * 20 JUN 2240 129 4.	.0	18.0 * 21 JUN 0700 229	4.	.0 18.0
20 JUN 1425 30 40 18.0 * 20 JUN 2245 130 4.	.0	18.0 * 21 JUN 0705 230	4.	.0 18.0
20 JUN 1430 31 40 18.0 * 20 JUN 2250 131 4.	.0	18.0 * 21 JUN 0710 231	4.	.0 18.0
20 JUN 1435 32 40 18.0 * 20 JUN 2255 132 4.	.0	18.0 * 21 JUN 0715 232	4.	.0 18.0
20 JUN 1440 33 40 18.0 * 20 JUN 2300 133 4.	.0	18.0 * 21 JUN 0720 233	4.	.0 18.0
20 JUN 1445 34 40 18.0 * 20 JUN 2305 134 4.	.0	18.0 * 21 JUN 0725 234	4.	.0 18.0 .0 18.0
20 JUN 1450 35 40 18.0 * 20 JUN 2310 135 4.	.0	18.0 * 21 JUN 0730 235 18.0 * 21 JUN 0735 236	4. 4.	.0 18.0 .0 18.0
20 JUN 1455 36 40 18.0 * 20 JUN 2315 136 4.	.0	18.0 * 21 JUN 0740 237	4.	.0 18.0
20 JUN 1500 37 40 18.0 * 20 JUN 2320 137 4.	.0	18.0 * 21 JUN 0745 238	4.	.0 18.0
20 JUN 1505 38 40 18.0 * 20 JUN 2325 138 4.	.0	18.0 * 21 JUN 0750 239	4.	.0 18.0
20 JUN 1510 39 40 18.0 * 20 JUN 2330 139 4.	.0		4.	.0 18.0
20 000 100 10	.0	18.0 * 21 JUN 0800 241	4.	.0 18.0
20 JUN 1520 41 40 18.0 * 20 JUN 2340 141 4.	.0	18.0 * 21 JUN 0805 242	4.	.0 . 18.0
20 JUN 1525 42 4	.0	18.0 * 21 JUN 0810 243	4.	.0 18.0
20 JUN 1530 43 40 18.0 * 20 JUN 2350 143 4. 20 JUN 1535 44 40 18.0 * 20 JUN 2355 144 4.	.0	18.0 * 21 JUN 0815 244	4.	.0 18.0
Lo Voir Loop II.	.0	18.0 * 21 JUN 0820 245	4.	.0 18.0
	.0	18.1 * 21 JUN 0825 246	4.	.0 18.0
TO 4511 15 15	.0	18.1 * 21 JUN 0830 247	4.	.0 18.0
20 JUN 1550 47 40 18.0 * 21 JUN 0010 147 4. 20 JUN 1555 48 40 18.0 * 21 JUN 0015 148 4.	.0	18.2 * 21 JUN 0835 248	4.	.0 18.0
20 JUN 1600 49 40 18.0 * 21 JUN 0020 149 4.	.0	18.2 * 21 JUN 0840 249	4.	.0 18.0
20 JUN 1605 50 40 18.0 * 21 JUN 0025 150 4.	.0	18.4 * 21 JUN 0845 250	4.	.0 18.0
20 JUN 1610 51 40 18.0 * 21 JUN 0030 151 5.	.i	18.7 * 21 JUN 0850 251	4.	.0 18.0
20 JUN 1615 52 40 18.0 * 21 JUN 0035 152 6.	.1	19.5 * 21 JUN 0855 252	4.	.0 18.0
20 JUN 1620 53 40 18.0 * 21 JUN 0040 153 19.	.2	20.4 * 21 JUN 0900 253	4.	.0 18.0
20 JUN 1625 54 40 18.0 * 21 JUN 0045 154 32.	.3	20.6 * 21 JUN 0905 254	4.	.0 18.0
20 JUN 1630 55 40 18.0 * 21 JUN 0050 155 26.	.2	20.5 * 21 JUN 0910 255	4.	.0 18.0
20 JUN 1635 56 40 18.0 * 21 JUN 0055 156 24.	.2	20.5 * 21 JUN 0915 256	4.	.0 18.0
20 JUN 1640 57 40 18.0 * 21 JUN 0100 157 20.	.2	20.4 * 21 JUN 0920 257	4.	.0 18.0
20 JUN 1645 58 40 18.0 * 21 JUN 0105 158 17.	.2	20.3 * 21 JUN 0925 258	4.	.0 18.0
20 JUN 1650 59 40 18.0 * 21 JUN 0110 159 14.	.2	20.3 * 21 JUN 0930 259	4.	.0 18.0
20 JUN 1655 60 40 18.0 * 21 JUN 0115 160 12.	.2	20.2 * 21 JUN 0935 260	4.	.0 18.0
20 JUN 1700 61 40 18.0 * 21 JUN 0120 161 10.	.2	20.2 * 21 JUN 0940 261	4.	.0 18.0
20 JUN 1705 62 40 18.0 * 21 JUN 0125 162 9.	.2	20.1 * 21 JUN 0945 262	4.	.0 18.0
20 JUN 1710 63 40 18.0 * 21 JUN 0130 163 8.	.2	20.1 * 21 JUN 0950 263	4.	.0 18.0
20 JUN 1715 64 40 18.0 * 21 JUN 0135 164 8.	.2	20.1 * 21 JUN 0955 264	4.	.0 18.0
20 JUN 1720 65 40 18.0 * 21 JUN 0140 165 7.	.2	20.1 * 21 JUN 1000 265	4.	.0 18.0
20 JUN 1725 66 40 18.0 * 21 JUN 0145 166 7.	.2	20.0 * 21 JUN 1005 266) 4.	.0 18.0
20 JUN 1730 67 40 18.0 * 21 JUN 0150 167 7.	.2	20.0 * 21 JUN 1010 267 20.0 * 21 JUN 1015 268		35 18.0 18.0
20 JUN 1735 68 40 18.0 * 21 JUN 0155 168 7.	.2 .2	20.0 * 21 JUN 1013 268 * 1	- 7. A	0 18.0 0 10.0
20 JUN 1740 69 40 18.0 * 21 JUN 0200 169 7.	- /	237-37 ii 23 3388 34201 CD3		

```
18.0
                                                                         20.0 * 21 JUN 1025 270
                                                                                                           .0
20 JUN 1745 70
                                 18.0 * 21 JUN 0205 170
                            .0
                                                                        19.9 * 21 JUN 1030 271
                                                                                                                18.0
                                 18.0 * 21 JUN 0210 171
                                                           7.
                                                                   .2
                                                                                                  4.
20 JUN 1750 71
                            .0
                                                                                                                18.0
                                                                         19.9 * 21 JUN 1035 272
                                                                                                  4.
                                                                                                           .0
                                 18.0 * 21 JUN 0215 172
                                                           6.
20 JUN 1755 72
                            .0
                                                                                                                18.0
                                                                   .2
                                                                        19.8 * 21 JUN 1040 273
                                 18.0 * 21 JUN 0220 173
                                                           6.
20 JUN 1800 73
                    4.
                            .0
                                                                         19.7 * 21 JUN 1045 274
                                                                                                  4.
                                                                                                                18.0
                                                                   .2
                                                                                                          .0
20 JUN 1805 74
                            .0
                                 18.0 * 21 JUN 0225 174
                                                           6.
                                                                 .1
                                                                        19.6 * 21 JUN 1050 275
                                                                                                  4.
                                                                                                                18.0
20 JUN 1810 75
                                 18.0 * 21 JUN 0230 175
                                                                                                          .0
                    4.
                           1.0
                                                                                                                18.0
                                                                        19.4 * 21 JUN 1055 276
                                                                                                   4.
                                 18.0 * 21 JUN 0235 176
                                                           6.
                                                                   .1
20 JUN 1815 76
                            .0
                                                                        19.3 * 21 JUN 1100 277
                                                                                                          .0
                                                                                                                18.0
                                                                   .1
                                 18.0 * 21 JUN 0240 177
                                                           6.
20 JUN 1820 77
                            .0
                                                                                                                18.0
                                                                         19.2 * 21 JUN 1105 278
                                                                                                  4.
                                                                                                          .0
                                                                . .1
20 JUN 1825 78
                    4.
                            .0
                                 18.0 * 21 JUN 0245 178
                                                           6.
                                                                                                  4.
                                                                                                          .0
                                                                                                                18.0
                                                                        19.1 * 21 JUN 1110 279
                                 18.0 * 21 JUN 0250 179
                                                           5.
                                                                  .1
20 JUN 1830 79
                   4.
                            .0
                                                                                                                18.0
                                                           5.
                                                                         18.9 * 21 JUN 1115 280
                                                                                                  4.
                                 18.0 * 21 JUN 0255 180
                                                                   .1
20 JUN 1835 80
                    4.
                            .0
                                                           5.
                                 18.0 * 21 JUN 0300 181
                                                                 .1
                                                                        18.8 * 21 JUN 1120 281
                                                                                                  4.
                                                                                                          .0
                                                                                                                18.0
                            . 0
20 JUN 1840 81
                                                                         18.7 * 21 JUN 1125 282
                                                                                                  4.
                                                                                                          .0
                                                                                                                18.0
                                                                 .1
                                 18.0 * 21 JUN 0305 182
20 JUN 1845 82
                    4.
                            .0
                                                                                                          .0
                                                                                                  4.
                                                                                                                18.0
                                                                         18.5 * 21 JUN 1130 283
                                                                 .0
                                 18.0 * 21 JUN 0310 183
                                                           5.
20 JUN 1850 83
                    4.
                            .0
                                                           5.
                                                                                                  4.
                                                                                                                18.0
                                                                        18.4 * 21 JUN 1135 284
                                                                  .0
                    4.
                            .0
                                 18.0 * 21 JUN 0315 184
20 JUN 1855 84
                                                                                                                18.0
                                                                . .0
                                                                                                  4.
                                                                                                          .0
                           .0
                                 18.0 * 21 JUN 0320 185
                                                           4.
                                                                         18.4 * 21 JUN 1140 285
20 JUN 1900 85
                                                                 .0
                                                                                                                18.0
                                                           4.
                                                                         18.3 * 21 JUN 1145 286
                                                                                                   4.
                                                                                                          .0
                           .0
                                 18.0 * 21 JUN 0325 186
                    4.
20 JUN 1905 86
                                                                        18.3 * 21 JUN 1150 287
                                                                                                  4.
                                                                                                                18.0
                                                           4.
                                                                 .0
                                 18.0 * 21 JUN 0330 187
20 JUN 1910 87
                    4.
                            .0
                                                           4.
                                                                         18.2 * 21 JUN 1155 288
                                                                                                   4.
                                                                                                                18.0
                                                                                                          .0
                          .0
                                 18.0 * 21 JUN 0335 188
                                                                 .0
20 JUN 1915 88
                                                                 .0
                                                                                                  4.
                                                                                                                18.0
                                                                        18.2 * 21 JUN 1200 289
                                                                                                          .0
                                                           4.
                                 18.0 * 21 JUN 0340 189
20 JUN 1920 89
                    4.
                            .0
                                                                                                  4.
                                                                                                                18.0
                                                                 .0
                                                                        18.1 * 21 JUN 1205 290
                                                                                                          .0
                                -18.0 * 21 JUN 0345 190
                            .0
20 JUN 1925 90
                    4.
                                                                                                  4.
                                                                                                                18.0
                                                           4.
                                                                 .0
                                                                        18.1 * 21 JUN 1210 291
                                 18.0 * 21 JUN 0350 191
20 JUN 1930 91
                   4.
                            .0
                                                          4.
                                                                 .0
                                                                         18.1 * 21 JUN 1215 292
                                                                                                  4.
                                                                                                               18.0
                                 18.0 * 21 JUN 0355 192
                           .0
20 JUN 1935 92
                                                                 .0
                                                                        18.1 * 21 JUN 1220 293
                                                                                                  4.
                                                                                                          .0
                                                                                                                18.0
                                                          4.
                                 18.0 * 21 JUN 0400 193
20 JUN 1940 93
                   4.
                           .0
                                                                                                  4.
                                                                                                          .0
                                                                                                                18.0
                                                                        18.1 * 21 JUN 1225 294
                                                          4.
                                                                 .0
                                 18.0 * 21 JUN 0405 194
20 JUN 1945 94
                    4.
                           .0
                                                         4. .0
4. .0
4. .0
4. .0
                                                                                                                18.0
                                                                                                  4.
                                                                        18.1 * 21 JUN 1230 295
                                 18.0 * 21 JUN 0410 195
20 JUN 1950 95
                    4.
                            .0
                                                                        18.0 * 21 JUN 1235 296
                                                                                                  4.
                                                                                                                18.0
                                 18.0 * 21 JUN 0415 196
                            .0
20 JUN 1955 96
                                                                        18.0 * 21 JUN 1240 297
                                                                                                                18.0
                                                                                                  4.
                                                                                                          .0
                                 18.0 * 21 JUN 0420 197
                            .0
20 JUN 2000 97
                    4.
                                                                                                  4.
                                                                         18.0 * 21 JUN 1245 298
                                                                                                          .0
                                                                                                                18.0
                                 18.0 * 21 JUN 0425 198
20 JUN 2005 98
                    4.
                            .0
                                                                                                                18.0
                                                                         18.0 * 21 JUN 1250 299
                    4.
                       .....0
                                 18.0 * 21 JUN 0430 199
20 JUN 2010 99
                                                                                                                18.0
                                 18.0 * 21 JUN 0435 200
                                                                         18.0 * 21 JUN 1255 300
                                                                                                          .0
                                                                   .0
20 JUN 2015 100
                            .0
```

72-HR

18.21

18.21

24-HR

18.22

MAXIMUM AVERAGE FLOW TIME PEAK FLOW 24.92-HR 72-HR 6-HR 24-HR (HR) (CFS) 5. 4. 7. 32. 12.75 (CFS) 2.127 2.064 2.127 (INCHES) .761 3. (AC-FT) MAXIMUM AVERAGE STORAGE TIME PEAK STORAGE 72-HR 24.92-HR (HR) 6-HR 24-HR (AC-FT) 0. 0. 0. 12.75 0. MAXIMUM AVERAGE STAGE PEAK STAGE TIME 24.92-HR

> CUMULATIVE AREA = .08 SQ MI

18.87

6-HR

(FEET)

20.62

(HR)

12.75

STATION RES2

				(I) IN	בוחש לטי	OUTFLOW									
	0.		4.		12.	16.	20.	24.	28. (S	32. STORAGE		. /* /	0 0	. 0	•
- RUDANI	.0		.0	.0	.0	.0	.0	.0	.1	.2		3.	0 .	0 .	0
Dahrmn 201200	PER 1I-								S				,		
201200	2.	I	0	•	•	•		. s							
201203	3.	1	ī	•				. S							
201210	4.		ī	•				. S		. ,		,		•	
201213	5.		I	•				. S				1		•	
201225	6.		ī					. S					•	•	
201223	7.		Ī	•				. S						•	
201235	8.		ī				•	S			•				
201240	9.		Ī					. S				•			
201245	10.		ī				•	. 5					•	•	
201250	11.		. I .					S							
201255			I					S	• •					•	•
201300			Ī				Ē	. S							•
201305			Ī					. S						•	•
201310			Ī					. S					•	• • • • •	•
201315			Ī				ı'	. S				•		•	•
201320			I					S					•		•
201325			Ī					. S					•		•
	19.		I			•		. 9					•		•
201335	20.		Ī				•	. S				•			
201340	21.		. і.					S							
201345	22.		I					S		. •				•	
201350	23.		I					. S				•		•	•
201355			I					. 5	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				• '	•	
201400	25.		I					. S							•
201405			I					. s		•					
201410			I					. S	•					•	
201415			I					. S					•	• • • • • • • • • • • • • • • • • • • •	
201420			I	,, •				. S				•	•		•
201425	30.		I					. S	•			•	• •		•
201430			. I .					S							•
201435			I					· . S		•		•		•	•
201440	33.		I					. S		•		•	•	*	•
201445	34.		I					. S				•	■ ** - *** ** ** * * * * * * *	• •	•
201450	35.		I			•	•	S		•		•	•	•	•
201455			Ι.	and the second		•	•	. S				•	•	•	•
201500			I		•		•	. S				•	•	•	•
201505			I	•	•	•	•					•	•	•	•
201510			I	•	•	•	•	S		•		•	•	•	•
201515			1	•	•	•	•*	. S				• 	•	•	•
201520	41.		. i .			• • • •		s							•
201525	42.		1		•	•	•	. s		•		•	•	•	•
201530			ļ	•	•	•	•	. 5		•		•	•	•	•
201535		-	1		•	•		. 5				• 54 Th 1 4	•	•	•
201540			i T	•	•	•	•	S		•			•		•
201545			ĭ	•		•	•	. s		•				•	
201550	47.	şar ı	Į.	•	ا د دردید ساد	•		. s		•				•	
201555			1		•	•	•	. S		-			· .		
201600	49. 50.		I T	•		•	•	. S				-		•	
201605	50. 51.		Ţ	•		•									
201610 201615			 T								- • • •	. •	11 -	スト	
201620			ĭ	•	•	•		S	; .			. K	1		
201625			ī	•	•	•	•	. S					•		
201023	JT.						<u> </u>			<u> </u>		<u> </u>		·	

	201630	55.				s				. S		ı		:			
:	201635	56.]	Ī		•		•	. S			, ,			•	•
	201640				[•	•	•	•	. S	•	1		•	•	•	•
	201645 201650	58. 59.			l T	• '	<u>.</u>	•		. s						•	
	201655			j			•	•		. s					• ,	•	
					I					.· S							
	201705]	Ī					. 5		,		ı		•	•
	201710				I -	•	•	•	•	. s . s	•	i		•	•		•
	201715 201720				l T	•	•	•		. s	•		•		•		
	201725			1	<u>.</u> [•		•		. s			•				
	201730				I	•	•			. s		i .		•	•	•	•
	201735				[•	•	•		. S	•			ı	•		•
	201740				I	•	•	•	• .	. S	•	•	•	•	•	•	
	201 745 201 75 0				L T	•				. s							
	201755			• • •	 [. S			• • •				•
	201800				I				•	. S		1		ı		•	•
	201805			1	I	*			•	. S	•		•	•	• 1	•	•
	201810				I .	•	•	•	•	. S	•	•	•	1			•
	201815 201820				l T	•				. s			•		• '	•	
	201825				I	•			•	. S			. ,	:	•	•	•
	201830	79.		. :	I				•	. S		,	<u>1</u>	1	•	•	•
	201835				* . k.	<u>.</u>	•	•	•	. 5	•		. ,	1	•		
	201840 201845			• • •	l T					. S							
	201850			•	I					. 5						1	
	201855				- I .					. S				ı		1	•
	201900				I		•	•		. 5		• • • •	# **	1	•	•	•
	201905				[*	•	•	•		. S			•	l The second second		•	•
	201910 201915				ı T		•	• 		. s							•
	201920				Ī		•			. S	•		•		•	•	
	201925				I		•	•	•	. 5	•		•	•	• •	•	•
	201930		• •	•	I					. s							•
	201935 201940			•	I .	•		•		. 5		•		•		•	
	201945				I		•			. 5				ı	•		•
	201950				I		•	•		. S	•	•	•	1	•	•	•
	201955				[•	*	•		. S	•					•	
	202000 202005			,	i T	•				. s					•		
	202010			•	I	•	•			. S		•					•
	202015					•	•	•	•	. 5	•	,				, ,	•
	202020 202025		• •	• •	[• • • • •	* 1.1.1.1.1.1.		. S							
	202023				ı I			•	• •	. 5			•	1		•	
	202035				I	•	•			. S		,		•			•
	202040					•	•	•	•	. S	•		• ,	ı	•	•	•
	2020 45 202050				<u>.</u> T	•	•	•	•	. S	•			•			
	202055				[•			. S				:		, ,	
	202100				I	•	•		•	. S			•	•	•	•	•
	202105]			•	•		. S	. •	1				, , ,	•
	202110 202115			• • ;	l r					. 5 . S							
	202115				i I		•	•	•	. 5			•	,		,	• .
	202125	114.		.]		•		•	• ,	. S	•	!					•
	202130	115.			·	•	•	•	•	. S	•	•	•				•
	202135 2021 4 0]	! [•		•		. S	•		· ` · ·		•		
	202140			. 1				•		. S			,	DI	-34	, ,	•
	202150	119.			_	•	•			. 5	,		• ,	KI:	7 34	9	•
•	707155	120		1	Ī	-			•	. S		•	•	ĺ	. •	•	•

the second control of the second control of

Adjustment of the post of the Common of the

	202200	121.		 Ι.										. 5						
	202205	122		ĭ		_								. S					•	•
				÷		•			•	_				. S			_	_	_	
	202210			i		•			•		ı	•			•		•	•	•	•
	202215	124.		I										. S	•		•	•	•	•
	202220			ī								_		. S					•	
						•		,	•		1	•								
	202225	126.		 Ι					•	•		•		. S	•	. * * *	•	•	•	•
	202230	127		Ţ		_								. S		ı				•
						•			•					. S			_	_	_	
	202235			1		•		•	•						•		•	•	•	•
	202240	129.		I							l	•		. 5	•	ı	•	•	•	•
				7										. S						
	202245			1				•	•	•		•			•			•		
	202250	131.		 Ι.										. 5						
	202255	132		Ţ		_								. S					•	
				•		•			•					. S			_	_	_	
	202300	133.		i					•	,	1	٠			•	1	•	•	•	•
	202305	134.		I										. S			•	•	•	•
	202310			ī										. S		1				
				1		•			•	•	*	•								
	202315	136.		I						•	ı	•		. 5	•		:	•	•	•
	202320	137.		Ī							1			. S			•		•	•
				7		•								. S			_			
	202325			I		•		1	•	•		•			•		•	•	•	·
	202330	139.		Ι							,			. S	•		•	•	•	•
	202335			Ţ										. S			•		**	
						*		1	•			•		c						
	202340			 i.										. 0						•
• '	202345	142.	•	I										. S			•	•		
				ī		-						_		. S		ı				
	202350			•		•			•	•	l.	•				•	-	-	-	
	202355	144.		Ι							į	•		. S	•	1		•	• 1	•
	210000			ī								_		. S					. •	
				-		•			•		J	• •								
	210005	146.		OI						,	i			. S			•	•	•	Para Para Para Para Para Para Para Para
	210010			OI					_					. S		i			•	
						•			•			-		. S						_
	210015	148.		01					•		1	•					•	•	•	•
	210020	149.		.0	ī						1			. 5	3 .		•		• ,	•
						•			-						s .		_	_		
	210025			.0	1	*		,	•	•	1	•		•	٠, ١		•	•	•	
	210030	151.		 . 0		Ι.									. 5					
	210035				0									I		S				
				•	u	•			•		١.	_		-			. s			
	210040	153.							•		:	0.		•	` -			•	•	•
																Ι	0 S	•		•
	210045	174																		
	210045			•		•			•	•	•	•			T .		. 5			
	210050	155.								,	•	•	_		Ι.	1	. 5	•	•	
	210050	155.		•						•	•	•	I		Ι.	ı	. S	•	•	• • // //
•	210050 210055	155. 156.						1	•	•	•			0	Ι.			* ************************************	• • • • • • • • • • • • • • • • • • •	#
	210050 210055 210100	155. 156. 157.		•		•		•		•		I .0		0	Ι .		. S	# ************************************	•	#
•	210050 210055	155. 156. 157.				•		•	* · · · · · · · · · · · · · · · · · · ·			0. I		0	I		. S . S	•	•	e Populari E
	210050 210055 210100 210105	155. 156. 157. 158.				•		•			0	I .0		0	I		. S	• • • • • • • • • • • • • • • • • • •	•	en periodical designation of the second of t
	210050 210055 210100 210105 210110	155. 156. 157. 158. 159.			: 4 F	•					0	1.0		0	I	i	. S . S . S		•	
	210050 210055 210100 210105 210110 210115	155. 156. 157. 158. 159. 160.		*	·	•		Ι (0	1 .0		0	I	ı	. S . S .S .S	•		
	210050 210055 210100 210105 210110 210115	155. 156. 157. 158. 159. 160.		 		•	.1.0.	Ι (0	I .0		0	I		. S . S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120	155. 156. 157. 158. 159. 160.				•	.I.O.	Ι (0	1.0			I		. S . S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125	155. 156. 157. 158. 159. 160. 161.				I	.I.O. O	Ι (0	I .0		0	I		. S . S . S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130	155. 156. 157. 158. 159. 160. 161. 162.				10	.I.O. O	Ι (0	1.0		0	I .		. S . S . S . S . S S S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130	155. 156. 157. 158. 159. 160. 161. 162.					.I.O. O	Ι (0	1.0		0	I	S	. S . S . S . S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135	155. 156. 157. 158. 159. 160. 161. 162. 163.				10 I.	.I.O. O	Ι (0	1.0		0	I		. S . S . S . S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140	155. 156. 157. 158. 159. 160. 161. 162. 163. 164.				IO I. I.	.I.O. O	Ι (0	1.0			I		. S . S . S . S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165.				IO I. I.	.I.O. O	Ι (0	1.0			I		. S . S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165.				IO I. I.	.I.O. O	Ι (0	I .0			I		. S . S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166.	• •		I	IO I. I. I.	.I.O. O	Ι (0	I .0			I .		. S . S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210155	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167.	• •		I	IO I. I. O.	.I.O. O	Ι (0	I .0			I		. S . S . S . S . S . S 			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210155 210200	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168.	• •		I I I0	IO I. I. O.	.I.O. O	Ι (0	I .D			I		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210155 210200	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168.	• •		I	IO I. I. O.	.I.O. 0	Ι (0	1.0			I		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210155 210200 210205	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168.	• •		I I0 I0	IO I. I. O.	.I.O. 0	I (0	0	1.0			I		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210200 210205 210210	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 169. 170.	•		I IO IO I O	IO I. I. O.	.I.O. 0	I (0	0	I .0			I		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210155 210200 210205	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 169. 170.	•		I IO IO I O I O	IO I. I. O.	.I.O. 0	I (0	0	I .0			I		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210140 210145 210150 210200 210205 210210 210210	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 169. 170.	•		I IO IO I O I O	IO I . I . O .	.I.O. 0	I (0	0	1.0			I		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210205 210200 210205 210210 210215 210220	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171. 172.		 . I	I IO IO IO IO	IO I . I . O .	.I.O. 0	I (0	0	1.0			I		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210155 210200 210205 210210 210215 210220 210225	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 170. 171. 172. 173.	• •		1 10 10 0 0 0 0	IO I . I . O .	.I.O. 0	I (0	0	1.0			I		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210155 210200 210205 210210 210215 210220 210225	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 170. 171. 172. 173.	• •	. I	I IO IO IO IO	IO I . I . O .	.I.O. 0	I (0	0	1.0					. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210155 210200 210205 210210 210215 210220 210225 210230	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 177. 178. 179. 171. 172. 173. 174.	•		0 0 10 10 10 10	IO I . I . O .	.I.O. 0	I (0	0	1.0					. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210155 210200 210205 210210 210225 210220 210225 210230 210235	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 177. 178. 179. 171. 172. 173. 174.	• •	· · · · · · · · · · · · · · · · · · ·	I IO IO I O O O O O	IO I . I . O .	.I.O. 0	I (0	0	1.0					. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210155 210200 210205 210210 210215 210220 210225 210230	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 177. 178. 179. 171. 172. 173. 174.	• •	· · · · · · · · · · · · · · · · · · ·	0 0 10 10 10 10	IO I . I . O .	.I.O. 0	I (0	0	1.0					. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210155 210200 210205 210210 210215 210220 210225 210230 210235 210240	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171. 172. 173. 174. 175.	•		I IO IO IO O O O	IO I . I . O .	.I.O. 0	I (0	0	1.0					. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210200 210205 210210 210215 210220 210225 210220 210225 210230 210235 210240 210245	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 170. 171. 172. 173. 174. 175. 176. 177.	• •		0 0 0 10 10 0 0 0 0 0	IO I . I . O .	.I.O. 0	I (0	0	1.0					. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210200 210205 210210 210215 210220 210225 210230 210235 210240 210245 210255	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179.	•		I IO IO IO O O O	IO I . I . O .	.I.O. 0	I (0	0	I .0			S		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210200 210205 210210 210215 210220 210225 210230 210235 210240 210245 210255	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179.	•		I I I I I I I I I I I I I I I I I I I	IO I . I . O .	.I.O. 0	I (0	0	I .0			SSSS		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210200 210205 210210 210215 210220 210225 210230 210235 210240 210245 210250 210255 210255	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 177. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180.	•		I IO IO O O O O O O O O O O O O O O O O	IO I . I . O .	.I.O. 0	I (0	0	1.0			S		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210205 210200 210205 210210 210225 210220 210225 210230 210240 210245 210250 210255 210300	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180. 181.			I IO IO O O O O O O O O O O O O O O O O	IO I . I . O .	.I.O. 0	I (0	0	1.0			S S S S		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210200 210205 210210 210215 210220 210225 210230 210235 210240 210245 210250 210255 210255	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180. 181.			I IO IO O O O O O O O O O O O O O O O O	IO I . I . O .	.I.O. 0	I (0	0	I .0			S S S S		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 21025 210200 210205 210210 210225 210220 210225 210230 210240 210255 210250 210255 210250 210255 210300 210305	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180. 181. 182.	•		I IO IO O O O O O O O O O O O O O O O O	IO I . I . O .	.I.O. 0	I (0	0	I .0			S S S S		. S . S . S . S			
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210155 210200 210205 210210 210225 210220 210225 210230 210240 210245 210250 210255 210300 210305 210300 210305 210310	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 178. 179. 171. 175. 176. 177. 178. 179. 180. 181. 182. 183.	•		I IO IO O O O O O O O O O O O O O O O O	IO I . I . O .	.I.O. 0	I (0	0	I .0			S S S S S S		. S . S . S . S		· · · · · · · · · · · · · · · · · · ·	
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210205 210200 210205 210210 210225 210220 210225 210230 210240 210245 210250 210255 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210310 210310 210315	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173. 174. 175. 176. 177. 180. 181. 182. 183. 184.			I IO IO O O O O O O O O O O O O O O O O	IO I . I . O .	.I.O. 0	I (0	0	1.0					. S . S . S . S		₹1- €	37
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210205 210200 210205 210210 210225 210220 210225 210230 210240 210245 210250 210255 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210310 210310 210315	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173. 174. 175. 176. 177. 180. 181. 182. 183. 184.			I IO IO O O O O O O O O O O O O O O O O	IO I . I . O .	.I.O. 0	I (0	0	1.0			S S S S S S		. S . S . S . S	F	₹1 - €	37
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210205 210200 210205 210210 210225 210230 210235 210240 210245 210255 210250 210255 210300 210305 210310 210315 210300 210315 210300 210315 210300 210315 210330	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179. 181. 182. 183. 184. 185.	•		I IO IO O O O O O O O O O O O O O O O O	IO I . I . O .	.I.O. 0	I (0	0	1.0					. S . S . S . S		71- 3	371
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210205 210200 210205 210210 210225 210220 210225 210230 210240 210245 210250 210255 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210300 210355 210310 210310 210315	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179. 181. 182. 183. 184. 185.	•		I IO IO O O O O O O O O O O O O O O O O	IO I . I . O .	.I.O. 0	I (0	0	I .0					. S . S . S . S		₹1- €	371

,

									c		*	•		
210330			1	0	•	•	•	•	. S	•	•	1	•	1
210335					•	•	•	•	. s		•	•		
210340			1	L !	•	•	•	•	. s	•	•			
210345				! T	•	•	•	•	. S	•		•		·
210350			• •		• • • • •				. S					
210355			į		•	•	•	•	. s	•	•	•		
210400				<u>[</u>	•	•	•	-	_	•	•	•	•	ı
210405					•	•	•	•	. S . S	•	•	•	• •	
210410					•	•	•	•		•	•	•		
210415]		•		•	• '	. S	•	•	•		
210420]	[•	•	•	•	. S	•	•	•	•	•
210425			3			•	•	•	. S	•	•	•		
210430]		•		•	•	. 5	•		•		
210435			3	[•	•	. S	•	•	•		
210440			•]	[. S					
210445			1				•	•	. S	• •	,	•		
210450	203.]		•		•	-	. S	•	•	•	•	
210455	204.]	[•	-	. S	•		•		
210500	205.		1	[-	. S	•	•			
 210505	206.]		•			-	. S	•	•	•		
210510]			• .			. S	•		•		
210515]	[,				-	. S					
210520			1					•	. S	•				
210525]	lan at well			•		. s					
210530			. 1						. S					
210535)						. S.			•	. ,	
210540			1						. S	•				
210545]	[.				****	. S	• .				
210550]	[. S					
210555			1		•		•	. :	. S					
210600				Ī				1	. S				, ,	
210605			,	-			•	. :	. S					
210610			1	· .	• •		-		. S					
210615			. 1		• -	_	•		. S					
			•		-									
210620	221.		.]	[. S ·					
210620		• • •	.]		<i>.</i> .				. S . S					
210625	222.]	[. , ,										
210625 210630	222. 223.]	[e 1	. S			, , , , , , , ,		a arte en en
210625 210630 210635	222. 223. 224.				• • • • •				. S	•	• • • • • • • • • • • • • • • • • • •	• • • • • • • •	· · · · · · · · · · · · · · · · · · ·	4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
210625 210630 210635 210640	222. 223. 224. 225.				•	•	· · · · · · · · · · · · · · · · · · ·	•	. S . S	• • • • • • • • • • • • • • • • • • •	• • • • •	• • • • • • • • • • • • • • • • • • •		
210625 210630 210635 210640 210645	222. 223. 224. 225. 226.				•		•	•	. S . S . S	· · · · · · · · · · · · · · · · · · ·	• • • • • • • • • • • • • • • • • • •	· · · · · · · · · · · · · · · · · · ·		
210625 210630 210635 210640 210645 210650	222. 223. 224. 225. 226. 227.				• • • • •	• • • • • •	• • • • • • •	•	. S . S . S . S		• • • • •	• • • • • • • • • • • • • • • • • • •		
210625 210630 210635 210640 210645 210650 210655	222. 223. 224. 225. 226. 227. 228.	•••			•	•		•	. S . S . S . S	• • • • • • • • • • • • • • • • • • •				
210625 210630 210635 210640 210645 210655 210700	222. 223. 224. 225. 226. 227. 228. 229.	• • •			•			•	. S . S . S . S . S	• • • • • • • • • • • • • • • • • • •				
210625 210630 210635 210640 210645 210650 210655 210700 210705	222. 223. 224. 225. 226. 227. 228. 229. 230.							•	. S . S . S . S . S					
210625 210630 210635 210640 210645 210655 210700 210705 210710	222. 223. 224. 225. 226. 227. 228. 229. 230. 231.							•	. S . S . S . S . S					
210625 210630 210635 210640 210645 210655 210700 210705 210710 210715	222. 223. 224. 225. 226. 227. 228. 229. 230. 231. 232.							•	. S . S . S . S . S					
210625 210630 210635 210640 210645 210655 210700 210705 210710 210715 210720	222. 223. 224. 225. 226. 227. 228. 229. 230. 231. 232. 233.							•	. S . S . S . S . S					
210625 210630 210635 210640 210645 210655 210700 210705 210710 210715 210720 210725	222. 223. 224. 225. 226. 227. 228. 229. 230. 231. 232. 233. 234.							•	. S . S . S . S . S . S . S . S . S . S					
210625 210630 210635 210640 210645 210655 210700 210705 210710 210715 210720 210725 210730	222. 223. 224. 225. 226. 227. 228. 229. 230. 231. 232. 233. 234. 235.							•	. S . S . S . S . S . S . S . S . S . S					
210625 210630 210645 210645 210650 210655 210700 210705 210715 210720 210725 210730 210735	222. 223. 224. 225. 226. 227. 228. 229. 230. 231. 232. 233. 234. 235. 236.							•	. S . S . S . S . S . S . S . S . S . S					
210625 210630 210645 210645 210655 210700 210705 210710 210720 210720 210725 210730 210740	222. 223. 224. 225. 226. 227. 228. 229. 230. 231. 232. 233. 235. 236. 237.							•						
210625 210630 210645 210645 210655 210700 210705 210710 210715 210720 210725 210730 210730 210740 210745	222. 223. 224. 225. 226. 227. 228. 229. 230. 231. 232. 233. 234. 235. 236. 237. 238.							•						
210625 210630 210635 210640 210655 210655 210700 210705 210710 210725 210720 210730 210730 210740 210745 210750	222. 223. 224. 225. 226. 227. 238. 239. 231. 232. 233. 234. 235. 236. 237. 238. 239.							•						
210625 210630 210640 210645 210655 210700 210705 210710 210720 210725 210730 210735 210740 210745 210750 210755	222. 223. 224. 225. 226. 227. 230. 231. 232. 233. 234. 235. 236. 237. 238. 239.							•	555555555555555555555555555555555555555					
210625 210630 210645 210645 210655 210700 210705 210710 210715 210720 210725 210730 210740 210745 210755 210755 210800	222. 223. 224. 225. 226. 227. 238. 231. 232. 233. 234. 235. 237. 238. 239. 240.							•	555555555555555555555555555555555555555					
210625 210630 210645 210645 210655 210700 210705 210715 210720 210725 210730 210735 210740 210745 210755 210750 210755 210800 210805	222. 223. 224. 225. 226. 227. 228. 230. 231. 232. 233. 234. 235. 236. 237. 238. 239. 240. 241. 242.							•	555555555555555555555555555555555555555					
210625 210630 210645 210645 210655 210700 210705 210715 210720 210725 210730 210745 210740 210755 210750 210755 210800 210805 210810	222. 223. 224. 225. 226. 227. 228. 230. 231. 232. 233. 234. 235. 236. 237. 238. 239. 240. 241. 242.							•						
210625 210630 210645 210645 210655 210700 210705 210715 210720 210725 210730 210735 210740 210745 210750 210800 210805 210810 210815	222. 223. 224. 225. 226. 227. 228. 239. 231. 232. 233. 234. 235. 236. 237. 238. 239. 240. 241. 242. 243.							•						
210625 210630 210645 210645 210655 210700 210705 210715 210720 210725 210730 210735 210740 210745 210750 210805 210805 210815 210820	222. 223. 224. 225. 226. 227. 238. 239. 231. 232. 233. 234. 235. 236. 237. 238. 239. 240. 241. 242. 243.							•						
210625 210630 210645 210645 210655 210700 210705 210710 210715 210720 210725 210730 210735 210740 210745 210750 210805 210805 210815 210820 210825	222. 223. 224. 225. 226. 227. 230. 231. 232. 233. 234. 235. 236. 237. 238. 239. 240. 241. 242. 243. 244. 245.							•						
210625 210630 210645 210645 210655 210700 210705 210710 210715 210720 210725 210730 210740 210745 210750 210755 210810 210815 210810 210815 210820 210825 210830	222. 223. 224. 225. 226. 227. 230. 231. 232. 233. 234. 235. 237. 238. 239. 240. 241. 242. 243. 244. 245. 247.							•						
210625 210630 210645 210645 210655 210700 210705 210710 210715 210720 210725 210730 210740 210745 210755 210810 210815 210810 210815 210820 210830 210835	222. 223. 224. 225. 226. 227. 230. 231. 232. 233. 234. 235. 237. 238. 239. 240. 241. 242. 243. 244. 245. 246. 247.							•						
210625 210630 210645 210645 210655 210700 210705 210710 210715 210720 210725 210730 210740 210745 210755 210800 210805 210815 210820 210825 210830 210835 210840	222. 223. 224. 225. 226. 227. 228. 230. 231. 232. 233. 234. 235. 237. 238. 239. 240. 241. 242. 243. 244. 245. 247. 248.							•				R1.	- 38	
210625 210630 210645 210645 210655 210700 210705 210710 210715 210720 210725 210730 210740 210745 210755 210800 210805 210815 210820 210825 210830 210835 210840 210845	222. 223. 224. 225. 226. 227. 228. 230. 231. 232. 233. 234. 235. 237. 238. 239. 240. 241. 242. 243. 244. 245. 247. 248. 249.							•				R1.	- 38	
210625 210630 210645 210645 210655 210700 210705 210710 210715 210720 210725 210730 210740 210745 210755 210800 210805 210815 210820 210825 210830 210835 210840	222. 223. 224. 225. 226. 227. 228. 230. 231. 232. 235. 236. 237. 238. 239. 241. 242. 243. 244. 245. 246. 247. 248. 249. 250. 251.											R1.	38	

```
**********
 129 KK
            ***********
 131 KO
                 OUTPUT CONTROL VARIABLES
                       IPRNT
                                      3 PRINT CONTROL
                       IPLOT
                                      1 PLOT CONTROL
                       QSCAL
                                      O. HYDROGRAPH PLOT SCALE
                       IPNCH
                                      1 PUNCH COMPUTED HYDROGRAPH
                                    21 SAVE HYDROGRAPH ON THIS UNIT
                       IOUT
                       ISAV1
                                      1 FIRST ORDINATE PUNCHED OR SAVED
                       ISAV2
                                     300 LAST ORDINATE PUNCHED OR SAVED
                                    .083 TIME INTERVAL IN HOURS
                      TIMINT
               HYDROGRAPH ROUTING DATA
 132 RD
                 MUSKINGUM-CUNGE CHANNEL ROUTING
                                   400. CHANNEL LENGTH
                           S
                                   .0079 SLOPE
                                    .025 CHANNEL ROUGHNESS COEFFICIENT
                          N
                          CA
                                    .00 CONTRIBUTING AREA
                      SHAPE
                                   TRAP CHANNEL SHAPE
                          WD)
                                   2.00 BOTTOM WIDTH OR DIAMETER
                          Z
                                   3.00 SIDE SLOPE
                                   COMPUTED MUSKINGUM-CUNGE PARAMETERS
                                          COMPUTATION TIME STEP
                   ELEMENT
                              ALPHA
                                                    DT
                                                                       PEAK
                                                                               TIME TO
                                                                                           VOLUME
                                                                                                    MAXIMUM
                                                                                 PEAK
                                                                                                    CELERITY
                                                  (MIN)
                                                             (FT)
                                                                      (CFS)
                                                                                (MIN)
                                                                                            (IN)
                                                                                                     (FPS)
                     MAIN
                                2.12
                                          1.34
                                                     1.39
                                                             200.00
                                                                       31,44
                                                                                 766.62
                                                                                            2.12
                                                                                                      4.80
                                         INTERPOLATED TO SPECIFIED COMPUTATION INTERVAL
                                2.12
                                                     5.00
                                                                       28.87
                                                                                 765.00
                                                                                            2.12
                     MAIN
                                          1.34
CONTINUITY SUMMARY (AC-FT) - INFLOW= .9246E+01 EXCESS= .0000E+00 OUTFLOW= .9233E+01 BASIN STORAGE= .1416E-01 PERCENT ERROR=
```

MAXIMUM AVERAGE FLOW
24-HR 72-HR 24-92-HR

CH4

HYDROGRAPH AT STATION

PEAK FLOW

TIME

R1-40

```
CUMULATIVE AREA =
                                           .08 SQ MI
*** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** ***
           **********
133 KK
                 B345 *
           **********
135 KO
               OUTPUT CONTROL VARIABLES
                    IPRNT
                                   3 PRINT CONTROL
                    IPLOT
                                   1 PLOT CONTROL
                    QSCAL
                                  O. HYDROGRAPH PLOT SCALE
                    IPNCH
                                  1 PUNCH COMPUTED HYDROGRAPH
                     IOUT
                                  21 SAVE HYDROGRAPH ON THIS UNIT
                    ISAV1
                                   1 FIRST ORDINATE PUNCHED OR SAVED
                    ISAV2
                                 300 LAST ORDINATE PUNCHED OR SAVED
                   TIMINT
                                 .083 TIME INTERVAL IN HOURS
             SUBBASIN RUNOFF DATA
136 BA
              SUBBASIN CHARACTERISTICS
                    TAREA
                             .01 SUBBASIN AREA
               PRECIPITATION DATA
137 PH
                                    DEPTHS FOR O-PERCENT HYPOTHETICAL STORM
               ..... HYDRO-35 .....
                                             ...... TP-40 ......
                                                                          ..... TP-49 .....
              5-MIN 15-MIN 60-MIN
                                             3-HR
                                                     6-HR
                                                         12-HR 24-HR
                                                                          2-DAY
                                      2-HR
                                                                                4-DAY
                                                                                         7-DAY 10-DAY
                                                                                   .00
                      .76
                              1.34
                                            1.44
                                                     1.56
                                                           1.69
                                                                  2.01
                                                                            .00
                                      1.40
                                                                                           .00
                                              STORM AREA =
                                                              .01
138 LS
              SCS LOSS RATE
                    STRTL
                                 .27 INITIAL ABSTRACTION
                   CRVNBR
                               88.00 CURVE NUMBER
                    RTIMP
                                 .00 PERCENT IMPERVIOUS AREA
139 UD
              SCS DIMENSIONLESS UNITGRAPH
                    TLAG
                                 .32 LAG
                                                    UNIT HYDROGRAPH -
                                                21 END-OF-PERIOD ORDINATES
                       7.
                               14.
                                         17.
                                                  17.
                                                           14.
                                                                     10.
              2.
                                                                               7.
                                                                                                  3.
                                1.
                                                   0.
                                                           0.
                                                                      0.
                                         1.
                     HYDROGRAPH AT STATION
```

R1-41

29.

12.75

(CFS)

2.01, TOTAL LOSS =

1.04, TOTAL EXCESS =

MAXIMIM AVERAGE FINW

TOTAL RAINFALL =

TIME

PEAK FLOW

(INCHES)

(AC-FT)

7.

.762

5.

2.125

9.

2.125

2.064

```
9.
              12.42
                          (CFS)
                                      1.
                                                  0.
                                                             0.
                                                                          0.
                       (INCHES)
                                     .833
                                                .973
                                                            .973
                                                                         .973
                       (AC-FT)
                                                  1.
                                                             1.
                                                                          1.
                       CUMULATIVE AREA =
                                             .01 SQ MI
           **********
 140 KK
                  B345 *
           ******
 142 KO
                OUTPUT CONTROL VARIABLES
                      IPRNT
                                      3 PRINT CONTROL
                                      1 PLOT CONTROL
                      IPLOT
                      QSCAL
                                    O. HYDROGRAPH PLOT SCALE
                      IPNCH
                                        PUNCH COMPUTED HYDROGRAPH
                       IOUT
                                    21 SAVE HYDROGRAPH ON THIS UNIT
                      ISAV1
                                     1 FIRST ORDINATE PUNCHED OR SAVED
                      ISAV2
                                   300 LAST ORDINATE PUNCHED OR SAVED
                     TIMINT
                                   .083 TIME INTERVAL IN HOURS
143 HC
               HYDROGRAPH COMBINATION
                      ICOMP
                                     2 NUMBER OF HYDROGRAPHS TO COMBINE
                       HYDROGRAPH AT STATION
                                                 B345
PEAK FLOW
             TIME
                                           MAXIMUM AVERAGE FLOW
  (CFS)
            . (HR)
                                   6-HR
                                              24-HR
                                                          72-HR
                                                                   24.92-HR
    34.
            12.75
                        (CFS)
                                    8.
                                                5.
                                                            5.
                                                                        5.
                      (INCHES)
                                   .772
                                              1.912
                                                          1.964
                                                                      1.964
                      (AC-FT)
                                                           10.
                                                                        10.
                                                10.
                                            .09 SQ MI
                      CUMULATIVE AREA =
          **********
144 KK
                 RES3 *
          **********
146 KO
               CUTPUT CONTROL VARIABLES
                     IPRNT
                                    1 PRINT CONTROL
                     IPLOT
                                    2 PLOT CONTROL
                                    O. HYDROGRAPH PLOT SCALE
                     QSCAL
                                       PUNCH COMPUTED HYDROGRAPH
                                                                                                   R1-42
                     IPNCH
```

SAVE HYDROGRAPH ON THIS UNIT

1 FIRST ORDINATE PUNCHED OR SAVED

IOUT

ISAV1

24-HR

6-HR

72-HR

24.92-HR

(CFS)

(HR)

ISAV2 300 LAST ORDINATE PUNCHED OR SAVED TIMINT .083 TIME INTERVAL IN HOURS

HYDROGRAPH ROUTING DATA

147 RS	STORAGE ROUT	TNG					
147 110	NSTPS		NUMBER OF	SUBREACHE	5		
	ITYP	_	TYPE OF IN				
	RSVRIC	12.83	INITIAL CO	ONDITION			
	<u>.</u> X	.00	WORKING R	AND D COEFI	FICIENT		
148 SV	STORAGE	.1	.2	.4	.7		
149 SE	ELEVATION	14.20	15.20	16.20	17.20		
150 SL	LOW-LEVEL OU	TLET					
	ELEVL	13.83	ELEVATION	AT CENTER	OF OUTLET		
	CAREA	.06	CROSS-SECT	TIONAL AREA	}		
	COQL	.60	COEFFICIEN	VT			
	EXPL	.50	EXPONENT (OF HEAD	174	* **	
151 SS	SPILLWAY						
	CREL	15.75	SPILLWAY (REST ELEVA	MOIT		
	SPWID	14.00	SPILLWAY W	IIDTH			
	COQW	2.70	WEIR COEFF	ICIENT			
	EXPW	1.50	EXPONENT O	IF HEAD			

			COM	PUTED OUTF	LOW-ELEVAT	ION DATA	
	OUTFLOW .00	.20	.21	.23	.24	.27	
	ELEVATION 14.20		14.31	14.39	14.49	14.61	

UUITLUW	.00	. 20	.21	.23	• 24	• Z /	• 27	•34	*70	.42
ELEVATION	14.20	14.25	14.31	14.39	14.49	14.61	14.77	14.99	15.30	15.75
OUTFLOW	.49	.96	2.23	4.70	8.74	14.77	23.17	34.34	48.67	66.55
ELEVATION	15.76	15.81	15.88	15.98	16.11	16.27	16.46	16.68	16.92	17.20
								*		
	•		COMPUTE	D STORAGE-	OUTFLOW-EL	EVATION DA	TA	* * .		
STORAGE	.08	.09	.10	.11	.12	.14	.16	.19	.22	.24
OUTFLOW	.18	.20	.21	.23	.24	.27	.29	.32	.35	.36
ELEVATION	14.20	14.25	14.31	14.39		14.61	14.77	14.99	15.20	15.30
STORAGE	.33	.33	.34	.35	.37	.40	.42	.43	.48	.53
OUTFLOW	.42	. 49	.96	2.23	4.70	8.74	11.87	14.77	23.17	34.34
ELEVATION	15.75	15.76	15.81	15.88	15.98	16.11	16.20	16.27	16.46	16.68
STORAGE	.60	.66			-					
OUTFLO W	48.67	66.55								
ELEVATION	16.92	17.20								•
		* * * * *								

HYDROGRAPH AT STATION RES3

						*					*				**
DA I	MON	HRMN	ORD	OUTFLOW	STORAGE	STAGE * DA	MON HE	RMN ORD	OUTFLOW	STORAGE	STAGE * DA	A MON HRMN ORD	OUTFLOW	STORAGE	STAGE
20 .	JUN	1200	1	0.	.1	14.2 * 20	JUN 20	20 101	4.	.4	15.9 * 21	JUN 0440 201	4.	. 4	16.0
20 3	JUN	1205	2	0.	.1	14.3 * 20	JUN 20	25 102	4.	.4	15.9 * 21	JUN 0445 202	4.	.4	16.0
20 3	JUN	1210	3	0.	.1	14.4 * 20	JUN 20	30 103	4.	.4	15.9 * 21	JUN 0450 203	1041	_ 4.4	16.0
20 3	TUN	1215	4	. 0.	.1	14.6 * 20	JUN 20	35 104	4.	.4	15.9 * 21	JUN 0455 204	L/I	- →	16.0
20 .	JUN	1220	5	0.	.2	14.7 * 20	JUN 20	40 105	4.	.4	15.9 * 21	JUN 0500 205	4.	.4	16.0

20 JUN	1225	6	0.		.2	14.9 *	20 JUN	2045	106		4.		.4	15.9	* 21	JUN	0505	206	4.	.4	
20 JUN		7	0		.2	15.1 *	20 JUN	2050	107		4.		.4	15.9	* 21	JUN	0510	207	4.	.4	16.0
20 JUN		8	0.		.2	15.2 *	20 JUN	2055	108		4.		.4	15.9	* 21	JUN	0515	208	4.	.4	16.0
20 JUN		9	0		.3	15.4 *					4.		.4	15.9	* 21	JUN	0520	209	4.	.4	16.0
					.3	15.5 * :					4.		.4	15.9					4.	.4	
20 JUN			0.											15.9					4.	.4	
20 JUN		11	0		.3	15.6 *					4.		.4								
20 JUN	1255	12	0.		.3	15.7 *	50 JUN	2115	112		4.		.4	15.9					4.	.4	
20 JUN	1300	13	1		.3	15.8 *	20 JUN	2120	113		4.		.4	15.9	* 21	JUN	0540	213	4.	.4	
20 JUN		14	3.		.4	15.9 *	20 JUN	2125	114		4.		.4	15.9	* 21	JUN	0545	214	4.	.4	16.0
20 JUN			3.		.4	15.9 *	20 JIIN	2130	115		4.		.4	15.9	* 21	JUN	0550	215	4.	.4	16.0
20 JUN			4.		.4	15.9 *					4.		.4	15.9					4.	4	16.0
						15.9 *					4.		4	15.9					4.	.4	
20 JUN			4.		.4									15.7					4.	.4	
20 JUN		18	4.		. 4	15.9 * :					4.		.4								
20 JUN		19	4	•	.4	15.9 *					4.		.4	15.9					4.	.4	
20 JUN	1335	20	4.		.4	15.9 *	20 JUN	2155	120		4.		.4	15.9					4.	.4	
20 JUN	1340	21	4.		.4	15.9 *	20 JUN	2200	121		4.		.4	15.9					4.	.4	
20 JUN		22	. 4.		.4	15.9 * 1	20 JUN	2205	122		4.		.4	15.9	* 21	JUN	0625	222	4.	.4	16.0
20 JUN			4		.4	15.9 *	20 JUN	2210	123		4.		.4	15.9	* 21	JUN	0630	223	4.	.4	16.0
		24	4.		.4	15.9 *					4.		.4	15.9	* 21	JIIN	0635	224	4.	.4	16.0
20 JUN						15.9 *					4.		.4	15.9				The second second	4.	.4	16.0
20 JUN			4.		.4									15.9					4.	.4	16.0
20 JUN		- 26	4,	•	.4	15.9 *					4.		.4								
20 JUN	1410	27	4.		.4	15.9 *					4.		.4	15.9					4.	.4	
20 JUN	1415	28	- 4.		.4	15.9 *	20 JUN	2235	128		4.		.4	15.9					4.	.4	
20 JUN	1420	29	4		.4	15.9 *	20 JUN	2240	129		4.		.4	15.9	* 21	JUN	0700	229	4.	.4	
20 JUN		30	4.		.4	15.9 * 1					4.		.4	15.9	* 21	JUN	0705	230	4.	4	16.0
20 JUN		31	4.			15.9 *					4.		.4	15.9	* 21	JUN	0710	231	4.	.4	16.0
				•	.4	15.9 *					4.		.4	15.9					4.	.4	16.0
20 JUN		32	4.								4.		.4	15.9					4.	.4	
20 JUN		33	4.		.4	15.9 *								15.9					4.	.4	
20 JUN		34	4,		.4	15.9 * :					4.		.4								
20 JUN	1450	35	4.		.4	15.9 *					4.		.4	15.9					4.	4	production and the second
20 JUN	1455	36	4.		.4	15.9 * 1	20 JUN	2315	136		4.		.4	15.9					4.	.4	
20 JUN	1500	37	4.		.4	15.9 *	20 JUN	2320	137		4.		.4	15.9					4.	.4	
20 JUN		38	4.		.4	15.9 * 1	20 JUN	2325	138		4.		.4	15.9	* 21	JUN	0745	238	4.	.4	16.0
20 JUN		39	4.		.4	15.9 *					4.		.4	15.9	* 21	JUN	0750	239	4.	.4	16.0
		40	4,		.4	15.9 *					4.		. 4	15.9					4.	.4	16.0
20 JUN						15.9 *					4.		.4	15.9					4	.4	16.0
20 JUN			4.		.4									16.0					4.	.4	16.0
20 JUN			4,		,4	15.9 *					4.		.4								
20 JUN	1530	43	4.		.4	15.9 *					4.		.4	16.0					4.	.4	
20 JUN	1535	44	4.		.4	15.9 *					4.		.4	16.0					4.	.4	
20 JUN	1540	45	4		.4	15.9 *	21 JUN	0000	145		5.		.4	16.0	* 21	JUN	0820	245	4.	.4	
20 JUN			4.	ı	. 4	15.9 *	21 JUN	0005	146		5.		.4	16.0	* 21	JUN	0825	246	4.	.4	16.0
20 JUN			4.		.4	15.9 *					7.		.4	16.1	* 21	JUN	0830	247	4.	.4	16.0
20 JUN			4.		.4	15.9 *					9.		.4	16.1					4.	.4	16.0
			_		4	15.9 *					1.		.4	16.2					4.	.4	16.0
20 JUN			4,			15.9 *					3.		.4	16.2					4.	.4	16.0
20 JUN		50	4.		. 4								.4	16.2					4.	.4	16.0
 20 JUN			4.		.4	15.9 *					.3. .3.			16.2					4.	.4	16.0
20 JUN			4.		.4	15.9 *							.4								16.0
20 JUN			4.		.4	15.9 *					6.		.4	16.3					4.	.4	
20 JUN			4.		.4	15.9 *					25.		.5	16.5					4.	.4	16.0
20 JUN			4		.4	15.9 *					51.		.5	16.6					4.	.4	16.0
20 JUN			4.	,	.4	15.9 *	21 JUN	0055	156	3	O.		•5	16.6					4.	.4	16.0
20 JUN			4		4	15.9 *				2	26.		.5	16.5					4.	.4	16.0
20 JUN			4.		. 4	15.9 *					2.		.5	16.4	* 21	JUN	0925	258	4.	.4	16.0
			4.			15.9 *					9.		.5	16.4					4.	. 4	16.0
20 JUN					4	15.7 * 1					6.		.4	16.3					4.	.4	16.0
20 JUN			4.		.4									16.2					4.	.4	16.0
20 JUN			4.		.4	15.9 *			-		.3.	* -	.4							.4	16.0
20 JUN			4.		.4	15.9 *					1.		.4	16.2					4.		
20 JUN			4.	•	.4	15.9 *					0.		.4	16.1					4.	.4	16.0
20 JUN			. 4.	ı	.4	15.9 *					9.		.4	16.1					4.	4	16.0
20 JUN			4.		.4	15.9 *	21 JUN	0140	165		8.		.4	16.1					4.	.4	16.0
20 JUN			4.		.4	15.9 *					8.		.4	16.1					4.	.4	16.0
20 JUN			4.		.4	15.9 *					8.		.4	16.1					4.	.4	16.0
20 JUN			4.		.4	15.9 *					7.		.4	16.1					4.	.4	16.0
			4.		.4	15.9 *					7.		.4	16.1					4.	. 4	16.0
20 JUN			4.		.4	15.9 *					7.		.4					27	4	40	16.0
20 JUN			4. 1		.4	15.7 *					7		Δ	14 1	¥ 71	TIM	1030	271	1	· 4	14.0
OU THE	. /-(1)																				

	20 JUN 1755	72	4.	.4	15.9 * 2	21 JUN 021	5 1/2	7.	.4	16.1 * 21 JUN	1035-272	4.	.4	16.0
	20 JUN 1800		4.	.4		21 JUN 022		7.	.4	16.0 * 21 JUN	1040 273	4.	.4	16.0
	20 JUN 1805		4.	.4	15.9 * 2	1 JUN 022	5 174	7.	.4	16.0 * 21 JUN	1045 274	4.	.4	16.0
	20 JUN 1810		4.	.4		21 JUN 023		7.	.4	16.0 * 21 JUN	1050 275	4.	.4	16.0
	20 JUN 1815	76	4.	.4		1 JUN 023		6.	.4	16.0 * 21 JUN	1055 276	4.	.4	16.0
	20 JUN 1820	. –	4.	.4		21 JUN 024		6.	.4	16.0 * 21 JUN	1100 277	4.	.4	16.0
	20 JUN 1825		4.	.4	15.9 * 2	21 JUN 024	5 178	6.	.4	16.0 * 21 JUN	1105 278	4.	.4	16.0
	20 JUN 1830		4.	.4		21 JUN 025		6.	.4	16.0 * 21 JUN.	1110 279	4.	.4	16.0
	20 JUN 1835		4.	.4		1 JUN 025		6.	.4	16.0 * 21 JUN	1115 280	4.	.4	16.0
	20 JUN 1840		4.	.4		21 JUN 030		6.	.4	16.0 * 21 JUN	1120 281	4.	.4	16.0
	20 JUN 1845		4.	.4		21 JUN 030		5.	.4	16.0.* 21 JUN	1125 282	4.	.4	16.0
	20 JUN 1850		4.	.4		21 JUN 031		5.	.4	16.0 * 21 JUN	1130 283	4.	. 4	16.0
	20 JUN 1855		4.	.4		21 JUN 031		5.	.4	16.0 * 21 JUN		4.	.4	16.0
	20 JUN 1900		4.	.4	15.9 * 2	21 JUN 032	0 185	5.	.4	16.0 * 21 JUN	1140 285	4.	.4	16.0
	20 JUN 1905		4.	.4	15.9 * 2	21 JUN 032	5 186	5.	.4	16.0 * 21 JUN		4.	.4	16.0
	20 JUN 1910		4.	.4	15.9 * 2	21 JUN 033	0 187	5.	.4	16.0 * 21 JUN		4.	.4	16.0
	20 JUN 1915		4.	.4	15.9 * 2	21 JUN 033	5 188	5.	.4	16.0 * 21 JUN		4.	.4	16.0
	20 JUN 1920		4.	.4	15.9 * 2	21 JUN 034	10 189	4.	.4	16.0 * 21 JUN		4.	.4	16.0
	20 JUN 1925		4.	.4	15.9 * 2	21 JUN 034	5 190	4.	.4	16.0 * 21 JUN		4.	.4	16.0
	20 JUN 1930		4.	.4		21 JUN 035		4.	.4	16.0 * 21 JUN		4.	.4	16.0
	20 JUN 1935	92	4.	.4	15.9 * 2	21 JUN 035	5 192	4.	.4	16.0 * 21 JUN		4.	.4	16.0
	20 JUN 1940	93	4.	.4		21 JUN 040		4.	.4	16.0 * 21 JUN		4.	.4	16.0
	20 JUN 1945	94	4.	.4	15.9 * 2	21 JUN 040	5 194	4.	.4	16.0 * 21 JUN		4.	.4	16.0
	20 JUN 1950	95	4.	. 4		21 JUN 041		4.	.4	16.0 * 21 JUN		4.	.4	15.9
	20 JUN 1955	96	4.	.4		21 JUN 041		4.	.4	16.0 * 21 JUN		4.	. 4	15.9
	20 JUN 2000	97	4.	. 4		21 JUN 042		4.	.4	16.0 * 21 JUN		4.	.4	15.9
	20 JUN 2005	98	4.	. 4		21 JUN 042		4.	.4	16.0 * 21 JUN		4.	.4	15.9
ă.	20 JUN 2010	99	4.	.4		21 JUN 043		4.	.4	16.0 * 21 JUN		4.	.4	15.9
	20 JUN 2015	100	4.	.4		21 JUN 043	5 200	4.	.4	16.0 * 21 JUN	1255 300	4.	.4	15.9
					¥					*		*********	******	*****
	*********	*****	*********	******	********	*******	*******	{*********	****	************	********	***********	*******	*****
		771				AVTMIM AL	ÆRAGE FLOW							
	PEAK FLOW	TIM				naximum av 24-HR	72-HR	24.92	-HR					
	(CFS)	(HR			6-HR 8.	24nr. 5.	72-nk 5.	47:14	5.					
	3i.	12.8	ن الل	FS)	o.	J.	J.							

PEAK FLOW	TIME		244	MAXIMUM AVE	RAGE FLOW	-
(CFS)	(HR)		6-HR	24-HR	72-HR	24.92-HR
31.	12.83	(CFS)	8.	5.	5.	5.
and the second		(INCHES)	.772	1.903	1.908	1.908
		(AC-FT)	4.	10.	10.	10.
	* -	*				
PEAK STORAGE	TIME			MAXIMUM AVER	AGE STORAGE	
(AC-FT)	(HR)	*	6-HR	24-HR	72-HR	24.92-HR
	12.83		0.	0.	0.	0.
PEAK STAGE	TIME			MAXIMUM AVEF	RAGE STAGE	
(FEET)	(HR)		6-HR	24-HR	72-HR	24.92-HR
16.62	12.83		16.07	15.98	15.94	15.94

CUMULATIVE AREA =

.09 SQ MI

STATION RES3

			(I) IN	FLOW, (D)	OUTFLOW								
	0.	4.			. 16.	20.	24.	28	. 32.	. 36.	0.	0.	0.
								1	(S) STORAGE				
	.0	.0	.0	.0	0	.0	.0		2 .4		.0	.0	.0
DAHRMN		•••	• •										
201200	1 I							S	,		,		,
201205	20	I .	•					S					
201210	3.0	Ī	-	-				S			, .		
201215	4.0	Ī	•	•				S				•	
201213	5.0	T	•	•				S					
201225	6.0	. 1		•		•		S		. ,			
	7.0	1	•	N. W. Carlot			•		5 .				
201230		1				•	,		.s				
201235	8.0	1	•		•	•			. 5				
201240	9.0			•	•				. S .	e de la compansión de l	A473 - a 1		
201245	10.0	1	•	•	•	•	•		s			· · · · · · · · · · · · · · · · · · ·	
201250	11.0.	i							. S.				
201255	12.0	1	•	• .	•	•	•		. S				
201300	13. 0		•		•	•	•		S.			_	•
201305	14.	0 I	•	•	•	•	•		. S		·		
201310	15.	0 I	•	•		•			. 5.			· ·	
201315		OI	•	•	•	*			. S.	4. *			
201320	17.	10		•	•	•	•		. S.				
201325	18.	10		•	•	•	•		. 5				
201330	19.	10 10	•	•	•				. S.				
201335	20.		•	•	•	•			5				
201340	21	ui I							. S.				
2013 4 5 201350	23.	I	. •	•	•				. S				
201350	24.	1	-	•	•				. S.				
201333	25.	I			•				. S.				
201400		Ţ	•	•					. S.				
201403		Ī	•		•				. S	e e anto .	ugata da seleta da s Seleta da seleta da s		
201415	28.	ī	•	•					. S.				•
201413	29.	Ī		•	•				. S				
201425	30.	ī		-	•				. S.				· · · · · · · · · · · · · · · · · · ·
201423	31	T											
201435	32.								. S.			•	•
201440		I							S		•	•	•
201445		· I							. 5.	·	•	•	į.
201450	35.	I							. S			•	•
201455	36.	I							. S.			•	
201500	37.	I							. S	•		•	•
201505	38.	I				•			. S.				•
201510	39.	I			•				. 5	. ,	•	•	•
201515	40.	I					•		. S.		•		•
201520	41	I							5				
201525	42.	I		•		•			. 5.			•	
201530	43.	I			•	•	•		. S.		•	•	•
201535	44.	I			•	•		-	. S.		, , , ,		
201540	45.	I			•		•		. S	•	•	•	
201545	46.	I		•		•	•		. 5.	•		. •	
201550	47.	I	•			•	•		. 5,	•		. •	•
201555	48.	I	•		•	•	•		. 5.	•		•	
201600	49.	I		•	•	•	. •		. 5	•	•		•
201605	50.	I	•		i	•	•			•			
201610	51	<u>I</u>											
201615	52.	I		•	•	•	•		. 5		RI	-44	o .
201620	53.	1	•	•	•	•	•		. 5.		L f	• •	
20175	ካΔ	1			•	-	-	•		-			

			,						ų		_		
201630	55. 56.		I .	•	•	•				•			
201635 201640			I	•	•			· •	. S			. •	
201645		,	· 1			- • :			. S				
201650			I	•		•			. 5		•		. •
201655	60.]	- [,			•	, ,		. S				•
201700			Ι						S				
201705		1	[,					1	. S				•
201710			I		•				. S		•		*
201715	64.	-]			•		· ·		, S			•	•
201720		:	I	•	•	•			. 5		•		. •
201725]	·		•	•				. •	•	•	
201730			[,	•	•	•		•	. 5	•	•	•	•
201735			! •	•	• '		• •		. s		•		
201740			<u>.</u> r	•		•	•		S				
201745	70. 71		[•	• .		, , , , , , , ,						
201750 201755	72.	1							S		. ,	•	
201733	73.			•	•			,	. S		•		
 201805]	[•			· · · · · · · · · · · · · · · · · · ·	. S	•	. "	•	•
201810			I ,						. S				•
201815]	[,				المنتخب والمنا	i			•		•
201820	77.		I .		•	· · · · · · · · · · · · · · ·			_		•	•	•
201825	78.		[.		•	•			. 5		•		•
201830	79.		I .	•		•	•		. S		•	•	•
201835	80.]		•	•	•		, ,		•	•		
201840	81												
201845	82. 83.		l '	•	•				. 5		•		
201850 201855		,	1 [• 445 + 11 14 14 -					. S				
201900	85.		I	• • • •		•			. S				•
201905	86.		[•		r Br		, ,	. S	1			
201710			I .		•				. 9		•		
201915	88.]	Ι,		•		, ,		. S			•	•
201920	89.		Ī	•	•	•	•		. S			•	•
201925	90.]	[-			•		. "	. S	•			•
201930		• •	I										
201935			[•	•	•	•	'	. S		_		
 201940 201945	93. 94.	1	L . T	•	•		•		. S		•	•	
201743			Ī			•	•		. S		•		
201955	96.		Ī	•			,	. 1	. S			•	
202000			I	•			•		. 9			•	•
202005	98.	1	Ι .		• 1				. S		• '		•
202010			I	•	•	• ,	•	i. =	. S	•	•		•
202015			i T	•	B. ** * * * * * * * * * * * * * * * * *	•				•			
202020 202025													
202023			I				· .		. 9	-	•		
202035		j	Ι .	• · · · · · · · · · · · · · · · · · · ·					. S				
202040	105.		I	•		•			. 9	_	•	•	•
202045]	Ι,	•	•				. S	-		•	•
202050			Ι .	•	•	•	•		. S		•	•	•
202055			[.	•		•		•	. s		• '	•	•
202100			I .	•	•	•	•	• • • •	. a		•	•	
202105 202110			T						5		·	·	
202110									. 5				
202120			I		• 1 55	•	•		. s		•		
202125		1	I .		•	•	. ,	,	. S				
202130	115.		I .		•	•		•	. 5			•	•
202135]	Ι,			•			. S		•	. •	•
202140			I .	•	•	•	•	•	. 9		•		•
202145				•	•		•	, ,			0	1 _ 1	7
202150			T		•	•					K	1- T	<i>I</i> .
. 202155	170.		· ·	· 		· ·	· ·						

					-										-				
	202200			.]		• •	• •			• •					5	• •			
	202205			ı	<u> </u>		•		•		•	•	•	•	5. 5.		•	•	•
	202210]			•		•		1	•	•	-			•	•	. ,
	202215			1			•		•		•	•	•	•			•	•	
	202220]	[• '		•		•	•	•	•	S.		*	•	• • • • • • • • • • • • • • • • • • •
	202225]	ĺ		•		•		•	•	•	•	3.		•	•	•
	202230]			•		•		•	•		•	5.		•	•	
	202235			1	[•		•		•		•	•	5 .		•	•	•
	202240]	Ī		•				•	•		•	5.		•	•	
	202245			I			• "				•	•	•	. 3	3.		Y * *	•	
	202250		1 1 1	. 1	[. .										5				
	202255			1	Ī		•		•		•	• .	•	•	3.		1 -	•	
	202300			1	1									-	5.		•	•	
	202305	134.		1	[•		•	•	3.		*	•	•
	202310	135.		1]						•		•	-	5.		•		
	202315	136.]								•		-	3 .		•		
	202320	137.		.]	· · .							•		-	5.		•	• 68 - 56	• • •
	202325	138.		. 1					•			•		-	3.				
	202330	139.		3	I								•	. ;	3.		•	•	
	202335		•	1								*			3.				
	202340			.]	Ι									:	5				
	202345		,	1	[•			•	3.				
	202350			j											5.		•		
	202355			C)[•	1		. (i.				
	210000			_	.O I							• **			S		• ***		
	210005				. 0	I		100					3		S.			•	. ,
	210010					0	. I								S.				
	210015						. 0	I					1		S		•		
	210020							0	. I		•	•	•		.S			•	
	210025								. O I					B # *	.S		•		
	210030								I.						S				
	210035					7 -			. 10						.S				
	210040										0	. I	•		· S				
				•	•		•		-				n n		_				
	210045	154.										• 1			. S			•	•
	210045 210050			•		,					•	4		•	Ι. :	5	•	•	
	210050	155.		٠	•				•		•		. I	. 0	• -		* ** ** ** ** ** ** ** ** ** ** ** ** *	•	engli (1)
	210050 210055	155. 156.					•				•	·	•	. 0	Ι. :		* ***	•	enge de
	210050 210055 210100	155. 156. 157.		•			•		:		: : :	. I	. I	. 0	I. :		•		engelster
a ver	210050 210055 210100 210105	155. 156. 157. 158.		•			•				. I		. I	. 0	I. ;		•	•	ender e
	210050 210055 210100 210105 210110	155. 156. 157. 158. 159.		•			•		· · · · · · · · · · · · · · · · · · ·		I 0		. I	. 0	I		• • • • • • • • • • • • • • • • • • • •		enge e
a sas .	210050 210055 210100 210105 210110 210115	155. 156. 157. 158. 159.						I	-	0	I 0		. I	. 0	I				
a sues	210050 210055 210100 210105 210110 210115 210120	155. 156. 157. 158. 159. 160.					•	I I 0	0.		I 0		. I	. 0	I				
a sias	210050 210055 210100 210105 210110 210115 210120 210125	155. 156. 157. 158. 159. 160. 161.				• •			0.	0	I 0		. I		I				
	210050 210055 210100 210105 210110 210115 210120 210125 210130	155. 156. 157. 158. 159. 160. 161. 162.						I 0	0.	0	I 0		. I	. 0	I				
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135	155. 156. 157. 158. 159. 160. 161. 162. 163.	• • •					I 0	0.	0	I 0		. I	. 0	I				
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140	155. 156. 157. 158. 159. 160. 161. 162. 163. 164.					IO .0	I 0	0.	0	I 0		. I	. 0	I				
ende i	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165.				. I	10 :0 0	I 0	0.	0	I 0		. I	. 0					
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166.	•••			. I I I I I	10 0 0	I 0	0.	0	I 0		. I						
ere i	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167.	•••			· I	10 0 0	I 0	0.	0	I 0		. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210155	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168.	•••			. I I I I I	10 0 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210155 210200	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 169.				- I I I I I	10 0 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210155 210200 210205	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 169.				- I I I I I	10 0 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210200 210205 210210	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171.				I I I I I I I I I I I I I I I I I I I	10 0 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210200 210205 210210 210215	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171. 172. 173.				I I I I I I I I I I I I I I I I I I I	10 0 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210155 210200 210205 210210 210215 210220 210225	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171. 172.				I I I IO I I I	10 0 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210140 210155 210200 210205 210210 210215 210210	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171. 172. 173. 174. 175.		•		I I I I I I I I I I I I I I I I I I I	10 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210150 210205 210210 210215 210220 210225 210230	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171. 172. 173. 174. 175.				I I IO I I I I I I	10 0 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210155 210200 210205 210210 210215 210220 210225 210230 210235	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171. 172. 173. 174. 175. 176. 177.			I	I I I I I I I I I I I I I I I I I I I	10 0 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210200 210205 210200 210205 210210 210225 210220 210225 210230 210235 210240 210245	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178.		•	I	I I I I I I I I I I I I I I I I I I I	10 0 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210200 210205 210210 210215 210220 210225 210230 210240 210245 210250	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179.		•	I	I I I I I I I I I I I I I I I I I I I	10 0 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210135 210140 210145 210200 210205 210200 210205 210210 210225 210220 210225 210230 210235 210240 210245	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180.		•	I I I I I I I I I I I I I I I I I I I	I I I I I I I I I I I I I I I I I I I	10 6 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210205 210205 210210 210215 210220 210225 210230 210240 210245 210250 210255 210250 210255 210250	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180. 181.		•	I I I I I I I I I I I I I I I I I I I	I I I I I I I I I I	10 6 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210155 210200 210205 210210 210225 210230 210240 210245 210250 210255 210230 210255 210300 210305	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180. 181. 182.		•	I I I I I I I I I I I I I I I I I I I	I I I I I I I I I I	10 6 0	O O	0.	0			. I						
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210155 210200 210205 210210 210215 210220 210225 210230 210240 210240 210245 210255 210300 210355 210300 210355 210300 210305 210310 210315	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180. 181. 182. 183. 184.			I I I I I I I I I I I I I I I I I I I	I I I I I I I I I I	10 0 0	O O	0.	0			. I					<i>A</i> .	
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210150 210155 210200 210205 210210 210225 210220 210225 210230 210240 210245 210250 210255 210300 210305 210300 210305 210310 210315 210300 210305 210310 210315 210320	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180. 181. 182. 183. 184. 185.				I I I I I I I I I I	10 0 0	O O	0.	0			. I				21-	48	
	210050 210055 210100 210105 210110 210115 210120 210125 210130 210145 210155 210200 210205 210210 210215 210220 210225 210230 210240 210240 210245 210255 210300 210355 210300 210355 210300 210305 210310 210315	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180. 181. 182. 183. 184. 185.				I I I I I I I I I I	10 0 0	O O	0.	0			. I				21-	48	

	210330	197			. I		,				-		. 5				1
	210335				.I				•				S				
	210340				. I				•			, ,	. S			•	ì
	210345				. I				•				, S				1
	210350				.I.								S		• • • • • • •		
	210355	192.			10								. S		•		
:	210400	193.			I						•		. S		•		1
:	210405	194.			I								S		• '		
	210410				I								. 5		•	•	•
	210415				I		•			•		•	. S		•	•	
	210420				I		•			•	•	, ,	. 5 . S		•	• .	
	210425				I		•			•	• •	•	, a . S		• '		
	210430				I		•			•	•	, ,	. s	•	•	•	<u>.</u>
	210435				1		•		•	•	•	•	, <u>,</u>	•			
	210440				i.		• •						S				
	210445				I		•		•	•			. S		•		
	210 4 50 210 4 55				I		•		•				S				
	210433				ī		•			•			S				
	210505				ī					,			. S				
	210510				I					•		, ,	. S	•	•		•
	210515				I	*, ****	•		•				. S				•
	210520				I				e de la companya de l		•		. S	•	•		•
	210525				I					• .			. S	1 → √√/m	•	•	•
	210530	211.			I.			1 ,1, 1,					S				
:	210535	212.			I					•			. S		•		
	210540				I		•		•	•	• • •	, ,			•	•	
	210545				I		•	1 ×		*	e , e	•	. S				
	210550				I		•			•	•	٠ '	. 5 . S		•	• '	1
	210555				I		•		• ,	• "		•	. 5				
	210600				i T	*	•		•	•	• 1	۱	_				<u>-</u> '
	210605 210610				1		•		•	•			. S	-	<u>.</u>	•	•
	210615				ī				•	-			. 5	s .	•		
	210620				Ī.								S				
	210625			• •	Ī							, .	. S		•		
	210630				I							Line September 1981	5	•			
	210635				I								, · S	• 1		. •	
:	210640	225.			I					•	•		. S	•	•	• '	•
	210645				I	•				•	1 1				.		
	210650				Ι		•		• .	•		, ,	. S	•	•		•
	210655				I		•		•	•	•		. 5 . S	•	• '		
	210700				i		•		•	•	•		. S	• ,	•		
	210705 210710				I T		•		•	• 			S				
	210715		٠.		ī						•		. S		,	, .	
	210720				Ī							,	. 5	•			•
	210725				I								. S	•	•	•	•
:	210730	235.			I				• • • • • • • • • • • • • • • • • • • •		•		. ; S			•	
	210735				I		•						. 5		. :		
	210740				I		•		•	•	•		. 5 . S	•	•	• '	1
	210745				I		•		•	•			. 5	•		• -	
	210750				1		•		•	•	•	•		•			
	210755				l T		•		•	•	•		5				rin Talahan
	210800 210805			. •	1 ·				· · · · ·				S				
	210810				Ī								. S				•
	210815				Ī										. ,		
	210820				I					•	•		, S		•		
	210825	246.			I							•	. 5		•		
	210830	247.			I				•		•		. S	•	•		
	210835				I		•		•	•	• •	•	. S	•			
	210840				I		•		•		•		. 5	•	01	΄_ Λ	a
	210845			-	i		•		•	•	• •	•	. 5	•	. L 1	- 4	
	210850			• •	1 -		• •	• • •					s	<i></i>			
:	210855	252.			1		•		•	•	• •	•		-	- '	•	

210900 253.	Ī								S.			
	-	•	•		•	•	•			•	•	•
210905 254.	I	•	•			•	•		5.	•	•	•
210910 255.	I								S.			
210915 256.	ī					•			5.		* .	-
	•	•	•		•	•	•			•	•	•
210920 257.	I	•				•	•		5.			
210925 258.	Ī	_	_		_	_	_	_ !	3 -	_		
210930 259.	- T	•	•		•	-	•	•	- ·	•	•	•
	1	. •			•	•	•		5.	•	>	
210935 260.	I							. :			•	
210940 261									5			
210945 262.	1				•		•		3.	•	•	
210950 263.	I				•			. ;	3.			
210955 264.	ī							(
	*	•	•		•	•	•			•	•	•
211000 265.	1	•	•			•				•	•	
211005 266.	Ī					•		. () ,		• • • • • • • • • • • • • • • • • • • •	
211010 267.	T						_	. (3			
	7	•	•		•		•			•	•	• •
211015 268.	1	•				•	•		•	• '	•	
211020 269.	I	•				•			; .		1	
211025 270.	ĭ	_	_			_	_	. 9				
211030 271			•	,			•			•		•
	1 .											· · · · · ·
211035 272.	I	•							parametric en region de re En il			
211040 273.	Ī		_			•		. 9		_		
211045 274.	7	•	•				-			•	• • •	•
	1	•	•	•			•				,	•
211050 275.	I	•						. 5				
211055 276.	. I	• .						. 9				
211100 277.	ī	•	-	•								
	1		•		•		•	-			- !	• •
211105 278.	. I							. 9	•			
211110 279.	I							. 9				
211115 280.	7		-					S		_	•	•
	-	•	• .	•	•		•		•	•	•	•
211120 281	I .							5	المحاجية			
211125 282.	I							S				
211130 283.	ī					****		S				
		•	•	•	•	'	•	_	•	•	•	•
211135 284.	1		•		1				•	•		
211140 285.	I							S	•			
211145 286.	ī							S				
	7	•	•	•			•		•	•	•	
211150 287.	1	•		•		•	•	5				
211155 288.	. I				•			S				
211200 289.	I		-		-		-	9			ي	=
211205 290.	- T	•	•	•	•	-	•	S		•		•
	<u>i</u>	•	•	•	•	•				•	•	•
211210 291	l .		pr + + +					S				
211215 292.	I							S			2	
211220 293.	T.							S			_	_
	*	•	•	•		•	*		• •	•	•	•
211225 294.	1	•	• .	•	•		•	5		•		•
211230 295.	I							S				
211235 296.	1	-				-		S				
	Ī	•	•	•	•	•	•	S			•	
211240 297.	i	•	•	•	•	•	•	-			,	•
211245 298.	I					•		S				•
211250 299.	I							S				
211255 300	_ :T		·						·	• • • • • • • • • • • • • • • • • • • •		
Z11Z00 000+	1		·,••	,		•						

RUNOFF SUMMARY FLOW IN CUBIC FEET PER SECOND TIME IN HOURS, AREA IN SQUARE MILES

OPERATION	STATION	PEAK FLOW	TIME OF PEAK	AVERAGE 6-HOUR	FLOW FOR MAX 24-HOUR	IMUM PERIOD 72-HOUR	BASIN AREA	MAXIMUM STAGE	TIME OF MAX STAGE
HYDROGRAPH AT	OF1	6.	12.42	1.	0.	0.	.02		
ROUTED TO	CH1	6.	12.50	1.	0.	.0.	.02	· · · · · · · · · · · · · · · · · · ·	e de la companya de la companya de la companya de la companya de la companya de la companya de la companya de La companya de la co
HYDROGRAPH AT	A2	3.	12.42	0.	0.	0.	.01		
2 COMBINED AT	A2	9.	12.42	1.	0.	0.	.02		
ROUTED TO	ST1	9.	12.50	1.	0.	0.	.02	• •	e e e e e e e e e e e e e e e e e e e
HYDROGRAPH AT	A3	3.	12.42	0.	0.	0.	.01		
2 COMBINED AT	A3	12.	12.50	2.	0.	0.	.03	g sa ^{r∎t}	
HYDROGRAPH AT	- 0F2	5.	12.67	. 1.	0.	0.	.02		
ROUTED TO	CH2	5.	12.67	i.	0.	0.	.02		
HYDROGRAPH AT	OF3	1.	12.67	. 0.	0.	0.	.00		: "
2 COMBINED AT	OF3	6.	12.67	1.	0.	0.	.02		-
2 COMBINED AT	0F3	17.	12.58	3.	1.	1.	.05		
HYDROGRAPH AT	A1	13.	12.58	2.	1.	1.	.03		
2 COMBINED AT	A1	31.	12.58	5.	1.	i.	.08		en en en en en en en en en en en en en e
ROUTED TO	P1	30.	12.58	5.	1.	1.	.08		
HYDROGRAPH AT	Bi	1.	12.08	0.	0.	 0.	.00	i je ga i Siere er i	
2 COMBINED AT	B1	30.	12.58	5.	1	1.	.08		
ROUTED TO	RES1	30.	12.67	7.	5.	4.	.08	23.17	12.67
ROUTED TO	CH3	30.	12.67	7.	5.	4.	.08		
HYDROGRAPH AT	B2	1.	12.08	0.	, ,0.	0.	.00		
2 COMBINED AT	B2	30.	12.67	7.	5.	4.	.08		
ROUTED TO	RES2	32.	12.75	7.	5.	4.	.08	20.62	12.75
ROUTED TO	CH4	29.	12.75	7.	5.	4.	.08		
HYDROGRAPH AT	B345	9.	12.42	1.	0.	0.	.01		
2 COMBINED AT	B 345	34.	. 12.75	8.	5.	5.	.09		
ROUTED TO	RES3	31.	12.83	Add 8.	TO R4	N*Z	.09	16.62	1-5

SUMMARY OF KINEMATIC WAVE - MUSKINGUM-CUNGE ROUTING (FLOW IS DIRECT RUNOFF WITHOUT BASE FLOW)

					•				LATED TO			
	ISTAQ	ELEMENT	TŒ	PEAK	TIME TO PEAK	VOLUME	DT	PEAK	IN INTERVAL TIME TO PEAK	VOLUME		
			(MIN)	(CFS)	(MIN)	(IN)	(MIN)	(CFS)	(MIN)	(IN)		
	CH1	MANE.	2.00	6.20	750.00	.53	5.00	6.20	750.00	53		
CONTINUITY	SUMMARY	(AC-FT) -	INFLOW= .49	730E+00 EX	CESS= .0000	E+00 OUTFLO	DW= .4930	E+00 BASIN	STORAGE=	.3153E-03 PERCENT	ERROR=	1
•	ST1	MANE	3.25	7.11	754.00	.60	5.00	9.02	750.00	.60		
CONTINUITY	SUMMARY	(AC-FT) -	INFLOW= .72	2 59 E+00 EX	CESS= .0000	E+00 OUTFLO)₩= .7260	E+00 BASIN	STORAGE=	.7201E-03 PERCENT	ERROR=	1
-	CH2	MANE	2.75	5.09	761.75	.53	5.00	5.08	760.00	.53		
CONTINUITY	SUMMARY	(AC-FT) ~	INFLOW= .52	163E+00 EX	CESS= .0000	E+00 OUTFLO	W= .5260	E+00 BASIN	STORAGE= .	.5692E-03 PERCENT	ERROR=	- . i
	P1	MANE	1.12	30.36	756.58	.68	5.00	30.28	755.00	.68		
CONTINUITY	SUMMARY	(AC-FT) -	INFLOW= .29	20E+01 EX	CESS= .00000	E+00 OUTFLO	W= .2919	E+01 BASIN	STORAGE= .	7790E-03 PERCENT	ERROR=	.0
	CH3	MANE	1.28	29.98	761.52	2.13	5.00	29.86	760.00	2.13		
CONTINUITY	SUMMARY	(AC-FT) -	INFLOW= .92	18E+01 EX	CESS= .0000&	E+00 DUTFLO	W= .9206	E+01 BASIN	STORAGE= .	1282E-01 PERCENT	ERROR=	.0
	CH4	MANE	1.39	31.44	766.62	2.12	5.00	28.87	765.00	2.12		
	A. ILJ. / A A. /	/AD ET!									-	

CONTINUITY SUMMARY (AC-FT) - INFLOW= .9246E. i EXCESS= .0000E+00 OUTFLOW= .9233E+01 BASIN STORAGE= .1416E-01 PERCENT ERROR=0

*** NORMAL END OF HEC-1 ***

GRAND VIEW SUB. (AddENDUM 1)

FLOOD HYDROGRAPH PACKAGE (HEC-1) SEPTEMBER 1990 VERSION 4.0

RUN DATE 06/20/1996 TIME 22:22:10 *

U.S. ARMY CORPS OF ENGINEERS HYDROLOGIC ENGINEERING CENTER 609 SECOND STREET DAVIS, CALIFORNIA 95616 (916) 756-1104

X	X	XXXXXXX	XX	XXX		X
X	.Х	χ	χ	X		XX
X	X	X	X			X
XXXX	XXXX	XXXX	X		XXXXX	X
X	X	χ	X			X
χ	X	X	X	X		X
X	X	XXXXXXX	XX	XXX		XXX

THIS PROGRAM REPLACES ALL PREVIOUS VERSIONS OF HEC-1 KNOWN AS HEC1 (JAN 73), HEC16S, HEC1DB, AND HEC1KW.

THE DEFINITIONS OF VARIABLES -RTIMP- AND -RTIOR- HAVE CHANGED FROM THOSE USED WITH THE 1973-STYLE INPUT STRUCTURE. THE DEFINITION OF -AMSKK- ON RM-CARD WAS CHANGED WITH REVISIONS DATED 28 SEP 81. THIS IS THE FORTRAN77 VERSION NEW OPTIONS: DAMBREAK OUTFLOW SUBMERGENCE, SINGLE EVENT DAMAGE CALCULATION, DSS:WRITE STAGE FREQUENCY, DSS:READ TIME SERIES AT DESIRED CALCULATION INTERVAL LOSS RATE:GREEN AND AMPT INFILTRATION KINEMATIC WAVE: NEW FINITE DIFFERENCE ALGORITHM

DEVELOPED 100 YEAR STORM
BASINS "C, D ! E

RUN # Z

```
PAGE 1
```

```
LINE
            ID......1.....2.....3.....4.....5.....6.....7.....8.....9......10
            ID GRAND VIEW SUBDIVISION
            ID DEVELOPED CONDITION
  3
            ID
               100 YEAR 24 HOUR STORM (GRAND JUNCTION URBANIZED AREA D-D-F DATA)
            IT
                   5 30JUN94 1200
                                     300
            10
                   5
            * ********
           KΚ
               D123
  7
              Basin runoff calculation for D123
  8
               3 1
           ΚO
                             0
                                    1
  9
              0.0187
 10
           PH
                        0
                             0.39
                                    0.76
                                          1.34
                                                       1.44
                                                                    1.69
                                                                           2.01
                                                 1.40
                                                              1.56
 11
 12
           UD 0.457
           * ********
 13
 14
           KM Muskingum-Cunge channel routing from
                                                 CP9 to
                                                         CP10
 15
           ΚO
               3 1 0 1 21
                 315 0.0045 0.025
                                          TRAP
 16
                                                   2
           * ********
 17
           KK
                  D4
 18
           KM Basin runoff calculation for
                                         21
 19
              3
                       1 0 1
 20
           BA 0.0036
                            0.39
 21
           PH
                        0
                                   0.76
                                          1.34
                                                1.40
                                                       1.44 1.56
                                                                    1.69
                                                                          2:01
 22
           LS
                        88
 23
           UD 0.484
           * ********
 24
           KK
 25
               Combining two hydrographs at control point
           K0
                  3 1 0 1
                                           21
26
 27
                  2
           HC
           * *******
 28
                RES4
29
           KM Reservoir routing operation
               1 2 0 1
30
           KΟ
                                           21
                      ELEV 17.30
31
           RS
                  1
32
           SV 0.0326 0.0994 0.0204 0.3618 0.5767 0.8459 1.0833
33
              18.3 19.3
                             20.3
                                   21.3
                                          22.3
                                                23.3
                18.3 0.0625
                                    0.5
34
           SL
                             0.6
               23.5 12.29
35
                             2.7
                                    1.5
           * *******
36
           KK.
                P1A
37
           KM Muskingum-Cunge channel routing from
                                                CP10 to
                                                           CP8
38
           KO 3 1 0 1 21
              655 0.0067 0.015
                                         CIRC
                                                 2.0
           * ********
```

```
ID......1.....2......3.....4......5.....6......7......8......9.....10
LINE
             KK
  40
                    C2
                 Basin runoff calculation for
             ΚM
  41
                                                  21
                                    0
                                          1
  42
             ΚO
                             1
  43
             BA 0.0049
                                                              1.44
                                                                      1.56
                                                                             1.69
                                                                                    2.01
                                 0.39
                                         0.76
                                                1.34
                                                       1.40
             PH
  44
                            88
             LS
  45
             806.0 QU
  46
             * ********
  47
             ΚK
                  Combining two hydrographs at control point
                                                             CP8
             ΚM
  48
                           1 0
                                         1
                     3
             ΚO
  49
             HC
                     2
  50
             * *******
                   C13
  51
                 Basin runoff calculation for
             ΚM
                            1 . . 0
                                         1 21
             КО
                     3
  53
             BA 0.0206
  54
                                                                                    2.01
                                                       1.40
                                                              1.44
                                                                      1.56
                             0
                                 0.39
                                         0.76
                                                1.34
  55
             PH
             LS
                            88
  56
             UD
                0.472
  57
             * *******
                   C12
  58
                  Combining two hydrographs at control point
  59
                            1 0 1 21
  60
             K0
                     3
             HC
                     2
  61
             * ********
             KK
                    P2A
  62
                                                                  CP11
                                                        CP8 to
                  Muskingum-Cunge channel routing from
             KM
  63
                                         1
 64
                            1
                                  0
             RD
                    277 0.0054 0.015
                                                CIRC
  65
             * *******
                    E1
  66
                  Basin runoff calculation for
 67
                                    0
             ΚĐ
                  3
                            1
  83
             BA 0.0009
 69
                                                                      1.56
                                                                             1.69
                                                                                    2.01
                                         0.76 1.34
                                                       1.40
             PH
                             0
                                 0.39
 70
 71
             LS
                            83
  72
             UD 0.129
             * ********
             KK
                    E1
  73
                                                             CP11
                  Combining two hydrographs at control point
 74
                                          1
                     3
                            1
                                   0
 75
             K0
  76
             HC
                     2
             * *******
```

LINE	ID.	1.	2.	3.	4 .	5,	6.	7	·	8	9	10
				• .								
77	KK	RES5										
78	KM	Reserv	oir rout	ing oper	ation							
79	KO	1	2	0	1	21						
80	RS	1	ELEV	11.24								
81	SV	0.0184	0.0693	0.1631	0.3126	0.5207	0.7889					
82	SE	12.0	13.0	14.0	15.0	16.0	17.0					
83	SL	12.24	0.0625	0.6	0.50		•					• •
84	SS	16.0	12.29	2.7	1.5							
	* *	*****	*									
85	77									-		

* FLOOD HYDROGRAPH PACKAGE (HEC-1) * SEPTEMBER 1990 * VERSION 4.0 * * RUN DATE 06/20/1996 TIME 22:22:10 * *

U.S. ARMY CORPS OF ENGINEERS HYDROLOGIC ENGINEERING CENTER 609 SECOND STREET DAVIS, CALIFORNIA 95616 (916) 756-1104

GRAND VIEW SUBDIVISION
DEVELOPED CONDITION
100 YEAR 24 HOUR STORM (GRAND JUNCTION URBANIZED AREA D-D-F DATA)

5 IO OUTPUT CONTROL VARIABLES

IPRNT 5 PRINT CONTROL

IPLOT 2 PLOT CONTROL

QSCAL O. HYDROGRAPH PLOT SCALE

IT HYDROGRAPH TIME DATA

NMIN 5 MINUTES IN COMPUTATION INTERVAL

IDATE 30JUN94 STARTING DATE
ITIME 1200 STARTING TIME

NQ 300 NUMBER OF HYDROGRAPH ORDINATES

NDDATE 1JUL94 ENDING DATE
NDTIME 1255 ENDING TIME
ICENT 19 CENTURY MARK

COMPUTATION INTERVAL .08 HOURS
TOTAL TIME BASE 24.92 HOURS

ENGLISH UNITS

DRAINAGE AREA SQUARE MILES

PRECIPITATION DEPTH INCHES LENGTH, ELEVATION FEET

FLOW CUBIC FEET PER SECOND

STORAGE VOLUME ACRE-FEET SURFACE AREA ACRES

TEMPERATURE DEGREES FAHRENHEIT

8 KO OUTPUT CONTROL VARIABLES

IPRNT 3 PRINT CONTROL
IPLOT 1 PLOT CONTROL

QSCAL O. HYDROGRAPH PLOT SCALE
IPNCH 1 PUNCH COMPUTED HYDROGRAPH

IOUT 21 SAVE HYDROGRAPH ON THIS UNIT

RZ-5

	210900 2	53.	1						5	•	•		•	•	•
	210905 2		T	_					S					, .	•
	210703 2		Ť						S			•	4 :		
			1	•	•	ı	•		S	_				, ,	
	210915 2		1	•	•	•			S	•	•				_
	210920 2		I							•	• ,	•	•	•	•
	210925 2	58.	I						S		• •	1	• '	. '	
	210930 2		T			i			S					,	
	210935 2		7		er og er				S			1			
					•		•		S						
	210940 2		 • i						S						
	210945 2		I	•		•				•	•	1	• '		
	210950 2	63.	I			ı			S	•	•		•	•	•
	210955 2	54.	I						S	•	• :	•	•		•
	211000 2		Ţ						S			•	•		
	211005 2		7	•	•		_		S			1			
			1		•	'		-	S			_	_		
	211010 2		1			•		-	S	•	•	•	•	-	_
•	211015 2		I			'				•	•	•	•		•
	211020 2	59.	I			ı	a (S	•	•	•	•		•
	211025 2	70.	I			,			S			ı		•	•
	211030 2		 _ 1	·					S						•
	211035 2		 - T						S			:			
			7			•	•		S						
	211040 2		1		• '		• .		S	-					
	211045 2		i		•	,	•		S	•	• .		•	•	•
	211050 2	75.	1		• **	,	• 1			• .	•	•	• '	•	•
	211055 2	76.	I						S	•	• .	•	• •	•	•
	211100 2		1			1			S		•	•	•		•
	211105 2		Ţ						S		. ,	•			
	211110 2				•	•			S					•	
			1			11	•	•	S	-		_			
	211115 2		1			'	•	•	c	•	•				
	211120 2		 . I												•
	211125 2	32.	I	•		1			S	•	•	Ī	•		
	211130 2	33.	1			•		-	S	•	•	•	•		•
	211135 2	34.	I			į			S	•		,	• '		•
	211140 2		I		. ,	•			S			1	•	•	•
	211145 2	27	7		_		. ,		S					•	
	211150 2		1	•	•		_		S	• '		•		•	
					• '		•	-	S	_				•	
	211155 2		1			•	• '		. S	•	•	•			
	211200 2		1	*5 * 4	•	ı	• '	•		•	•	•	•	•	•
	211205 2	70.	I			•			S	•	•	•	• '	•	1
	211210 2	71.	 . 1						5						•
	211215 29	72.	Ι			.			S	•				•	٠
	211220 2		I	,					S	•				•	•
	211225 2		T		- -				S		*				
			1		•	·			S	•					
	211230 2		1		•	•		-	S	•		-			
	211235 2		- I		. ` '	•	s - 1 - 10 to		S	•	•	•	•	-	_
	211240 2]				•			•	•	•	•		•
	211245 2		I		,		•			•	•	•	• '	•	,
	211250 2	99.	 3			•				•	•	•	•	•	•
	211255 3		 I		,		,,	,,	-S			,		,	
		-													

TIMINT .083 TIME INTERVAL IN HOURS SURBASIN RUNOFF DATA 9 BA SUBBASIN CHARACTERISTICS TAREA .02 SUBBASIN AREA PRECIPITATION DATA 10 PH DEPTHS FOR O-PERCENT HYPOTHETICAL STORM TP-40 5-MIN 15-MIN 60-MIN 2-HR 3-HR 6-HR 12-HR 24-HR 2-DAY 4-DAY 7-DAY 10-DAY 1.69 2.01 .76 1,34 1.40 1.44 1.56 .00 . .00 .00 .00 STORM AREA = .02 11 LS SCS LOSS RATE STRTL .27 INITIAL ABSTRACTION 88.00 CURVE NUMBER CRVNBR RTIMP .00 PERCENT IMPERVIOUS AREA 12 UD SCS DIMENSIONLESS UNITGRAPH TLAG ---.46 LAG UNIT HYDROGRAPH 29 END-OF-PERIOD ORDINATES 14. 17. 18. 17. 15. 12. 7. 5. 3. 2. 2. 1. 1. 1. 0. 0. 0. 0. 0. 0. 0. 0. *** HYDROGRAPH AT STATION D123 2.01, TOTAL LOSS = 1.04, TOTAL EXCESS = .97 TOTAL RAINFALL = MAXIMUM AVERAGE FLOW PEAK FLOW TIME 24-HR 72-HR 24.92-HR (CFS) (HR) 2. 0. · ·· 0. 10. 12.58 (CFS) ů. (INCHES) .832 .973 . .973 .973 (AC-FT) CUMULATIVE AREA = .02 SQ MI ****** 13 KK 15 KO **DUTPUT CONTROL VARIABLES IPRNT** 3 PRINT CONTROL RZ-6 1 PLOT CONTROL **IPLOT**

1 FIRST ORDINATE PUNCHED OR SAVED

300 LAST ORDINATE PUNCHED OR SAVED

ISAV1

ISAV2

QSCAL

IPNCH

O. HYDROGRAPH PLOT SCALE

1 PUNCH COMPUTED HYDROGRAPH

	IOUT ISAV1 ISAV2 TIMINT	1 300	FIRST ORDIN	RAPH ON THIS U ATE PUNCHED OR TE PUNCHED OR AL IN HOURS	SAVED	· · · · · · · · · · · · · · · · · · ·				
	HYDROGRAPH ROUTI	NG DATA							* ***	
16 RD	MUSKINGUM-CUNG L S N	315. .0045 .025	CHANNEL LENG SLOPE CHANNEL ROUG	SHNESS COEFFIC	IENT		* *			
	CA SHAPE WD Z	TRAP 2.00	CONTRIBUTING CHANNEL SHAF BOTTOM WIDTE SIDE SLOPE	PE H OR DIAMETER			•			• .
		COMPUT		*** 1-cunge parame						
	ELEMENT	ALPHA	COMPUTATION M [N TIME STEP DX	PEAK	TIME TO PEAK	VOLUME	MAXIMUM CELERITY		
			(MI	(FT)	(CFS)			(FPS)		
	MAIN	1.50	1.34	1.90 157.50	10.44	754.36	. 97	2.76	•	
i de la companya de l	MAIN			TO SPECIFIED	COMPUTATION		.97			
CONTINUITY S	UMMARY (AC-FT) - INF	e v						4809E-03 PERCEI	NT ERROR=	.0
##¥ ** *	***	***		** *	***					-
	HYDROGE	IAPH AT STAT	TION CH1	A	To ay					
PEAK FLOW (CFS) 10.	TIME (HR) 12.58 (CFS) (INCHES) (AC-FT)	6-HR 2. .832 1.	MAXIMUM A 24-HR 0. .972	VERAGE FLOW 72-HR 0. .972 1.	24.92-HR 0. .972 1.				10 (20%) 10 (20%) 11 (20%)	
	CUMULATI	VE AREA =	.02 5Q M	I						
							an an enga	e en '	e e esta	
*** *** ***	*** *** *** ***	*** *** ***	**** *** **	* *** *** ***	*** *** ***	*** *** **	* *** ***	· *** *** *** ***	*** *** **	* ***
	******	in the second second	e e du e f	a same get a la			44			
٠.	*					· · · · · ·		•		

***** 17 KK *********

19 KO **OUTPUT CONTROL VARIABLES**

IPRNT

3 PRINT CONTROL

IPLOT QSCAL 1 PLOT CONTROL

IPNCH

O. HYDROGRAPH PLOT SCALE

1 PUNCH COMPUTED HYDROGRAPH

RZ-7

IOUT 21 SAVE HYDROGRAPH ON THIS UNIT ISAV1 1 FIRST ORDINATE PUNCHED OR SAVED ISAV2 300 LAST ORDINATE PUNCHED OR SAVED TIMINT .083 TIME INTERVAL IN HOURS SUBBASIN RUNOFF DATA SUBBASIN CHARACTERISTICS Tarea .00 SUBBASIN AREA PRECIPITATION DATA DEPTHS FOR O-PERCENT HYPOTHETICAL STORM HYDRO-35 TP-40 TP-49 5-MIN 15-MIN 60-MIN 2-HR 3-HR 6-HR 12-HR 24-HR 2-DAY 4-DAY 7-DAY 10-DAY .39 .76 1.34 1.40 1.44 1.56 1.69 2.01 .00 .00 .00 STORM AREA = .00 SCS LOSS RATE STRTL .27 INITIAL ABSTRACTION CRVNBR 88.00 CURVE NUMBER RTIMP .00 PERCENT IMPERVIOUS AREA SCS DIMENSIONLESS UNITGRAPH TLAG .48 LAG UNIT HYDROGRAPH 31 END-OF-PERIOD ORDINATES 1. 1. 2. 3. 3. 3. 3. 2. 0. 0. 3. 0. 2. 2. 1. 0. 0. 0. 1. 1. 0. 1. 1. 0. 0. Û. Û. *** *** HYDROGRAPH AT STATION D4 TOTAL RAINFALL = 2.01, TOTAL LOSS = 1.04, TOTAL EXCESS = MAXIMUM AVERAGE FLOW PEAK FLOW TIME (CFS) (HR) 6-HR 24-HR 72-HR 24.92-HR 0. 0. 0. 0. 12.58 (CFS) .972 .972 (INCHES) .832 .972 (AC-FT) 0. 0. 0. 0. CUMULATIVE AREA = .00 SQ MI ***

24 KK

20 BA

21 PH

22 LS

23 UD

26 KO OUTPUT CONTROL VARIABLES

IPRNT

3 PRINT CONTROL

IPLOT

1 PLOT CONTROL

```
ISAV1
                                      1 FIRST ORDINATE PUNCHED OR SAVED
                      ISAV2
                                    300 LAST ORDINATE PUNCHED OR SAVED
                     TIMINT
                                   .083 TIME INTERVAL IN HOURS
  27 HC
                HYDROGRAPH COMBINATION
                      ICOMP
                                      2 NUMBER OF HYDROGRAPHS TO COMBINE
                                                              ***
      ***
                                                                    ***
                        HYDROGRAPH AT STATION
 PEAK FLOW
              TIME
                                           MAXIMUM AVERAGE FLOW
   (CFS)
              (HR)
                                               24-HR
                                                          72-HR
                                                                    24.92-HR
                                    6-HR
             12.58
     12.
                         (CFS)
                                    2.
                                               1.
                                                           1.
                                                                        1.
                                                                        .972
                                                           .972
                      (INCHES)
                                    .832
                                                .972
                       (AC-FT)
                                                            1.
                       CUMULATIVE AREA =
                                            .02 SQ MI
*** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** ***
           **********
 28 KK
 30 KD
                OUTPUT CONTROL VARIABLES
                     IPRNT
                                     1 PRINT CONTROL
                     IPLOT
                                     2 PLOT CONTROL
                     QSCAL
                                    O. HYDROGRAPH PLOT SCALE
                     IPNCH
                                     1 PUNCH COMPUTED HYDROGRAPH
                      IOUT
                                    21 SAVE HYDROGRAPH ON THIS UNIT
                     ISAV1
                                    1 FIRST ORDINATE PUNCHED OR SAVED
                     ISAV2
                                   300 LAST ORDINATE PUNCHED OR SAVED
                                  .083 TIME INTERVAL IN HOURS
                    TIMINT
             HYDROGRAPH ROUTING DATA
 31 RS
               STORAGE ROUTING
                     NSTPS
                                     1 NUMBER OF SUBREACHES
                      ITYP
                                  ELEV TYPE OF INITIAL CONDITION
                    RSVRIC
                                 17.30 INITIAL CONDITION
                                   .00 WORKING R AND D COEFFICIENT
 32 SV
                 STORAGE
                                  .0
                                            .1
                                                      .0
                                                                                   .8
                                                                                            1.1
 33 SE
               ELEVATION
                               18.30
                                         19.30
                                                  20.30
                                                            21.30
                                                                      22.30
                                                                                23.30
                                                                                          24.00
 34 SL
               LOW-LEVEL OUTLET
                                 18.30 ELEVATION AT CENTER OF DUTLET
                     ELEVL
                     CAREA
                                   .06 CROSS-SECTIONAL AREA
                      COQL
                                   .60 COEFFICIENT
```

USCAL

IPNCH

IOUT

EXPL

.50 EXPONENT OF HEAD

O. HYDROGRAPH PLOT SCALE

1 PUNCH COMPUTED HYDROGRAPH

21 SAVE HYDROGRAPH ON THIS UNIT

35	SS	SPILLWAY

CREL 23.50 SPILLWAY CREST ELEVATION
SPWID 12.29 SPILLWAY WIDTH
COQW 2.70 WEIR COEFFICIENT
EXPW 1.50 EXPONENT OF HEAD

**

COMPUTED OUTFLOW-ELEVATION DATA

OUTFLOW	.00	.11	.13	.14	.17	.20	.24	.31	.42	.69
ELEVATION	18.30	18.45	18.48	18.53	18.61	18.73	18.93	19.33	20.28	23.50
OUTFLOW	.70	.78	1.01	1.45	2.17	3.24	4.74	6.72	9.27	12.45
ELEVATION	23.51	23.52	23.55	23.58	23.63	23.68	23.75	23.82	23.91	24.00
							• .			
1.4			COMPUTE	D STORAGE-	OUTFLOW-EL	EVATION DA	TA			
STORAGE	.03	.04	.04	.05	.05	.06	.07	.10	.10	.02
OUTFLOW	.00	.11	.13	.14	.17	.20	.24	.30	.31	.42
ELEVATION	18.30	18.45	18.48	18.53	18.61	18.73	18.93	19.30	19.33	20.28
STORAGE	.02	.36	.58	.85	.91	.92	93	.94	.96	.97
OUTFLOW	.43	.52	.60	67	. 69	.78	1.01	1.45	2.17	3.24
ELEVATION	20.30	21.30	22.30	23.30	23.50	23.52	23.55	23.58	23.63	23.68
STORAGE	1.00	1.02	1.05	1.08						
OUTFLOW	4.74	6.72	9.27	12.45						
ELEVATION	23.75	23.82	23.91	24.00						

HYDROGRAPH AT STATION RES4

*******	****	*******	******	(******	***	****	****	*****	******	******	***	***	****	***	******	******	*****	
				ž						¥						5		
DA MON HRMN	ORD	OUTFLOW	STORAGE	STAGE * DA	MON	HRMN	ORD	OUTFLOW	STORAGE	STAGE *	DA	MON	HRMN	ORD	OUTFLOW	STORAGE	STAGE	
•				*						*		,						
30 JUN 1200	1	0.	.0	18.3 * 30	JUN	2020	101	.0.	0	18.3 *	. <u>1</u>	JUL	0440	201	1.	.8	23.0	
30 JUN 1205	2	0.	• .0	18.3 * 30	JUN	2025	102	0.	.0	18.3 *	1	JUL	0445	202	1.	8.	23.0	. ,
30 JUN 1210	3	0.	.0	18.3 * 30	JUN	2030	103	0.	.0	18.3 *	1	JUL	0450	203	1.	.8	23.0	
30 JUN 1215	4	0.	.0	18.3 * 30				0.	.0	18.3 *	1	JUL	. 0455	204	1.	.8	23.0	
30 JUN 1220		0.	.0	18.3 * 30				0.	.0		_		0500		1.	.8	23.0	
30 JUN 1225	_	. 0.	.0	18.3 * 30				0.	.0	18.3 *	_				1	•	22.9	
-30 JUN 1230		0.	.0	18.3 * 30				0.	.0				0510		1	7	22.9	
30 JUN 1235	_	0.	.0	18.3 * 30				0.	.0	18.3 *			0515		1.	.7	22.9	
30 JUN 1240	•	0.	.0	18.3 * 30				0.	.0		_		0520		1.	.7	22.9	
30 JUN 1245		0.	.0	18.3 * 30				0.	.0	18.3 *	-		0525		1.	.7	22.9	
30 JUN 1250		0.	.0	18.3 * 30				0.	.0.	18.3 *	_				1.	.7	22.9	
30 JUN 1255	12	0.	.0	18.3 * 30				0.	10	18.3 *					1.	.7	22.9	
30 JUN 1300	13 14	. 0.	.0	18.3 * 30				0.	.0		_		0540 0545		1.	.7 .7	22.9	
30 JUN 1305 30 JUN 1310		0. 0.	.0	18.3 * 30 18.3 * 30				0. 0.	.0		_		0550		1. 1.		22.9	
30 JUN 1310	15	0.	.0	18.3 * 30				0.	0. 0.	18.3 *	-					.7 .7	22.9	
30 JUN 1313		0.	.0 .0	18.3 * 30				0.	.0	18.3 *	-				1. 1.	.7	22.8 22.8	
30 JUN 1325	18	0.	.0	18.3 * 30				0.	.0		_		0605		i.		22.8	
30 JUN 1323	19	0.	.0	18.3 * 30				0.	.0		_		0610		1.	.7	22.8	
30 JUN 1335	20	0.	.0	18.3 * 30				ŏ.	.0.	18.3 *	_				1.	.7	22.8	
30 JUN 1340	21	0.	.0	18.3 * 30				0.	.0	18.3 *	-				1.	.7	22.8	
30 JUN 1345	22	0.	.0	18.3 * 30				0.	.0		-		0625		1.	.7	22.8	
30 JUN 1350	23	0.	.0	18.3 * 30				0.	.0				0630		1.	.7	22.8	
30 JUN 1355	24	Ô.	.0	18.3 * 30	JUN	2215	124	0.	.0		_		0635		1.	.7	22.8	
30 JUN 1400	25	0.	.0	18.3 * 30	JUN	2220	125	0.	.0		_		0640		والمرا	.7	22.7	
30 JUN 1405	26	0.	.0	18.3 * 30	JUN	2225	126	0.	.0	18.3 *	1	JUL	0645	226	K17	-10	22.7	
30 JUN 1410	27	0.	.0	18.3 * 30	JUN	2230	127	0.	.0	18.3 *	1	JUL	0650	227		',	22.7	

30 JUN 1413 Z8 U.		. 20 10M SS20 1		.0	18.9 * 1 10F_0922		./ ZZ./
30 JUN 1420 29 0	0 18.3	* 30 JUN 2240 1	29 0.	.0	18.3 * 1 JUL 0700		.7 22.7
30 JUN 1425 30 0.	0 18.3	+ 30 JUN 2245 13	30 0.	.0	18.3 * 1 JUL 0705	230 1.	.7 22.7
30 JUN 1430 31 0	0 18.3	* 30 JUN 2250 13	31 0.	.0	18.3 * 1 JUL 0710	231 1.	.7 22.7
30 JUN 1435 32 0.		€ 30 JUN 2255 1		.0	18.3 * 1 JUL 0715	232 1.	.7 22.7
30 JUN 1440 33 0		* 30 JUN 2300 1		.0	18.3 * 1 JUL 0720		.7 22.7
				_	18.3 * 1 JUL 0725		.7 22.7
30 JUN 1445 34 0.		* 30 JUN 2305 1		.0			
30 JUN 1450 35 0		* 30 JUN 2310 1		.0	18.3 * 1 JUL 0730		.7 22.7
30 JUN 1455 36 . 0.	0 18.3	₹ 30 JUN 2315 1	36 0.	.0	. 18.3 * 1 JUL 0735		.7 22.7
30 JUN 1500 37 0.	0 18.3	* 30 JUN 2320 1	37 0.	.0	18.3 * 1 JUL 0740	237 1.	.7 22.7
30 JUN 1505 38 0.		₹ 30 JUN 2325 1	38 0.	.0	18.3 * 1 JUL 0745	238 1.	.7 22.7
30 JUN 1510 39 0	and the second s	* 30 JUN 2330 1		.0	18.3 * 1 JUL 0750		.7 22.6
		₹ 30 JUN 2335 14		.0	18.3 * 1 JUL 0755		.7 22. <i>6</i>
30 JUN 1515 40 0.				.0	18.3 * 1 JUL 0800		.7 22.6
30 JUN 1520 41 0.		* 30 JUN 2340 1					.7 22.6
30 JUN 1525 42 0.		* 30 JUN 2345 1		.0	18.3 * 1 JUL 0805		
30 JUN 1530 43 0		* 30 JUN 2350 1		.0	18.3 * 1 JUL 0810		.7 22.6
30 JUN 1535 44 0.	0 18.3	* 30 JUN 2355 14	44 0.	.0	18.4 * 1 JUL 0815		.7 22.6
30 JUN 1540 45 0.	0 18.3	* 1 JUL 0000 1	45 0.	.0	18.4 * 1 JUL 0820	245 1.	.7 22.6
30 JUN 1545 46 0	_	* 1 JUL 0005 1	46 0.	.0	18.5 * 1 JUL 0825	246 1.	.7 22.6
30 JUN 1550 47 0		* 1 JUL 0010 1		.1	18.8 * 1 JUL 0830	247 1.	.7 22.6
		* 1 JUL 0015 1		.1	19.2 * 1 JUL 0835		.7 22.6
30 JUN 1555 48 0.	_				20.6 * 1 JUL 0840		.7 22.6
30 JUN 1600 49 0.		* 1 JUL 0020 1		.1	20.8 * 1 JUL 0845	The second secon	
30 JUN 1605 50 0.		€ 1 JUL 0025 1		.2			
30 JUN 1610 51 0		* 1 JUL 0030 1		.3	21.0 * 1 JUL 0850		.6 22.6
30 JUN 1615 52 0.	0 18.3	€ 1 JUL 0035 1	52 1.	.4	21.3 * 1 JUL 0855		.6 22.6
30 JUN 1620 53 0.	0 18.3	* 1 JUL 0040 1	53 1.	.4	21.6 * 1 JUL 0900		.6 22.5
30 JUN 1625 54 0.		+ 1 JUL 0045 1		.5	22.0 * 1 JUL 0905	254 1.	.6 22.5
30 JUN 1630 55 0.	_	* 1 JUL 0050 1		.6	22.3 * 1 JUL 0910	255 1.	.6 22.5
		+ 1 JUL 0055 1		.6	22.5 * 1 JUL 0915		.6 22.5
30 JUN 1635 56 0.				.7	22.7 * 1 JUL 0920		.6 22.5
30 JUN 1640 57 0		* 1 JUL 0100 1			22.8 * 1 JUL 0925		.6 22.5
30 JUN 1645 58 0.		• 1 JUL 0105 1		.7			
30 JUN 1650 59 0		* 1 JUL 0110 1		.7	22.9 * 1 JUL 0930		
30 JUN 1655 60 0.	0 18.3	* 1 JUL 0115 1	50 1.	.8	23.0 * 1 JUL 0935		.6 22.5
30 JUN 1700 61 0	0 18.3	* 1 JUL 0120 1	61 1.	.8	23.0 * 1 JUL 0940		.6 22.5
30 JUN 1705 62 0.	_	€ 1 JUL 0125 1	52 1.	.8	23.1 * 1 JUL 0945	262 1.	.6 22.5
30 JUN 1710 63 0		* 1 JUL 0130 1		.8	23.1 * 1 JUL 0950	263 1.	.6 22.5
_		* 1 JUL 0135 1		.8	23.2 * 1 JUL 0955		.6 22.5
		* 1 JUL 0140 1		.8	23.2 * 1 JUL 1000		.6 22.4
30 JUN 1720 65 0.				.8	23.2 * 1 JUL 1005		.6 22.4
30 JUN 1725 66 0.		* 1 JUL 0145 1			23.2 * 1 JUL 1010		.6 22.4
30 JUN 1730 67 0		* 1 JUL 0150 1		.8			
30 JUN 1735 68 0.		* 1 JUL 0155 1		.8	23.2 * 1 JUL 1015		.6 22.4
30 JUN 1740 69 0		* 1 JUL 0200 1		.8	23.2 * 1 JUL 1020		.6 22.4
30 JUN 1745 70 0.	0 18.3	* 1 JUL 0205 1	70 1.	.8	23.2 * 1 JUL 1025		.6 22.4
30 JUN 1750 71 0		* 1 JUL 0210 1		.8	23.2 * 1 JUL 1030		.6 22.4
30 JUN 1755 72 0		* 1 JUL 0215 1		.8	23.2 * 1 JUL 1035	272 1.	.6 22.4
30 JUN 1800 73 0		* 1 JUL 0220 1		.8	23.2 * 1 JUL 1040	273. 1.	.6. 22.4
30 JUN 1805 74 0.		* 1 JUL 0225 1		.8	23.2 * 1 JUL 1045		.6 22.4
30 JUN 1810 75 0		* 1 JUL 0230 1			23.2 * 1 JUL 1050	275 1.	.6 22.4
		* 1 JUL 0235 1		.8	23.2 * 1 JUL 1055		.6. 22.4
30 JUN 1815 76 0:		* 1 JUL 0233 1 * 1 JUL 0240 1			23.2 * 1 JUL 1100		.6 22.3
30 JUN 1820 77 0				_	23.2 * 1 JUL 1105		.6 22.3
30 JUN 1825 78 0.		* 1 JUL 0245 1					.6 22.3
30 JUN 1830 79 0		* 1 JUL 0250 1			23.2 * 1 JUL 1110		
30 JUN 1835 80 0		* 1 JUL 0255 1		.8	23.2 * 1 JUL 1115		.6 22.3
30 JUN 1840 81 0		* 1 JUL 0300 1		.8	23.2 * 1 JUL 1120		.6 22.3
30 JUN 1845 82 0.	0 18.3	* 1 JUL 0305 1	B2 1.	.8	23.2 * 1 JUL 1125		.6 22.3
30 JUN 1850 83 0	_	* 1 JUL 0310 1		.8	23.2 * 1 JUL 1130	283 1.	.6 22.3
30 JUN 1855 84 0		* 1 JUL 0315 1		.8	23.1 * 1 JUL 1135	284 1.	.6 22.3
30 JUN 1900 85 0		* 1 JUL 0320 1			23.1 * 1 JUL 1140		.6 22.3
		* 1 JUL 0325 1		.8	23.1 * 1 JUL 1145		.6 22.3
30 JUN 1905 86 0				.8	23.1 * 1 JUL 1150		.6 22.3
30 JUN 1910 87 0		* 1 JUL 0330 1			23.1 * 1 JUL 1155		.6 22.2
30 JUN 1915 88 0.		* 1 JUL 0335 1		8.			
.30 JUN 1920 89 0		* 1 JUL 0340 1			23.1 * 1 JUL 1200		
30 JUN 1925 90 0		* 1 JUL 0345 1		.8	23.1 * 1 JUL 1205		.6 22.2
30 JUN 1930 91 0		* 1 JUL 0350 1		.8	23.1 * 1 JUL 1210		7 - 4 22.2
30 JUN 1935 92 0.	0 18.3	* 1 JUL 0355 1	92 1.	.8	23.1 * 1 JUL 1215		Z6 22.2
30 JUN 1940 93 0	2.7	* 1 JUL 0400 1	93 1.	.8	23.1 * 1 JUL 1220	293 1.	.6 22.2

30 JUN 1945	94	0.	.0 18.3	* 1 JUL 0405	194	1	3 23	. 1 *	1	IIII	1225	294	1.
30 JUN 1950	95		.0 18.3		-	1.		.1 *			1230		1.
30 JUN 1955	96		.0 18.3	• •		1.		.0 *	_		1235		1.
30 JUN 2000	97	0.	.0 18.3	* 1 JUL 0420	197	1.	3 23	.0 *			1240		1.
30 JUN 2005	98	0.		* 1 JUL 0425		1.					1245		1.
30 JUN 2010	99	0.	.0 18.3	* 1 JUL 0430	199	1.	3 23	* 0.	1	JUL	1250	299	1.
30 JUN 2015	100	0.	.0 18.3	* 1 JUL 0435	200	1	3 23.	.0 *	1	JUL	1255	300	1.
				*				¥					
**********	******	********	*******	***********	*******	********	*****	****	***	***	****	****	*********
PEAK FLOW	TIME			MAXIMUM AVEF	מאפר בו חוו								
(CFS)	(HR)		6-HR	24-HR	72-HR	24.92-H							
1.	13.83	(CFS)	1.	24-rav 0.	0.	27.72 ⁻¹ # 0.							
1.	19:09					-							
		(INCHES)	.272	.555	.555	.55							
		(AC-FT)	0.	1.	1.	1							
PEAK STORAGE	TIME			MAXIMUM AVERA	AGE STORAG	Ε		•	•				
(AC-FT)	(HR)		6-HR	24-HR	72-HR	24.92-HF							
1.	14.08		1.	0.	0.	0.							
PEAK STAGE	TIME	•		MAXIMUM AVER	RAGE STAGE								
(FEET)	(HR)		6-HR	24-HR	72-HR	24.92-HF							
23.20	14.17		23.01	20.60	20.52	20.52							;
		CUMULATIV	K ABEA =	.02 SQ MI									• :

.5 .5 .5

.5 .5

.5

22.2 22.2 22.1

22.1 22.1

22.1 22.1 STATION RES4

-				,	*1.15	-1.60		DUTE: DU								P = -	
		0.	2.		1Nt 4.		(u) 6.	OUTFLOW 8.	10.	12.	•		O. STORAGE				
n. 7 *04		.0	.()	.0		.0	.0	.0	.0)	.2	.4		6 .8	3 1.0	0,
	DAHRMN										_C						
•	301200	1 I -	-					,-			 . S				•		
	301205	21		ı	*		•	•	•		. S	•	•		•		
	301210	- 3I	•	•			. •	•	•	•	. J		•		•		
	301215	4 I	•		•		٠	•	•	•	. O	•	•	•			
	301220	51	•	•	•		•	1	•	•		•	•		•		· · · · · · · · · · · · · · · · · · ·
27 270 28 28 28 28 28 28 28 28 28 28 28 28 28 2	301225	6I	1		•	100	•	•	•	•			. •		•		
ivia	301230	71		•	•		•		•	•		•	•		•		
-	301235	81	•	ı	•	-	•	•	*	•		•	•		•		
	301240	91	•		. •			*	•	•	. Q	•	•	- L. 61 - 4	•		
7	301245	10I	•		٠		•	. •	•	•	. 5	•	•		• '		
س	301250	11 I		• • •	• •		•										
	301255	121	•	ı	•		•		•	•	. S	•	•		•	'	
***	301300		•	•			•	•			. S	•	•		•		•
1	301305	14 I		u e e e	•		•	•	•		. S	•	•		•	'	•
_	301310		•	•	•		•		•		. S	1	•		•	,	
	301315		•		•		•	• • • •	* * *		. S	•	•	•			
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	301320		•		٠		•	•	•			•	•		•	,	•
	301325			ı	٠		•				. S	•	•		•	•	
	301330			ı				•	•		. S	•	•			•	•
4.4	301335	201	•		. •		٠	1,000	er er er er er er er er er er	•	. S	•	•		•		•
i esta	301340				• •		•				. 5 .						
_	301345						•	•	4	_	. 5	•	•		•		•
*	301350			1	•		•		•		. S	•			• '		
- Adj	301355			i	•			•		_	. S	•			• '	•	•
	301400		, .	:			•	•	•		. 5	•	•		• !		•
	301405				•		•		•	_	. S	•	•			•	•
***	301410					* ** .	•		. •		. S	•	•		•	• •	•
	301415				•		•	•	•		. S	•	•		. '	, ,	•
	301420	291					1				. 5	•	*				•
	301425										. 5	•	•		• '	•	•
8.3	301430										. S .						
	301435	32I								•	. S		•		•	•	
	301440		•	Ī			•		•		. 5	•			*	- •	•
	301445		. •				•	•	•		. S	•	•		• •	•	•
	301450			•	•		•		•		. S	•	•		•		•
	301455						•		•		. S	•			• '	•	. •
1.9	301500		•	ı			•	•	•		. S	•	•		* '	, ,	•
	301505		•				•	•	•	•	. S	•	•		• '	•	•
_	301510		•	•	•			•	•		. S	•	•		•	,	•
- 104	301515				•		٠	•	•		. S	•	•		• '	'	•
14	301520						٠				. 5 .						
	301525	42I					*	•	•		. S	•	•		,	•	•
	301530			ı			•		* * * * *		. 5	•	•		•	•	•
	301535		•		٠			•	•		. S	•	•		. '		•
	301540		•	ı	•		•	•	•	•	. 5	•	•		•		•
	301545	46 I			•		•				S	•	•				
igt.	301550			. "	•				•		. 5	•	•		•	i .	
منس	301555	48 I			•		•	•	•		S	•	•				
	301600			ı	•		•	•			. 5		•		•	, ,	•
	301605	5 01			•		•	•		•	. S	•	, •		•	•	
	301610						*				. S .				ہز	2-1	2
	301615	52I			•		•	•	•		. S	•	•		· [2	L- 1	つ ・
	301620						•	•			. S	•	•			₹ ,	
	301625	541	•	,	•			•		•	. S	•	•		• •	•	

	301630 301635	56 I				1	•	, ,		5 .			, ,		
	301640 301645 301650	58I			•	• •	•	•		ā .			•	· •	
	301655 301700	60I				· ·			, ,						
	301705 301710	63 I			• ·	•	e :		, e i	6.					
•	301715 301720 301725	65I			•	•				5 .	•				
	301723 301730 301735	67 I				•				s .		•		•	
	301740 301745	70 I			*		•	•				•			
	301750 301755 301800	72I		• •						5.					
	301805 301810	74I - 75I			* " " " " " " " " " " " " " " " " " " "	• •				S .					
	301815 301820 301825					•		•	,	5.		•			
	301830 301835	791 801			• •	· ·	a :			S .	remanda e				
	301840 301845 301850	8 21		• •						5 5 .			, , , , , ,		
	301855 301900	84 I 85 I		٠.	•	•				5.					
	301905 301910 301915	87 I					* · · · · · · · · · · · · · · · · · · ·	• ·		S .	, ,	•			
	301920 301925	891 901			•	•	*				•				
	301930 301935 301940	9 2I								S .					
	301945 301950	941 951				•	* · · ·	• · · · · · · · · · · · · · · · · · · ·		S ,		, ·			
	301955 302000 302005	971			1.	•		•	!	S .	· · · · · · · · · · · · · · · · · · ·	·	•	•	
	302010 302015	9 91 1001			•	i care	•			5 . 5 .					
	302020 302025 302030	102I 103I	••	•						s,		, ,	•	•	
	302035 302040 302045	104I 105I			•		•	*		5 5	, i	, ,			
	302050 302055	107I			•		*	•		S .				•	
	302100 302105 302110	1101			• • * * * * * * * * * * * * * * * * * *		•	•		S S				· · · · · ·	
	302115 302120	112I 113I								S,					
	302125 302130 302135	115I				•	•			S.					
	302140 302145	117I 118I			•	.	•				, " i	, ;	122	-14	,
	302150 302155				•	•	•	• •		6 .	, ,				

	TIME ION	4174.1									ű					
	302200			• •			٠.				 . s					
	302205			•	•	•	•	·	• •		. S	•		•	•	
	302210			•	•	•	•		•		. S	•	•		•	
	302215			•	ı	•	٠	•			. S	•		•		
	302220			1		1	•	,	• January 1	-	. S	•		•		
	302225			•	1	•	•	•			. S	•	•	•	•	
	302230			٠	1	•	•		•		. S	•	•	•	•	
	302235				ı	•	•	i				•		•		•
	302240				r• ' ·		٠				. S	•	•	•	•	•
	302245					•	•	1			. 5	•		•	•	•
	302250										. 5				• • • • • .	
	302255				ı	•	•	i			. 5	•	•	•	•	• •
	302300				i			į	•	-	. S				•	
	302305				:			•			. S			•	•	
	302310	135I	[,			•				. 5	•	•	• • • •	•	
	302315	136I			1						. S			•	•	
	302320	137I			1						. S	•	•	•	•	•
	302325	138I			ı			i			. S	•	•	•	•	
	302330	139I	[,	<u>.</u>						. 5	•	•		•	
	302335	140I			·			,		, :	. S		•	•	•	
	302340										. S					
-	302345				ı						. S	•				•
	302350				ı						. S	• ,				
	302355							,			, S					
	10000								*		. S				• * *	
	10005			·						. :	. S					
	10010			•	. 1						. S				• '	
	10015				-		Ι.		, ;	i 1	S		•			
	10020			•	<u>'</u>	•			.I		. S		•			
	10025								. ,	I	•	S	•			
	10030										[5				
	10035							• • • •			. I	. S	•			
	10040			•	•				_				. S			
	-				•	•			•	I		•	. 8			
	10045	154.	, O						. I	· -				: :		
	10045 10050	154. 155.	. O . O		•		•	- :	. I	· -	• •	•	. S	.S		
	10045 10050 10055	154. 155. 156.	. O . O		•	•	•	· :	. I	· -	•		. S	•	•	
	10045 10050 10055 10100	154. 155. 156. 157.	. O . O					I	. I	· -	•	•	. S	.s . s . s	· · · · ·	· · · · · · · · · · · · · · · · · · ·
	10045 10050 10055 10100 10105	154. 155. 156. 157. 158.	. O				•	I	. I	· -	•		. S	.s . s	•	
	10045 10050 10055 10100 10105 10110	154. 155. 156. 157. 158. 159.	. 0		·	•		I	I I	· -			. S	.s . s . s	•	
	10045 10050 10055 10100 10105 10110 10115	154. 155. 156. 157. 158. 159.			I		•	I	I	· -			. S	.S . S . S		
	10045 10050 10055 10100 10105 10110 10115 10120	154. 155. 156. 157. 158. 159. 160.			I		•	I		· -			. S	.S . S . S . S S	 S	
	10045 10050 10055 10100 10105 10110 10115 10120 10125	154. 155. 156. 157. 158. 159. 160. 161.			I I		•	I		· -			. S	.S . S . S . S S	 S S	
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130	154. 155. 156. 157. 158. 159. 160. 161. 162.		I	I I		•	I		· -			. S	.S . S . S . S S	 S	
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10135	154. 155. 156. 157. 158. 159. 160. 161. 162. 163.			I I		•	I		· -			. S	.S . S . S S S	 5 5 5 .S	
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10135 10140	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164.			I I		•	I		· -			. S	.S . S . S S	 S S S .S	
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10135 10140	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165.			I I		•	I		· -			. S	.S .S .S .S S	 S S S .S .S	
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10140 10145 10150	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165.			I I		•	I		· -			. S	.S . S . S S		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10140 10145 10150	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166.			I I		•	I		· -			. S	.s . s . s s		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10140 10155 10200	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168.			I I		•	I		· -			. S	.s . s . s s		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10140 10145 10150 10155 10200 10205	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168.			I I		•	I		· -			. S	. S . S . S 		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10140 10145 10150 10200 10205 10210	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 170.			I I		•	I		· -			. S	.S . S . S S		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10155 10200 10205 10210	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 170. 171.			I I		•	I		· -			. S	.S . S . S S		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10200 10205 10210 10215 10220	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172.			I I		•	I		· -			. S	. S . S . S		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10205 10210 10215 10220 10225	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173.			I I		•	I		· -			. S	.S . S . S S		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10205 10210 10215 10220 10225 10230	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 170. 171. 172. 173. 174.			I I		•	I		· -			. S	.S . S . S S		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10205 10200 10205 10210 10225 10230 10235	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173. 174.			I I		•	I		· -			. S	.s . s . s s		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10200 10205 10210 10215 10220 10225 10230 10235 10240	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176.			I I		•	I		· -			. S	.s . s . s s		
	10045 10050 10055 10100 10105 10110 10125 10120 10135 10140 10145 10150 10200 10205 10210 10215 10220 10225 10230 10235 10240 10245	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176.			I I		•	I		· -			. S	. S		
	10045 10050 10055 10100 10105 10110 10115 10120 10135 10140 10145 10200 10205 10210 10215 10220 10230 10235 10240 10245 10250	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 177. 178.			I I		•	I		· -			. S	. S		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10200 10205 10210 10215 10220 10225 10230 10240 10245 10250 10255	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173. 174. 175. 177. 178.			I I		•	I		· -			. S	. S		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10205 10210 10205 10210 10225 10230 10240 10245 10250 10255 10300	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173. 174. 175. 177. 178. 179. 180.	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		I I		•	I		· -			. S	. S		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10205 10210 10205 10210 10225 10230 10240 10245 10250 10255 10300 10305	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173. 174. 175. 177. 178. 179. 180. 181.	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		I I		•	I		· -			. S	. S		
•	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10205 10210 10205 10210 10225 10230 10235 10240 10245 10250 10255 10300 10305 10310	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173. 174. 175. 177. 178. 179. 180. 181.	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		I I		•			· -			. S	. S		
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10205 10210 10215 10220 10225 10230 10240 10245 10250 10255 10300 10305 10310 10315	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173. 174. 175. 176. 177. 180. 181. 182. 183. 184.	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		I I		•	I		· -			. S	. S		15
	10045 10050 10055 10100 10105 10110 10115 10120 10125 10130 10145 10150 10205 10210 10205 10210 10225 10230 10235 10240 10245 10250 10255 10300 10305 10310	154. 155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 167. 170. 171. 172. 173. 174. 175. 176. 177. 178. 180. 181. 182. 183. 184.	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		I I		•	I		· -			. S			

1	0330 1	87. IO						_	_				. (·	1
		88. IO		:		•							. 9		•
		89. IO				1	•						. 9	3 .	
		90. IO				:						•	. 9		
		91. IO											S.		
1	0355 1	92. IO				•		•	•			•	. <u>s</u> .		
		93. IO			•	•	•		•	Ì		•	. S.		
		94. IO			•		•			•		•	. S.		ı
		95.I O		•		•		•		1	•	•	. S.		
		96.I O		•			•		•		•	•	. s. . s.		1
_		97.10	-	•				•	•	•	•	•	. S.		
		98.I O		•	•	ı	•	•		<u> </u>			. S.		
		99.I O 00.I O		.*			•	•			•		. S.		·
				•		· · • • • •									
		02.I O							•	•			. S.		
		03.I D											. S.	, ,	
		04.I O				i		•				•	. 5.		
		05.I O				ì							S.		•
. 1	0505 2	06.1 0				,			•			Į.	. S.		•
		07.I O				ı	•		•	1		•	. S.	, ,	•
		01.80				•			•		•		. S.		
		09.I O		•		•		•		•	•		. 5.		
		10.I O	•	•	***		•	•	•		•	•	,	' .	
		11.I.O		• • •											
		12.I O 13.I O			•	•	•	• 2	•				, S.		
		13.1 U		•	_	,				·		•	. s.		ı
		15.I O				•		• 1		t.		•	. s .		
		16.I O							*				. s .		
		17.Î O				1	•			•		•	. 5.		•
		18.I O								•			. 5 .	•	•
_		19.I O			•		•		•	•		•	. 5.	, '	
		20.I O					•	•			•	•	S		
		21.I.O.		• • •	• • •				, , , , ,				. 5		
		22.I O 23.I O		•	•	1	•	•	•		•		. 5		•
		24.I O		• .	•			-	•			·· .	, S ,		•
		25. IO				•		•					. S .	, !	
		26. IO						•	• ', '	• ***	. .		. S.		,
		27. IO								•		•	. s .		•
		28. IO		•		ı	•	1	• (**,*)			•	S,		•
		29. IO						*	•	•	•	•	. S .		•
		30. IO		•	•		•		•		•	•	S	,	
		31. IO 32. IO						ara aya a							
		33. IO								•	•		. S .		
		34. IO		•		1			•		•		. 5 .	, ,	
		35. IO				•		•		•	•		. S		
		36. IO		•	•		*		•	•	•	•	. S .		•
		37. IO			•	•	•	•	•	•	•	•		. '	•
		38. 10		· ·	•	ı	•	•	•	* .	•	•	. 5		
		39. IO		•	•	1	•	•	•	•	•	•	. S		
		40. IO 41. IO		•		' 							S		
		41. IO 42. IO							- , - , - ,	•			. s .		•
		43. IO						•	•	•	•		. S		•
		44. IO				ı		•	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		•	•	. s .		•
1	0820 2	45. IO				ī	•				•	•	. S		•
		46. IO		•	•	,	•	•	•		• .	• .	. S .		•
		47. IO		•	•	•	•	•	•	•	•	•	. 5 . . S .	•	
		48. IO		•	•	·	•	•	•	_			. 5		
		49. IO 50. IO					•			•		1	~		11
		51. IO											. S	RZ-	صا
		52. IO							•	•	•	·	.s .	,	. —
•															

-

100

10900 253. IU	ī								. 5	•		•
10905 254. IO			_	_				,	. S			
	•	•							. S		_	
10910 255. ID	•		•	•	•	•	•			•	•	•
10915 256. IO	 •	•		•		•			. S	•	•	•
10920 257. IO								1	. S			
10925 258. IO	-	•							. S	-		
	•	• ;	•	•					.s	-		
10930 259. IO		•					•			•	•	•
10935 260. IO				,					. S			
10940 261.I.O	-								.S			
									.5		_	
10945 262.I O		•		•	•		•				•	•
10950 263.I O		•							.S	•	•	*
10955 264.I O								ı	.S		• 1	
11000 265.I O						_			.S			
		•	•	•	•	_	-		. S		_	
11005 266.I O	•		• '	•	•	• '	•			•	•	•
11010 267.I D		•	•			•			.S	•	•	•
11015 268.I O			. !			. ,			S .	•	•	
11020 269.I O	-			_				ì	S	•		
	•	•	•	•	•	•			S			
11025 270.I O	•	•	• •	•		• '	•	•			•	•
11030 271.I.O	 								5			•
 11035 272.I O									5 .		*	
11040 273.I O	-			_	_		. ,		S			*
4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	•	•	•	•	•	_			S .		_	
11045 274.I O	•		•			•					•	•
11050 275.I O	•					•	•	•	S	•	•	•
11055 276.I O			*					ı	S .	•	• •	
11100 277.I O	-		_	_				, 9			• ·	
	•	•	•	•	-			. 9	_	=,		
11105 278.I O	•		•	•	•	,		. 9		•	-	
11110 279.I O		•		•	•		•			•	•	•
11115 280.I O			•		i :			. S		•		
11120 281.I.O								9				•
11125 282.I O					_	_		. 9				
	•	•	No. of		•	•		. S			_	
11130 283.1 0		•	•	•		•	•			•	•	•
11135 284.I O	•	■ 2 × 5		•				. S		•		
11140 285.I O								. 9				
11145 286.I O				_				, S		•		
	•	-	• '	-			_	. S				
11150 287.I O	•	•	•	•	•	•	•	. с	•	-		_
11155 288.I O	•		•	•		•		. 5	•	•	•	•
11200 289.I O				. .	• ,	•		. S	•	• ,	•	•
11205 290.I D	_							. 8		•		
11210 291.I.O	-		-					5				
								. 5				
11215 292.I O	1	•		•	•	•	'	. S	-	•	-	
11220 293.I O		• .		•		•	•		•	· .,	1	•
11225 294.I O							, ,	. S	•	3		•
11230 295.I O		_					. :	. 5				
	-	-	-		_	_		. 8		•	•	
11235 296.I D	•	•	•	•	•	•		. S	-		_	
11240 297.I O		•	•	•	•	•			•	•	•	•
11245 298I O						•	. ,	. 5	•	•	•	•
11250 2991 0					,		•	. 5	•	•	•	•
11255 300I0-							,	S				
11700 0001 _0	•	-	•	-								
								•				

```
*** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** ***
   36 KK
                    P1A
            ******
   38, KO
                 OUTPUT CONTROL VARIABLES
                       IPRNT
                                       3 PRINT CONTROL
                       IPLOT
                                       1 PLOT CONTROL
                       QSCAL
                                      O. HYDROGRAPH PLOT SCALE
                       IPNCH
                                       1 PUNCH COMPUTED HYDROGRAPH
                                      21 SAVE HYDROGRAPH ON THIS UNIT
                        IOUT
                       ISAV1
                                       1 FIRST ORDINATE PUNCHED OR SAVED
                       ISAV2
                                     300 LAST ORDINATE PUNCHED OR SAVED
                      TIMINT
                                    .083 TIME INTERVAL IN HOURS
               HYDROGRAPH ROUTING DATA
  39 RD
                 MUSKINGUM-CUNGE CHANNEL ROUTING
                           L
                                    655. CHANNEL LENGTH
                           S
                                   .0067 SLOPE
                                    .015 CHANNEL ROUGHNESS COEFFICIENT
                           Ν
                                     .00 CONTRIBUTING AREA
                          CA
                       SHAPE
                                    CIRC CHANNEL SHAPE
                          WD)
                                    2.00 BOTTOM WIDTH OR DIAMETER
                                     .00 SIDE SLOPE
                                   COMPUTED MUSKINGUM-CUNGE PARAMETERS
                                          COMPUTATION TIME STEP
                    ELEMENT
                               ALPHA
                                                    DT
                                                                       PEAK
                                                                               TIME TO
                                                                                          VOLUME
                                                                                                    MAXIMUM
                                                                                PEAK ...
                                                                                                    CELERITY
                                                                                                     (FPS)
                                                  (MIN)
                                                             (FT)
                                                                      (CFS)
                                                                                (MIN)
                                                                                           (IN)
                      MAIN
                                4.92
                                          1.25
                                                     3.04
                                                             327.50
                                                                          .67
                                                                                851.14
                                                                                             .55
                                                                                                      3.59
                                         INTERPOLATED TO SPECIFIED COMPUTATION INTERVAL
                     MAIN
                                4.92
                                          1.25
                                                     5.00
                                                                                855.00
                                                                                             .55
CONTINUITY SUMMARY (AC-FT) - INFLOW= .6587E+00 EXCESS= .0000E+00 DUTFLOW= .6560E+00 BASIN STORAGE= .2736E-02 PERCENT ERROR=
     ***
```

HYDROGRAPH AT STATION

6-HR

PEAK FLOW

(CFS)

TIME

(HR)

P1A

24-HR

MAXIMUM AVERAGE FLOW

72-HR

24.92-HR

```
*** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** ***
 40 KK
                  C2 *
 42 KO
              OUTPUT CONTROL VARIABLES
                    IPRNT
                                 3 PRINT CONTROL
                                 1 PLOT CONTROL
                    IPLOT
                   QSCAL
                                 O. HYDROGRAPH PLOT SCALE
                   IPNCH
                                1 PUNCH COMPUTED HYDROGRAPH
                    IOUT
                                21 SAVE HYDROGRAPH ON THIS UNIT
                    ISAV1
                                1 FIRST ORDINATE PUNCHED OR SAVED
                   ISAV2
                                300 LAST ORDINATE PUNCHED OR SAVED
                   TIMINT
                               .083 TIME INTERVAL IN HOURS
            SUBBASIN RUNOFF DATA
 43 BA
              SUBBASIN CHARACTERISTICS
                   Tarea
                          .00 SUBBASIN AREA
              PRECIPITATION DATA
                                   DEPTHS FOR O-PERCENT HYPOTHETICAL STORM
44 PH
              ..... HYDRO-35 .....
                                    ..... TP-40 ..... TP-49 .....
                                           3-HR
                                                                                      7-DAY 10-DAY
              5-MIN 15-MIN 60-MIN
                                    2-HR
                                                   6-HR 12-HR 24-HR
                                                                       2-DAY 4-DAY
                    .76
                           1.34
                                    1.40
                                          1.44
                                                   1.56
                                                        1.69
                                                                 2.01
                                            STORM AREA =
                                                            .00
45 LS
              SCS LOSS RATE
                               .27 INITIAL ABSTRACTION
                   STRTL
                  CRVNBR
                              88.00 CURVE NUMBER .
                   RTIMP
                                .00 PERCENT IMPERVIOUS AREA
46 UD
              SCS DIMENSIONLESS UNITGRAPH
                    TLAG
                                .61 LAG
                                                  UNIT HYDROGRAPH
                                              38 END-OF-PERIOD ORDINATES
                                        2.
                                                 3.
                                                          3.
                      1.
                               1.
                                                                   4.
                                                                             4.
                      2.
                               2.
                                        1.
                                                 1.
                                                          1.
                                                                   1.
                                                                            1.
                                                                                    1.
                                                 0.
                                        0.
                                                          0.
                                                                   0.
                                                                            0.
                                                 0.
                                        0.
                                                           0.
                                                                    0.
```

13.92

(CFS)

CUMULATIVE AREA =

HYDROGRAPH AT STATION

TOTAL RAINFALL = 2.01, TOTAL LOSS = 1.04, TOTAL EXCESS = .97

(INCHES)

(AC-FT)

0.

.552

1.

.02 SQ MI

0.

0.

.552

1.

0.

.552

```
(CFS)
              (HR)
                                  6-HR
                                            24-HR
                                                       72-HR
                                                                24.92-HR
      2.
             12.75
                        (CFS)
                                   0.
                                             0.
                                                        0.
                                                                  0.
                                  .830
                      (INCHES)
                                              .971
                                                         .971
                                                                    .971
                       (AC-FT)
                                                                     0.
                       CUMULATIVE AREA =
                                           .00 SQ MI
*** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** ***
           *********
  47 KK
           ***********
                OUTPUT CONTROL VARIABLES
                     IPRNT
                                3 PRINT CONTROL
                     IPLOT
                                   1 PLOT CONTROL
                     QSCAL
                                  O. HYDROGRAPH PLOT SCALE
                     IPNCH
                                   1 PUNCH COMPUTED HYDROGRAPH
                      TUOI
                                  21 SAVE HYDROGRAPH ON THIS UNIT
                     ISAV1
                                  1 FIRST ORDINATE PUNCHED OR SAVED
                     ISAV2
                                  300 LAST ORDINATE PUNCHED OR SAVED
                    TIMINT
                                 .083 TIME INTERVAL IN HOURS
  50 HC
               HYDROGRAPH COMBINATION
                     ICOMP
                                   2 NUMBER OF HYDROGRAPHS TO COMBINE
     ***
                      HYDROGRAPH AT STATION
                                                C2
PEAK FLOW
             TIME
                                         MAXIMUM AVERAGE FLOW
             (HR)
                                           24-HR
                                                      72-HR
  (CFS)
                                 6-HR
                                                                24.92-HR
                                                       0.
      3.
            12.75
                       (CFS)
                                  i.
                                            0.
                                                                   0.
                                                       .628
                     (INCHES)
                                             .628
                                  .362
                      (AC-FT)
                                  1.
                                              1.
                                                        1.
                     CUMULATIVE AREA =
                                          .03 SQ MI
*** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** *** ***
 51 KK
                 C13 *
```

MAXIMUM AVERAGE FLOW

PEAK FLOW

53 KO

OUTPUT CONTROL VARIABLES
IPRNT 3

IPLOT

QSCAL

IPNCH

IOUT

3 PRINT CONTROL

1 PLOT CONTROL

O. HYDROGRAPH PLOT SCALE1 PUNCH COMPUTED HYDROGRAPH

21 SAVE HYDROGRAPH ON THIS UNIT

TIME

12-20

	S	UBBASI	N RUNOFF	DATA							
54 BA		SUBBA	SIN CHARA TAREA	CTERISTICS .02	SUBBASIN AF	REA					
		PRECI	PITATION	DATA							
55 PH				D	EPTHS FOR	O-PERCENT H	IYPOTHET I	CAL STO	RM		
				*****	******	TP-40					
		5-MIN .39			2-HR 3-H 1.40 1.4						
	,et				SI	ORM AREA =	.02				
56 LS		SCS LO	ISS RATE								
			STRTL		INITIAL ABS	STRACTION					
					CURVE NUMBE		'Λ				
			RTIMP	.00	PERCENT IMP	EKVIUUS AKE	.H				•,
57 UD				ESS UNITGRA	APH						
	e tyreyta e		TLAG	.47	LAG						

						UNIT H	YDROGRAP	Н			
						30 END-OF-P	ERIOD OR	DINATES			
					14.	18. 3.	19.	19.	17.	 14.	10.
		8. 1.	6. 0.	5. 0.	٠. 0.	o.	0.	0.	0.	0.	1.
- 44 4	í	. ¥	**	***			**				
	•			ARA			***	•			
			HYDROGR	APH AT STA	TION C	13					
TOTAL	. RAINFAL	L =	Ż.01, TO	TAL LOSS =	1.04, T	DTAL EXCESS	= .	97			
PEAK FLO	W TI	ME			MAXIMUM	AVERAGE FLO	d.				
(CFS)		R)	(000)	6-HR	24-HR			.92-HR			
11.	12.		(CFS) (INCHES)		1. .972			1. .972			
			(AC-FT)	1.	1.			1.			
			CUMULATI	ve area =	.02 SQ 1	1 I					
						. •					

1 FIRST URDINATE PUNCHED OR SAVED

300 LAST ORDINATE PUNCHED OR SAVED

.083 TIME INTERVAL IN HOURS

4

60 KO OUTPUT CONTROL VARIABLES

IPRNT IPLOT 3 PRINT-CONTROL

QSCAL

15AV1

ISAV2

TIMINT

1 PLOT CONTROL

IPNCH

O. HYDROGRAPH PLOT SCALE
1 PUNCH COMPUTED HYDROGRAPH

RZ- 21

```
ISAV1
                                  1 FIRST ORDINATE PUNCHED OR SAVED
                    ISAV2
                                    LAST ORDINATE PUNCHED OR SAVED
                   TIMINT
                                .083 TIME INTERVAL IN HOURS
               HYDROGRAPH COMBINATION
                    ICOMP
                                  2 NUMBER OF HYDROGRAPHS TO COMBINE
                                                        ***
                   ***
                     HYDROGRAPH AT STATION
             TIME
                                       MAXIMUM AVERAGE FLOW
             (HR)
                                          24-HR
                                                    72-HR
                                6-HR
                                                             24.92-HR
            12.58
                       (CFS)
                                 3.
                                           1.
                                                     1.
                                                                 i.
                                                     .776
                    (INCHES)
                                .561
                                           .776
                                                                .776
                     (AC-FT)
                                  1.
                                            2.
                                                      2.
                                                                  2.
                     CUMULATIVE AREA =
                                        .05 SQ MI
*****
              OUTPUT CONTROL VARIABLES
                   IPRNT
                                3 PRINT CONTROL
                   IPLOT
                                1 PLOT CONTROL
                   QSCAL
                                O. HYDROGRAPH PLOT SCALE
                   IPNCH
                                1 PUNCH COMPUTED HYDROGRAPH
                    IOUT
                                21 SAVE HYDROGRAPH ON THIS UNIT
                   ISAV1
                                1 FIRST ORDINATE PUNCHED OR SAVED
                   ISAV2
                               300 LAST ORDINATE PUNCHED OR SAVED
                               .083 TIME INTERVAL IN HOURS
                  TIMINT
            HYDROGRAPH ROUTING DATA
              MUSKINGUM-CUNGE CHANNEL ROUTING
                      L
                              277. CHANNEL LENGTH
                      S
                              .0054 SLOPE
                      Ν
                              .015 CHANNEL ROUGHNESS COEFFICIENT
                     CA
                               .00 CONTRIBUTING AREA
                   SHAPE
                              CIRC CHANNEL SHAPE
                              3.00 BOTTOM WIDTH OR DIAMETER
                     WD
                      Z
                               .00 SIDE SLOPE
                                                       ***
                              COMPUTED MUSKINGUM-CUNGE PARAMETERS
                                    COMPUTATION TIME STEP
                ELEMENT
                                          DT
                                                     DΧ
                                                             PEAK.
                                                                    TIME TO
                          ALPHA
                                    М
                                                                               VOLUME
                                                                                       MAXIMUM
                                                                      PEAK
                                                                                       CELERITY
                                           (MIN)
                                                     (FT)
                                                            (CFS)
                                                                     (MIN)
                                                                                        (FPS)
                                                                               (IN)
                                                                                                RZ-ZZ
                                                     138.50
                  MAIN
                           4.73
                                    1.25
                                              .72
                                                              13.98
                                                                      755.76
                                                                                 .78
```

IOUT

61 HC

PEAK FLOW

(CFS)

62 KK

64 KO

65 RD

14.

21 SAVE HYDROGRAPH ON THIS UNIT

MAIN 4.73 1.25 5.00 13.93 755.00 .78 CONTINUITY SUMMARY (AC-FT) - INFLOW= ,1979E+01 EXCESS= .0000E+00 DUTFLOW= .1978E+01 BASIN STORAGE= .1287E-02 PERCENT ERROR= *** HYDROGRAPH AT STATION PEAK FLOW TIME MAXIMUM AVERAGE FLOW (CFS) (HR) 24-HR 72-HR 6-HR 24.92-HR 1. 14. 12.58 (CFS) 3. 1. 1. .561 .776 (INCHES) .776 .776 (AC-FT) 2. 1. CUMULATIVE AREA = .05 SQ MI *** E1 * 66 KK *********** 68 KO -OUTPUT CONTROL VARIABLES **IPRNT** 3 PRINT CONTROL **IPLOT** 1 PLOT CONTROL QSCAL O. HYDROGRAPH PLOT SCALE 1 PUNCH COMPUTED HYDROGRAPH IPNCH IOUT 21 SAVE HYDROGRAPH ON THIS UNIT 1 FIRST ORDINATE PUNCHED OR SAVED ISAV1 ISAV2 300 LAST ORDINATE PUNCHED OR SAVED TIMINT .083 TIME INTERVAL IN HOURS SUBBASIN RUNOFF DATA SUBBASIN CHARACTERISTICS 69 BA Tarea .00 SUBBASIN AREA PRECIPITATION DATA 70 PH DEPTHS FOR O-PERCENT HYPOTHETICAL STORM TP-40 5-MIN 15-MIN 60-MIN 2-HR 3-HR 6-HR 12-HR 24-HR 2-DAY 4-DAY 7-DAY 10-DAY .00 .39 .76 1.34 1.40 1.44 1.56 1.69 2.01 .00 .00 STORM AREA = .00

72 UD SCS DIMENSIONLESS UNITGRAPH

SCS LOSS RATE

STRTL CRVNBR

RTIMP

.41 INITIAL ABSTRACTION

.00 PERCENT IMPERVIOUS AREA

122-23

83.00 CURVE NUMBER

71 LS

TLAG .13 LAG

UNIT HYDROGRAPH
10 END-DF-PERIOD ORDINATES

1. 3. 2. 1. 0. 0. 0. 0. 0. 0

*** *** *** ***

HYDROGRAPH AT STATION

TOTAL RAINFALL = 2.01, TOTAL LOSS = 1.31, TOTAL EXCESS = .70

PEAK FLOW TIME MAXIMUM AVERAGE FLOW (CFS) (HR) 72-HR 6-HR 24-HR 24.92-HR 12.17 0. 0. (CFS) 0. 0. (INCHES) .590 .702 .702 .702 0. (AC-FT) 0.

CUMULATIVE AREA = .00 SQ MI

*** ***

73 KK * E1 *

* 1

75 KO OUTPUT CONTROL VARIABLES

IPRNT 3 PRINT CONTROL
IPLOT 1 PLOT CONTROL

QSCAL 0. HYDROGRAPH PLOT SCALE

I PUNCH COMPUTED HYDROGRAPH

IOUT 21 SAVE HYDROGRAPH ON THIS UNIT

ISAVI 1 FIRST ORDINATE PUNCHED OR SAVED

ISAV2 300 LAST ORDINATE PUNCHED OR SAVED

TIMINT .083 TIME INTERVAL IN HOURS

76 HC HYDROGRAPH COMBINATION

ICOMP 2 NUMBER OF HYDROGRAPHS TO COMBINE

*** *** *** ***

HYDROGRAPH AT STATION ES

PEAK FLOW TIME MAXIMUM AVERAGE FLOW (CFS) (HR) 24-HR 72-HR 24.92-HR 6-HR 14. 12.58 (CFS) 3. 1. 1. 1. (INCHES) .775 .775 .775 .562 (AC-FT) 1.

CUMULATIVE AREA = .05 SQ MI

		*	*										
77 I	KK	. *	RES5 *										
		*	*										
		*****	*****										
79	KN	nu	TPUT CONTROL	VARIABLE!	3 ·								
			IPRNT		PRINT CON	ΙΠΩΠΙ							
			IPLOT		PLOT CONT								
					HYDROGRAP		_						
			QSCAL										
			IPNCH		PUNCH COM								
			IOUT		SAVE HYDR								
		* •	ISAV1		FIRST ORD								
			ISAV2		LAST ORDI				•		•		
			TIMINT	.083	TIME INTE	RVAL IN HO	JRS						
		HYDRO	OGRAPH ROUTIN	IG DATA									
80 F	₹5	STO	DRAGE ROUTING	3									
			NSTPS	1	NUMBER OF	SUBREACHES	3						
			ITYP		TYPE OF I								
			RSVRIC		INITIAL C								٠
			χ		WORKING R		ICIENT						
					11W1111211W 11	2 000.							
81 9	a)	(STORAGE	.0	.1	.2	3	.5	.8				
01 -	74		JUNNOL	••	• •	**	10	10	10				
82 S	:=	ELC	EVATION	12.00	13.00	14.00	15.00	16.00	17.00	7.64	. "		
02 0	iL.			12.00	10.00	14100	10100	10100	. 17100				
83 S	4	1.06	-LEVEL OUTLE	т									
60.0)L	LUY			CLEUATION	AT CENTED	NE NUTLET						
- 1			ELEVL		ELEVATION								
			CAREA		CROSS-SEC								
			COQL		COEFFICIE								
			EXPL	.50	EXPONENT (JF HEAD "							
	_				•								
84 S	S	SPI	LLWAY										
			CRĘL		SPILLWAY (TION						
سد در ودي			SPWID		SPILLWAY V								
			COQW		WEIR COEF								
			EXPW	1.50	EXPONENT ()F HEAD							

					COM	1PUTED OUTF	LOW-ELEVAT	ION DATA					
					•					•			
		OUTFLOW	.00	.00				.18	.21	.27	.37	.58	•
		ELEVATION	12.00	12.24	12.39	12.43	12.49	12.58	12.74	13.05	13.75	16.00	
		OUTFLOW	.62	.86	1.50	2.73	4.77	7.80	12.02	17.64		33.84	
		ELEVATION	16.01	16.04	16.09	16.16	16.25	16.36	16.49	16.64	16.81	17.00	
		***								4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 -			
		•			COMPUTE	D STORAGE-	DUTFLOW-ELE	EVATION DA	TA				
				•									
		STORAGE	.02	.03	.04	.04	.04	.05	.06	.07	.07	.14	
		OUTFLOW	.00	.00	.12	.13	.15	.18	.21	.26	.27	.37	
		ELEVATION	12.00	12.24		12.43			12.74		13.05		
				·									
		STORAGE	.16	.31	.52	.52	.53	.55	.56	.59	.62	.65	
			- 	- 			. –						
		OUTFLOW	.40	.50	.58	.62	.86	1.50	2.73	4.77	7.80	12.02	
		OUTFLOW ELEVATION	.40 14.00	.50 15.00	.58 16.00	.62 16.01	.86 16.04	1.50 16.09				12.02 16.49	

RZ- 25

STORAGE

OUTFLOW

.69

17.64

.74

24.85

.79

33.84

ELEVATION 16.64 16.81 17.00

HYDROGRAPH AT STATION RESS

DA MO	N HRMN	ORD	OUTFLOW	STORAGE	STAGE * DA	MON	HRMN ORD	OUTFLOW	STORAGE	STAGE	*		A M	ION	HRMN	ORD	OUTFLOW	STORAGE	STAGE
30 JU	N 1200	1	0.	.0	12.0 * 30	JUN	2020 101	0.	.0	12.0			1 J	UL	0440	201	1.	,.5	16.1
	N 1205		0.	.0	12.0 * 30	JUN	2025 102	0.	.0	12.0							1.	.5	16.0
30 JU	N 1210	3	0.	.0	12.0 * 30				.0	12.0							1.	.5	16.0
	N 1215		0.	.0	12.0 * 30			0.	.0	12.0							1.	.5	16.0
	N 1220		0.	.0	12.0 * 30			0.	.0	12.0							i.	.5	16.0
	N 1225		0.	.0	12.0 * 30			0.	.0	12.0							1.	.5 .5	16.0
	N 1230		0.	.0	12.0 * 30			0.	.0	12.0 12.0							1.	.5	16.0
	N 1235		0.	.0	12.0 * 30 12.0 * 30			0. 0.	.0 .0	12.0							1.	.5	16.
	N 1240		0.	.0 .0	12.0 * 30			. 0.	.0	12.0							1.	.5	16.0
	N 1245 N 1250		0. 0.	.0	12.0 * 30				٥	12.0							1.	.5	16.0
	N 1250 N 1255		0.	.0	12.0 * 30			0.	.0	12.0							1.	.5	16.0
	N 1200 N 1300		0.	.0	12.0 * 30			o.	.0	12.0							1.	.5	16.
	N 1305		0.	.0	12.0 * 30			0.	.0	12.0	*	1	IJ	UL	0545	214	1.	.5	16.0
	N 1310		0.	.0	12.0 * 30			0.	.0	12.0	*	1	J	UL	0550	215	1.	.5	16.0
	V 1315		0.	.0	12.0 * 30			0.	.0	12.0	¥	1	J	UL	0555	216	1.	.5	16.0
	N 1320		0.	.0	12.0 * 30	JUN	2140 117	0.	.0	12.0	¥	1	J	UL	0600	217	1.	.5	16.
	V 1325		0.	.0	12.0 * 30	JUN	2145 118	0.	0.0	12.0	¥	1	J	UL	0605	218	1.	.5	16.
	N 1330		0.	.0	12.0 * 30	JUN	2150 119	0.	0								1.	.5	16.
	N 1335		0.	.0	12.0 * 30	JUN	2155 120	0.	.0	12.0							1.	.5	16.
30 JU	N 1340	21	0.	.0	12.0 * 30	JUN	2200 121	0.	.0	12.0							1.	.5	16.9
50 JUI	N 1345	22	0.	.0	12.0 * 30			0.	.0								-1.	.5	16.
30 JU	N 1350	23	0.	.0	12.0 * 30			0.	.0	12.0							1.	.5	16.
50 JUI	N 1355	24	Ō.	.0	12.0 * 30			0.	.0								1.	.5	16.1
	N 1400		0.	.0	12.0 * 30			0.	.0	12.0							i.	.5 .5	16.0 16.0
	V 1405		0.	.0	12.0 * 30			0.	.0	12.0							1.	.5	16.0
	N 1410		0.	.0	12.0 * 30			0.	.0 .0	12.0 12.0							1.	.5	16.
	V 1415		0.	.0	12.0 * 30			0.		12.0							1.	.5	
	N 1420		0.	.0	12.0 * 30 12.0 * 30			0. 0.		12.0							1.	.5	16.
	V 1425		0.	.0 .0	12.0 * 30			0.	.0								1.	.5	16.
	N 1430 N 1435		0. 0.	.0	12.0 * 30												1.	.5	16.
	N 1430 N 1440									12.0							1.	_	16.
	N 1440 N 1445		0.	.0	12.0 * 30			0.	.0	12.0							1.	.5	16.
	N 1450		0.	.0	12.0 * 30				.0	12.0							1.	.5	16.
	N 1455		0.	.0	12.0 * 30			.0.	.0	12.0	¥	1	. J	UL :	0735	236	1.	.5	16.
	N 1500		0.	.0	12.0 * 30			0.	.0	12.0							1.	.5	16.
	N 1505		0	0.	12.0 * 30			0.	.0	12.0							1.	.5	16.
io JUI	N 1510	39	0.	.0	12.0 * 30			0.	.0	12.0							1.	.5	16.
o Jul	V 1515	40	0.	.0	12.0 * 30			0.	.0	12.0							1.	.5	16.
	N 1520		0.	.0	12.0 * 30			0.	.0								1.	.5	16. 16.
	V 1525		0.	.0	12.0 * 30			0.	.0	12.0							1.	.5	16.
	N 1530		0.	.0	12.0 * 30				.0	12.1 12.1							1. 1.	.5	16.
	V 1535		0.	0	12.0 * 30			0.	.0 .0	12.1							1.	.5	16.
	N 1540		0.	.0	12.0 * 1 12.0 * 1			0. 0.	.0	12.5							1.	.5	16.
	N 1545		0.	.0	12.0 * 1			0.	.1	12.9							i.	.5	16.
	V 1550		0. 0.	.0 .0	12.0 * 1			0.	.1	13.3							1.	.5	16.
	N 1555 N 1600		0.	.0	12.0 * 1			0.	.2	13.9							i.	.5	16.3
	N 1605		0.	.0	12.0 * 1			0.	.2	14.4							1.	.5	16.
	N 1610		0.	.0	12.0 * 1			0.	.3	15.0							1.	.5	16.
	N 1615		0.	.0	12.0 * 1			1.	.4	15.4	¥	1	J	UL :	0855	252	1.	5	16.
	N 1620		0.	.0	12.0 * 1	JUL	0040 153	i.	.5	15.9							1.	.5	16.
	V 1625		0.	.0	12.0 * 1	JUL	0045 154	4.	.6	16.2							1	.5	16.1
	N 1630		0.	.0	12.0 * 1			8.	.6	16.4							ほる	2-2	
	V 1635		0.	.0	12.0 * 1	JUL	0055 156	10.	.6	16.4	¥	1	J	UL :	0915	256	1		16.

											7/ 1
30 JUN 1640	57	0(1 JUL 0100		96		1 JUL 0920 25/	1.	.5	16.1
30 JUN 1645	58	00		1 JUL 0105		86		1 JUL 0925 258	i.	.5	16.1
30 JUN 1650	59	00	12.0 *	1 JUL 0110	159	76		1 JUL 0930 259	1.	.5	16.1
30 JUN 1655	60	00	12.0 *	1 JUL 0115	160	66	16.3 *	1 JUL 0935 260	1.	.5	16.1
30 JUN 1700		0	12.0 *	1 JUL 0120	161	56	16.3 *	1 JUL 0940 261	1.	.5	16.0
30 JUN 1705		00		1 JUL 0125		56	16.2 *	1 JUL 0945 262	1.	.5	16.0
30 JUN 1710		0(1 JUL 0130		46	16.2 *	1 JUL 0950 263	1.	.5	16.0
				1 JUL 0135		36		1 JUL 0955 264	1.	.5	16.0
30 JUN 1715		=		1 JUL 0140		36		1 JUL 1000 265	1.	.5	16.0
30 JUN 1720		0(1 JUL 0145		36		1 JUL 1005 266	1.	.5	16.0
30 JUN 1725		00				26		1 JUL 1010 267	i.	.5	16.0
30 JUN 1730		0(1 JUL 0150		26		1 JUL 1015 268	1.	.5	16.0
30 JUN 1735		00		1 JUL 0155				1 JUL 1020 269	1.	.5	16.0
30 JUN 1740		0(1 JUL 0200		26				.5	16.0
30 JUN 1745		00		1 JUL 0205		26		1 JUL 1025 270	1.		16.0
30 JUN 1750	71	0(1 JUL 0210		25		1 JUL 1030 271	1.	.5	
30 JUN 1755	72	00		1 JUL 0215		25		1 JUL 1035 272	1.	.5	.16.0
30 JUN 1800	73	0(1 JUL 0220		25		1 JUL 1040 273	1.	.5	16.0
30 JUN 1805	74	00		1 JUL 0225		25		1 JUL 1045 274	1.	.5	16.0
30 JUN 1810	75	00		1 JUL 0230		15		1 JUL 1050 275	1.	.5	16.0
30 JUN 1815	76	00	12.0 *	1 JUL 0235	176	15		1 JUL 1055 276	1.	.5	16.0
30 JUN 1820	77	00	12.0 *	1 JUL 0240	177	15		1 JUL 1100 277	1.	.5	16.0
30 JUN 1825		00	12.0 *	1 JUL 0245	178	15	16.1 *	1 JUL 1105 278	1.	.5	16.0
30 JUN 1830		0(1 JUL 0250		15	16.1 *	1 JUL 1110 279	1.	.5	16.0
30 JUN 1835		00		1 JUL 0255		15	16.1 *	1 JUL 1115 280	1.	.5	16.0
30 JUN 1840		0(1 JUL 0300		15	16.1 *	1 JUL 1120 281	1.	.5	16.0
30 JUN 1845		· 0		1 JUL 0305		1	16.1 *	1 JUL 1125 282	1.	.5	16.0
30 JUN 1850		00		1 JUL 0310		15	16.1 *	1 JUL 1130 283	1.	.5	16.0
30 JUN 1855		00		1 JUL 0315		15	16.1 *	1 JUL 1135 284	1.	.5	16.0
30 JUN 1900		0(1 JUL 0320		15		1 JUL 1140 285	1.	.5	16.0
		00		1 JUL 0325		15		1 JUL 1145 286	1.	.5	16.0
30 JUN 1905		0(1 JUL 0330		15		1 JUL 1150 287	1.	.5	16.0
30 JUN 1910				1 JUL 0335		15		1 JUL 1155 288	1.	.5	16.0
30 JUN 1915				1 JUL 0340		15		1 JUL 1200 289	1.	.5	16.0
30 JUN 1920		0(1 JUL 0345		15		1 JUL 1205 290	1.	.5	16.0
30 JUN 1925		0		1 JUL 0343		15		1 JUL 1210 291	1.	.5	16.0
30 JUN 1930		0(15		1 JUL 1215 292	1.	.5	16.0
30 JUN 1935		0		1 JUL 0355				1 JUL 1220 293	1.	.5	16.0
30 JUN 1940		0(1 JUL 0400			-	1 JUL 1225 294	1.	.5	16.0
30 JUN 1945		0, .(1 JUL 0405		15		1 JUL 1230 295	1.	.5	16.0
30 JUN 1950		0		1 JUL 0410		15		1 JUL 1235 296	1.	.5	16.0
30 JUN 1955		0(1 JUL 0415		15		1 JUL 1240 297	1.	.5	16.0
30 JUN 2000		0(1 JUL 0420		15		1 JUL 1245 298	1.	.5	16.0
30 JUN 2005		.0.		1 JUL 0425		15				.5	16.0
30 JUN 2010	99	0.		1 JUL 0430		15		1 JUL 1250 299	1.		16.0
30 JUN 2015	100	, o . .0		1 JUL 0435	200	15		1 JUL 1255 300	1.	.5	16.0
******	******	**********	* ********	**********	********	**************************************	* *******	************	******	******	*****
PEAK FLOW	TIME			MAXIMUM AVEF	RAGE FLOW						
(CFS)	(HR)		6-HR	24-HR	72-HR	24.92-HR					
10.	12.92	(CFS)	2.	1.	1.	1.					
10.	14.74	(INCHES)	.380	.578	.578	.578					
		(AC-FT)	1.	2.	2.	2.					
** *** *** *** *** ***		(DO LI)	4.4			-•					

PEAK FLOW	TIME			MAXIMUM AVE	RAGE FLOW	
(CFS)	(HR)		6-HR	24-HR	72-HR	24.92-HR
10.	12.92	(CFS)	2.	1.	1.	1.
		(INCHES)	.380	.578	.578	.578
•		(AC-FT)	1.	2.	2.	2.
PEAK STORAGE	TIME	•		MAXIMUM AVERA	AGE STORAGE	
(AC-FT)	(HR)		6-HR	24-HR	72-HR	24.92-HR
1.	12.92		1.	0.	0.	0.
PEAK STAGE	TIME			MAXIMUM AVEF	RAGE STAGE	
(FEET)	(HR)		6-HR	24-HR	72-HR	24.92-HR
16.41	12.92		16.10	14.14	14.06	14.06

CUMULATIVE AREA = .05 SQ MI

STATION RESS

		- 1							A. E.		
	6	(I) INFLOW,		JTFLOW 8.	10.	12.	14.	16.	0.	0.	0.
0.	2.	4.	6.	O.			(S) STOR	46E			
	.0	.0	.0	.0	.0	.0	.2	.4	.6	.8	.0
Dahrmn Per								. 3			
301200 11-	,				,		,	,	,		
301205 2I		•		•	•	.5	•	•	•	•	•
301210 3I					5	.5	•	•			•
301215 4I	,					.5				•	•
301220 5I						.S		,			
301225 6I	•	-		_	•	.S	,	1			•
301230 7I	•	•	•		_	.S					
	•	•	•	•	•	.S	-		_	•	
	•			•	•	.s	•	•	•	_	_
301240 9I	•		•	*	•		•	1	•	. •	•
301245 10I	•	•	•		*	.S		•	•		•
301250 111						5					
301255 12I		• •	•		•	.S	•	•		•	
301300 13I						.S	•	•			. •
301305 14I						.5				•	•
301310 151						.S				•	
301315 161	•	-	_		:	.S					
301320 17I	•	•	•	<u>-</u>	_	.S					
	•	•	•		•	.s	• .	•		_	
301325 181	•	e	•	. •	, :	.5	•	•	•	. •	•
301330 191	•	•	•	•				•	•	•	•
301335 20I	•	•	•	•	*	.5	•		•		
301340 211						5					
301345 22I	•					5	•	•	•	*	• '
301350 231						.S	•		•		
301355 24I						.5	•			*	•
301400 25I						.5					•
301405 26I		_	_			.5					
301410 27I	•	•	•	-		.S					
	•	•	•	•		.5	_			•	
301415 28I		•	•	•	•	5	•	•	-		_
301420 29 I	•	•	•	•	•		•	•	•	•	•
301425 30I			•	•		.5	*.	•	•	•	
301430 311						5					
301435 32I	•	•	•			.5		•	•	• •	
301440 33I					•	5	•		•		enga je in in see s
301445 341			•			.5			•	•	
301450 35I		,				.5				•	•
301455 36I				2 · · · · · ·		.9	1 Section ♥	\$20 . T &	•		
301500 37I	_					.S					
301505 38I	•	•		-		.s		,	•		•
	•	•		•	•	S	•	,			
	•	•	•	•	•	.s	•	_	_		
301515 40I	•	•		•	•		*	•	•	•	
301520 41I .											
301525 42I	•		•	•	ŧ	.5	Ē	•	•	•	• .
301530 43I	•	•		•	•	.s	•	•	3	•	•
301535 44I					•	.s	•	•			
301540 451						.5		•	•	•	
301545 46I				•	1	.s		•			•
301550 47I		- -				.5	•		•		•
301555 48I	•	•	-			.S					
	•	•	•	•	•	.S					
	•	•	•	•	3	.s					
301605 50I	. •	•	•	•	•		•	•	•	•	
301610 51I .											
301615 52I	•	•	•	•	•	.s	•	•	•	177	-28
301620 53I	•	•	•	•	•		•	•	•	164	20
301625 54I		•	•	•	•	.s	•	•	•	•	
						~					

	VC9100	JJ1		1	•	2	,	•	.5	•	1	,		
		56I	1			. ,			.S			1		
		57 I		,		• '			. S			•		
		58I				, .	ı		. S			1		•
		59 I					1		. S		•	•		
		60I				,			.5			,		
		611							.S					
		62I	 •					_	.s	- -				
	301703		1		•	•	_	•	.S	- -		•		
				•		•	:	•	.5	•	•	•	•	• •
	501715		•		•	• '	•	•	.5	•		1		•
		65I		1	•	•	•	•	.S	*	•	•	•	•
		661				•		•		•		1	•	<u>y</u>
		67 I			•	• '	•	•	.5	•		•	•	•
		68I	•		•		•	•	.S	•		i	•	
		69I				•	•	• .	.5		•			•
		70I	٠, ١			•	t	•	.5	• • .		ı	• '	•
		71 I	 •						.5					
		72 I					1	•	.S			ı	•	•
3	501800	731	1		1				. S	•				
3	01805	74I					•		. S	•			, ,	•
3	501810	75 I	1		1		•		.S			!		Ī
3	01815	76I						•	.S					•
3	301820	77 I					•		.5	•			. ,	
		78I					•		.S			i a e		1
		79I					•		.5			1	•	3
		80I	,						.S			•		i
		B1 I				grienie e e o			.S					
		821					1.		.S					
		831			•				.5			1	• .	•
		841							.s		. ,			,
		851			•		•		.S			1	. ,	•
		861							.5					
		87 I	,		•				.S			ì		•
		881					-	- -	.S			i :		
		89I			•	•		- -	S					1
		90I	'		•		-		.5		, ,	i ·		ı
		701 911	,		•				.S					
		92I	 •						.5					
		93I	•		1	•		- -	.S			· · · · · · · · · · · · · · · · · · ·	. ,	
		94I	- 1		•	•	•		S					
		95I	•		•				.5				. ,	
		961	,		•	•	• • •	-	. S				, .	1
		97I	,		•	•			.S	•		1		
		981	,		•	•	•	• -	.S	•				
	502003 502010		•		•	•	-		.S			i		•
	302015 1		,					•	. S	•		ı :		
	302020 1		 	·					.s					
	02020 1 02025 1		 • •						S					
	302030 1				-				.S		,	1	. ,	•
	02035 1						•		.S					
	502040 1				•		•		.S			rin.		
	02045 1				•		•		.S	•	. ,			ì
	302050 I				•	•	•		.S			:		•
	02055 1				•				,S			ı		1
					•				.S					
	302100 I				•				.S		. 1	i	, ,	•
	302100 1 302105 1								.S					
· 3	02105 1	110I												
· 3	302105 1 302110 1	110I 111I							.5					1
3 3	02105 1 02110 1 02115 1	110I 111I 112I							.S					
3 3 3	502105 1 502110 1 502115 1 502120 1	110I 111I 112I 113I	# 1		• • • • • • • •		• • • • • •		.S					·
3 3 3	502105 1 502110 1 502115 1 502120 1 502125 1	110I 111I 112I 113I 114I	**************************************		• • • • • • • • • • • • • • • • • • • •				.S				· · · · · · · · · · · · · · · · · · ·	•
2 2 3	502105 1 502110 1 502115 1 502120 1 502125 1 502130 1	110I 111I 112I 113I 114I 115I	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		•			•	.S .S				•	•
3 3 3 3 3 3 3 3 3 3	502105 1 502110 1 502115 1 502120 1 502125 1 502130 1	110I 111I 112I 113I 114I 115I 116I	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			•			.S .S .S					
3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	502105 1 502110 1 502115 1 502120 1 502125 1 502135 1 502135 1	110I 111I 112I 113I 114I 115I 116I 117I			·			•		•		0		
3 3 3 3 3 3	502105 1 502110 1 502115 1 502120 1 502125 1 502135 1 502135 1 502145 1	110I 111I 112I 113I 114I 115I 116I 117I 118I	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		· · · · · · · · · · · · · · · · · · ·				.s .s .s .s			R	2-2	29
3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	502105 1 502110 1 502115 1 502120 1 502125 1 502130 1 502135 1 502140 1 502145 1	110I 111I 112I 113I 114I 115I 116I 117I 118I 119I	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1						.s .s .s .s .s			R	2-2	29
3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	502105 1 502110 1 502115 1 502120 1 502125 1 502135 1 502135 1 502145 1	110I 111I 112I 113I 114I 115I 116I 117I 118I 119I							.s .s .s .s			R	2-2	29

of a following to the confidence of

JV.	ZZ00	1211											, ,				5.						٠.		. • •		
	2205																S		,								•
		123 I															5								•		
	2215														1		S										
	2220										v 1912						S										•
		1261			•			_									S										1
		1271			•			•		•							S								· ·		
		1271 128I			•			•		•		•		-			5										1
					•		:	•		•		•		1			S		•		•		_				
		1291			•			•		•		*			•		S		•		•		•				
		1301			•		,	•		•		•		1			S.		•		•		•				
		131I			•	• •	• •				• • •			• •			5						• •				
	2255					•		•		٠		*					.5		•		¥		•		•	,	
	2300				•			•		•		•			•		S		•		•		•		•		•
	2305				•			• "		•		,		- 1	٠				•		•		•		•		
		135I										•			• .		9				•		•		•		•
300	2315	1361												1			S		•	• .	•		•		•		•
30	2320	1371													• .		S		•		•				•		
300	2325	1381												,	:		5				•		•			•	•
30	2330	1391													•		S		•						•		•
300	2335	140I															S				•				•	1	
		141 I													,		5.										
		1420															S								*	į	
		1430															S										
		1440															S									,	
		1450		ĭ	•			-		•							5										
		146.		•		T		•		•							S									,	3
		147.			•	ı		* T		•		•					S										
					•			• •		•	Ŧ	•					_	S				-, -				,	
		148.			•			•		•	7	•		ī				5	•								
		149.			•			•		•				•	•			Ū	.s		•		-				
		150.			•					•		•			•	•		Ţ	• •	. S .			•				
		151.			•	• •	• •	• •		• •			• •			• • •			. I		 S	• •	•	• • •			
		152.			•			•		•		•						1			. 9	3	•		•		
		153.	0		1		_	•		•		•			•	•		נ ז				, S	•		•		•
	$\triangle \triangle A = -$	154.					0								•			ī			•				•		
												-				7 '		* * * .					C				_
1	0050	155.										0			•	I .		***,	•		•		.S		•		•
1: 1:	0050 0055	155. 156.					- 1					0		0	I	I		**.	•				. s				
1: 1:	0050	155. 156.			· ·		- '						I	0		I		***					. S .S			•	•
1: 1: 1:	0050 0055 0100 0105	155. 156. 157. 158.						:		:	I				·	I		***	•		•		. S .S		:	· .	•
1: 1: 1:	0050 0055 0100	155. 156. 157. 158.			,						I O		I			I		***				* *	. s .s .s		:	· .	•
10 10 10 10 10	0050 0055 0100 0105	155. 156. 157. 158. 159.						:	I	I.			I			I		***				• ,	. S .S .S		: :		•
10 10 10 10 10 10	0050 0055 0100 0105 0110	155. 156. 157. 158. 159. 160.						: :	I		0		I						· · · · · · · · · · · · · · · · · · ·						: : :		•
10 10 10 10 10 10 10	0050 0055 0100 0105 0110 0115	155. 156. 157. 158. 159. 160.	•				·		I 0.	.0	0		I			I	· · · · · · · · · · · · · · · · · · ·				1		. S . S . S . S		: : :		•
10 10 10 10 10 10 10 10	0050 0055 0100 0105 0110 0115 0120	155. 156. 157. 158. 159. 160. 161. 162.	• •		: :	 I	Ī	I.	I 0.	.0	0		I			I ·							. S . S . S . S . S		: : :		· · · · · · · · · · · · · · · · · · ·
10 10 10 10 10 10 10 10 10 10	0050 0055 0100 0105 0110 0115 0120 0125	155. 156. 157. 158. 159. 160. 161. 162. 163.	• •			 I	I	I. . O	I 0.	.0	0		I			I .			· · · · · · · · · · · · · · · · · · ·				. S . S . S . S . S		* * * * * * * * * * * * * * * * * * *		
10 10 10 10 10 10 10 11 10 11	0050 0055 0100 0105 0110 0115 0120 0125 0130	155. 156. 157. 158. 159. 160. 161. 162. 163.	• •		-	-	0	I. . O	I 0.	.0	0		I			I			• • • • • • • • • • • • • • • • • • • •				. S . S . S . S . S				
10 10 10 10 10 10 10 10 10 10 10 10 10 1	0050 0055 0100 0105 0110 0115 0120 0125 0130	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165.	• •		·	I 0	0	I. . O	I 0.	.0	0		I			I		• • •					. S . S . S . S . S				
1- 1- 1- 1- 1- 1- 1- 1- 1- 1- 1-	0050 0055 0100 0105 0110 0115 0120 0125 0130 0135 0140	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166.	•		I I	I 0 0 0	0	I. . O	I 0.	.0	0		I			I							. S . S . S . S . S				
10 10 10 10 10 10 10 10 10 10 10 10 10 1	0050 0055 0100 0105 0110 0115 0120 0125 0130 0135 0140 0145 0150	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166.	• •]	I I.	I 0 0 0	0	I. . O	I 0.	.0	0		I			I		• • •					. S . S . S . S . S	• • •			
10 10 10 10 11 10 11 10 10 11 10 11	0050 0055 0100 0105 0110 0115 0120 0125 0130 0135 0140 0145 0150	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166.	• •] I	I I. I.O	I 0 0 0	0	I. . O	I 0.	.0	0		I			I		• • •					. S . S . S . S . S				
10 10 10 10 10 10 10 10 10 10 10 10 10 1	0050 0055 0100 0105 0110 0115 0120 0125 0130 0140 0150 0150 0155 0200	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170.	•] I I(I I. I.O O	I 0 0 0	0	I. . O	I 0.	.0	0		I					• • •					. S . S . S . S . S				
10 10 10 10 10 10 10 10 10 10 10 10 10 1	0050 0055 0100 0105 0110 0115 0120 0125 0130 0140 0150 0150 0155 0200	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170.] I	I I. I.O O	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				
10 10 10 10 10 10 10 10 10 10 10 10 10 1	0050 0055 0100 0105 0110 0115 0120 0125 0130 0140 0150 0150 0155 0200	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171.] I I(I I. I.O O O.	I 0 0 0	0	I. . O	I 0.	.0	0		I					• • •					. S . S . S . S . S				
10 10 10 10 11 10 11 10 11 10 11 10 11 10 11	0050 0055 0100 0105 0110 0115 0120 0125 0130 0140 0150 0155 0200 0205	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171.		I I(I. I.O O O.	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0050 0055 0100 0105 0110 0115 0120 0125 0130 0135 0140 0145 0150 0205 0210 0215 0220	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 167. 168. 170. 171. 172. 173.		I I(. I(IO	[.0].	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				
10 10 10 11 10 11 10 11 10 11 10 11 10 11 11	0050 00055 0100 0105 0110 0115 0120 0130 0135 0140 0155 0200 0205 0210 0215 0220	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174.	•	I I(I(IO IO	[.0].	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				
10 10 10 10 11 10 10 10 11 10 10 11 10 10	0050 0055 0100 0105 0110 0115 0120 0135 0130 0145 0150 0205 0200 0205 0210 0220 0225 0230	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 171. 172. 173. 174. 175.		I I I IO IO IO IO	[.0].	I 0 0 0	0	I. . O	I 0.	.0	0		I							•••			. S . S . S . S . S				
10 10 10 10 10 10 10 10 10 10 10 10 10 1	0050 0055 0100 0105 0110 0115 0120 0135 0140 0145 0150 0200 0205 0210 0220 0225 0230 0235	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176.		I I I IO IO	[.0].	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				
10 10 10 10 11 10 10 10 10 10 11 10 11 10 11 10 11 10 11 11	0050 0055 0100 0105 0110 0115 0120 0130 0130 0140 0145 0150 0205 0210 0225 0220 0225 0230 0235 0240	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 171. 172. 173. 174. 175. 176. 177.		I I IO IO IO I IO	I	I 0 0 0	0	I. . O	I 0.	.0	0		I							• • •			. S . S . S . S . S				
10 10 10 10 11 10 10 11 10 11 10 11 11 1	0050 00055 0100 0105 0110 0115 0120 0125 0130 0135 0140 0155 0200 0205 0210 0220 0225 0230 0235 0240 0245	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 177. 177.		I I IO IO IO IO I	I	I 0 0 0	0	I. . O	I 0.	.0	0		I							• • • •			. S . S . S . S . S				
10 10 10 10 11 10 11 10 11 10 11 10 11 10 11 11	0050 00055 0100 0105 0110 0115 0120 0125 0130 0135 0140 0145 0150 0205 0210 0225 0220 0225 0230 0240 0245 0250	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 171. 172. 173. 174. 175. 176. 177. 178. 179.		1 1 10 10 10 10 10 10	I	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				
10 10 10 10 10 10 10 11 10 10 11 10 11 10 11 10 11 10 11 11	0050 00055 0100 0105 0110 0115 0120 0125 0130 0135 0140 0145 0150 0205 0210 0225 0220 0225 0230 0240 0245 0255 0255	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 175. 176. 177. 178.		10 10 10 10 10 10 10 10	I	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0050 0055 0100 0105 0110 0115 0120 0135 0140 0145 0205 0210 0215 0220 0225 0230 0235 0240 0245 0250 0255 0300	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180. 181.		10 10 10 10 10 10 10 10	I	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				
10 10 10 10 11 10 11 10 11 10 11 11 11 1	0050 0055 0100 0105 0110 0115 0120 0135 0140 0145 0205 0210 0215 0220 0225 0230 0235 0240 0255 0250 0255 0300 0305	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 171. 172. 173. 174. 175. 176. 177. 178. 179. 180. 181.		I I I I I I I I I I I I I I I I I I I	I	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				
10 10 10 10 11 10 11 10 11 10 11 11 11 1	0050 0055 0100 0105 0110 0115 0120 0135 0140 0155 0200 0215 0220 0225 0230 0225 0230 0255 0240 0255 0300 0305 0310	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 170. 171. 172. 173. 174. 175. 176. 177. 178. 180. 181. 182. 183.		10 10 10 10 10 10 10 10	I	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				
10 10 10 10 10 10 10 10 10 10 10 10 10 1	0050 0055 0100 0105 0110 0115 0120 0130 0135 0140 0155 0200 0205 0210 0225 0220 0225 0230 0225 0230 0255 0230 0305 0310 0315	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 170. 171. 172. 173. 174. 177. 178. 177. 178. 181. 182. 183. 184.		I I I I I I I I I I I I I I I I I I I	I	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				30
10 10 10 10 10 10 10 10 10 10 10 10 10 1	0050 0055 0100 0105 0110 0115 0120 0130 0135 0140 0155 0200 0205 0210 0225 0220 0225 0230 0225 0230 0235 0240 0255 0300 0305 0310 0315	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 177. 178. 177. 178. 177. 178. 181. 182. 183. 184. 185.		1	I	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				30
10 10 10 10 10 10 10 10 10 10 10 10 10 1	0050 0055 0100 0105 0110 0115 0120 0130 0135 0140 0155 0200 0205 0210 0225 0220 0225 0230 0225 0230 0255 0230 0305 0310 0315	155. 156. 157. 158. 159. 160. 161. 162. 163. 164. 165. 166. 177. 178. 177. 178. 177. 178. 181. 182. 183. 184. 185.		I I I I I I I I I I I I I I I I I I I	I	I 0 0 0	0	I. . O	I 0.	.0	0		I										. S . S . S . S . S				30

.

	10330-18	U.	iU	1	•				•					ς,	•	4		
	10335 18		10										. (3.	:			
	10340 18		IO										. (3.	•			
	10345 19		I		•	-				•			. 9	3.	ı			
	10350 19		I.		•	•		•	•					S				
			-	•										3		_		
	10355 19		I		•			5	•	•	•	•		3.	ľ	•		•
	10400 19		I		•			s y _{estern} .	•	•	•		•		•	•	•	•
	10405 19	4.	I						x .	•			. 9	•		•		
	10410 19	75.	I						•				(3,		•	•	•
	10415 19	26.	Ī										. 9	3,				
	10420 19		ī		•			2	_				. (3		•		
	10425 17		Ī		•	•		•	•	-	_	_	. 9	3.				
			_		,	•		•	•		•	•	-	3,			. -	_
	10430 19		I		•	. •		•	•	•	•	•	. (<u>l</u>	•	•	•
	10435 20		I					•	•	1	•	•) , -	l	•	•	•
	10440 20		I.). ·				٠.
	10445 20	2.	I											΄,		± :		
	10450 20)3.	I									•	. (3,	ı			•
	10455 20		I										. (3,				
	10500 20		7	•		_			<u>.</u>				. (3,	ı		•	
	10505 20		Ī		•	•		•		_	_	-	. 9	3,				
			_		1	•		•	•	•	•	•		3 .			_	
	10510 20		I		•	•		•	•		•	•				•	· .	_
	10515 20		I		•	•		•	•	•	•	•				• 1		•
	10520-20		I		*				•	•	*	1			1	•		
	10525 21	0.	I										. 5				• .	•
	10530 21	1.	I.											3. ,				•
	10535 21		I										. 9	3.			•	•
	10540 21		ΙO		_	_		_	•				. 9	3.				
	10545 21		10		•	•		•					. (3.				
			10		•	*		•	•		_	•	. 9	3.	•			
	10550 21				•	•		• .	•		•	•		,			_	
	10555 21		I		•	٠		•	• '	•	•	•				•		
	10600 21		I		•	•		•	•	•	•	•		,		*	1	•
	10605.21	8.	I							•	•	•				• •		•
	10610 21	9.	I							•		•	. 9	j,		•	3	•
	10615 22	0.	I					•		•				·		•	•	•
	10620 22	11.	. OI.											j.,				*
	10625 22		OI	-					<u>.</u> '				. 9	3.				
	10630 22		I			Ī			_				. (3		g tra		
			-		•	•		•	•	-			. 9				1	
	10635 22		i		•	•		•	• '	•	•	•	. 9	3				
	10640 22		1		•			•	•		•	1				•		
	10645 22		I		•	•		•	• '	•						•	•	•
	10650 22		, I					•	•	•	•	•				• •		•
,	10655 22		I		•				•	•	•	•	. 5				•	•
	10700 22	29.	I				44				•	t	. 5					•
	10705 23	0.	I		•			•					. 9	·			•	
	10710 23		I.											3				•
	10715 23		I										. 5	3.			ı	•
	10720 23	53.	I							3	3	1	. 9	3.		. ,	•	
	10725 23		Ī						, :				. 9				1 · ·	
	10730 23		Ī		_	_		_		•	•		. 9	3.				
	10735 23		Ī	:	_	•				•				3.			1	
	10740 23		I		•	٠		•			-			3.	. *			
			I		•	•		•	-				. 9					,
	10745 23		_	•		•		•	• '				. 9					
	10750 23		I		•	٠			•	•	•	•	. 9			•	•	•
	10755 24		ì	•	•	•		•				•		•			•	•
	10800 24		I.	•] -				•
	10805 24	2.	I						•	•		•	. 9			•	•	•
	10810 24	3.	I							•		•	. 9			•	•	•
	10815 24		I					•				•	. 9					•
	10820 24		I										. 9	3 .		. ,	•	
	10825 24		Ī					•					. 5	3.				
	10830 24		I	•	•	•		_					. 9	3.			•	
			I		•	٠		•	- '	-	-		. 9				•	
	10835 24		_		3	•		•	•	•	· ·	-						
	10840 24		I		•	•		•	•	•	•	•	. 9		1	1	2 1	
	10845 25		1		•	•		•	•	•	•	•			K	ム・ こ	71	•
	10850 25		I.	•		•								, .				•
	10855 25	2.	Ι			•		•	•		•	•	. 9	•			1	•

では、これには Manager これには、 これを Annager は Manager
to the Management of the School Company of the Section of the Sect

五萬 三十九十二

10900-253	. 1	•	•		•		•	1	. 5	•	•	•
10905 254					-			_	. s		•	•
10910 255					•		•	•	. 5	•	•	•
10915 256		•	•	•	•	•	•	•	. 5	•	•	•
10920 257		•	•	Ī	•	•	•	•	. S	•	•	•
10720 257		or '∎''s -		•	•		•	•		•		•
		•	•	•	•	•	•	•	. 5	•	•	•
10930 259			•	•	•	•	•	•	. 5	•	•	•
10935 260		•	•	•	•	•	•	•	. S		•	•
10940 261									5.			
10945 262			•	•		•			. S	•		1
10950 263			•	•					. S	•		
10955 264						•	•		. S			
11000 265	. I	•							. S		•	
11005 266	. I					•			. 5			
11010 267	. I	•							. S			
11015 268	. I	•							. S	•		
11020 269	. I								. 9			
11025 270	. I								. s			
11030 271									S.			
11035 272									. S			
11040 273			-	_	_	_		_	. 5	-	•	
11045 274				• -		• .	_		. 9		•	•
11050 275		•	•	•	•		•	•		•,		1
11055 276		•	•	•	•	•	1		. 5	•	•	•
11100 277		•	•	•	• '	•			. s	*		•
11100 277		1	•	•	•		*	•		•	t veregelet	
		•		•	. 1	•	•	•		•		ı i
11110 279.		•	•		•	•	•	•	. 5	•	•	•
11115 280.		•	•	•		ı`	• ;	•	. 5	•		
11120 281.									5.			
11125 282.		•	•	•	, ,	1	• ,		. <u>S</u> .		•	· <u>.</u> .
11130 283.		*		•		•		•	. 5			
11135 284.									: 5			,
11140 285.							• :		. 5			
11145 286.									. S		*	
11150 287.									. S			
11155 288.						,			. S		•	
11200 289.							. ,		. S			,
11205 290.												
					. 1				. 5			
							·		S.			
	.I				· · · · · · · · · · · · · · · · · · ·			· • • • · ·	S.			
11210 291.	. I	•				•	· · · · · · · ·		S. S			
11210 291. 11215 292.	. I I	1				•						
11210 291. 11215 292. 11220 293.	IIII					•						
11210 291. 11215 292. 11220 293. 11225 294.	. I I I I		 	•		•	•				•	
11210 291. 11215 292. 11220 293. 11225 294. 11230 295.	I I I I I I I I I I I I I I I I I I I		· · · · · · · · · · · · · · · · · · ·	•				•				
11210 291. 11215 292. 11220 293. 11225 294. 11230 295. 11235 296.	I I I I I I I I I I I I I I							•				
11210 291. 11215 292. 11220 293. 11225 294. 11230 295. 11235 296. 11240 297. 11245 298. 11250 299.	. I I I I I I I I I I I I I I I I I											
11210 291. 11215 292. 11220 293. 11225 294. 11230 295. 11235 296. 11240 297. 11245 298. 11250 299.	. I I I I I I I I I I I I I I I I I											

100 YEAR

RUNOFF SUMMARY FLOW IN CUBIC FEET PER SECOND TIME IN HOURS, AREA IN SQUARE MILES

OPERATION	STATION	PEAK FLOW	TIME OF PEAK	AVERAGE FL 6-HOUR	OW FOR MAXIN 24-HOUR	NUM PERIOD 72-HOUR	BASIN AREA	MAXIMUM STAGE	TIME OF MAX STAGE
HYDROGRAPH AT	D123	10.	12.58	2.	0.	0.	.02		
ROUTED TO	CHIA	10.	12.58	2.	0.	.0.	.02		
HYDROGRAPH AT	D4	2.	12.58	0.	0.	0.	.00		
2 COMBINED AT	D4	12.	12.58	2.	1.	1.	.02		
ROUTED TO	RES4	1.	13.83	1.	0.	0.	.02	23.20	14.17
ROUTED TO	P1A	1.	13.92	1.	0.	0.	.02		
HYDROGRAPH AT	C2	2.	12.75	0.	0.	0.	•00		
2 COMBINED AT	C2	3.	12.75	1.	0.	0.	.03		
HYDROGRAPH AT	C13	11.	12.58	2.	1.	1.	.02		fire ₄
2 COMBINED AT	C12	14.	12.58	3.	1.	1.	.05		
ROUTED TO	P2A	14.	12.58	3.	i.	1.	.05		
HYDROGRAPH AT	E1	1.	12.17	0.	0.	0.	.00		
2 COMBINED AT	E1	14.	12.58	3.	1.	1.	.05	• ••	
ROUTED TO	RES5	10.	12.92	2.	1.	1.	.05	16.41	12.92

 $Run^{+}1$ 10 CFS + 31 CFS = 41 CFS

SUMMARY OF KINEMATIC WAVE - MUSKINGUM-CUNGE ROUTING

(FLOW IS DIRECT RUNOFF WITHOUT BASE FLOW)

	ISTAQ	ELEMENT	DT	PEAK	TIME TO PEAK	VOLUME	DT	COMPUTATIO PEAK	TIME TO PEAK	- Volume		
			(MIN)	(CFS)	(MIN)	(IN)	(MIN)	(CFS)	(MIN)	(IN)		
	CH1A	MANE	1.90	10.44	754.36	.97	5.00	10.44	755.00	.97		
CON	ITINUITY SUMMARY	(AC-FT) -	INFLOW= .96	99 E+00 E)	(CESS= .0000	E+00 O UTFL	O₩= .9696	E+00 BASIN	STORAGE=	.4809E-03 PERCENT	ERROR=	.0
	P1A	MANE	3.04	.67	851.14	.55	5.00	.67	855.00	.55		
CON	TINUITY SUMMARY	(AC-FT) -	INFLOW= .65	B7E+00 EX	(CESS= .0000)	E+00 OUTFL(DW= .65 60	E+00 BASIN	STORAGE=	.2736E-02 PERCENT	ERROR=	.0
	P2A	MANE	.72	13.98	755.76	.78	5.00	13.93	755.00	.78		

CONTINUITY SUMMARY (AC-FT) - INFLOW= .1979E+01 EXCESS= .0000E+00 OUTFLOW= .1978E+01 BASIN STORAGE= .1287E-02 PERCENT ERROR=

^{***} NORMAL END OF HEC-1 ***



Grand Junction Community Development Department Planning • Zoning • Code Enforcement 250 North Fifth Street Grand Junction, Colorado 81501-2668 (970) 244-1430 FAX (970) 244-1599

June 5, 1996

Tom Logue Elam Construction, Inc. 1225 S. 7th Street Grand Junction CO 81501

RE: Grand View Filing #2 (Our File #FP-96-114)

Dear Mr. Logue:

As requested I am providing you with a summary of outstanding issues for the above referenced project to detail why the project was pulled from the June 11th Planning Commission agenda. Only after all issues are resolved to the satisfaction of City staff will the item be placed on the July Planning Commission agenda.

One of the two principal issues which remains outstanding is that to date no documentation has been provided to this office to indicate that an easement has been obtained to accommodate the drainage structures and stormwater which are located on the property to the south (the Dawn Subdivision property). The required drainage easement was to be obtained with the Filing #1 approval and was not. Stormwater from both Filing #1 and Filing #2 discharges into the subject drainage facility. If no easement is obtained, the petitioner is responsible for an alternative design to accommodate the stormwater for both filings. The alternative design must be reviewed and approved by City staff.

The second major issue is the required revisions to the HEC-1 run. We have not been provided with the revised document for review and no longer had sufficient time to review the report prior to the June 11th meeting. As you know, the HEC run is significant in that the results may impact the calculated runoff and required storage volumes. The Development Engineer also requested a revised drainage report which has also not been provided.

There are a number of the Development Engineer's other comments which were not adequately addressed with your response to comments. The outstanding item are numbered to correspond with the Development Engineer's original comments:

To: Tom Logue/June 5, 1996 Re: Grand View Filing #2

- 1. See discussion of the HEC-1 run above.
- 2. A profile, grades and a cross-section drawing are required and were not provided; the existing and proposed pavement needs to be shown as well.
- 3. OK
- 4. The improvements to the northern part of the Ridge Drive ROW are still not indicated on the plans. Also, please indicate the driveway relocation for the adjacent existing house (as required with the preliminary approval) and indicate the extent of the vertical curb along Ridge Drive. If curb returns are to be provided on Ridge Drive at 28 Road please indicate; if not proposed, please explain why.
- 5. OK
- 6. OK



140

- 7. See comments in #4 related to vertical curb; also see red-lined drawings for required correction to Ridge Drive detail on Sheet 13.
- 8. The inlet sizes must also be shown on the street plans; the size and type of inlets are not indicated on the plans. A stand-alone drainage report for Filing #2 is required which details the sizing of the inlets, culverts, street flows and any modifications to the detention facilities.



- 9. The location of the street lighting is not adequate. Please refer to the Transportation Engineering Design Standards (TEDS) Manual, page 48 regarding required spaces and locations of street lights and revise plans accordingly.
- 10. OK
- 11. OK
- 12. OK

In addition to the above, the southern end of Grand View Drive is required to be extended to the property line. Since the extension involves the crossing of the ditch, we would suggest that you coordinate with the developer of the property to the south concerning the completion of the stub street.

I would also refer you to the attached red-lined drawings for additional required changes to the plat and the engineering drawings.

To: Tom Logue/June 5, 1996 Re: Grand View Filing #2

The City Utility Engineer has informed me that your response to comments did not adequately his comments #2, 5 & 6. Please contact Trent directly if you have any questions regarding his comments.

For reference, in all future responses to staff comments all items must be addressed individually, blanket statements which state that "all modifications have been made" with a reference to the plans is unacceptable.

I trust that the above information is of use to you in revising the plans. Please call to discuss resubmittal dates and hearing schedules. Please do not hesitate to contact me should you have any questions or if you require further explanation of any item.

Sincerely yours

Michael T. Drollin

Senior Planner

Encls.

cc: Jody Kliska, City Development Engineer

Don dela Motte, Donada Inc.

h:\cityfil\1996\96-114.lt1

POSTING OF PUBLIC NOTICE SIGNS

The posting of the Public Notice Sign is to make the public aware of development proposals. The requirement and procedure for public notice sign posting are required by the City of Grand Junction Zoning and Development Code.

To expedite the posting of public notice signs the following procedure list has been prepared to help the petitioner in posting the required signs on their properties.

- 1. All petitioners/representatives will receive a copy of the Development Review Schedule for the month advising them of the date by which the sign needs to be posted. IF THE SIGN HAS NOT BEEN PICKED UP AND POSTED BY THE REQUIRED DATE, THE PROJECT WILL NOT BE SCHEDULED FOR THE PUBLIC HEARING.
- 2. A deposit of \$50.00 per sign is required at the time the sign is picked up.
- 3. You must call for utility locates before posting the sign. Mark the location where you wish to place the sign and call 1-800-922-1987. You must allow two (2) full working days after the call is placed for the locates to be performed.
- 4. Sign(s) shall be posted in a location, position and direction so that:
 - a. It is accessible and readable, and
 - b. It may be easily seen by passing motorists and pedestrians.
- 5. Sign(s) MUST be posted at least **10 days** before the Planning Commission hearing date and, if applicable, shall stay posted until after the City Council Hearing(s).
- 6. After the Public Hearing(s) the sign(s) must be taken down and returned to the Community Development Department within FIVE (5) working days to receive a full refund of the sign deposit. For each working day thereafter the petitioner will be charged a \$5.00 late fee. After eight working days Community Development Department staff will retrieve the sign and the sign deposit will be forfeited in its' entirety.

The Community Development Department staff will field check the property to ensure proper posting of the sign. If the sign is not posted, or is not in an appropriate place, the item will be pulled from the public hearing agenda.

I have read the above information and agree to its terms and conditions.

V#40006669

·	
Com to gue	96-6-18-96
SIGNATURE , DATE	
	CEIPT # <u>403(</u>
PETITIONER/REPRESENTATIVE: Tom Logue	PHONE #242-5370
DATE OF HEARING: 1-11-96 57-2-96 POST SIGN(S) BY: 5	
DATE SIGN(S) PICKED-UP 5-20-96 RETURN SIGN(S) BY:	7-9-96
DATE SIGN(S) RETURNED 8-9-96 RECEIVE	ED BY: MyC
	•

June 21, 1996

Michael Drollinger City of Grand Junction Community Development Dept. 250 North 5th St. Grand Junction, CO 81501

RE: Grand View Drainage Easement

Dear Michael,

I have reached an agreement with Don della Motte, the developer of the Grand View Subdivision, to provide a 8 foot drainage easement along the north boundary of Dawn Subdivision. Our agreement is contingent upon the following items:

- 1. The City must approve this use as part of their approval of the next phase to Grand View Subdivision.
- 2. No detrimental results will accrue to Dawn Subdivision other than the occasional wetting of the easement ground.
- 3. The "100-year flood" level shall not top the bank of the Grand Valley Water Users Association access road as shown on the Dawn Grading and Drainage Plan, 6/3/96.
- 4. The Grand View Home Owners Association shall be responsible for maintenance of the drain ditch resulting from its use by Grand View as a detention facility.
- 5. Mr. della Motte shall be responsible for all costs to construct all Grand View Drive required road improvements to the Dawn subdivision boundary and for the cost of the drain pipe under this road but on the Dawn property. On or before 3 working days after Mr. della Motte has been given a Parkerson Construction, Inc. estimate for the aforesaid costs, he will put in place an improvements guarantee satisfactory to the City for the amount of the estimate. In the event that I wish to complete the above improvements before Grand View has completed them, I will notify Mr. della Motte, he shall make payment to me for the amount of the estimate within 5 working days, and I will complete the improvements within 30 days.
- Other financial payment to me by Mr. della Motte by separate agreement.

I anticipate recording the Dawn plat prior to the City's approval of the next phase of Grand View. Upon completion of the above contingencies, I will within 7 working days record the 8 ft. easement for the benefit of the Grand View Home Owners Association. Any prospective purchasers of Dawn lots or homes will be given notice of the 8 ft. easement, and it will be recorded before any home sales are closed.

We are hopeful that the above provides you with the information necessary to allow Grand View Subdivision to proceed to hearing before the Planning Commission. If you have any further questions do not hesitate to contact me or Ward Scott.

Sincerely

John Davis

cc: Tom Logue

RECEIVED GRAND JUNCTION PLANNING DEPARTMENT.

FINAL DRAINAGE REPORT FOR: GRAND VIEW SUBDIVISION, FILING NO. TWO JUN 2 1 1998

June, 1996

Prepared by: Atkins and Associates, 321 7th. Street, Meeker, Colorado 81641 Phone (970) 878-4041 Prepared for: DONADA, Inc., 634 Avalon Drive, Grand Junction, Colorado (970) 434-6224

PURPOSE - the purpose of this study is to present hydraulic design calculations for the drainage improvements required for Grand View Subdivision, Filing No. Two. calculations included herein are based on data contained within the Master Drainage Study for Grand View Subdivision, and the First Addendum to the study. Information contained herein is intended to augment data contained within the master study. The reader is encouraged to carefully review the master study prior to this report.

LOCATION - Filing Two is the second phase of a multi-phased single family development located SE of Ridge Drive and 28 Road. Filing One forms part of the southerly boundary of Filing Two. The accompanying Exhibit 16 & 17 shows the location of 33 single family lots on 12.3 acres and its relationship to Filing One.

HYDROLOGIC CALCULATIONS - This report analyses the developed storm water runoff from sub-basins OF 1, 2, & 3, and basins A-1,2, & 3: B1 thru B-5 from the Master Study to and through storm inlets 1,2, 3, 4 5 & 6. A HEC-1 computer program was utilized in implementing the parameter within the Master Study.

HYDRAULIC CALCULATIONS - The City of Grand Junction's Stromwater Management Manual, June 1994 was used to size the various elements of the stormwater conveyance system within Filing Two.

DETENTION CALCULATIONS - Filing Two will be the last phase of construction for the detention reservoirs required for Grand View. The first phase included the construction of two of the five reservoirs and outlet control structures. Filing Two construction will include the completion of Reservoirs 1, 2 and 3. These 3 reservoirs convey approximately 3.53 cfs of irrigation tailwater based on field observations. A summary of the storage volume provided based on the final construction plans for Filing 2 follows:

RESERVOIR	2 yr. required	2 yr. provided	100 yr. required	100 yr. provided
1	2,614 cf	2,750 cf	17,424 cf	18,752 cf
2	2,178 cf	2,648 cf	11,761 cf	12,058 cf
3	17,860	19,222	24,394 cf	26,113 cf

CONCLUSIONS - The results of the report meet or exceed the minimum requirements for detention storage as required in the Master Drainage Study for Grand View Subdivision and the First Addendum.

CERTIFICATION - I hereby certify that the Drainage Report for Grand View Subdivision, Filing Two was prepared under my direct supervision.

R.L. Atkins, P.E.- P.L.S Colorado No. 12291

GRAND VIEW SUB. (ADDENDUM #1) 2 YEAR STORM EVENT

ROUTED TO

RUNOFF SUMMARY FLOW IN CUBIC FEET PER SECOND TIME IN HOURS, AREA IN SQUARE MILES

PEAK TIME OF AVERAGE FLOW FOR MAXIMUM PERIOD BASIN MAXIMUM TIME OF OPERATION STATION FLOW PEAK AREA STAGE MAX STAGE 6-HOUR 24-HOUR 72-HOUR HYDROGRAPH AT OF1 1. 12.58 0. 0. 0. .02 ROUTED TO 0. 0. .02 CH1 1. 12.67 0. HYDROGRAPH AT 1. 12.58 0. .01 **A2** 0. 0. 2 COMBINED AT A2 2. 12.67 0. 0. 0. .02 ROUTED TO 2. 12.75 0. 0. 0. ST1 .02 HYDROGRAPH AT 1. 12.58 A3 0. .01 2 COMBINED AT A3 2. 12.75 1. 0. 0. .03 HYDROGRAPH AT 1. 13.00 0. 0. 0. .02 OF2 ROUTED TO + CH2 1. 13.08 0. 0. ٥. .02 HYDROGRAPH AT 0. 13.08 0. 0. 0. .00 OF3 2 COMBINED AT 1. 13.08 OF3 0. 0. 0. .02 2 COMBINED AT OF3 3. 12.75 0. 0. .05 1. HYDROGRAPH AT 3. 12.92 0. A1 0. .03 2 COMBINED AT Al 6. 12.83 2. 1. 0. .08

+	P1	6. 12.83	2.	1.	0.	.08	
+	HYDROGRAPH AT B1	0. 1 2 .08	0.	0.	0.	.00	
+	2 COMBINED AT B1	6. 12.83	2.	1.	0.	.08	
++	ROUTED TO RESI	5. 13.17	4 .	4.	4.	.08 20.35	13.17
+	ROUTED TO CH3	5. 13.25	4.	4.	4.	.08	ZYEAR WS
+	HYDROGRAPH AT	0. 12.08	0.	0.	0.	.00	
+	2 COMBINED AT B2	5. 13.25	4.	4.	4.	.08	
++	ROUTED TO RES2	5 . 13. 5 0	4.	4.		.08 18.49	13.50
+	ROUTED TO CH4	5. 13.58	4.	4 .	4.	.08	2 YEAR WS
+	HYDROGRAPH AT B345	2. 12.58	0.	0.	0.	.01	
+	2 COMBINED AT B345	6. 12.58	4.	4.	4.	.09	
++	ROUTED TO RES3	6. 1 2 .6 7	4 .	4.		.09 16.04	12.67 ZYEARWS
1	\$	SUMMARY OF	KINEN	ATIC V	VAVE -	- MUSK	INGUM-CUNGE ROUTING

SUMMARY OF KINEMATIC WAVE - MUSKINGUM-CUNGE ROUTING (FLOW IS DIRECT RUNOFF WITHOUT BASE FLOW)

INTERPOLATED TO COMPUTATION INTERVAL

ISTAQ ELEMENT DT PEAK TIME TO VOLUME DT PEAK TIME TO VOLUME

PEAK

PEAK

(MIN) (CFS) (MIN) (IN) (MIN) (CFS) (MIN) (IN)
CH1 MANE 3.00 1.10 762.00 .17 5.00 1.09 760.00 .17

CONTINUITY SUMMARY (AC-FT) - INFLOW=.1577E+00 EXCESS=.0000E+00 OUTFLOW=.1576E+00 BASIN STORAGE=.3005E-03 PERCENT ERROR= -.1

ST1 MANE 5.00 1.76 765.00 .20 5.00 1.76 765.00 .20

EXHIBIT Z

GRAND VIEW SUB. (ADDENDUM #1) 100 YEAR STORM EVENT

RUNOFF SUMMARY FLOW IN CUBIC FEET PER SECOND TIME IN HOURS, AREA IN SQUARE MILES

MAX	CIMUM TIN	Æ OF					LOV	FOR MA	XIMUM PERIO		
STA	OPERATION GE	ı sı	ATI	I NC	LOW	PEAK			AREA	STAGE	MAX
+				6-	HOUR	24-HOU	TR '	72-HOUR			
+	HYDROGRA			12.42	. 1	. 0.	0	02			=SINGLE
+	ROUTED TO		6.	12.50) 1	. 0.	0	02	Combi = 13		n incet
+	HYDROGRA			12.42	0.	0.	0.	.01	- 15	<i>J</i> . <i>J</i>	
+	2 COMBINE	D AT A2	9.	12.42	1.	0.	0.	.02			
+	ROUTED TO		9.	12.50	1.	0.	0.	.02			
+	HYDROGRA			12.42	0.	0.	0.	.01			
+	2 COMBINE		12.	12.50	2.	0.	0.	.03	Flow to	INLE	2
+	HYDROGRA			12.67	1.	0.	0.	.02	CAPACIT	4 or	
+	ROUTED TO		5 .	12.67	1.	. 0.	0	02			
+	HYDROGRA		1.	12.67	0.	0.	0.	.00			
+	2 COMBINE		6.	12.67	1.	0.	0.	.02	FLOW TO	INLE	r#3_
+	2 COMBINE		17.	12.58	3	. 1 .	1	05	CAPACI	my c	大
+	HYDROGRA		13.	12.58	2.	1.	1.	.03	FLOWT	6 INL	ET#1
+	2 COMBINE		31.	12.58	5.	1.	1.	.08	FLOWT	4 ox	
+	ROUTED TO		30.	12.58	5 .	1.	1.	.08			

+	HYDROGRAPH A	T 1. 12.08	0.	0.	0.	.00	
+	2 COMBINED AT B1	30. 1 2. 58				.08	
	ROUTED TO		•	••		. • •	
++	RES1	30. 12.67	7.	5.	4.	.08 23.17	12.67
+	ROUTED TO	30. 1 2.67	7	5 .	4.	.08	— 100 WS ELEY. Year
	HYDROGRAPH A		,,	3.		.00	
+		1. 12.08	0.	0.	0.	.00	
+	2 COMBINED AT B2	30. 12.67	7.	5 .	4.	.08	
+ +	ROUTED TO RES2	32. 12.75	7.	5 .	4.	.08 20.62	12.75
+	ROUTED TO CH4	2 9. 1 2.75	7.	5 .	4.	.08	- 100 WS ELEV. YEAR
+	HYDROGRAPH A B345	T 9. 12.42	1.	0.	0.	.01	FLOW TO INLETS \$ 566
+	2 COMBINED AT B345	34. 12.75	8.	5.	5.		CAPALITY OK "
++	ROUTED TO RES3	31. 12.83	8.	5 .		.09 16.62	12.83 122 1 X FIEV
1		SUMMARY OF (FLOW IS DI					ngum-cunge routing ase flow)

CT RUNOFF WITHOUT BASE FLOW)
INTERPOLATED TO

COMPUTATION INTERVAL

ISTAQ ELEMENT DT PEAK TIME TO VOLUME DT PEAK TIME TO VOLUME

PEAK

PEAK

(MIN) (CF3) (MIN) (IN) (MIN) (CF3) (MIN) (IN)

CHI MANE 2.00 6.20 750.00 .53 5.00 6.20 750.00 .53

CONTINUITY SUMMARY (AC-FT) - INFLOW= .4930E+00 EXCESS= .0000E+00 OUTFLOW= .4930E+00 BASIN STORAGE= .3153E-03 PERCENT ERROR= -.1

ST1 MANE 3.25 9.11 754.00 .60 5.00 9.02 750.00 .60

Open Channel - Uniform flow

Worksheet Name: INLET 1 TO INLET 2

Comment: INLET 1 TO INLET 2

Solve For Full Flow Capacity

Given Input Data:

Diameter..... Slope.....

Manning's n.....

Discharge.....

-z4"

2.00 ft 0.0060 ft/ft

0.013

17.52 cfs > 13 CFS OK

17.52 cfs

2.00 ft

Computed Results:

Full Flow Capacity.... Full Flow Depth.....

Velocity..... Flow Area..... Critical Depth....

Critical Slope.... Percent Full.....

Full Capacity.... QMAX @.94D..... Froude Number....

5.58 fps 3.14 sf 1.51 ft 0.0071 ft/ft 100.00 %

17.52 cfs 18.85 cfs FULL

Q100 = 13 CFS

Open Channel Flow Module, Version 3.16 (c) 1990 Haestad Methods, Inc. * 37 Brookside Rd * Waterbury, Ct 06708

Open Channel - Uniform flow

Worksheet Name: INLET 2 TO INLET 3

Comment: INLET 2 TO INLET 3

Solve For Full Flow Capacity

Given Input Data:

Discharge..... 31.77 cfs

Computed Results:

Full Flow Capacity..... 31.77 cfs > ZSCF5 OK

Full Flow Depth...... 2.50 ft
Velocity...... 6.47 fps
Flow Area..... 4.91 sf
Critical Depth... 1.92 ft

Critical Slope.... 0.0068 ft/ft

Percent Full..... 100.00 %
Full Capacity.... 31.77 cfs
QMAX @.94D..... 34.18 cfs
Froude Number.... FULL

Q100 = 25CFS

Open Channel Flow Module, Version 3.16 (c) 1990 Haestad Methods, Inc. * 37 Brookside Rd * Waterbury, Ct 06708

Exhibit 6

Open Channel - Uniform flow

Worksheet Name: INLET 3 TO INLET 4

Comment: INLET 3 TO INLET 4 TO OUTLET

Solve For Full Flow Capacity

Given Input Data:

Diameter.... Slope.....

Manning's n..... Discharge.....

3.00 ft ' 0.0060 ft/ft

0.013 = 51.66 cfs

Computed Results:

Full Flow Capacity.... Full Flow Depth.....

> Velocity..... Flow Area.... Critical Depth....

Critical Slope.... Percent Full..... Full Capacity....

QMAX @.94D..... Froude Number

51.66 cfs > 34.53CF5 3.00 ft

7.31 fps 7.07 sf

2.34 ft 0.0066 ft/ft

100.00 % 51.66 cfs 55.58 cfs

FULL

Q100 = 31 CFS+ 3.53 CFS (IRRIGATION TAILWATE

Open Channel Flow Module, Version 3.16 (c) 1990 Haestad Methods, Inc. * 37'Brookside Rd * Waterbury, Ct 06708

Open Channel - Uniform flow

Worksheet Name: INLET 4-TO INLET 5

Comment: INLET 4 TO INLET 5

Solve For Full Flow Capacity

Given Input Data:

Discharge..... 10.50 cfs

Computed Results:

Full Flow Capacity.... 10.50 cfs > 4.5 CFS OF Full Flow Depth..... 1.50 ft

Percent Full..... 100.00 %
Full Capacity.... 10.50 cfs
QMAX @.94D...... 11.30 cfs

Froude Number.... FULL

9100 = 4.5 CFS

Open Channel Flow Module, Version 3.16 (c) 1990 Haestad Methods, Inc. * 37 Brookside Rd * Waterbury, Ct 06708

Open Channel - Uniform flow

Worksheet Name: INLET 5 TO OUTLET

Comment: INLET 5 TO OUTLET

Solve For Full Flow Capacity

Given Input Data:

Diameter..... 1.50 ft Slope..... 0.0100 ft/ft

Manning's n..... 0.013 Discharge..... 10.50 cfs

Computed Results:

Full Flow Capacity.... 10.50 cfs
Full Flow Depth..... 1.50 ft
Velocity..... 5.94 fps
Flow Area..... 1.77 sf
Critical Depth... 1.25 ft
Critical Slope... 0.0098 ft/ft

Percent Full.... 100.00 % Full Capacity.... 10.50 cfs QMAX @.94D..... 11.30 cfs

Froude Number.... FULL

Open Channel Flow Module, Version 3.16 (c) 1990 Haestad Methods, Inc. * 37 Brookside Rd * Waterbury, Ct 06708

RES #1 2 YEAR STRM

HYDROGRAPH ROUTING DATA

101 RS STORAGE ROUTING

> NSTPS 1 NUMBER OF SUBREACHES

ELEV TYPE OF INITIAL CONDITION

RSVRIC 18.60 INITIAL CONDITION

.00 WORKING R AND D COEFFICIENT

102 SV STORAGE .0 .1 .2 .3 .5

103 SE ELEVATION 19.60 20.60 21.60 22.60 23.60

104 SL LOW-LEVEL OUTLET

ELEVL 18.60 ELEVATION AT CENTER OF OUTLET

CAREA .79 CROSS-SECTIONAL AREA

COQL .60 COEFFICIENT

EXPL .50 EXPONENT OF HEAD

105 33 SPILLWAY

CREL 22.60 SPILLWAY CREST ELEVATION

SPWID 19.00 SPILLWAY WIDTH 2.70 WEIR COEFFICIENT COQW

EXPW 1.50 EXPONENT OF HEAD

COMPUTED OUTFLOW-ELEVATION DATA

OUTFLOW .00 4.03 4.28 4.56 4.89 5.26 5.70 6.22 6.84 7.60 19.60 19.72 19.87 20.04 20.25 20.52 20.85 21.28 21.84 ELEVATION 22.60

8.12 9.20 11.23 14.50 19.30 25.94 34.70 45.89 7.69 OUTFLOW 59.80

22.61 22.64 22.70 22.77 22.86 22.97 23.10 23.24 23.41 ELEVATION 23.60

COMPUTED STORAGE-OUTFLOW-ELEVATION DATA

K 0.06 DL. FT. .02 .03 .01 .02 .06 .06 .09 .13 .16 STORAGE .04 3.80 4.03 4.28 4.56 4.89 5.26 5.38 5.70 6.22 6.58 OUTFLOW $19.60 \quad 19.72 \quad 19.87 \quad 20.04 \quad 20.25 \, \textcolor{red}{\blacktriangle} \, 20.52 \quad 20.60 \quad 20.85 \quad 21.28$ ELEVATION MAX W5 = 20.35 21.60

.32 .34 .35 .36 .38 STORAGE .20 .31 .31 .32 6.84 7.60 7.69 8.12 9.20 11.23 14.50 19.30 25.94 34.70 OUTFLOW ELEVATION 21.84 22.60 22.61 22.64 22.70 22.77 22.86 22.97 23.10 23.24

.46 STORAGE .43 45.89 59.80 OUTFLOW ELEVATION 23.41 23.60

VOLUME REQUIRED = 2,614 CF EXHIBIT 10

REG # Z ZYEA: Storm

HYDROGRAPH ROUTING DATA

124 RS STORAGE ROUTING

NSTPS 1 NUMBER OF SUBREACHES

ITYP ELEV TYPE OF INITIAL CONDITION

RSVRIC 17.00 INITIAL CONDITION

X .00 WORKING R AND D COEFFICIENT

125 SV STORAGE .0 .1 .2 .3

126 SE ELEVATION 18.00 19.00 20.00 21.00

127 SL LOW-LEVEL OUTLET

ELEVL 17.00 ELEVATION AT CENTER OF OUTLET

CAREA .79 CROSS-SECTIONAL AREA

COQL .60 COEFFICIENT

EXPL .50 EXPONENT OF HEAD

128 SS SPILLWAY

CREL 20.00 SPILLWAY CREST ELEVATION

SPWID 19.00 SPILLWAY WIDTH COOW 2.70 WEIR COEFFICIENT

EXPW 1.50 EXPONENT OF HEAD

COMPUTED OUTFLOW-ELEVATION DATA

OUTFLOW .00 3.99 4.20 4.42 4.68 4.97 5.29 5.66 6.09 6.58 ELEVATION 18.00 18.10 18.22 18.35 18.52 18.71 18.94 19.22 19.57 20.00

OUTFLOW 6.67 7.12 8.22 10.26 13.55 18.38 25.03 33.80 45.00 58.90

ELEVATION 20.01 20.04 20.10 20.17 20.26 20.37 20.50 20.64 20.81 21.00

COMPUTED STORAGE-OUTFLOW-ELEVATION DATA

STORAGE .01 .02 .03 .04 .05 .06 .07 .08 .10 .14 OUTFLOW 3.80 3.99 4.20 4.42 4.68 4.97 5.29 5.38 5.66 6.09 ELEVATION 18.00 18.10 18.22 18.35 18.52 18.71 18.94 19.00 19.22 19.57

STORAGE .18 .19 .19 .19 .20 .21 .22 .24 .25 .27 OUTFLOW 6.58 6.67 7.12 8.22 10.26 13.55 18.38 25.03 33.80 45.00 ELEVATION 20.00 20.01 20.04 20.10 20.17 20.26 20.37 20.50 20.64

20.81

STORAGE .29 OUTFLOW 58.90 ELEVATION 21.00

*** WARNING *** MODIFIED PULS ROUTING MAY BE NUMERICALLY UNSTABLE FOR OUTFLOWS BETWEEN 10. TO 59.

VOLUME REQUIRED = 2,178 C.F.
EXHIBIT !!

RES#2 2 YEAR Synn

HYDROGRAPH ROUTING DATA

147 RS STORAGE ROUTING

NSTPS 1 NUMBER OF SUBREACHES

ITYP ELEV TYPE OF INITIAL CONDITION

RSVRIC 12.83 INITIAL CONDITION

X .00 WORKING R AND D COEFFICIENT

148 SV STORAGE .1 .2 .4 .7

149 SE ELEVATION 14.20 15.20 16.20 17.20

150 SL LOW-LEVEL OUTLET

ELEVL 13.83 ELEVATION AT CENTER OF OUTLET

CAREA .06 CROSS-SECTIONAL AREA

COOL .60 COEFFICIENT

EXPL .50 EXPONENT OF HEAD

151 SS SPILLWAY

CREL 15.75 SPILLWAY CREST ELEVATION

SPWID 12.30 SPILLWAY WIDTH COOW 2.70 WEIR COEFFICIENT

EXPW 1.50 EXPONENT OF HEAD

COMPUTED OUTFLOW-ELEVATION DATA

OUTFLOW .00 .20 .21 .23 .24 .27 .29 .32 .36 .42 ELEVATION 14.20 14.25 14.31 14.39 14.49 14.61 14.77 14.99 15.30 15.75

OUTFLOW .48 .90 2.02 4.18 7.74 13.04 20.42 30.24 42.83 58.54 ELEVATION 15.76 15.81 15.88 15.98 16.11 16.27 16.46 16.68 16.92 17.20

COMPUTED STORAGE-OUTFLOW-ELEVATION DATA

.12 .19 STORAGE .08 .09 .10 .11 .14 .16 .22 .35 OUTFLOW .18 .20 .21 .23 .24 .27 .29 .32 14.61 14.77 14.99 15.20 14.20 14.25 14.31 14.39 14.49 ELEVATION

15.30

STORAGE .33 .33 .34 .35 .37 .40 .42 .43 .48 .53
OUTFLOW .42 .48 .90 2.02 4.18 7.74 10.49 13.04 20.42 30.24
ELEVATION 15.75 15.76 15.81 15.88 15.98 16.11 16.20 16.27 16.46

16.68

STORAGE .60 .66

OUTTO OUT 40.03 .604

OUTFLOW 42.83 58.54 ELEVATION 16.92 17.20

VOLUME REQUIRED = 17,860 CF

EXHIBH 12

RES. #1 100 YEAR STORM

IOUT

21 SAVE HYDROGRAPH ON THIS UNIT

ISAV1

1 FIRST ORDINATE PUNCHED OR SAVED

ISAV2

300 LAST ORDINATE PUNCHED OR SAVED

TIMINT

.083 TIME INTERVAL IN HOURS

HYDROGRAPH ROUTING DATA

101 RS

STORAGE ROUTING

Nalba

1 NUMBER OF SUBREACHES

ITYP

ELEV TYPE OF INITIAL CONDITION

RSVRIC

18.60 INITIAL CONDITION

X

.00 WORKING R AND D COEFFICIENT

102 SV

STORAGE

.0 .1 .2

103 SE

ELEVATION

19.60 20.60 21.60 22.60 23.60

.3

104 SL

LOW-LEVEL OUTLET

ELEVL

18.60 ELEVATION AT CENTER OF OUTLET

CAREA

.79 CROSS-SECTIONAL AREA

COQL

.60 COEFFICIENT

EXPL

.50 EXPONENT OF HEAD

12" & RCP LOW FLOW OUTLET

105 33

SPILLWAY

CREL 22.60 SPILLWAY CREST ELEVATION

SPWID

19.00 SPILLWAY WIDTH

COQW

2.70 WEIR COEFFICIENT

EXPW

W 1.50 EXPONENT OF HEAD

COMPUTED OUTFLOW-ELEVATION DATA

OUTFLOW .00 4.03 4.28 4.56 4.89 5.26 5.70 6.22 6.84 7.60 ELEVATION 19.60 19.72 19.87 20.04 20.25 20.52 20.85 21.28 21.84 22.60

22.00

OUTFLOW 7.69 8.12 9.20 11.23 14.50 19.30 25.94 34.70 45.89

59.80

ELEVATION 22.61 22.64 22.70 22.77 22.86 22.97 23.10 23.24 23.41

23.60

COMPUTED STORAGE-OUTFLOW-ELEVATION DATA

STORAGE .01 .02 .02 .03 .04 .06 .06 .09 .13 .16 OUTFLOW 3.80 4.03 4.28 4.56 4.89 5.26 5.38 5.70 6.22 6.58 ELEVATION 19.60 19.72 19.87 20.04 20.25 20.52 20.60 20.85 21.28

21.60

0.40 AL.F

.38 .34 .35 .36 STORAGE .20 .31 .31 .32 .32 OUTFLOW 6.84 7.60 7.69 8.12 9.20 11.23 14.50 19.30 25.94 34.70

21.84 22.60 22.61 22.64 22.70 22.77 22.86 22.97

23.24

ELEVATION

MAX WS. = 23.17

VOLUME REQUIRED = 17,424 C.F.

RES #Z 100 YEAR STIMM

HYDROGRAPH ROUTING DATA

124 RS STORAGE ROUTING

> 1 NUMBER OF SUBREACHES NSTPS

ITYP ELEV TYPE OF INITIAL CONDITION

RSVRIC 17.00 INITIAL CONDITION

.00 WORKING R AND D COEFFICIENT

125 SV STORAGE .0 .1 .2 .3

126 SE ELEVATION 18.00 19.00 20.00 21.00

127 SL LOW-LEVEL OUTLET

> ELEVL 17.00 ELEVATION AT CENTER OF OUTLET

CAREA .79 CROSS-SECTIONAL AREA

COQL .60 COEFFICIENT

EXPL .50 EXPONENT OF HEAD

SPILLWAY 128 33

> CREL 20.00 SPILLWAY CREST ELEVATION

SPWID 19.00 SPILLWAY WIDTH

COQW 2.70 WEIR COEFFICIENT

EXPW 1.50 EXPONENT OF HEAD

COMPUTED OUTFLOW-ELEVATION DATA

.00 3.99 4.20 4.42 4.68 4.97 5.29 5.66 6.09 ELEVATION 18.00 18.10 18.22 18.35 18.52 18.71 18.94 19.22 19.57

20.00

OUTFLOW 7.12 8.22 10.26 13.55 18.38 25.03 33.80 45.00 6.67

58.90

ELEVATION 20.01 20.04 20.10 20.17 20.26 20.37 20.50 20.64 20.81

21.00

COMPUTED STORAGE-OUTFLOW-ELEVATION DATA

.05 .06 .07 .08 .10 STORAGE .02 .03 .04 OUTFLOW 3.80 3.99 4.20 4.42 4.68 4.97 5.29 5.38 5.66 6.09

ELEVATION 18.00 18.10 18.22 18.35 18.52 18.71 18.94 19.00 19.22

19.57

C 0.27 AL.FT. .19 .27 STORAGE .18 .19 .19 .20 .21 .22 .24 .25

OUTFLOW

6.58 6.67 7.12 8.22 10.26 13.55 18.38 25.03 33.80 45.00

20.00 20.01 20.04 20.10 20.17 20.26 20.37 20.50 20.64

20.81

Max WS = 20.62

- IZ"ØRLP

LOW FLOW DUTLET

.29 STORAGE OUTFLOW 58.90 ELEVATION 21.00

VOLUME REQUIRED = 11,761 C.F.

RES#3 100 YEAR STORM

HYDROGRAPH ROUTING DATA

147 RS STORAGE ROUTING

NSTPS 1 NUMBER OF SUBREACHES

ITYP ELEV TYPE OF INITIAL CONDITION

RSVRIC 12.83 INITIAL CONDITION

X .00 WORKING R AND D COEFFICIENT

148 SV STORAGE .1 .2 .4 .7

149 SE ELEVATION 14.20 15.20 16.20 17.20

150 SL LOW-LEVEL OUTLET

ELEVL 13.83 ELEVATION AT CENTER OF OUTLET

CAREA .06 CROSS-SECTIONAL AREA

COQL .60 COEFFICIENT

EXPL .50 EXPONENT OF HEAD

151 SS SPILLWAY

CREL 15.75 SPILLWAY CREST ELEVATION

SPWID 14.00 SPILLWAY WIDTH

COQW 2.70 WEIR COEFFICIENT EXPW 1.50 EXPONENT OF HEAD

COMPUTED OUTFLOW-ELEVATION DATA

OUTFLOW .00 .20 .21 .23 .24 .27 .29 .32 .36 .42 .
ELEVATION 14.20 14.25 14.31 14.39 14.49 14.61 14.77 14.99 15.30

15.75

OUTFLOW .49 .96 2.23 4.70 8.74 14.77 23.17 34.34 48.67 66.55 ELEVATION 15.76 15.81 15.88 15.98 16.11 16.27 16.46 16.68 16.92

17.20

COMPUTED STORAGE-OUTFLOW-ELEVATION DATA

STORAGE .08 .09 .10 .11 .12 .14 .16 .19 .22 .24 OUTFLOW .18 .20 .21 .23 .24 .27 .29 .32 .35 .36 ELEVATION 14.20 14.25 14.31 14.39 14.49 14.61 14.77 14.99 15.20

15.30

STORAGE .33 .33 .34 .35 .37 .40 .42 .43 .48 .53

OUTFLOW .42 .49 .96 2.23 4.70 8.74 11.87 14.77 23.17 34.34


ELEVATION 15.75 15.76 15.81 15.88 15.98 16.11 16.20 16.27 16.46


16.68

STORAGE .60 .66 MAY W.S. = 16.62

OUTFLOW 48.67 66.55 ELEVATION 16.92 17.20

YOWME REQUIRED = 24,394 CF.








EXHIBIT IT

STREET CARRING CAPACITY

(2 YEAR)

PROJECT:

GRAND VIEW SUB., FILING NO. TWO

LOCATION:

CITY OF GRAND JUNCTION, COLORADO

DATE:

Jun-96

Street Information:	R.O.W. Width =	44.00	FT.	Flow Area =	3.76 SF.
	Flowline Width =	31.00	FT.		
	Classification =	URBAN			
	Mannings =	0.015			
	Max. Depth =	0.42	FT.	Above Gutter Fig	owline
	Str/ X-Slope =	1.00	%		
	Gutter Slope =	8.33	%	Drive Over Curb	, Gutter and Walk
	Sidewalk Slope =	2.08	%	1/4" / FT.	
	Roadside Slope =	2.08	%	1/4" / FT.	

SLOPE OF STREET	REDUCTION FACTOR FOR SLOPE	ALLOWABLE CAPACITY C.F.S.	VELOCITY F.P.S.
0.50	0.60	5.83	1.55
0.86	0.80	10.20	2.71
1.00	0.80	11.00	2.93

MAX ZYEAR FLOW = 6.0 CFS FROM TWO SEPERATE DIRECTIONS OK

2/3 1/2

Formula:

 $Qa = F \times (1.49/N) \times R \times S \times A$

F = Reduction Factor For Slope

N = Mannings Coefficient = 0.0150 0.2234 R = Hydraulic Radius = AWP =

3.760 A = Cross Sectional Area Sq.Ft. =

16.83 WP = Wetted Perimeter Ft. =

S = Street Slope FT_/FT.

STREET CARRING CAPACITY

(100 YEAR)

PROJECT:

GRAND VIEW SUB., FILING NO. TWO

LOCATION:

CITY OF GRAND JUNCTION, COLORADO

DATE:

Jun-96

Street Information:	R.O.W. Width =	44.00	FT.	Flow Area =	15.49 SF.
	Flowline Width =	31.00	FT.		
	Classification =	URBAN			
	Mannings =	0.015			
	Max. Depth =	1.00	FT.	Above Gutter Fl	lowline
	Str/ X-Slope =	1.00	%		
	Gutter Slope =	8.33	%	Drive Over Curt	b, Gutter and Walk
	Sidewalk Slope =	2.08	%	1/4" / FT.	
	Roadside Slope =	2.08	%	1/4" / FT.	

SLOPE OF STREET	REDUCTION FACTOR FOR SLOPE	ALLOWABLE CAPACITY C.F.S.	VELOCITY F.P.S.
0.50	0.60	51.81	3.34
0.86	0.80	90.59	5.85
1.00	0.80	97.69	6.31

1/2

MAX 100 YEAR FLOW = 13.0CFS OK

2/3

Formula:

 $Qa = F \times (1.49/N) \times R \times S \times A$

F = Reduction Factor For Slope

N = Mannings Coefficient = 0.0150 0.7070 R = Hydraulic Radius = AWP =

A = Cross Sectional Area Sq.Ft. =

15,490 WP = Wetted Perimeter Ft. = 21.91

S = Street Slope FT JFT.



June 21, 1996

Michael T. Drollinger, Sr. Planner City of Grand Junction Community Development Department 250 Main Street Grand Junction, CO 81501

RE: GRAND VIEW, FILING 2, File No. FP-96-114

Dear Mr. Drollinger:

In response to your letter dated June 5, 1996, the following is provided:

- 1. A letter from the developer of Dawn Subdivision indicating their willingness to dedicate a 12 foot drainage easement across their northerly property line.
- 2. Copies of the revised HEC-1 drainage study are attached.
- 3. Cross Sections for 28 Road have been included with the accompanying revised construction plans and plat. Additionally, the limits of the proposed pavement widen along 28 Road have also been added to the plans.
- 4. The plans have been modified to reflect a paved return on the north side of Ridge Drive at 28 Road. Concrete returns have not been indicated. By doing so will allow the designer of future 28 Road improvement additional flexibility in establishing new grades at the intersection. If it is the City's desire to construct a concrete return, the applicant will do so.
- 5. The vertical curb detail has been changed on sheet 13. Notations of the extent of the vertical curb and gutter have been "highlighted" on the returned set of red lined drawing which are attached.
- 6. The inlet sizes and types are also highlighted on the returned set of red line drawings.
- 7. The street lighting plan has been modified to conform to the requirements of the City standards.
- 8. A detail has been added to the Sewer and Water Plan indicating the exact location of Manhole B-1 in relationship to the sidewalk. A new Water Detail sheet has been added to the plans reflecting Ute Waters current specifications.

We are hopeful that the accompanying responds to the items which needed addressed and the project can now be schedule before the Planning Commission for hearing. Do not hesitate to contact me if you have any further questions or require any additional information. We will commit our available resources to the project in order that any future requests are responded to promptly.

Respectfully,

ELAM CONSTRUCTION, INC.

Thomas A. Logue

Governmental Affairs Manager

xc: Richard Atkins
Donald della Motte



Memorandum

DATE: June 24, 1996

TO: Trenton Prall

FROM: Michael T. Drollinger

RE: Grand View Filing #2 - Response to

comments

Please review the attached plans and written response and advise whether the remaining outstanding issues have been addressed to your satisfaction. It appears that the item will be pulled from the July PC agenda but I would like to summarize the remaining items for the petitioner so that they can try again for August. I will need a written (e-mail is OK) response no later than 12 noon on Tuesday 6/25.



Grand Junction Community Development Department Planning • Zoning • Code Enforcement 250 North Fifth Street Grand Junction, Colorado 81501-2668 (970) 244-1430 FAX (970) 244-1599

June 25, 1996

Tom Logue Elam Construction, Inc. 1225 S. 7th Street Grand Junction CO 81501

RE: Grand View Filing #2 (Our File #FP-96-114)

Dear Mr. Logue:

As requested I am providing you with a summary of outstanding issues for the above referenced project to detail why the project was pulled from the July 2nd Planning Commission agenda. Only after all issues are resolved to the satisfaction of City staff will the item be placed on the August Planning Commission agenda.

There remain a number of the Development Engineer's comments which were not adequately addressed with your latest response to comments and revised plans as follows:

- 1. Revised roadway plans and profiles for Grand View Drive and Ridge Drive were not provided for review with the resubmittal.
- 2. Left and right flow line profiles as per the SSID manual and the original comments for all streets have not been provided.
- 3. Notations for inlet sizes and types are still not indicated on the roadway plans. Please identify the above on the plans with a reference to the standard City detail sheet. Include detail sheet in plan set.
- 4. Grading Plan shall identify reservoirs consistent with the Drainage Report. A plan shall be submitted for each reservoir as per SSID sheet IX-16, items #6-#10. Also refer to SWMM manual regarding grading of slopes and slope erosion treatment for the reservoirs and provide details on plans as required.
- 5. The plat is still under review by the City property agent's office, however, to date the following corrections have been identified (1) Tract A should be relabeled "Outlot A"

To: Tom Logue/June 25, 1996 Re: Grand View Filing #2

(this was incorrectly labeled on our red-lined drawings); and (2) please correct the spelling of "acreage."

The Utility Engineer has informed me that his comments have been adequately addressed.

For reference, in all future responses a complete set of plans shall be submitted which allows us to more efficiently review the project without reference to earlier plans.

I trust that the above information is of use to you in revising the plans. Please call to discuss resubmittal dates and hearing schedules. Please do not hesitate to contact me should you have any questions or if you require further explanation of any item.

Sincerely yours

Michael T. Drollinger

Senior Planner

cc: Jody Kliska, City Development Engineer

Trenton Prall, City Utility Engineer

Don dek Woue, Donack Inc.

h:\cityfil\1996\96-114.lt2

STATE OF COLORADO


COLORADO GEOLOGICAL SURVEY

Division of Minerals and Geology

Department of Natural Resources 1313 Sherman Street, Room 715 Denver, Colorado 80203 Phone (303) 866-2611 FAX (303) 866-2461

July 19, 1996

City of Grand Junction Community Development Department 250 North 5th Street Grand Junction, Colorado 81501





Roy Romer Governor

James S. Lochhead Executive Director

Michael B. Long Division Director

Vicki Cowart State Geologist and Director

Re: Proposed Filing 2 of the Grand View Subdivision -- East of the Intersection of 28 Road and Proposed Ridge Drive, Grand Junction

Gentlemen:

At your request, we have reviewed the materials submitted for and made a field inspection of the site of the second filing of Grand View. Thwe following comments summarizes our findings.

The geologic conditions of this parcel are essentially identical to those in the first filing about which we reported to you in our correspondence of August 30, 1994 (copy attached). At the time of this site visit I inspected excavations for and construction of new houses in the first filing to hopefuly corroborate my earlier observations about potential soil and drainage problems in the area and how construction techniques were dealing with them. I can report that the builders whose housing products were in their early stages of construction are doing an excellent job of quality control (for the most part, it is not possible to inspect below grade construction of buildings without basements after backfilling and framing have been completed or are underway) of foundations, grading, and concrete-flatwork placements. As we indicated in our earlier comments, it will be absolutely critical to maintain good surface drainage control in this area and this will mean that, in addition to proper homeowner on-lot maintenance, the city should carefully maintain the streets and curbs and gutters as well.

If the present construction practices are continuesd in the new filing, then we have no geology-related objection to your approval of it.

Sincerely,

ames M. Soule

Engineering Geologist

MEMORANDUM

DATE:

July 24, 1996

TO:

Trenton Prall

FROM:

Michael T. Drollinger

RE:

RESPONSE TO REVIEW COMMENTS

FP-96-114

Please review the attached plans on the above project and advise in writing no later than **Friday**, **July 26**, **1996** whether your department's identified concerns have been met. I'm not sure whether I had already forwarded these plans to you. If no response is received by noon on the above date, I will assume that your department's concerns have been adequately addressed. If you are unable to comply with this deadline, please advise ASAP.

PLANNING COMMISSION STAFF REPORT

FILE:

#FP-96-114

DATE:

July 31, 1996

STAFF:

Michael T. Drollinger

REQUEST:

Final Major Subdivision

GRAND VIEW FILING #2

LOCATION: E of 28 Road and N of Hawthorne Avenue

APPLICANT: Donada, Inc.

634 Avalon Avenue

Grand Junction CO 81504

EXECUTIVE SUMMARY:

Petitioner is requesting final major subdivision approval for Grand View Filing #2 located on the east side of 28 Road north of Hawthorne. The proposed development consists of 36 single family lots on about 12.3 acres. Staff recommends approval of the application with conditions.

EXISTING LAND USE:

Vacant

PROPOSED LAND USE:

Single Family Residential

SURROUNDING LAND USE:

NORTH:

Vacant/ Single Family Residential

SOUTH:

Single Family Residential (Grand View Filing #1)

EAST:

Vacant

WEST:

Single Family Residential (Spring Valley Subdivision)

EXISTING ZONING: RSF-5

PROPOSED ZONING: no change

SURROUNDING ZONING:

NORTH:

RSF-5

SOUTH:


RSF-5

EAST:

R-2 (County)

WEST:

RSF-5



AERIAL PHOTOGRAPH
Grand View Filing #2
Final Major Subdivision FP-96-114

RELATIONSHIP TO COMPREHENSIVE PLAN:

The draft Grand Junction Growth Plan classifies the subject parcel in the "Residential Medium (4-7.9 units/acre) land use category. The proposed density for Grand View Subdivision is consistent with the Growth Plan recommendations

STAFF ANALYSIS:

The site is located directly north of Grand View Filing #1 on the east side of 28 Road north of Hawthorne Avenue and consists of approximately 12.3 acres. The property is zoned of RSF-5. The petitioner is requesting final major subdivision approval for 36 single family lots to be developed in accordance with the adopted Preliminary Plan for the project. Further details of the proposal are in the attached project narrative. Also, an aerial photograph of the site along with a copy of the subdivision plans are attached to this staff report for orientation and reference.

All major issues related to the subdivision have been addressed to staff's satisfaction, however, the City Development Engineer has as of the date of this staff report not completed a final review of the latest plan set. The final review and approval of the construction drawings by the City Development Engineer should be a condition of subdivision approval.

In summary, staff recommends approval of Grand View Filing #2 subject to the following condition:

1. Final review and acceptance of the latest plan set by the City Development Engineer.

STAFF RECOMMENDATION:

Staff recommends approval of the final major subdivision for Grand View Filing #2 with the above condition.

SUGGESTED PLANNING COMMISSION MOTION:

Mr. Chairman, on item #FP-96-114, a request for final major subdivision approval for Grand View Filing #2, I move that the subdivision be approved with the condition in the staff report dated July 31, 1996.

COPY/ FILE

MEMORANDUM

DATE:

August 10, 1996

TO:

Marcia Rabideaux

FROM:

Michael T. Drollinger

RE:

Grand View Improvements Agreement

Please record the attached Improvements Agreement for the Grand View Subdivision (note: this is for improvements in conjunction with Filing #1). The check for \$3,258.50 guaranteeing the improvements is in the envelope in Finance. Please have the check deposited and put the receipt in my box. A check for \$36 is attached for the recording of the agreement. I have already made a copy of the agreement for our records. Also, please put the receipt for the \$36 and the recording information for the agreement in my box. Thanks.



August 9, 1996

Community Development Department City of Grand Junction 250 North 5th. Street Grand Junction, CO 81501

RE: GRAND VIEW, FILING TWO, TCP

Dear Staff:

Accompanying you will find a Construction Cost Schedule for improvements to 28 Road adjacent to Grand View Subdivision, Filing Two. The limits of construction are depicted on the construction documents for Filing Two.

The cost schedule indicates that a total of \$31,722.50 will be spent for improvements to 28 Road adjacent to Filing Two. According to Section 5-3-1-H, Transpiration Capacity Payment, (TCP) of the City of Grand Junction *Zoning and Development Code*, Grand View, Filing Two would qualify for a credit against the TCP for 63 lots. Since there are more than 63 lots in Filing Two the developer, DONADA, Inc. would like the City to apply the additional credit towards any future filings.

Please notify us upon your acceptance of the credit for the TCP. Further, if you have any questions or required any additional data in regard to this matter, feel free to contact our office.

Respectfully,

Thomas A. Logue

Governmental Affairs Manger

xc: Don della Motte

CITY OF GRAND JUNCTION DEPARTMENT OF PUBLIC WORKS & UTILITIES 250 NORTH 5TH STREET GRAND JUNCTION, CO 81501 (970) 244-4003

THIS IS TO CERTIFY that the herein named Subdivision Plat,

TO THE MESA COUNTY CLERK & RECORDER:

GRAND VIEW SUBDIVISION FILING NO. Z	
Situated in the Nw esw 1/4 of Section 6,	
Township SOUTH, Range EAST,	
of the OTE Meridian in the City of Grand Junctic County of Mesa, State of Colorado, has been reviewed under direction and, to the best of my knowledge, satisfies to requirements pursuant to C.R.S. 38-51-106 and the Zoning as Development Code of the City of Grand Junction for the recording subdivision plats in the office of the Mesa County Clerk as Recorder.	the and of
This certification makes no warranties to any person for a purpose. It is prepared to establish for the County Clerk a Recorder that City review has been obtained. This certification does not warrant: 1) title or legal ownership to the land here platted nor the title or legal ownership of adjoiners; 2) error and/or omissions, including, but not limited to, the omission(s) rights-of-ways and/or easements, whether or not of record; liens and encumbrances, whether or not of record; 4) to qualifications, licensing status and/or any statement(s) representation(s) made by the surveyor who prepared the above-name subdivision plat.	and lon leby ors of 3) lhe or
Dated this 9 day of September, 1996.	
City of Grand Junction, Department of Public Works & Utilities	
By: James J. Shanks, P.E., P.L.S. Director of Public Works & Utilities	
Recorded in Mesa County 1773043 0345PM 10/02 Monika Tood CLKARec Mesa C	/96 OUNTY Co
Date:	
Plat Book: 15 Page: 174+175	
g:\special\platcert.doc Fee	
3. Topectat (praccett. doc 1 CC 2	



City of Grand Junction, Colorado 250 North Fifth Street 81501-2668 FAX: (970)244-1599

May 27, 1997

Attn: Don Della Motte Donada, Inc. 634 Avalon Drive Grand Junction CO 81504

RE: Grand View Filing #2 - Release of Funds

Dear Mr. Della Motte:

Our records indicate that the public improvements on Grand View Drive adjacent to the Dawn Subdivision have been completed to our satisfaction. Enclosed please find the check in the amount of \$ 3,258.50 which represents the guarantee for the improvements and is being returned to you.

Please do not hesitate to contact me if you have any questions or require additional information.

Sincerely yours,

Michael T. Drollinger

Senior Planner

Encl.

cc: File # FP-1996-114

h:\cityfil\1996\96-114.It3

FP-1996-17



December 29, 1997

Don Dela Motte 634 Avalon Drive Grand Junction, CO 81504 City of Grand Junction, Colorado 250 North Fifth Street 81501-2668 FAX: (970)244-1599

Subject: Grandview Filing 2 Subdivision

Dear Mr. Dela Motte:

A final inspection of the streets and drainage facilities in Grandview filing 2 Subdivision was conducted on June 18, 1997. As a result of this inspection, a list of remaining items was given to you for completion. These items were reinspected and found to be satisfactorily completed.

"As Built" record drawings and required test results for the streets and drainage facilities were received on September 5, 1997. These have been reviewed and found to be acceptable.

In light of the above, the streets, sewer and drainage improvements in the right of way are eligible to be accepted for future maintenance by the City of Grand Junction one year after the date of substantial completion. The date of substantial completion is July 1, 1997.

Your warranty obligation for all materials and workmanship for a period of one year beginning with the date of substantial completion will expire upon acceptance by the City. If you are required to replace or correct any defects which are apparent during the period of the warranty, a new acceptance date and extended warranty period will be established by the City.

Thank you for your cooperation in the completion of the work on this project.

Sincerely,

Jody Kliska

City Development Engineer

Sincerely,

Trenton Prall

City Utility Engineer


cc: Don Newton Doug Cline


Walt Hoyt

//Kathy Portner


Atkins & Associates

Jerry O-Brien












AERIAL PHOTOGRAPH
Grand View Filing #2
Final Major Subdivision
FP-96-114



N

AERIAL PHOTOGRAPH
Grand View Filing #2
Final Major Subdivision
FP-96-114

Q. NDGAMINGS\1203-03 Non Apr 29 19. 41: 35 1996 Station 1, C.E.A.